

Rajalakshmi Engineering College

Name: Jesvanth Sabarish V K
Email: 240701214@rajalakshmi.edu.in
Roll no: 240701214
Phone: 9080128264
Branch: REC
Department: CSE - Section 6
Batch: 2028
Degree: B.E - CSE

Scan to verify results



2024_28_III_OOPS Using Java Lab

REC_Week 12_Java_Lamba Expressions_PAH

Attempt : 1
Total Mark : 40
Marks Obtained : 37.5

Section 1 : COD

1. Problem Statement

Sneha is developing a feature for an e-commerce application that helps display product details after applying a seasonal discount.

She decides to use lambda expressions with the Consumer functional interface to print each product's name, original price, and discounted price neatly.

The program should:

Accept a list of product names and their prices. Apply a 15% discount on all products. Use a Consumer lambda expression to display the details in a formatted manner.

Input Format

The first line of input consists of an integer n, representing the number of products.

The next n lines each contain a String (product name) and a double (price) separated by a space.

Output Format

For each product, print the details in the format:

Product: <name>, Original Price: <price>, Discounted Price: <discounted price>

If there are no products, print:

No products available

Sample Test Case

Input: 1

Phone 60000

Output: Product: Phone, Original Price: 60000.0, Discounted Price: 51000.0

Answer

// You are using Java

import java.util.*;

import java.util.function.Consumer;

```
public class Main {  
    public static void main(String[] args) {
```

```
        Scanner sc = new Scanner(System.in);  
        int n = sc.nextInt();  
        sc.nextLine();
```

```
        if (n == 0) {  
            System.out.println("No products available");  
            return;  
        }
```

```
        List<String> names = new ArrayList<>();  
        List<Double> prices = new ArrayList<>();
```

```
        for (int i = 0; i < n; i++) {  
            String name = sc.next();
```

```

        double price = sc.nextDouble();
        names.add(name);
        prices.add(price);
    }

    Consumer<Integer> displayProduct = i -> {
        double original = prices.get(i);
        double discounted = original * 0.85; // apply 15% off
        System.out.println("Product: " + names.get(i)
            + ", Original Price: " + original
            + ", Discounted Price: " + discounted);
    };

    for (int i = 0; i < n; i++) {
        displayProduct.accept(i);
    }
}

```

Status : Partially correct

Marks : 7.5/10

2. Problem Statement

Rishi is working as an HR analyst in a software company. He wants to filter a list of employees based on their salary using modern Java techniques. He has a list of employee names and salaries and wants to use lambda expressions to filter those who earn more than a specific threshold.

Implement a program using lambda expressions and functional interfaces to print the names of employees whose salary is greater than or equal to 50,000.

Input Format

The first line of input consists of an integer n , representing the number of employees.

The next n lines. Each line contains a String (employee name) and an int (salary).

Output Format

The output prints the names of employees whose salary is greater than or equal

to 50000, each on a new line.

If no employee found with salary greater than 50000, print: No employee found with salary \geq 50000

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 4

Amit 45000

Sneha 50000

Ravi 60000

Priya 30000

Output: Sneha

Ravi

Answer

// You are using Java

import java.util.*;

import java.util.function.Predicate;

```
public class Main {
    public static void main(String[] args) {

        Scanner sc = new Scanner(System.in);
        int n = sc.nextInt();

        List<String> names = new ArrayList<>();
        List<Integer> salaries = new ArrayList<>();

        for (int i = 0; i < n; i++) {
            String name = sc.next();
            int salary = sc.nextInt();
            names.add(name);
            salaries.add(salary);
        }

        Predicate<Integer> highSalary = sal -> sal >= 50000;
```

```
boolean found = false;

for (int i = 0; i < n; i++) {
    if (highSalary.test(salaries.get(i))) {
        System.out.println(names.get(i));
        found = true;
    }
}

if (!found) {
    System.out.println("No employee found with salary >= 50000");
}
}
```

Status : Correct

Marks : 10/10

3. Problem Statement

Aditya is developing a reading app that recommends books to users based on a predefined list.

Each time a user opens the app, it should supply the next book title in the list, one at a time, using a lambda expression and the Supplier functional interface.

When all books have been recommended, the list should start again from the beginning.

Input Format

The first line contains an integer n — the total number of available book titles.

The next n lines each contain a book title (a string).

The next line contains an integer m — the number of times users open the app (i.e., the number of recommendations to be made).

Output Format

Print the supplied book title for each recommendation, one per line.

If $m > n$, repeat the list from the start.

Sample Test Case

Input: 3

The Alchemist

Atomic Habits

Ikigai

5

Output: The Alchemist

Atomic Habits

Ikigai

The Alchemist

Atomic Habits

Answer

// You are using Java

```
import java.util.*;
```

```
import java.util.function.Supplier;
```

```
public class Main {
```

```
    public static void main(String[] args) {
```

```
        Scanner sc = new Scanner(System.in);
```

```
        int n = Integer.parseInt(sc.nextLine());
```

```
        List<String> books = new ArrayList<>();
```

```
        for (int i = 0; i < n; i++) {  
            books.add(sc.nextLine());  
        }
```

```
        int m = Integer.parseInt(sc.nextLine());
```

```
        // Index tracker (array used so lambda can modify it)
```

```
        int[] idx = {0};
```

```
        // Supplier to give next book cyclically
```

```
        Supplier<String> recommendBook = () -> {
```

```
            String book = books.get(idx[0]);
```

```
            idx[0] = (idx[0] + 1) % n; // wrap around
```

```
            return book;
```

```
        };
```

```
        for (int i = 0; i < m; i++) {  
            System.out.println(recommendBook.get());  
        }  
    }  
}
```

Status : Correct

Marks : 10/10

4. Problem Statement

Emily, an analyst at a data processing firm, is tasked with cleaning up datasets to remove duplicate values from lists of integers.

Create a Java program that allows Emily to input a series of integers, with the program then utilizing a lambda expression to efficiently remove any duplicates.

Input Format

The first line of input consists of an integer N, representing the size of the array.

The second line consists of N space-separated integers, each denoting an array element.

Output Format

The output prints the array elements after removing the duplicates inside the square bracket separated by a comma and space.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 15

1 2 3 4 3 2 1 2 3 4 4 4 5 5 6

Output: [1, 2, 3, 4, 5, 6]

Answer

```
// You are using Java
import java.util.*;
import java.util.function.Function;

public class Main {
    public static void main(String[] args) {

        Scanner sc = new Scanner(System.in);

        int n = sc.nextInt();
        List<Integer> list = new ArrayList<>();

        for (int i = 0; i < n; i++) {
            list.add(sc.nextInt());
        }

        // Lambda to remove duplicates and preserve order
        Function<List<Integer>, List<Integer>> removeDuplicates =
            numbers -> new ArrayList<>(new LinkedHashSet<>(numbers));

        List<Integer> uniqueList = removeDuplicates.apply(list);

        System.out.println(uniqueList);
    }
}
```

Status : Correct

Marks : 10/10