

Asynchronous Session-based Concurrency: Deadlock Freedom by Typing

Jorge A. Pérez
www.jperez.nl

University of Groningen, The Netherlands

Dutch Winter School 2026
(Part 3)


Taking Stock

Up to here:

- ▶ Concurrent interpretation of LL: statics and dynamics
- ▶ Left and right rules per connective - rely and guarantee interactive behaviors
- ▶ Cut reductions and process synchronizations
- ▶ A look at the correctness properties ensured by the logic-based type system
- ▶ The computational interpretation of proof transformations
- ▶ Deadlock freedom (DF) and progress


Today:

- ▶ Asynchronous processes, based on classical linear logic, and DF



The Deadlock Freedom Property (DF)

- ▶ Informally, the guarantee that processes “never get stuck”.
- ▶ Most desirable for the message-passing programs that enable today’s concurrent and distributed software systems.
- ▶ Even a single component that becomes permanently blocked waiting for a message can impact system reliability.
- ▶ Difficulty: Non-local component analysis.



Example

```
peter c1 c2 =  
  let (x, c1) = receive c1 in  
  let c2 = send (41) c2 in  
  wait c1;  
  close c2;  
  ()
```

```
miles c1 c2 =  
  let (x, c2) = receive c2 in  
  let c1 = send (42) c1 in  
  wait c2;  
  close c1;  
  ()
```

Example

```
peter c1 c2 =  
  let (x, c1) = receive c1 in  
  let c2 = send (41) c2 in  
  wait c1;  
  close c2;  
  ()
```

```
miles c1 c2 =  
  let (x, c2) = receive c2 in  
  let c1 = send (42) c1 in  
  wait c2;  
  close c1;  
  ()
```

This program follows its protocol ✓

Example

```
peter c1 c2 =  
  let (x, c1) = receive c1 in  
  let c2 = send (41) c2 in  
  wait c1;  
  close c2;  
  ()
```

This program follows its protocol ✓

```
miles c1 c2 =  
  let (x, c2) = receive c2 in  
  let c1 = send (42) c1 in  
  wait c2;  
  close c1;  
  ()
```

This program follows its protocol ✓

Example, with Concurrency

```
peter c1 c2 =  
  let (x, c1) = receive c1 in  
  let c2 = send (41) c2 in  
  wait c1;  
  close c2;  
  ()
```

```
miles c1 c2 =  
  let (x, c2) = receive c2 in  
  let c1 = send (42) c1 in  
  wait c2;  
  close c1;  
  ()
```

```
main =  
  let (c1, c1dual) = new @T () in  
  let (c2, c2dual) = new @T () in  
  fork (miles c1dual c2);  
  peter c1 c2dual
```

Is 'main' deadlock-free?



Using Processes to Enforce DF

Program (Rust, Go, ABS...)

Processes (π -calculus)

Using Processes to Enforce DF

Program (Rust, Go, ABS...)

Processes (π -calculus)

Type System (for DF)



Using Processes to Enforce DF

Program (Rust, Go, ABS...)


Processes (π -calculus)

Type System (for DF)




✓ or ✗


Using Processes to Enforce DF




Using Processes to Enforce DF



Using Processes to Enforce DF: Many Different Type Systems!



Using Processes to Enforce DF: Many Different Type Systems!



Challenges

Contrast type systems
that enforce DF

Design more advanced
type systems for DF

Challenges

Contrast type systems
that enforce DF



Design more advanced
type systems for DF

Challenges

Contrast type systems
that enforce DF



Design more advanced
type systems for DF

Our Insight: Session type systems derived from Linear Logic ('Propositions as Sessions') offer a guiding reference for both!

Some Observations

- ▶ Asynchronous communication is the cleanest setting to study DF by typing

Some Observations

- ▶ Asynchronous communication is the cleanest setting to study DF by typing
- ▶ Asynchrony unblocks behaviors / session types constrain behaviors

Some Observations

- ▶ Asynchronous communication is the cleanest setting to study DF by typing
- ▶ Asynchrony unblocks behaviors / session types constrain behaviors
- ▶ Asynchronous sessions “in between” untyped synchrony and asynchrony:

Some Observations

- ▶ Asynchronous communication is the cleanest setting to study DF by typing
- ▶ Asynchrony unblocks behaviors / session types constrain behaviors
- ▶ Asynchronous sessions “in between” untyped synchrony and asynchrony: (output) actions from different sessions are independent, but (output) actions within a session should respect their session type.

Some Observations

- ▶ Asynchronous communication is the cleanest setting to study DF by typing
- ▶ Asynchrony unblocks behaviors / session types constrain behaviors
- ▶ Asynchronous sessions “in between” untyped synchrony and asynchrony: (output) actions from different sessions are independent, but (output) actions within a session should respect their session type.

Today We overview DF enforcement in three typed asynchronous π -calculi:

Some Observations

- ▶ Asynchronous communication is the cleanest setting to study DF by typing
- ▶ Asynchrony unblocks behaviors / session types constrain behaviors
- ▶ Asynchronous sessions “in between” untyped synchrony and asynchrony: (output) actions from different sessions are independent, but (output) actions within a session should respect their session type.

Today We overview DF enforcement in three typed asynchronous π -calculi:

1. AP: processes follow protocols but ‘happily deadlock’ (**no DF enforcement**)

Some Observations

- ▶ Asynchronous communication is the cleanest setting to study DF by typing
- ▶ Asynchrony unblocks behaviors / session types constrain behaviors
- ▶ Asynchronous sessions “in between” untyped synchrony and asynchrony: (output) actions from different sessions are independent, but (output) actions within a session should respect their session type.

Today We overview DF enforcement in three typed asynchronous π -calculi:

1. AP: processes follow protocols but ‘happily deadlock’ (**no DF enforcement**)
2. ACP: DF by typing for tree-like process topologies (**basic enforcement**)

Some Observations

- ▶ Asynchronous communication is the cleanest setting to study DF by typing
- ▶ Asynchrony unblocks behaviors / session types constrain behaviors
- ▶ Asynchronous sessions “in between” untyped synchrony and asynchrony: (output) actions from different sessions are independent, but (output) actions within a session should respect their session type.

Today We overview DF enforcement in three typed asynchronous π -calculi:

1. AP: processes follow protocols but ‘happily deadlock’ (**no DF enforcement**)
2. ACP: DF by typing for tree-like process topologies (**basic enforcement**)
3. APCP: DF even for circular process topologies (**advanced enforcement**)

Some Observations

- ▶ Asynchronous communication is the cleanest setting to study DF by typing
- ▶ Asynchrony unblocks behaviors / session types constrain behaviors
- ▶ Asynchronous sessions “in between” untyped synchrony and asynchrony: (output) actions from different sessions are independent, but (output) actions within a session should respect their session type.

Today We overview DF enforcement in three typed asynchronous π -calculi:

1. AP: processes follow protocols but ‘happily deadlock’ (**no DF enforcement**)
2. ACP: DF by typing for tree-like process topologies (**basic enforcement**)
3. APCP: DF even for circular process topologies (**advanced enforcement**)

Full details: Our LMCS and ICE’24 papers.

Session Processes and Deadlocks

Process Syntax

$P, Q ::= x[a, b]$	send		$x(y, z); P$	receive
$x[b] \triangleleft j$	selection		$x(z) \triangleright \{i : P\}_{i \in I}$	branch
$P \mid Q$	parallel		$(\nu xy)P$	restriction
0	inaction		$[x \leftrightarrow y]$	forwarder

Process Syntax

$P, Q ::= x[a, b]$	send		$x(y, z); P$	receive
$x[b] \triangleleft j$	selection		$x(z) \triangleright \{i : P\}_{i \in I}$	branch
$P \mid Q$	parallel		$(\nu xy)P$	restriction
0	inaction		$[x \leftrightarrow y]$	forwarder

Conventions:

- ▶ We write $a, b, c, \dots, x, y, z, \dots$ to denote **names** (or **endpoints**)
- ▶ Early letters of the alphabet denote **objects** of output-like constructs.
- ▶ We write $\tilde{x}, \tilde{y}, \tilde{z}, \dots$ to denote finite sequences of names.

Reduction

[red-send-recv]

$$\frac{}{(\nu xy)(x[a, b] \mid y(a', b'); Q) \longrightarrow Q\{a/a', b/b'\}}$$

Reduction

[red-send-recv]

$$\frac{}{(\nu xy)(x[a, b] \mid y(a', b'); Q) \longrightarrow Q\{a/a', b/b'\}}$$

[red-sel-bra]

$$\frac{j \in I}{(\nu xy)(x[b] \triangleleft j \mid y(b') \triangleright \{i : Q_i\}_{i \in I}) \longrightarrow Q_j\{b/b'\}}$$

Reduction

[red-send-recv]

$$\frac{}{(\nu xy)(x[a, b] \mid y(a', b'); Q) \longrightarrow Q\{a/a', b/b'\}}$$

[red-sel-bra]

$$\frac{j \in I}{(\nu xy)(x[b] \triangleleft j \mid y(b') \triangleright \{i : Q_i\}_{i \in I}) \longrightarrow Q_j\{b/b'\}}$$

[red-fwd]

$$\frac{y \neq z}{(\nu xy)([x \leftrightarrow z] \mid P) \longrightarrow P\{z/y\}}$$

Reduction

[red-send-recv]

$$\frac{}{(\nu xy)(x[a, b] \mid y(a', b'); Q) \longrightarrow Q\{a/a', b/b'\}}$$

[red-sel-bra]

$$\frac{j \in I}{(\nu xy)(x[b] \triangleleft j \mid y(b') \triangleright \{i : Q_i\}_{i \in I}) \longrightarrow Q_j\{b/b'\}}$$

[red-fwd]

$$\frac{y \neq z}{(\nu xy)([x \leftrightarrow z] \mid P) \longrightarrow P\{z/y\}}$$

[red-sc]

$$\frac{P \equiv P' \quad P' \longrightarrow P' \quad Q' \equiv Q}{P \longrightarrow Q}$$

[red-res]

$$\frac{P \longrightarrow Q}{(\nu xy)P \longrightarrow (\nu xy)Q}$$

[red-par]

$$\frac{P \longrightarrow Q}{P \mid R \longrightarrow Q \mid R}$$

Derived Constructs / Syntactic Sugar

$$\overline{x}[y] \cdot P \triangleq (\nu ya)(\nu zb)(x[a, b] \mid P\{z/x\})$$

$$x(y); P \triangleq x(y, z); P\{z/x\}$$

$$\overline{x} \triangleleft \ell \cdot P \triangleq (\nu zb)(x[b] \triangleleft \ell \mid P\{z/x\})$$

$$x \triangleright \{i : P_i\}_{i \in I} \triangleq x(z) \triangleright \{i : P_i\{z/x\}\}_{i \in I}$$

Note: We use ‘.’ to signify that output-like operations are non blocking.

Continuations Induce Protocols

$$P \triangleq (\nu zu) \Big((\nu xy) \Big((\nu ax') (x[v_1, a] \mid x'[v_2, b]) \\ \mid (\nu cz') (z[v_3, c] \mid y(w_1, y'); y'(w_2, y''); Q) \Big) \\ \mid u(w_3, u'); R \Big)$$

Continuations Induce Protocols

$$P \triangleq (\nu zu) \Big((\nu xy) \Big((\nu ax') (x[v_1, a] \mid x'[v_2, b]) \\ \mid (\nu cz') (z[v_3, c] \mid y(w_1, y'); y'(w_2, y''); Q) \Big) \\ \mid u(w_3, u'); R \Big)$$

Or, using the sugared syntax:

$$P = (\nu zu) ((\nu xy) (\bar{x}[v_1] \cdot \bar{x}[v_2] \cdot 0 \mid \bar{z}[v_3] \cdot y(w_1); y(w_2); Q') \mid u(w_3); R')$$

where $Q' \triangleq Q\{y/y''\}$ and $R' \triangleq R\{u/u'\}$.

Continuations Induce Protocols

$$P \triangleq (\nu zu) \Big((\nu xy) \Big((\nu ax') (x[v_1, a] \mid x'[v_2, b]) \\ \mid (\nu cz') (z[v_3, c] \mid y(w_1, y'); y'(w_2, y''); Q) \Big) \\ \mid u(w_3, u'); R \Big)$$

Or, using the sugared syntax:

$$P = (\nu zu) ((\nu xy) (\bar{x}[v_1] \cdot \bar{x}[v_2] \cdot 0 \mid \bar{z}[v_3] \cdot y(w_1); y(w_2); Q') \mid u(w_3); R')$$

where $Q' \triangleq Q\{y/y''\}$ and $R' \triangleq R\{u/u'\}$.

We have:

$$P \longrightarrow (\nu zu) ((\nu xy) (\bar{x}[v_2] \cdot 0 \mid \bar{z}[v_3] \cdot y(w_2); Q'\{v_1/w_1\}) \mid u(w_3); R') \\ P \longrightarrow (\nu xy) (\bar{x}[v_1] \cdot \bar{x}[v_2] \cdot 0 \mid y(w_1); y(w_2); Q') \mid R'\{v_3/w_3\}$$

Note: There is no reduction involving the send on x' : because x' is connected to the continuation of the send on x , it is thus not (yet) paired with a dual receive.

A Deadlocked Process

The “hello world” of deadlocked message-passing processes:

$$(\nu xy)(\nu uw)(x(v, x'); u[a, b] \mid w(z, w'); y[c, d])$$

Process is stuck:

- ▶ The input on x is waiting for the right output on y ...
- ▶ ...the output on y is blocked by a receive (on w) waiting for the left output on u , which is blocked by the input on x .

A Deadlocked Process

The “hello world” of deadlocked message-passing processes:

$$(\nu xy)(\nu uw)(x(v, x'); u[a, b] \mid w(z, w'); y[c, d])$$

Process is stuck:

- ▶ The input on x is waiting for the right output on y ...
- ▶ ...the output on y is blocked by a receive (on w) waiting for the left output on u , which is blocked by the input on x .

In other words, there is a **cyclic dependency** between the two threads.

Session Types

Types correspond to propositions in Linear Logic:

$A, B ::= A \otimes B$	send		$A \wp B$	receive
$\oplus\{i : A\}_{i \in I}$	selection		$\&\{i : A\}_{i \in I}$	branching
\bullet	closed protocol			

Session Types

Types correspond to propositions in Linear Logic:

$A, B ::= A \otimes B$	send		$A \wp B$	receive
$\oplus\{i : A\}_{i \in I}$	selection		$\&\{i : A\}_{i \in I}$	branching
\bullet	closed protocol			

The **dual** of session type A , denoted \overline{A} :

$$\begin{array}{lll}
 \overline{A \otimes B} \triangleq \overline{A} \wp \overline{B} & \overline{\oplus\{i : A_i\}_{i \in I}} \triangleq \&\{i : \overline{A_i}\}_{i \in I} & \overline{\bullet} \triangleq \bullet \\
 \overline{A \wp B} \triangleq \overline{A} \otimes \overline{B} & \overline{\&\{i : A_i\}_{i \in I}} \triangleq \oplus\{i : \overline{A_i}\}_{i \in I} &
 \end{array}$$

Typing Judgments

Judgments are of the form

$$P \vdash \Gamma$$

where

- ▶ P is a process
- ▶ Γ records endpoint/protocol assignments of the form $x : A$.

Typing Judgments

Judgments are of the form

$$P \vdash \Gamma$$

where

- ▶ P is a process
- ▶ Γ records endpoint/protocol assignments of the form $x : A$.

Γ disallows

- ▶ *weakening* (all assignments must be used, except names typed with \bullet)
- ▶ *contraction* (assignments may not be duplicated).

but obeys *exchange* (assignments may be silently reordered).

The empty context is written \emptyset .

AP: Typing Rules

[typ-send]

$$\frac{}{x[a, b] \vdash x : A \otimes B, a : \overline{A}, b : \overline{B}}$$

[typ-recv]

$$\frac{P \vdash \Gamma, y : A, z : B}{x(y, z); P \vdash \Gamma, x : A \wp B}$$

AP: Typing Rules

[typ-send]

$$\frac{}{x[a, b] \vdash x : A \otimes B, a : \overline{A}, b : \overline{B}}$$

[typ-recv]

$$\frac{P \vdash \Gamma, y : A, z : B}{x(y, z); P \vdash \Gamma, x : A \wp B}$$

[typ-par]

$$\frac{P \vdash \Gamma \quad Q \vdash \Delta}{P \mid Q \vdash \Gamma, \Delta}$$

[typ-res]

$$\frac{P \vdash \Gamma, x : A, y : \overline{A}}{(\nu xy)P \vdash \Gamma}$$

AP: Typing Rules

[typ-send]

$$\frac{}{x[a, b] \vdash x : A \otimes B, a : \overline{A}, b : \overline{B}}$$

[typ-recv]

$$\frac{P \vdash \Gamma, y : A, z : B}{x(y, z); P \vdash \Gamma, x : A \wp B}$$

[typ-par]

$$\frac{P \vdash \Gamma \quad Q \vdash \Delta}{P \mid Q \vdash \Gamma, \Delta}$$

[typ-res]

$$\frac{P \vdash \Gamma, x : A, y : \overline{A}}{(\nu xy)P \vdash \Gamma}$$

[typ-sel]

$$\frac{j \in I}{x[b] \triangleleft j \vdash x : \oplus\{i : A_i\}_{i \in I}, b : \overline{A_j}}$$

[typ-bra]

$$\frac{\forall i \in I : P_i \vdash \Gamma, z : A_i}{x(z) \triangleright \{i : P_i\}_{i \in I} \vdash \Gamma, x : \&\{i : A_i\}_{i \in I}}$$

[typ-fwd]

$$\frac{}{[x \leftrightarrow y] \vdash x : \overline{A}, y : A}$$

[typ-end]

$$\frac{P \vdash \Gamma}{P \vdash \Gamma, x : \bullet}$$

[typ-inact]

$$\frac{}{0 \vdash \emptyset}$$

Properties of AP

Well-typed processes respect their session protocols under reduction:

Theorem (Type Preservation for AP)

Given $P \vdash \Gamma$ and Q such that $P \equiv Q$ or $P \longrightarrow Q$, we have $Q \vdash \Gamma$.

Deadlocks are Typable in AP

Recall the process

$$(\nu xy)(\nu uw)(x(v, x'); u[a, b] \mid w(z, w'); y[c, d])$$

It can be typed as follows:

$$\begin{array}{c}
 \frac{u[a, b] \vdash u : \bullet \otimes \bullet, a : \bullet, b : \bullet}{u[a, b] \vdash u : \bullet \otimes \bullet,} \text{[typ-end]}^2 \\
 \frac{u[a, b] \vdash u : \bullet \otimes \bullet, \quad v : \bullet, x' : \bullet, a : \bullet, b : \bullet}{x(v, x'); u[a, b] \vdash x : \bullet \wp \bullet, \quad u : \bullet \otimes \bullet, \quad a : \bullet, b : \bullet} \text{[typ-recv]} \\
 \frac{x(v, x'); u[a, b] \vdash x : \bullet \wp \bullet, \quad u : \bullet \otimes \bullet, \quad a : \bullet, b : \bullet \quad \quad \quad w(z, w'); y[c, d] \vdash w : \bullet \wp \bullet, \quad y : \bullet \otimes \bullet, \quad c : \bullet, d : \bullet}{x(v, x'); u[a, b] \mid w(z, w'); y[c, d] \vdash x : \bullet \wp \bullet, u : \bullet \otimes \bullet, a : \bullet, b : \bullet, \quad w : \bullet \wp \bullet, y : \bullet \otimes \bullet, c : \bullet, d : \bullet} \text{[typ-par]} \\
 \frac{x(v, x'); u[a, b] \mid w(z, w'); y[c, d] \vdash x : \bullet \wp \bullet, u : \bullet \otimes \bullet, a : \bullet, b : \bullet, \quad w : \bullet \wp \bullet, y : \bullet \otimes \bullet, c : \bullet, d : \bullet}{(\nu xy)(\nu uw)(x(v, x'); u[a, b] \mid w(z, w'); y[c, d]) \vdash a : \bullet, b : \bullet, c : \bullet, d : \bullet} \text{[typ-res]}^2
 \end{array}$$

Enforcing Deadlock Freedom

ACP: Asynchronous CP

- ▶ An asynchronous variant of Wadler's Classical Processes (CP).

ACP: Asynchronous CP

- ▶ An asynchronous variant of Wadler's Classical Processes (CP).
- ▶ Obtained from AP by a minor yet crucial modification.
 - Replace:

$$\frac{P \vdash \Gamma \quad Q \vdash \Delta}{P \mid Q \vdash \Gamma, \Delta} [\text{typ-par}] \qquad \frac{P \vdash \Gamma, x : A, y : \bar{A}}{(\nu xy)P \vdash \Gamma} [\text{typ-res}]$$

+ Add:

$$\boxed{\frac{P \vdash \Gamma, x : A \quad Q \vdash \Delta, y : \bar{A}}{(\nu xy)(P \mid Q) \vdash \Gamma, \Delta} [\text{typ-cut}]}$$

ACP: Asynchronous CP

- ▶ An asynchronous variant of Wadler's Classical Processes (CP).
- ▶ Obtained from AP by a minor yet crucial modification.
 - Replace:

$$\frac{P \vdash \Gamma \quad Q \vdash \Delta}{P \mid Q \vdash \Gamma, \Delta} [\text{typ-par}] \qquad \frac{P \vdash \Gamma, x : A, y : \overline{A}}{(\nu xy)P \vdash \Gamma} [\text{typ-res}]$$

+ Add:

$$\boxed{\frac{P \vdash \Gamma, x : A \quad Q \vdash \Delta, y : \overline{A}}{(\nu xy)(P \mid Q) \vdash \Gamma, \Delta} [\text{typ-cut}]}$$

- ▶ ACP guarantees DF by ruling out all possible cyclic dependencies: sub-processes can connect along **exactly one pair of names**.

ACP: Asynchronous CP

- ▶ An asynchronous variant of Wadler's Classical Processes (CP).
- ▶ Obtained from AP by a minor yet crucial modification.
 - Replace:

$$\frac{P \vdash \Gamma \quad Q \vdash \Delta}{P \mid Q \vdash \Gamma, \Delta} [\text{typ-par}] \qquad \frac{P \vdash \Gamma, x : A, y : \overline{A}}{(\nu xy)P \vdash \Gamma} [\text{typ-res}]$$

+ Add:

$$\boxed{\frac{P \vdash \Gamma, x : A \quad Q \vdash \Delta, y : \overline{A}}{(\nu xy)(P \mid Q) \vdash \Gamma, \Delta} [\text{typ-cut}]}$$

- ▶ ACP guarantees DF by ruling out all possible cyclic dependencies: sub-processes can connect along **exactly one pair of names**.
- ▶ We write $\textcolor{blue}{c}\vdash$ instead of \vdash to distinguish the two type systems.

The Deadlocked Process, Revisited

- The deadlocked process

$$(\nu xy)(\nu uw)(x(v, x'); u[a, b] \mid w(z, w'); y[c, d])$$

is not typable under $\textcolor{blue}{c}\vdash$:

its parallel sub-processes are connected on two pairs of names.

The Deadlocked Process, Revisited

- ▶ The deadlocked process

$$(\nu xy)(\nu uw)(x(v, x'); u[a, b] \mid w(z, w'); y[c, d])$$

is not typable under $\textcolor{blue}{c}\vdash$:

its parallel sub-processes are connected on two pairs of names.

- ▶ A well-typed variant, obtained by ‘parallelizing’ the right sub-process:

$$(\nu xy)\big((\nu uw)(x(v, x'); u[a, b] \mid w(z, w'); 0) \mid y[c, d]\big) \textcolor{blue}{c}\vdash \begin{array}{l} a : \bullet, b : \bullet, \\ c : \bullet, d : \bullet \end{array}$$

Properties of ACP

As in AP, well-typed processes respect their protocols:

Theorem (Type Preservation for ACP)

Given $P \text{ }^c\vdash \Gamma$ and Q such that $P \text{ }^c\equiv Q$ or $P \text{ }^c\longrightarrow Q$, we have $Q \text{ }^c\vdash \Gamma$.


Thanks to the cut rule, we now also have:

Theorem (Deadlock Freedom for ACP)

Given $P \text{ }^c\vdash \emptyset$, if $P \text{ }^c\not\rightarrow$, then $P \text{ }^c\equiv 0$.

Not Typable in ACP: Milner's Cyclic Scheduler

$$\begin{aligned}
 &(\nu c_1 d_1) \cdots (\nu c_6 d_6) \Big((\nu a_1 b_1)(A_1 \mid P_1) \mid \\
 &\quad (\nu a_2 b_2)(A_2 \mid P_2) \mid \\
 &\quad \vdots \\
 &\quad (\nu a_6 b_6)(A_6 \mid P_6) \Big)
 \end{aligned}$$



Can We Get It All?

DF in Circular Topologies

APCP: Priority-Based DF Enforcement

Asynchronous **Priority-Based** Classical Processes:

- ▶ Back to **separate rules** for parallel composition and restriction (as in AP)
- ▶ Excluding cyclic dependencies using **priorities**

APCP: Priority-Based DF Enforcement

- ▶ We write π, ρ, \dots to denote priorities (integers).
We write ω to denote the ‘ultimate priority’: it is greater than all other priorities and cannot be increased further.

APCP: Priority-Based DF Enforcement

- ▶ We write π, ρ, \dots to denote priorities (integers).
We write ω to denote the ‘ultimate priority’: it is greater than all other priorities and cannot be increased further.
- ▶ Types are as before, now annotated with priorities:

$$A, B ::= A \otimes^{\pi} B \mid A \wp^{\pi} B \mid \oplus^{\pi} \{i : A\}_{i \in I} \mid \&^{\pi} \{i : A\}_{i \in I} \mid \bullet$$

APCP: Priority-Based DF Enforcement

- ▶ We write π, ρ, \dots to denote priorities (integers).
We write ω to denote the ‘ultimate priority’: it is greater than all other priorities and cannot be increased further.
- ▶ Types are as before, now annotated with priorities:

$$A, B ::= A \otimes^{\pi} B \mid A \wp^{\pi} B \mid \oplus^{\pi} \{i : A\}_{i \in I} \mid \&^{\pi} \{i : A\}_{i \in I} \mid \bullet$$

- ▶ For session type A , $pr(A)$ denotes its *priority*:

$$\begin{aligned} pr(A \otimes^{\pi} B) &\triangleq pr(A \wp^{\pi} B) \triangleq pr(\oplus^{\pi} \{i : A_i\}_{i \in I}) \triangleq pr(\&^{\pi} \{i : A_i\}_{i \in I}) \triangleq \pi \\ pr(\bullet) &\triangleq \omega \end{aligned}$$

APCP: Priority-Based DF Enforcement

- ▶ We write π, ρ, \dots to denote priorities (integers).
We write ω to denote the ‘ultimate priority’: it is greater than all other priorities and cannot be increased further.
- ▶ Types are as before, now annotated with priorities:

$$A, B ::= A \otimes^{\pi} B \mid A \wp^{\pi} B \mid \oplus^{\pi} \{i : A\}_{i \in I} \mid \&^{\pi} \{i : A\}_{i \in I} \mid \bullet$$

- ▶ For session type A , $pr(A)$ denotes its *priority*:

$$\begin{aligned} pr(A \otimes^{\pi} B) &\triangleq pr(A \wp^{\pi} B) \triangleq pr(\oplus^{\pi} \{i : A_i\}_{i \in I}) \triangleq pr(\&^{\pi} \{i : A_i\}_{i \in I}) \triangleq \pi \\ pr(\bullet) &\triangleq \omega \end{aligned}$$

- ▶ Duality: $A = \overline{B}$ iff (i) actions in A and B are complementary (as before) and (ii) their priority annotations coincide.

The Laws of Priorities

Key Idea

Prefixes with **lower priority** must not be blocked by prefixes with **higher priority**.

The Laws of Priorities

Key Idea

Prefixes with **lower priority** must not be blocked by prefixes with **higher priority**.

Typing enforces the following laws:

1. Outputs with priority π must have messages and continuations with priority **strictly larger** than π ;
2. A prefix typed with priority π must be prefixed only by inputs with priority **strictly smaller** than π ;
3. Dual prefixes leading to a synchronization must have **equal priorities**.

Typing rules of APCP: AP with Priorities

[typ-send]

$$\frac{\pi < pr(A), pr(B)}{x[y, z] \text{ } ^P\vdash x : A \otimes^\pi B, y : \overline{A}, z : \overline{B}}$$

[typ-recv]

$$\frac{P \text{ } ^P\vdash \Gamma, y : A, z : B \quad \pi < pr(\Gamma)}{x(y, z); P \text{ } ^P\vdash \Gamma, x : A \wp^\pi B}$$

Typing rules of APCP: AP with Priorities

[typ-send]

$$\frac{\pi < pr(A), pr(B)}{x[y, z] \textcolor{blue}{^P} \vdash x : A \otimes^\pi B, y : \overline{A}, z : \overline{B}}$$

[typ-recv]

$$\frac{P \textcolor{blue}{^P} \vdash \Gamma, y : A, z : B \quad \pi < pr(\Gamma)}{x(y, z); P \textcolor{blue}{^P} \vdash \Gamma, x : A \wp^\pi B}$$

[typ-sel]

$$\frac{j \in I \quad \pi < pr(A_j)}{x[z] \triangleleft j \textcolor{blue}{^P} \vdash x : \oplus^\pi \{i : A_i\}_{i \in I}, z : \overline{A_j}}$$

[typ-bra]

$$\frac{\forall i \in I : P_i \textcolor{blue}{^P} \vdash \Gamma, z : A_i \quad \pi < pr(\Gamma)}{x(z) \triangleright \{i : P_i\}_{i \in I} \textcolor{blue}{^P} \vdash \Gamma, x : \&^\pi \{i : A_i\}_{i \in I}}$$

(Other rules unchanged, with the extended duality)

Properties of APCP

Theorem (Type Preservation for APCP)

Given $P \text{ }^P\vdash \Gamma$ and Q such that $P \equiv Q$ or $P \longrightarrow Q$, we have $Q \text{ }^P\vdash \Gamma$.

Theorem (Deadlock Freedom for APCP)

Given $P \text{ }^P\vdash \emptyset$, if $P \not\rightarrow$, then $P \equiv 0$.

Properties of APCP

Theorem (Type Preservation for APCP)

Given $P \text{ }^{\text{p}}\vdash \Gamma$ and Q such that $P \equiv Q$ or $P \longrightarrow Q$, we have $Q \text{ }^{\text{p}}\vdash \Gamma$.

Theorem (Deadlock Freedom for APCP)

Given $P \text{ }^{\text{p}}\vdash \emptyset$, if $P \not\rightarrow$, then $P \equiv 0$.

Let \vdash , $\text{}^{\text{c}}\vdash$, and $\text{}^{\text{p}}\vdash$ denote **sets of well-typed processes** in AP, ACP, and APCP, respectively. We immediately have:

Theorem (Comparative Expressiveness)

We have $\text{}^{\text{c}}\vdash \subset \text{}^{\text{p}}\vdash \subset \vdash$.

Examples

- Recall the deadlocked process; it is rejected under $\mathbb{P} \vdash$:

$$(\nu xy)(\nu uw)(x(v, x'); u[a, b] \mid w(z, w'); y[c, d])$$

Suppose the actions on x , y have priority π , and that the actions on u , w have priority ρ . Using Rule [typ-recv] we require $\pi < \rho$ and $\rho < \pi$.

Examples

- ▶ Recall the deadlocked process; it is rejected under $\textcolor{blue}{P}\vdash$:

$$(\nu xy)(\nu uw)(x(v, x'); u[a, b] \mid w(z, w'); y[c, d])$$

Suppose the actions on x , y have priority π , and that the actions on u , w have priority ρ . Using Rule [typ-recv] we require $\pi < \rho$ and $\rho < \pi$.

- ▶ Recall the non-deadlocked variant:

$$(\nu xy)\big((\nu uw)(x(v, x'); u[a, b] \mid w(z, w'); 0) \mid y[c, d]\big)$$

In this case, $\textcolor{blue}{P}\vdash$ only requires $\pi < \rho$ but not $\rho < \pi$, so no cyclic dependency is detected—the process is considered well typed.

Application: DF in Concurrent Functional Sessions


LASTⁿ:
Concurrent functions
(can deadlock)

Application: DF in Concurrent Functional Sessions


LASTⁿ:
Concurrent functions
(can deadlock)




Application: DF in Concurrent Functional Sessions



Application: DF in Concurrent Functional Sessions



Application: DF in Concurrent Functional Sessions



Summing Up

Summary Three typed asynchronous π -calculi based on Linear Logic:

1. AP: processes correctly follow protocols but deadlock
2. ACP: AP with logic-based composition, DF for tree-like topologies
3. APCP: extension of AP with priorities, DF for circular topologies

Summing Up

Summary Three typed asynchronous π -calculi based on Linear Logic:

1. AP: processes correctly follow protocols but deadlock
2. ACP: AP with logic-based composition, DF for tree-like topologies
3. APCP: extension of AP with priorities, DF for circular topologies

Further Results

- ▶ Typed specification of the cyclic scheduler
- ▶ Processes with recursion and recursive session types (tail-recursive)
- ▶ Full treatment of LAST^n and its encoding into APCP
- ▶ Analysis of multiparty protocols with APCP

Summing Up

Summary Three typed asynchronous π -calculi based on Linear Logic:

1. AP: processes correctly follow protocols but deadlock
2. ACP: AP with logic-based composition, DF for tree-like topologies
3. APCP: extension of AP with priorities, DF for circular topologies

Further Results

- ▶ Typed specification of the cyclic scheduler
- ▶ Processes with recursion and recursive session types (tail-recursive)
- ▶ Full treatment of LAST^n and its encoding into APCP
- ▶ Analysis of multiparty protocols with APCP

Ongoing Work

- ▶ APCP extended with PCF-like servers (with J. Jaramillo and D. Mazza)
- ▶ Priority-based DF in FreeST (with A. Mordido)

Asynchronous Session-based Concurrency: Deadlock Freedom by Typing

Jorge A. Pérez
www.jperez.nl

University of Groningen, The Netherlands

Dutch Winter School 2026
(Part 3)