

# Emergent Architecture Design

Computer Games Contextproject 2015-2016  
Course TI2806, Delft University of Technology

Group PixelPerfect

April 28, 2016

## Supervisor

Dr. ir. Rafael Bidarra

## Teaching Assistants

Sander van den Oever

Jurgen van Schagen

## Team

David Alderliesten	4368703	<i>J.W.D.Alderliesten@student.tudelft.nl</i>
Floris Doolaard	4362748	<i>F.P.Doolaard@student.tudelft.nl</i>
Dmitry Malarev	4345274	<i>D.R.Malarev@student.tudelft.nl</i>
Jesse Tilro	4368142	<i>J.Tilro@student.tudelft.nl</i>
Wouter Zirkzee	4398858	<i>W.J.Zirkzee@student.tudelft.nl</i>

# Table of Contents

Introduction

Architectural Views

Subsystem Decomposition

Hardware & Software Mapping

UML System Design

Persistent & Session Data Management

Concurrency

# Introduction

Pixelperfect was assembled during the fourth quarter of the academic year of 2015-2016 for the Context Project course of the Computer Science bachelor program at the Delft University of Technology. The team consists of five members and was assigned to design, develop, and release a virtual reality game for the Oculus Rift platform.

The project requires an array of specialized hardware devices in order to be played, including a virtual reality headset called the “Oculus Rift” which is at the heart of the software product. The connectivity between the other participants of the game on their phones or devices and the dependability of the game on the motion tracking hardware makes for a tough challenge which will be solved using [TECHNOLOGY]. The continuous interdependability is outlined in this document and was at the core focus of the design for the game.


The focus of the design of the system architecture was to find a balance between performance, reliability, and manageability. The performance of the system was crucial due to the interdependability between the Oculus Rift player and all the mobile players, who must be able to reliably communicate during time-restricted moments of the game. The reliability refers to the reliability of the connections and interactions between the players, which must be stable to allow for a simple implementation and to prevent frustration during the act of connecting of the players. The maintainability is of the essence for the maintenance of the project, which must be advanced enough to offer a rich experience to the player, yet maintainable for the programmers to prevent bloat and clutter.

This document outlines the decision made for the software project with regards to the subsystem decomposition, the mapping of hardware and software, the method utilized for the storage of data, and how concurrency in systems is handled. A glossary can be found at the end of the document outlining certain important terms for the project.

# Architectural Views

## Subsystem Decomposition


The game runs on JMonkeyEngine, and relies on the Android mobile OS libraries and the OpenVR integration library to display the relevant game data and interactions on the phone and Oculus Rift, respectively. Verbal communication occurs between the players of the game, regardless of their hardware. In the subsystem decomposition diagram, integration systems are shown in red, the engine is shown in blue, and players and their hardware is shown as yellow.



## Hardware & Software Mapping

The peripherals required for the project are the Oculus Rift virtual reality system, the mobile devices used by the other players, and a central computer that acts as the processor for the Oculus Rift and the central access point for the other players. The Oculus client handles the game data and displays the 3D cockpit

interface on the Oculus Rift. The Mobile Client takes selected game data (active events, game score, ship health) and displays the score and health on the UI, and allows the players to perform actions associated to their chosen role in order to complete the events. The Android OS is responsible for the engine to phone integration, while the OpenVR library is responsible for the engine to VR integration.



As can be seen, the Oculus Rift player's device acts as a type of server for the game session, and the mobile devices act as clients which connect to the server through the use of a LAN. Connection is done by having the mobile clients connect to the server using the local IP address of the server.

## UML System Design

The project contains the following interactions between the classes and their subsystems.



where multiple completions to incompatible mini-games results in ship damage and perhaps even game loss.

Concurrency control also exists within the game engine and handling devices to ensure that the multiplayer/networking, graphical updates, game logic, and game audio can all be updated and displayed/shown/function as required without interruptions occurring to any of them due to a lack of suitable concurrency.

A final location in which concurrency control exists is within the synchronization of the oculus client and the mobile clients. Sockets within the operating system are triggered by interrupts from the mobile client, which allow the game to both send and receive relevant game data in order to remain synchronized with the master client.