

Seven-Eleven / Musashino

Production Facility Study

Effectiveness measurement at a designated dietary production facility operated by Musashino Corporation, a Seven-Eleven supply manufacturer. Dr.Fry ProWave™ installed on commercial fryer lines; oil usage, absorption, and product calorie load measured against pre-installation baseline under live production volume.

OPERATOR	TEST CATEGORY	MEASUREMENT	MECHANISM
Musashino Corp. — Seven-Eleven designated production facility	Deep-fried & roast pork cutlet (tonkatsu) lines	Oil usage, absorption, calorie, prep time	50,000 Hz field — prevents oxidation at source

50,000Hz

Prevention, not filtration. The field acts *during* frying — so less oil enters the food and less degrades in the vat.


Every figure below: same facility · baseline vs. Dr.Fry · live production volume

MEASURED RESULTS — BASELINE VS. DR.FRY

METRIC	BASELINE no Dr.Fry	WITH DR.FRY 50,000 Hz field	CHANGE
Oil usage FACILITY, PER PERIOD	2,158 _L	1,398 _L	−36% 760 L saved
Oil absorption DEEP-FRIED	100% reference	75% of baseline	−25%
Oil absorption ROAST PORK CUTLET	100% reference	60% of baseline	−40%
Calorie load DEEP-FRIED, /100G	290 _{kcal}	246 _{kcal}	−15%
Calorie load PORK CUTLET, /100G	396 _{kcal}	284 _{kcal}	−28%

OIL ABSORBED INTO FOOD — ROAST PORK CUTLET





Method. Baseline and Dr.Fry figures measured at the same Musashino facility under live production volume — not a controlled single-batch test. Absorption shown as share of baseline; calorie figures per 100g equivalent. *Source: Dr_Fry_SevenEleven_Factory.pdf*

DR.FRY PROWAVE™ — EVIDENCE ARCHITECTURE All Rights Reserved © Dr.Fry Japan Co., Ltd.