

# Custom Item Fields as XML Definitions

You can create XML definitions for custom item fields as SDF custom objects using SuiteCloud Development Framework (SDF). You can either create an `itemcustomfield` object in a SuiteCloud project or import a custom item field from a NetSuite account into a SuiteCloud project. For information about creating a custom item field in a NetSuite account, see the following:

- [Creating Custom Item Fields](#)
- [Field Type Descriptions for Custom Fields](#)

Add custom item fields to your item records to gather information specific to your business needs.

After an `itemcustomfield` object is deployed to an account, a custom item field is created. The field appears on the item records that you applied the object to. You can create custom item records in a NetSuite account or in your SuiteCloud IDE. For more information about creating custom item records, see [Creating Item Records](#).

## Setting Values on the itemcustomfield SDF Custom Object

Provide a readable script ID attribute by using the underscore followed by a meaningful name for the SDF custom object. NetSuite automatically adds a `custitem` prefix that indicates the type of field, for example, `custitem_mynewfield`.

The following fields are required for `itemcustomfield` objects:

- `label` - Specifies the label for the custom field. The `label` is the text that your users see as the name of the custom field when it is displayed on the record.
- `fieldtype` - Specifies the type of custom field. For more information about the possible values of `fieldtype`, see [generic\\_customfield\\_fieldtype](#).
- `selectrecordtype` (conditional) - Specifies the list or record that contains the items for the custom field. This field is required only when the `fieldtype` value is equal to `SELECT` or `MULTISELECT`.

The following XML definition example is a basic `itemcustomfield` object with the required fields:

```
1 <itemcustomfield scriptid="custitem_mynewfield">
2   ...
3   <fieldtype>SELECT</fieldtype>
4   <label>SAMPLE  ITEMCUSTOMFIELD</label>
5   <selectrecordtype>-112</selectrecordtype>
6   ...
7 </itemcustomfield>
```

Copy

For more information about possible fields for `itemcustomfield` objects, see [itemcustomfield](#).

If you include any SDF custom objects, files, or scripts in your fields, you must define the dependencies for them in your SuiteCloud project's manifest. For more information, see [SDF Custom Object Dependencies in SuiteApps](#).

To index a custom field to be included in global search, set the `globalsearch` field value to `T`. The `globalsearch` field can equal to `T` only if the following field conditions are met:

- `storevalue` equals to `T`
- `fieldtype` equals to one of the following:
  - `CURRENCY`
  - `FLOAT`
  - `EMAIL`
  - `TEXT`
  - `HELP`
  - `URL`
  - `INLINEHTML`
  - `INTEGER`
  - `PERCENT`
  - `PHONE`
  - `TEXTAREA`

**Warning:** You cannot index a custom field for global search if any of your `searchlevel` field values equal to `0`.

## Embedding Structured Fields Within an itemcustomfield SDF Custom Object

You can create custom filters for your custom field by embedding `customfieldfilter` structured fields within the `itemcustomfield` SDF custom object. You can also customize the default access that a role has to the custom field by embedding `roleaccess` structured fields within the object.

For more information about the possible fields to define for these structured fields, see the following:

- [Custom Field Filters](#)
- [Role Accesses](#)

To view a full XML definition example for an `itemcustomfield` object, see [Example of an itemcustomfield SDF Custom Object](#).

## Custom Field Filters

You can add custom field filters to a list/record or multiple select custom field to filter the choices available in that custom field on records and transactions. In SDF, you can use custom field filters by embedding `customfieldfilter` structured fields within a custom field object.

**Note:** Filtering can apply only when the `fieldtype` value of your custom field object is equal to `SELECT` or `MULTISELECT`. It does not apply to custom lists, meaning if you include `customfieldfilter` structured fields, your `selectrecordtype` value cannot equal a custom list scriptid.

`customfieldfilters` is the parent element and `customfieldfilter` is the child element. You can include multiple `customfieldfilter` child elements within the parent.

The `fldfilter` subfield specifies a standard field on the list/record that you entered for the `selectrecordtype` field. The `fldfilter` subfield is required. For more information about the supported fields and values for `customfieldfilter` structured fields, see [customfieldfilter](#).

When an object with a `customfieldfilter` structured field is deployed to a target account, the **Sourcing & Filtering** subtab of the custom field record is populated with the field values specified by the structured field. The choices available to users in a record or transaction for that custom field are tailored by the filter settings from the structured field.

Here is an example of a custom item field configuration page in NetSuite with filters set for the field:

Custom Item Field

Save

Cancel

Reset

Change ID

Apply to Forms

Actions

LABEL \*  
SAMPLE ITEMCUSTOMFIELD

PUBLISHER ID

APP ID

ID  
custitem\_sample\_itemcust

INTERNAL ID  
543

OWNER  
Larry Nelson

DESCRIPTION

MATRIX OPTION

TYPE  
List/Record

LIST/RECORD  
Account

☒ STORE VALUE

☐ USE ENCRYPTED FORMAT

☐ SHOW IN LIST

☐ GLOBAL SEARCH

☐ RECORD IS PARENT

☐ INACTIVE

Applies To

Display

Validation & Defaulting

Sourcing & Filtering

Access

Translation

History

SOURCE LIST

SOURCE FROM

SOURCE FILTER BY

FILTER USING \*  
Name

IS CHECKED  
contains

COMPARE TYPE  
paid

COMPARE VALUE TO  
equal

VALUE IS  
<Type & tab for single value>

IS NOT EMPTY

IS EMPTY

COMPARE TO FIELD

✓ Add

✕ Cancel

+ Insert

🗑 Remove

**Important:** If you change the field type or the list/record for a field that is used for sourcing or filtering on other custom fields, all sourcing and filtering based on the field is removed.

Additionally, you can define custom field filters in NetSuite. For more information, see [Setting Filtering Criteria](#).

### Example of a customfieldfilter Structured Field

The following XML definition example is a `customfieldfilter` structured field embedded within an `itemcustomfield` object whose `fieldtype` equals `SELECT`. After this object is deployed to the target account, a custom item field labeled `SAMPLE ITEMCUSTOMFIELD` appears on the **Main** tab of all Inventory item records. The `fldfiltercomparetype` equals `LIKE` and `fldfilterval` equals `paid`. Therefore, the field's dropdown list is filtered to display only accounts that contain 'paid' in the account name.

```
1 <itemcustomfield scriptid="custitem_sample_itemcust">
2   <appliestoinventory>T</appliestoinventory>
3   <fieldtype>SELECT</fieldtype>
4   <label>SAMPLE ITEMCUSTOMFIELD</label>
5   <selectrecordtype>-112</selectrecordtype>
6   ...
7   <customfieldfilters>
8     <customfieldfilter>
9       <fldcomparefield></fldcomparefield>
10      <fldfilter>STDRECORDACCOUNTACCTNAME</fldfilter>
11      <fldfilterchecked></fldfilterchecked>
12      <fldfiltercomparetype>LIKE</fldfiltercomparetype>
13      <fldfilternotnull>F</fldfilternotnull>
14      <fldfilternull>F</fldfilternull>
15      <fldfiltersel></fldfiltersel>
16      <fldfilterval>paid>
17    </customfieldfilter>
18  </customfieldfilters>
19  ...
20 </itemcustomfield>
```

Copy

### Role Accesses

In SDF, you can control how roles access the information in custom fields by embedding `roleaccess` structured fields within a custom field object. The accesses that you specify determines how the custom field can be accessed on the record or through search results and reports. This helps you to maintain the security of your business information.

`roleaccesses` is the parent element and `roleaccess` is the child element. You can include multiple `roleaccess` child elements within the parent.

After an object with a `roleaccess` structured field is deployed to a NetSuite account, the **Role** section under the **Access** subtab of the custom field record is populated with the access level values of the fields specified by the structured field.

Here is an example of a custom item field configuration page in NetSuite with access levels set for a role:

The following subfields are required for roleaccess structured fields:

- `role` - Specifies the role.
- `accesslevel` - Specifies the access level granted to the role for the custom field object.

Possible access level values:

- 0 - None
- 1 - View
- 2 - Edit

- `searchlevel` - Specifies the access level granted to the role for the custom field object through search results and reports.

Possible access level values:

- 0 - None
- 1 - Run
- 2 - Edit

For more information about the supported fields and values for `roleaccess`, see [roleaccess](#).

Additionally, you can define role accesses to custom fields from a NetSuite account. For more information, see [Restricting Access to Custom Fields](#).

## Example of a roleaccess Structured Field

The following XML definition example is a `roleaccess` structured field embedded within a `itemcustomfield` object. In this example, the `accesslevel` for the Accountant role equals 1 and the `searchlevel` equals 1. Therefore, the role's access to the field is set to **View** and the access level through searching and reporting is set to **Run**.

```
1 <itemcustomfield scriptid="custitem_sample_itemcust">
2   <appliedtoinventory>T</appliedtoinventory>
3   <fieldtype>SELECT</fieldtype>
4   <label>SAMPLE_ITEMCUSTOMFIELD</label>
5   <selectrecordtype>-112</selectrecordtype>
6   ...
7   <roleaccesses>
8     <roleaccess>
9       <accesslevel>1</accesslevel>
10      <role>ACCOUNTANT</role>
11      <searchlevel>1</searchlevel>
12    </roleaccess>
13  </roleaccesses>
14  ...
15 </itemcustomfield>
```

[Copy](#)

## Example of an itemcustomfield SDF Custom Object

The following XML definition example is for an `itemcustomfield` SDF custom object. After this SDF custom object is deployed to the target account, a custom item field labeled `SAMPLE_ITEMCUSTOMFIELD` appears on the **Main** tab of all item records that the object is applied to. In this example, the object applies to inventory item records. The `fieldtype` equals `SELECT`. Therefore, a value for `selectrecordtype` is required.

```
<itemcustomfield scriptid="custitem_sample_itemcust">
  <accesslevel>2</accesslevel>
  <appliedtogroup>F</appliedtogroup>
  <appliedtoinventory>T</appliedtoinventory>
  <appliedtokit>F</appliedtokit>
  <appliedtononinventory>F</appliedtononinventory>
  <appliedtoothercharge>F</appliedtoothercharge>
  <appliedtopricelist>F</appliedtopricelist>
  <appliedtoservice>F</appliedtoservice>
  <appliedtospecificitems>F</appliedtospecificitems>
  <appliedtosubplan>F</appliedtosubplan>
  <applyformatting>F</applyformatting>
  <checkspelling>F</checkspelling>
  <defaultchecked>F</defaultchecked>
  <defaultselection></defaultselection>
  <defaultvalue></defaultvalue>
  <description>Sample description for field.</description>
  <displayheight></displayheight>
  <displaytype>NORMAL</displaytype>
  <displaywidth></displaywidth>
  <dynamicdefault></dynamicdefault>
  <encryptatrest>F</encryptatrest>
```

```

23 <fieldtype>SELECT</fieldtype>
24 <globalsearch>F</globalsearch>
25 <help>Enter a brief explanation of the kind of information you want entered in this field.</help>
26 <includechilditems>F</includechilditems>
27 <isformula>F</isformula>
28 <ismandatory>F</ismandatory>
29 <isparent>F</isparent>
30 <itemmatrix>F</itemmatrix>
31 <itemsubtype>BOTH</itemsubtype>
32 <label>SAMPLE ITEMCUSTOMFIELD</label>
33 <linktext></linktext>
34 <maxlength></maxlength>
35 <maxvalue></maxvalue>
36 <minvalue></minvalue>
37 <onparentdelete>NO_ACTION</onparentdelete>
38 <parentsubtab></parentsubtab>
39 <searchcomparefield></searchcomparefield>
40 <searchdefault></searchdefault>
41 <searchlevel>2</searchlevel>
42 <selectrecordtype>-112</selectrecordtype>
43 <showhierarchy>T</showhierarchy>
44 <showinlist>F</showinlist>
45 <sourcefilterby></sourcefilterby>
46 <sourcefrom></sourcefrom>
47 <sourcelist></sourcelist>
48 <storevalue>T</storevalue>
49 <subtab>ITEMMAIN</subtab>
50 <customfieldfilters>
51   <customfieldfilter>
52     <fldcomparefield></fldcomparefield>
53     <fldfilter>STDRECORDACCOUNTACCTNAME</fldfilter>
54     <fldfilterchecked></fldfilterchecked>
55     <fldfiltercomparetype>LIKE</fldfiltercomparetype>
56     <fldfilternotnull>F</fldfilternotnull>
57     <fldfilternull>F</fldfilternull>
58     <fldfiltersel></fldfiltersel>
59     <fldfilterval>paid>
60   </customfieldfilter>
61 </customfieldfilters>
62 <roleaccesses>
63   <roleaccess>
64     <accesslevel>1</accesslevel>
65     <role>ACCOUNTANT</role>
66     <searchlevel>1</searchlevel>
67   </roleaccess>
68 </roleaccesses>
69 </itemcustomfield>

```

## Related Topics