

Custom Item Number Fields as XML Definitions

You can create XML definitions of custom item number fields as SDF custom objects using SuiteCloud Development Framework (SDF). You can either create an `itemnumbercustomfield` object in a SuiteCloud project or import custom item number fields from a NetSuite account into a SuiteCloud project. For information about creating a custom item number field in a NetSuite account, see the following:

- [Creating Custom Item Number Fields](#)
- [Field Type Descriptions for Custom Fields](#)

Add custom item number fields to serialized or lot numbered inventory item records to track information specific to each item or workflow unique to your business. For example, you can track quality control procedures or recall information.

Prerequisites for Using Custom Item Number Fields

Before creating a custom item number field, complete the following tasks to ensure the field can be used in a target account. These tasks include:

1. [Enabling Serial Numbered Inventory](#) and [Lot Numbered Items](#).
To create serialized or lot numbered inventory items, enable both of the inventory features.
2. [Inventory Adjustments](#).
To enter new serial or lot numbers for serialized or lot numbered inventory items, enter an Inventory Adjustment. The quantity of serial or lot numbers entered must equal the quantity of the adjustment.
Adjust the inventory if the inventory item has a quantity on hand amount of zero.
3. [Advanced Bin / Numbered Inventory Management](#).
To edit the value of your custom item number field, you must enable the Advanced Bin /Numbered Inventory Management feature. The Advanced Bin / Numbered Inventory Management feature lets you to view an item's Inventory Detail subrecord, which contains the serial/lot number record.

Setting Values on the `itemnumbercustomfield` SDF Custom Object

Provide a readable script ID attribute by using the underscore followed by a meaningful name for the SDF custom object. NetSuite automatically adds a `customitemnumber` prefix that indicates the type of field, for example, `customitemnumber_mynewfield`

The following fields are required for `itemnumbercustomfield` objects:

- `label` - Specifies the label for the custom field. The `label` is the text that your users see as the name of the custom field when it is displayed on the record.
- `fieldtype` - Specifies the type of custom field. For more information about the possible values of `fieldtype`, see [generic_customfield_fieldtype](#).
- `selectrecordtype` (conditional) - Specifies the list or record that contains the items for the custom field. This field is required only when the `fieldtype` value is equal to `SELECT` or `MULTISELECT`.

The following XML definition example is a basic `itemnumbercustomfield` object with the required fields:

```
1 <itemnumbercustomfield scriptid="custitemnumber_mynewfield">
2   ...
3   <fieldtype>SELECT</fieldtype>
4   <label>SAMPLE ITEMNUMBERFIELD</label>
5   <selectrecordtype>-127</selectrecordtype>
6   ...
7 </itemnumbercustomfield>
```

[Copy](#)

For more information about possible fields for `itemnumbercustomfield` objects, see [itemnumbercustomfield](#).

Important: Your `appliesToAll` field can equal `T` if either `appliesToLots`, `appliesToSerialized`, or both are set to `T` as well. Otherwise, the `itemnumbercustomfield` object does not appear on the serial or lot number records.

If you include any SDF custom objects, files, or scripts in your fields, you must define the dependencies for them in your SuiteCloud project's manifest. For more information, see [SDF Custom Object Dependencies in SuiteApps](#).

After an `itemnumbercustomfield` object is deployed to an account, an item number field is created.

To apply the custom field to particular items, go to the object's item number field configuration page. Choose **Specific Items**. In the **Applies To** subtab, choose **Select Items to Apply Field** field, hold down the `Ctrl` key and click all the items you want this field to apply to, and click **Save**.

Here is an example of a custom item number field configuration page that applies to specific inventory items:

Item Number Field

SaveCancelResetChange IDActions

LABEL

SAMPLE ITEMNUMBERFIELD

PUBLISHER ID

APP ID

ID

custitemnumber_record_nbr

INTERNAL ID

544

OWNER

Larry Nelson

DESCRIPTION

Sample description for field.

TYPE

List/Record

LIST/RECORD

Tax Period

☒ STORE VALUE

☐ USE ENCRYPTED FORMAT

☐ SHOW IN LIST

☐ INACTIVE

Applies To

DisplayValidation & DefaultingSourcing & FilteringAccessTranslationHistory

SPECIFIC ITEMS

SELECT ITEMS TO APPLY FIELD

CARPETS/FLOORCOVERINGS : SAMPLE ITEMNAME 2

SAMPLE ITEMNAME

SAMPLE LOTITEM

Serialized-Test

±\$100 Gift Certificate

☐ ALL ITEMS

☐ SERIALIZED

☐ LOTS

☐ GIFT CERTIFICATE

SaveCancelResetChange IDActions

To view and edit the custom item number field, go to an inventory item record that has the custom field applied to it. On the **Inventory Detail** subtab, select a number under the **Serial/Lot Number** column. When you click a number, the serial or lot number record displays in a popup window. The field you created is included here.

Here is an example of a custom item number field included on a serial number record:

Serial Number Record

Edit

Back

Search Transactions

ITEM NAME

Serialized-Test

SERIAL/LOT NUMBER

1

STATUS

Available

MEMO

SAMPLE ITEMNUMBERFIELD
FY 2013 : Q4 2013 : Dec 2013

TEST 1

Note: In the NetSuite UI, the inventory detail subrecord also displays as a popup window on records and transaction forms when you click the **Inventory Detail** icon (📄 or 📄). On the popup window, click a number under the **Serial/Lot Number** column to display the serial or lot number record.

Embedding Structured Fields Within an itemnumbercustomfield SDF Custom Object

You can create custom filters for your custom field by embedding `customfieldfilter` structured fields within the `itemnumbercustomfield` SDF custom object. You can also customize the default access that a role has to the custom field by embedding `roleaccess` structured fields within the `itemnumbercustomfield` object.

For more information about the possible fields to define for these structured fields, see the following:

- [Custom Field Filters](#)
- [Role Accesses](#)

To view a full XML definition example for an `itemnumbercustomfield` object, see [Example of an itemnumbercustomfield SDF Custom Object](#).

Custom Field Filters

You can add custom field filters to a list/record or multiple select custom field to filter the choices available in that custom field on records and transactions. In SDF, you can use custom field filters by embedding `customfieldfilter` structured fields within a custom field object.

Note: Filtering can apply only when the `fieldtype` value of your custom field object is equal to `SELECT` or `MULTISELECT`. It does not apply to custom lists, meaning if you include `customfieldfilter` structured fields, your `selectrecordtype` value cannot equal a custom list scriptid.

`customfieldfilters` is the parent element and `customfieldfilter` is the child element. You can include multiple `customfieldfilter` child elements within the parent.

The `fldfilter` subfield specifies a standard field on the list/record that you entered for the `selectrecordtype` field. The `fldfilter` subfield is required. For more information about the supported fields and values for `customfieldfilter` structured fields, see [customfieldfilter](#).

When an object with a `customfieldfilter` structured field is deployed to a target account, the **Sourcing & Filtering** subtab of the custom field record is populated with the field values specified by the structured field. The choices available to users in a record or transaction for that custom field are tailored by the filter settings from the structured field.

Here is an example of a custom item field configuration page in NetSuite with filters set for the field:

Custom Item Field

Save

Cancel

Reset

Change ID

Apply to Forms

Actions

LABEL *
SAMPLE ITEMCUSTOMFIELD

PUBLISHER ID

APP ID

ID
custitem_sample_itemcust

INTERNAL ID
543

OWNER
Larry Nelson

DESCRIPTION

MATRIX OPTION

TYPE
List/Record

LIST/RECORD
Account

☒ STORE VALUE

☐ USE ENCRYPTED FORMAT

☐ SHOW IN LIST

☐ GLOBAL SEARCH

☐ RECORD IS PARENT

☐ INACTIVE

Applies To

Display

Validation & Defaulting

Sourcing & Filtering

Access

Translation

History

SOURCE LIST

SOURCE FROM

SOURCE FILTER BY

FILTER USING *
Name

IS CHECKED
contains

COMPARE TYPE
paid

COMPARE VALUE TO
equal

VALUE IS
<Type & tab for single value>

IS NOT EMPTY

IS EMPTY

COMPARE TO FIELD

✓ Add

✕ Cancel

+ Insert

Remove

Important: If you change the field type or the list/record for a field that is used for sourcing or filtering on other custom fields, all sourcing and filtering based on the field is removed.

Additionally, you can define custom field filters in NetSuite. For more information, see [Setting Filtering Criteria](#).

Example of a customfieldfilter Structured Field

The following XML definition example is a `customfieldfilter` structured field embedded within an `itemcustomfield` object whose `fieldtype` equals `SELECT`. After this object is deployed to the target account, a custom item field labeled `SAMPLE ITEMCUSTOMFIELD` appears on the **Main** tab of all Inventory item records. The `fldfiltercomparetype` equals `LIKE` and `fldfilterval` equals `paid`. Therefore, the field's dropdown list is filtered to display only accounts that contain 'paid' in the account name.

1

2

3

4

5

6

7

8

9

10

11

12

13

14

15

16

17

18

19

20

```
<itemcustomfield scriptid="custitem_sample_itemcust">
  <appliestoinventory>T</appliestoinventory>
  <fieldtype>SELECT</fieldtype>
  <label>SAMPLE ITEMCUSTOMFIELD</label>
  <selectrecordtype>-112</selectrecordtype>
  ...
  <customfieldfilters>
    <customfieldfilter>
      <fldcomparefield></fldcomparefield>
      <fldfilter>STDRECORDACCOUNTACCTNAME</fldfilter>
      <fldfilterchecked></fldfilterchecked>
      <fldfiltercomparetype>LIKE</fldfiltercomparetype>
      <fldfilternotnull>F</fldfilternotnull>
      <fldfilternull>F</fldfilternull>
      <fldfiltersel></fldfiltersel>
      <fldfilterval>paid>
    </customfieldfilter>
  </customfieldfilters>
  ...
</itemcustomfield>
```

Copy

Role Accesses

In SDF, you can control how roles access the information in custom fields by embedding `roleaccess` structured fields within a custom field object. The accesses that you specify determines how the custom field can be accessed on the record or through search results and reports. This helps you to maintain the security of your business information.

`roleaccesses` is the parent element and `roleaccess` is the child element. You can include multiple `roleaccess` child elements within the parent.

After an object with a `roleaccess` structured field is deployed to a NetSuite account, the **Role** section under the **Access** subtab of the custom field record is populated with the access level values of the fields specified by the structured field.

Here is an example of a custom item field configuration page in NetSuite with access levels set for a role:

The following subfields are required for roleaccess structured fields:

- `role` - Specifies the role.
- `accesslevel` - Specifies the access level granted to the role for the custom field object.

Possible access level values:

- 0 - None
- 1 - View
- 2 - Edit

- `searchlevel` - Specifies the access level granted to the role for the custom field object through search results and reports.

Possible access level values:

- 0 - None
- 1 - Run
- 2 - Edit

For more information about the supported fields and values for roleaccess, see [roleaccess](#).

Additionally, you can define role accesses to custom fields from a NetSuite account. For more information, see [Restricting Access to Custom Fields](#).

Example of a roleaccess Structured Field

The following XML definition example is a roleaccess structured field embedded within a itemcustomfield object. In this example, the accesslevel for the Accountant role equals 1 and the searchlevel equals 1. Therefore, the role's access to the field is set to **View** and the access level through searching and reporting is set to **Run**.

```
1 <itemcustomfield scriptid="custitem_sample_itemcust">
2   <appliedtoinventory>T</appliedtoinventory>
3   <fieldtype>SELECT</fieldtype>
4   <label>SAMPLE_ITEMCUSTOMFIELD</label>
5   <selectrecordtype>-112</selectrecordtype>
6   ...
7   <roleaccesses>
8     <roleaccess>
9       <accesslevel>1</accesslevel>
10      <role>ACCOUNTANT</role>
11      <searchlevel>1</searchlevel>
12    </roleaccess>
13  </roleaccesses>
14  ...
15 </itemcustomfield>
```

[Copy](#)

Example of an itemnumbercustomfield SDF Custom Object

The following XML definition example is for an itemnumbercustomfield SDF custom object. After this object is deployed to the target account, a custom item number field labeled SAMPLE_ITEMNUMBERFIELD appears on all serial and lot number records. The fieldtype equals SELECT. Therefore, a value for selectrecordtype is required.

```
<itemnumbercustomfield scriptid="custitemnumber_record_nbr">
  <accesslevel>2</accesslevel>
  <appliedtoallitems>T</appliedtoallitems>
  <appliedtogiftcerts>F</appliedtogiftcerts>
  <appliedtolots>T</appliedtolots>
  <appliedtoserialized>T</appliedtoserialized>
  <applyformatting>F</applyformatting>
  <checkspelling>F</checkspelling>
  <defaultchecked>F</defaultchecked>
  <defaultselection></defaultselection>
  <defaultvalue></defaultvalue>
  <description>Sample description for field.</description>
  <displayheight></displayheight>
  <displaytype>NORMAL</displaytype>
  <displaywidth></displaywidth>
  <dynamicdefault></dynamicdefault>
  <encryptatrest>F</encryptatrest>
  <fieldtype>SELECT</fieldtype>
  <help>Enter a brief explanation of the kind of information you want entered in this field.</help>
  <isformula>F</isformula>
  <ismandatory>F</ismandatory>
  <label>SAMPLE_ITEMNUMBERFIELD</label>
```

```

23 <linktext></linktext>
24 <maxlength></maxlength>
25 <maxvalue></maxvalue>
26 <minvalue></minvalue>
27 <onparentdelete>NO_ACTION</onparentdelete>
28 <searchcomparefield></searchcomparefield>
29 <searchdefault></searchdefault>
30 <searchlevel>2</searchlevel>
31 <selectrecordtype>-127</selectrecordtype>
32 <showhierarchy>T</showhierarchy>
33 <showinlist>F</showinlist>
34 <sourcefilterby></sourcefilterby>
35 <sourcefrom></sourcefrom>
36 <sourcelist></sourcelist>
37 <storevalue>T</storevalue>
38 <customfieldfilters>
39   <customfieldfilter>
40     <fldcomparefield></fldcomparefield>
41     <fldfilter>STDRECORDTAXPERIODPERIODNAME</fldfilter>
42     <fldfilterchecked></fldfilterchecked>
43     <fldfiltercomparetype>LIKE</fldfiltercomparetype>
44     <fldfilternotnull>F</fldfilternotnull>
45     <fldfilternull>F</fldfilternull>
46     <fldfiltersel></fldfiltersel>
47     <fldfilterval>2013</fldfilterval>
48   </customfieldfilter>
49 </customfieldfilters>
50 <roleaccesses>
51   <roleaccess>
52     <accesslevel>1</accesslevel>
53     <role>ACCOUNTANT</role>
54     <searchlevel>1</searchlevel>
55   </roleaccess>
56 </roleaccesses>
57 </itemnumbercustomfield>

```

Related Topics