The nacv class *

Jesse Knight †
April 22, 2023

Abstract

The *nacv* document class provides three basic features: a dates column, some tools for listing publications from a bib file, and some icons via *fontawesome* for contact info.

Contents

1	Usage	2
2	Implementation	3

 $[\]begin{tabular}{ll} *v0.1.0 [2023/04/22], & ctan.org/pkg/nacv, & github.com/jessexknight/ut-thesis \\ \end{tabular}$

[†]maintainer, contact: jesse.x.knight@protonmail.com

1 Usage

\documentclass[<options>]{nacv}

2 Implementation

```
1% options
2 \RequirePackage{kvoptions}
3 \SetupKeyvalOptions{family=nacv,prefix=nacv0}
4 \DeclareStringOption[Oex] {itemsep}
5 \DeclareStringOption[--]{datesep}
6 \DeclareStringOption[4em] {datewid}
7 \DeclareStringOption[1em] {dategap}
8 \DeclareStringOption[35mm] {margin}
9 \DeclareBoolOption[true] {bibnamebold}
10 \DeclareOption*{\PassOptionsToClass{\CurrentOption}{article}}
11 \ExecuteOptions{}
12 \ProcessKeyvalOptions*
13 \ProcessOptions\relax
14 \LoadClass{article}
15% packages
16 \RequirePackage[nomarginpar,margin=\nacv@margin] {geometry}
17 \RequirePackage{calc}
18 \RequirePackage{fontawesome5}
19% misc lengths
20 \setlength\parindent{0pt}
21\setlength\parskip{0pt}
22 \newlength\nacv@w@itemsep
23\setlength\nacv@w@itemsep{\nacv@itemsep}
24 \newlength\nacv@w@bullet
25% date lengths
26 \newlength\nacv@w@date
27 \newlength\nacv@w@datesep
28 \newlength\nacv@w@dategap
29 \newlength\nacv@w@datex
30 \newlength\nacv@w@afterdatex
31 \newcommand{\nacv@w@update}[1]{%
32 \setlength\nacv@w@datex{\dimexpr#1}%
33 \setlength\nacv@w@afterdatex{\dimexpr\linewidth-\nacv@w@datex-\nacv@w@dategap}}
34 \newcommand{\nodate}{\nacv@w@update{-\nacv@w@dategap}}
35 \newcommand{\onedate}{\nacv@w@update{\nacv@w@date}}
37 \AtBeginDocument{%
   \setlength\nacv@w@bullet{\widthof{\bulletsymbol}}%
   \setlength\nacv@w@date{\nacv@datewid}%
   \setlength\nacv@w@datesep{\widthof{\nacv@datesep}}%
41 \setlength\nacv@w@dategap{\nacv@dategap}%
42 \twodate}
43 % date boxes
44\newcommand{\ifempty}[3]{\if\relax\detokenize{#1}\relax#2\else#3\fi}
45 \newcommand{\datestr}[2]{\datestyle\strut%
46 \ifempty{#1}{\hfill#2}{#1\hfill\nacv@datesep\hfill#2}}
47 \newcommand{\datebox}[3]{%
48 \ifdim\nacv@w@datex<Opt\hskip\nacv@w@datex\fi%
49 \parbox[t]{\nacv@w@datex}{\datestr{#1}{#2}}%
50 \hskip\nacv@w@dategap%
51 \parbox[t]{\nacv@w@afterdatex}{\strut#3\strut}\par}
52 \newcommand{\dated}[4][\nacv@w@itemsep]{\par%
53 \addvspace{#1}\datebox{#2}{#3}{#4}\par}
54 \renewcommand{\bullet}[1][\nacv@w@itemsep]{\par%
```

```
55 \addvspace{#1}\hskip\dimexpr\nacv@w@datex+\nacv@w@dategap%
56 {\bulletsymbol}\hskip\labelsep\ignorespaces}
57% name & title
58 \newcommand{\name}[2]{
59 \gdef\nacv@name@given{#1}
60 \gdef\nacv@name@family{#2}}
61 \name{(First)}{(Last)}
62 \renewcommand{\title}[1]{
63 \gdef\nacv@title{#1}}
64 \title{(Title)}
65% contact info & icons
66 \newcommand{\nacv@contact@data}{}
67 \newcommand{\nacv@icon}[1]{%
68 \parbox{1em}{\centering\small\ifempty{#1}{~}{\faIcon{#1}}}}
69 \newcommand{\nacv@iconlink}[3]{%
70 \ifempty{#1}{#3~\nacv@icon{#2}}}{\href{#1#3}{#3~\nacv@icon{#2}}}}
71 \newcommand{\contact}[3][]{%
72 \g@addto@macro\nacv@contact@data{\nacv@iconlink{#1}{#2}{#3}\par}}
73% TODO: \contact*{site}{id} -> \contact[https://site.com]{site}{id}
74% https://tex.stackexchange.com/questions/4386
75% maketitle
76 \renewcommand{\maketitle}{%
    \thispagestyle{empty}%
77
    \parbox[t]{\textwidth}{%
78
       {\namestyle\nacv@name@given~\nacv@name@family}\par%
80
      \addvspace{1ex}%
      {\titlestyle\nacv@title}\par}%
82 \hspace{-\textwidth}%
83 \parbox[t]{\textwidth}{%
      \raggedleft\contactstyle\nacv@contact@data\par}}
85% bib stuff
86 \RequirePackage[
87 backend=biber,
88 sorting=symd,
89 style=numeric,
90 defernumbers=true,
91]{biblatex}
92 \DeclareSortingTemplate{symd}{
93 \sort[direction=descending]{\field{sortyear}\field{year}}
94 \sort[direction=descending]{\field{month}}
95 \sort[direction=descending]{\field{day}}}
96 \newcommand{\nacv@mkbibname}[1]{\ifthenelse{%
97 \equal{\nacv@name@given}{\namepartgiven} \AND
98 \equal{\nacv@name@family}{\namepartfamily} \AND
    \boolean{nacv@bibnamebold}}%
100 {\mkbibbold{#1}}{#1}}
101 \let\mkbibnamegiven\nacv@mkbibname
102 \let\mkbibnamefamily\nacv@mkbibname
103 \setlength{\biblabelsep}{\labelsep}
{\tt 104 \backslash DeclareFieldFormat\{labelnumberwidth\}\{\#1\backslash adddot\backslash hfill\}}
105 \newcommand{\publications}[2][]{\nocite{#1}\par%
   \addvspace{\nacv@w@itemsep}%
107 \printbibliography[resetnumbers=true,heading=none,#2]}
108 % hyperref hack: https://tex.stackexchange.com/questions/484088
109 \AtEndOfClass{\ifx\ver@hyperref\relax\else\newcommand{\href}[2]{#2}\fi}
110% hooks
```

- 111 \renewcommand{\@seccntformat}[1]{}
- ${\tt 113 \backslash newcommand \{ \backslash contactstyle \} \{ \backslash normal size \}}$
- 115 \newcommand{\titlestyle}{\normalsize}
- 116 \newcommand{\bulletsymbol}{\textbullet}