


```

1  /* ----- */
2
3  /* Metropolis algorithm, generic illustration
4     [Note: One point particle in 3d cube. You will not get "good
5     statistics" with one particle, of course. Illustration only!
6     Use as template for Project 5.] */
7
8  /* Header files */
9  #include <stdlib.h>
10 #include <stdio.h>
11 #include <math.h>
12 /* #include "f2c.h" */
13 /* #include "slatec.h" */
14
15 /* Global constants */
16 #define N 6  ← # of dimensions; 3 momenta, 3 position
17 #define M 1000
18 #define L 50 ← reduces statistical dependence
19
20 /* Aliases */
21 #define RAN (rand()/(float)RAND_MAX)
22
23 /* Prototypes */
24 float p(float *x, int n); /* probability distribution function */
25
26 /* ----- */
27 int main (void)
28 {
29     /* declarations */
30     unsigned int seed;
31     const int n=N;
32     int i,ii,j,k;
33     float x[N],xx[N],r,acpt,eps, ekin,ekin1,ekin2,epot,epot1,epot2;
34
35     FILE *mtout;
36
37     seed=305;
38     srand(seed);
39
40     eps=0.2;
41
42     /* Initial X, counters */
43     x[0]=0.0;
44     x[1]=0.0; } momentum
45     x[2]=0.0; } initial conditions.
46     x[3]=0.5; } space
47     x[4]=0.5;
48     x[5]=0.0;
49     i=0;
50     j=0;
51     acpt=0.0;
52
53     /* Initialize observables, counters */
54     ekin1=0.0;
55     ekin2=0.0;
56     epot1=0.0;
57     epot2=0.0;
58     k=0;

```

this code is for only one particle
I need to change it for many
interacting particles.




```

59
60 /*      For the record */
61 mtout=fopen("metropolis.out","w");
62
63 /*      Initial energies */
64 ekin=(powf(x[0],2.0)+powf(x[1],2.0)+powf(x[2],2.0))/2.0;
65 epot=x[5];
66 fprintf(mtout,"%6i%15.7e%15.7e\n",i,ekin,epot);
67
68 /*      Limit length of chain to M */
69
70 A:
71 if (i>=M) goto C;
72
73 /*      Trial X' */
74 /*      momenta */
75 xx[0]=x[0]+(RAN-.5)*eps;
76 xx[1]=x[1]+(RAN-.5)*eps;
77 xx[2]=x[2]+(RAN-.5)*eps;
78 /*      positions */
79 xx[3]=x[3]+(RAN-.5)*eps;
80 xx[4]=x[4]+(RAN-.5)*eps;
81 xx[5]=x[5]+(RAN-.5)*eps;
82
83 /*      Metropolis update */
84 if ( p(xx,n) >= p(x,n) )
85     /*      Accept */
86     goto B;
87 else {
88     r=RAN;
89     if ( p(xx,n) > r*p(x,n) )
90         /*      Accept */
91         goto B;
92     else {
93         /*      Reject */
94         j++;
95         goto A;
96     }
97 }
98
99 B:
100
101 /*      Next element of chain */
102 i++;
103 for (ii=0; ii<n; ii++) x[ii]=xx[ii];
104 acpt=(float)i/(float)(i+j);
105
106 /*      Energies */
107 ekin=(powf(x[0],2.0)+powf(x[1],2.0)+powf(x[2],2.0))/2.0;
108 epot=x[5];
109
110 /*      For the record */
111 fprintf(mtout,"%6i%15.7e%15.7e\n",i,ekin,epot);
112
113 if (L*(int)(i/L)==i) { /* mod function */
114     /*      accumulate 1st and 2nd moments */
115     k++;
116     ekinl=ekinl+ekin;

```

eps=small # (set to .2)



```

117         ekin2=ekin2+powf(ekin,2.0);
118         epot1=epot1+epot;
119         epot2=epot2+powf(epot,2.0);
120         printf("%6i%7.4f%4i%14.6e\n",i,acpt,k,(ekin1+epot1)/(float)k);
121     }
122     goto A;
123
124     C:
125
126     /*      Final results      */
127     ekin1=ekin1/(float)k;
128     ekin2=ekin2/(float)k;
129     ekin2=sqrt(ekin2-powf(ekin1,2.0))/sqrt((float)k);
130     epot1=epot1/(float)k;
131     epot2=epot2/(float)k;
132     epot2=sqrt(epot2-powf(epot1,2.0))/sqrt((float)k);
133     printf("%6i%7.4f%4i%14.6e%12.4e%14.6e%12.4e\n",i,acpt,k,ekin1,ekin2,epot1,epot2);
134
135     return 0;
136 }
137
138 /* ----- */
139
140 /*      Probability distribution function, def      */
141
142 float p(float *x, int n)
143 {
144     float s, beta=4.0;
145     int i;
146
147     /*      outside box      */
148     s=0.0;
149     for (i=3; i<5; i++) if (x[i]<0.0 || x[i]>1.0) return s;
150     if (x[5]<0.0) return s;
151
152     /*      Boltzmann      */
153     s=exp(-beta*(powf(x[0],2.0)+powf(x[1],2.0)+powf(x[2],2.0))/2.0+x[5]);
154
155     return s;
156 }
157
158 /* ----- */

```

line 68-124 is looking @
his outline

if they are interacting
then I am
potentially


this line reads:

$$s = e^{-\beta \left[\frac{1}{2} (p_x^2 + p_y^2 + p_z^2) + z \right]}$$
 The K.E. the P.E.
 w/ mg=1
 actually $\frac{1}{2} m$ w/ $m=1$.

so this is

$s = e^{-\beta E_{tot}}$, the Boltzmann factor.

make a plot of E_{tot} vs. simulation time



the average energy is const but \exists
fluctuations about that average.

(the kinetic energy is going
to be similar in shape, but
not @ same time.)

Markov Chain Process

Implementation

0 Generate initial config x_i , $p(x_i)$, $i=0$

1 Generate a (new) trial config x' , $p(x')$

2 if $p(x') \geq p(x_i)$

accept, $i=i+1$, $x_i = x'$

goto 1

else

gen $r \in [0,1)$ uniform

if $p(x')/p(x_i) > r$

accept, $i=i+1$, $x_i = x'$

goto 1

else

reject

goto 1

endif

endif