
Code For China
Lesson 7

Today's Overview

- Classes & Inheritance
- Break 🤗
- Final Project Info
- Breakout Project

Classes

- So far, we have used **variables**
- What if we have a bunch of variables that are ***all related***?
- We can organize these variables using **classes**

For example...

动物
Animals!

How does that all look like in code?

[example]

```python
class Animal:

    def __init__(self, species, color):
        self.species = species
        self.color = color
        self.foods = []
        self.sleep_hours = []

    def eat(self, food):
        self.foods.append(food)

    def sleep(self, num_hours):
        self.sleep_hours.append(num_hours)
```

```
class Animal:

    def __init__(self, species, color):
        self.species = species
        self.color = color
        self.foods = []
        self.sleep_hours = []

    def eat(self, food):
        self.foods.append(food)

    def sleep(self, num_hours):
        self.sleep_hours.append(num_hours)
```

Name of class

```
class Animal:

    def __init__(self, species, color):
        self.species = species
        self.color = color
        self.foods = []
        self.sleep_hours = []

    def eat(self, food):
        self.foods.append(food)

    def sleep(self, num_hours):
        self.sleep_hours.append(num_hours)
```

Name of class

Initializer

```
class Animal:

    def __init__(self, species, color):
        self.species = species
        self.color = color
        self.foods = []
        self.sleep_hours = []

    def eat(self, food):
        self.foods.append(food)

    def sleep(self, num_hours):
        self.sleep_hours.append(num_hours)
```

Name of class

Initializer

Class Variables


class Animal:
def __init__(self, species, color):
self.species = species
self.color = color
self.foods = []
self.sleep_hours = []
def eat(self, food):
self.foods.append(food)
def sleep(self, num_hours):
self.sleep_hours.append(num_hours)
Name of class
Initializer
Class Variables
Class Functions

```
my_animal = Animal("pig", "male")
my_animal.sleep(12)
my_animal.eat("grass")
```

```
my_animal = Animal("pig", "male")
my_animal.sleep(12)
my_animal.eat("grass")
```

Creating an instance of the Animal class

```
my_animal = Animal("pig", "male")
my_animal.sleep(12)
my_animal.eat("grass")
```

Creating an instance of the Animal class

Calling class functions on the instance

Inheritance - 继承

- Classes can **inherit properties and functions** from other classes
- This way, we can be lazy and not have to rewrite code 😛

For example, Pig is a type of animal. It can inherit the properties of the Animal class.

```python
class Pig(Animal):
    pass

pig = Pig("pig", "female")
pig.sleep(14)
pig.eat("acorn")
```

Pig class

```
class Pig(Animal):
    pass

pig = Pig("pig", "female")
pig.sleep(14)
pig.eat("acorn")
```

Animal class

```
class Animal:

    def __init__(self, species, gender):
        self.species = species
        self.gender = gender
        self.foods = []
        self.sleep_hours = []

    def eat(self, food):
        self.foods.append(food)

    def sleep(self, num_hours):
        self.sleep_hours.append(num_hours)



my_animal = Animal("pig", "male")
my_animal.sleep(12)
my_animal.eat("grass")
```

Name of class

```
class Pig(Animal):
    pass

pig = Pig("pig", "female")
pig.sleep(14)
pig.eat("acorn")
```

Class it inherits from

Name of class

```
class Pig(Animal):
    pass

pig = Pig("pig", "female")
pig.sleep(14)
pig.eat("acorn")
```

Class it inherits from

Calling Animal class functions on the Pig instance

Pig inherits the `init`, `sleep`, and `eat` functions from Animal, so we don't have to do anything!

We can also add properties / functions specific to the `Pig` class

What are some characteristics or actions of pigs that are unique / no other animals do?

We can also override functions from the inherited `Animal` class

We can also override functions from the inherited `Animal` class

`Pig` inherits `eat` and `sleep` functions from `Animal`. Compared to other animals, pigs eat a lot. Perhaps we want to make its own `eat` function.

We can also override functions from the inherited `Animal` class

`Pig` inherits `eat` and `sleep` functions from `Animal`. Compared to other animals, pigs eat a lot. Perhaps we want to make its own `eat` function.

```
class Pig(Animal):
    def eat(self, food, amount):
        for i in range(amount):
            self.foods.append(food)
        print("Pig eats")
```

Here, `self.foods` is not defined in Pig, but it is defined in Animal, (which Pig inherits from), thus we can use it

What about both: keep the **eat** function in **Animal** & also make a new **eat** function in **Pig**?

SOLUTION: Use **super**

```
class Pig(Animal):
    def eat(self, food, amount):
        super(Pig, self).eat(food)
        for i in range(amount):
            self.foods.append(food)
        print("Pig eats")
```

Using super

CODING TIME!

Activity: Design your own `class`

- Design 2 classes (or more)
- Think of the hierarchies & add **inheritance** (at least 1 class must inherit, but you can always do more 🤓)
- Examples: Cars, Humans, Books...and anything else you think of

This assignment is NOT about writing the correct code. It is about understanding inheritance and the relationship between classes.

15 min break

Structure for Future CS Classes

- First, finish Breakout
- Classes will be:
  - Short lectures on interesting topics (AI, Unity3D, algorithms, etc.)
  - Time to work on final projects with teacher help

Final Project

- **Goal:**
  - Code a Game
  - Can be new or extending something we did in class (e.g. Breakout)
- **Tools**
  - Can use turtle and what we learned in class
  - Can also use other libraries if you want
- Teams of 1-3
- Final Presentation
  - Share your project with parents / classmates / teachers
- Talk to us if you need ideas or help 😊

Breakout Game



Steps

1. **First Make Ball Bounce**



- The ball begins with a random downward-facing angle and continues moving infinitely
- If it collides with the border:
  - If corner: reverse direction
  - If wall: switch angle

Steps

2. Next, add paddle



- Now, add the paddle
- User can move the paddle using the Left / Right keys
- The ball can now collide with the paddle and change direction (switch angle)

Hint:

- If you draw the paddle using paddle.shape(“square”), its coordinates are at the **center**
- Default square size is (20, 20)
- Must use: **paddle.shapesize(paddle_height/20.0, paddle_width / 20.0)**

Steps

3. Complete Game



- Add the bricks
- Check for collisions with bricks, and remove the brick if hit by ball
- Add colors, other design choices

- *Extra*:
  - Tough bricks that require multiple hits to disappear
  - Add score label
  - Accelerate ball as game continues
  - Any other ideas!

Breakout Starter Code



github.com/jessicae5/CodeForChina

Turtle Commands

```
turtle.forward(length)
turtle.backward(length)
turtle.left(angle)
turtle.right(angle)
turtle.goto(x, y)
```

```
turtle.setheading(angle)
turtle.shape("turtle")
turtle.pensize(width)
turtle.showturtle()
turtle.hideturtle()
```

For more:
https://docs.python.org/3.3/library/turtle.html?highlight=turtle

Turtle setHeading()

```
turtle.setHeading(angle)
```