

CMPSC473, Spring 2020

Pointer lab: A review of C and pointers

Assigned: Tuesday Jan 14, Due: Thursday Jan 23 at Noon

Introduction

Note that the assignment is due at noon.

This assignment serves as a review of C and pointers. You will be implementing all the functions in `pointer.c`. The comments provide details on what each function should do. Any relevant structure definitions, constants, and inline functions are provided for you in `pointer.h`. **You should NOT make any changes in any file besides `pointer.c`.**

The assignment consists of 4 parts that build on top of each other:

1. Object functions (20 pts)

These functions serve to introduce the concept of polymorphism and object-oriented programming. You will be programming two types of objects that represent inventory in a store. The `StaticPriceObject` represents an item with a fixed price. The `DynamicPriceObject` represents an item that varies the price based on the remaining quantity of items left. Both objects are based on a base `Object` that corresponds to the base class in an object-oriented language.

Polymorphism is the concept that a pointer to a base object can refer to objects of different sub-types. For example, an `Object` pointer can refer to a `StaticPriceObject` or a `DynamicPriceObject`. Object-oriented languages handle this automatically, but in a non-object-oriented language like C, we must emulate this behavior ourselves. This is done by having the `Object` struct located at the beginning of the `StaticPriceObject` and `DynamicPriceObject` structs (as shown in `pointer.h`). Thus, casting a `StaticPriceObject` pointer to an `Object` pointer is valid since the beginning of the `StaticPriceObject` is an `Object`.

To support virtual functions (i.e., Object functions that can either refer to `StaticPriceObject` functions or `DynamicPriceObject` functions), we use what's known as a virtual function pointer table that contains function pointers that refer to the correct functions. For example, the `StaticPriceObject` will have function pointers that point to `StaticPriceObject` functions, and the `DynamicPriceObject` will have function pointers that point to `DynamicPriceObject` functions. Thus, an `Object` can call the appropriate function by using the virtual function pointer table. For example, the provided `object_price` function uses the table to call the appropriate price function for the `Object`.

Your role in this part of the assignment is to A) understand how the objects are manipulated, and B) implement a set of functions that emulate object-oriented programming in C. The first two functions illustrate how to compare generic `Objects`, which may either be `StaticPriceObjects`, `DynamicPriceObjects`, or some other `Object`. The next two functions illustrate the initialization of each object. The following two functions implement the pricing function for each object, and the last two functions implement the bulk pricing function for each object.

2. Iterator functions (30 pts)

An iterator is a structure that refers to the current position in some data structure. It is used to iterate through a data structure without needing to know the underlying details of the data structure. In other words, it encapsulates the process of iterating through a data structure.

In this part of the assignment, you will be implementing a linked list iterator for a singly-linked list of Objects. The linked list structure and iterator structure can be found in `pointer.h`. Each linked list node will have a pointer to an Object as well as a pointer to the next node in the linked list. The head of the list is simply a piece of data that points to the first node in the list. Functions will typically use a pointer to the head of the list (i.e., a pointer to that piece of data). The iterator will contain a pointer to the current node as well as a pointer to the previous node's next pointer to support removals and insertions. The first four functions allow you to iterate through the list and get the objects in the list. The next function provides the ability to remove nodes from the list, and the last two functions provide the ability to insert nodes into the list.

3. List functions (20 pts)

The list functions illustrate how to utilize the iterator to go through the list. You should be calling the functions you implemented in the previous part rather than reimplementing list iteration. The memory for the iterator structure can be allocated as a local variable in your functions. The first function is a simple list iteration, the second function illustrates how to use function pointers, and the last function returns the length of the list. You are welcome to create a helper function and use the `foreach` function in implementing the length function. The `foreach` function uses a union datatype, which can be copied/assigned/passed by value without issue.

4. Mergesort functions (30 pts)

These last three functions implement the mergesort algorithm. They provide more experience with using iterators, function pointers, working with pointers, and recursion. Mergesort works by splitting the list into two halves, sorting each half recursively, and then merging the sorted halves.

Hints

To compile your code in debug mode (to make it easier to debug with `gdb`), you can simply run:

```
make debug
```

It is highly advised to use `gdb` to debug crashes (e.g., segmentation faults) in your code. You can launch `gdb` on your program by running:

```
gdb pointer
```

Within `gdb`, you can type:

```
r
```

to run all of the tests, or you can type:

```
r test_name
```

with `test_name` replaced by whatever test you want to specifically run. You can find the tests in `test.c`. When debugging test failures, you should read the relevant test code in `test.c` to understand the failure.

Programming rules

You are not allowed to use any libraries besides the `math.h` library already included in `pointer.h`. Do not include any other libraries/files in `pointer.c`. If you really think you need some library function, please contact the course instructor to determine eligibility. You are allowed to use any of the inline functions, constants, etc. within the `pointer.h` file.

Evaluation and testing your code

You will receive zero points if:

- You violate the academic integrity policy (sanctions can be greater than just a 0 for the assignment)
- You break any of the programming rules
- Your code does not compile/build
- Your code crashes the grading script

Your code will be evaluated for correctness. We have provided some tests, though we reserve the right to add additional tests during the final grading, so you are responsible for ensuring your code is correct. In terms of a grade point breakdown, we will assign:

- (20 pts) Object functions
- (30 pts) Iterator functions
- (20 pts) List functions
- (30 pts) Mergesort functions

To run the grading script, simply run the following command in the assignment folder:

```
make test
```

Handin

Submit the `pointer.c` file in Canvas