

DEFAULT OS X KEYMAP

Editing

^ Space	Basic code completion
7.0	Show intention actions and quick-fixes
 ₩P	Parameter info (within method call arguments)
^J	Quick documentation lookup
	Brief Info
₩ F1	Show descriptions of error or warning at caret
^ ~, % N	Generate code
⊤₩T	Surround with (ifelse, trycatch, for, etc.)
жJ	Insert Live template 代码提示
% /	Comment/uncomment with line comment
光 ① /	Comment/uncomment with block comment
77	Select successively increasing code blocks
7.1	Decrease current selection to previous state
^	Context info
\#L	Reformat code 格式化
7 % I	Auto-indent line(s)
→1	Indent selected lines
। →।	Unindent selected lines
% ∨	Paste from recent buffers
 BD	Duplicate current line or selected block
% ⊠	Delete line at caret
↑☆↑	Move line up
\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	Move line down
^û J	Join lines
% ←	Split line
û↔	Start new line
₩ûU	Toggle case for word at caret or selected block
∵Ж☆]	Select till code block end
∵☆器[Select till code block start
X.	Delete to word end
V.	Delete to word start
₩+/₩-	Expand/collapse code block
☆ ₩+	Expand all
☆ ₩-	Collapse all
₩W	Close active editor tab

Multiple carets and selections

∵ + Click	Add or remove caret
^ ж G	Select all occurrences
^ G	Select next occurrence
^	Unselect occurrence
0	Unselect all occurrences or carets

Running

^\ R	Select configuration and run
D 7 ^	Select configuration and debug
^R/^D	Run/Debug
^ûR,^ûD	Run context configuration from editor
^#R	Rerun tests
₹ F11	Run Gulp/Grunt/npm tasks

Debugging

F8 / F7	Step over / step into
û F7	Smart step into
ੂੰ F8	Step out
∵ F9	Run to cursor
∵ F8	Evaluate expression
∖%R	Resume
% F8	Toggle breakpoint
☆ ₭ F8	View breakpoints

Navigation

₩B, ₩Click	Go to declaration
#0	Go to class
☆ Ж O	Go to file
O 第7	Go to symbol
ዕ∺]	Go to next editor tab
⊕₩[Go to previous editor tab
F12	Go back to previous tool window
<i>5</i>)	Go to editor (from tool window)
	Go to line
₩E	Recent files popup
\# ←	Navigate back
∑ ₩ →	Navigate forward
Ж☆≪	Navigate to last edit location
∵ F1	Select current file or symbol in any view
\%B	Go to implementation(s)
∑Space, %Y	Open quick definition lookup
^☆B	Go to type declaration
₩U	Go to super-method/super-class
^†	Go to previous method
^↓	Go to next method
Z#]	Move to code block end
Z#[Move to code block start
^ M	Move caret to matching brace
₩ F12	File structure popup
^H	Type hierarchy
H 7^	Call hierarchy
F2	Next highlighted error
☆ F2	Previous highlighted error
F4, ₩↓	Jump to source
% ↑	Jump to navigation bar
F3	Toggle bookmark
₹ F3	Toggle bookmark with mnemonic
^0^9	Go to numbered bookmark
%F3	Show bookmarks

Search/Replace

%F/%R	Find / Replace
#G/û#G	Find next/previous
մ ജ F	Find in path
ଫ ଝ R	Replace in path

Usage Search

₹F7	Find usages
	Find usages in file
☆ ೫ F7	Highlight usages in file
\% F7	Show usages

Refactoring

^T	Refactor this
F5 / F6	Copy / Move
% ⊗	Safe Delete
☆ F6	Rename
₩ F6	Change function signature
√₩N	Inline variable
V₩V	Extract Variable
Σ₩C	Extract Constant
√₩P	Extract Parameter

VCS/Local History

^ V	'VCS' quick popup
%K	Commit project to VCS
жт	Update project from VCS
て企C	View recent changes

General

Double û	Search everywhere
☆ ₩ A	Find Action
₩0₩9	Open corresponding tool window
⊕ ж F12	Toggle maximizing editor
\\û F	Add to Favorites
1位プ	Inspect current file with current profile
^ §, ^ `	Quick switch current scheme
₩,	Open Preferences
^ → I	Switch between tabs and tool window

To find any action inside the IDE use Find Action (企業A)







jetbrains.com/webstorm blog.jetbrains.com/webstorm @WebStormIDE