

## **Lesson Overview**

After diagnosing the problem, the technician must perform the correct repair. TESDA NC II requires learners to:

- Replace defective hardware
- Correct loose connections
- Fix network configuration errors

*This stage is fast-paced and tests precision under pressure.*

## **Replace RAM**

### **When:**

- PC has “No Display”
- RAM is loose or defective

### **Correct Steps:**

1. Turn off and unplug the system
2. Release RAM side locks
3. Remove the faulty module
4. Insert new RAM firmly until both locks click
5. Test boot the system

## **Reconnect Loose Cables**

### **Common Loose Cables:**

- SATA cables (HDD/SSD not detected)
- Power connectors
- GPU PCIe power cables
- Monitor cables
- Ethernet cables

**Correct Steps:**

- Check every connector
- Push until fully seated
- Ensure no cable blocks fans or airflow

**Reconfigure Network IP****When:**

- “Slow network” or “No Internet”
- IP conflict is detected

**Correct Steps:**

1. Open Network Settings
2. Check IPv4 settings
3. Assign correct IP, subnet mask, gateway
4. Run connection test (ping or network diagnostics)

**FOR MORE READINGS:**

Technical Education and Skills Development Authority. (2019). *Computer Systems Servicing NC II training regulations*. TESDA. [TR Computer Systems Servicing NC II.pdf](#)