

What is concurrency?

- Multiple 'pieces of code' accessing the same data at the same time
- Key issue in multi-processor systems (i.e. most computers today)
- Key issue for parallel databases
- Main question: how do we ensure data stay consistent without sacrificing (too much) performance?

Lock-Based Protocols (Cont.)

- **Lock-compatibility matrix**

	S	X
S	true	false
X	false	false

- A transaction may be granted a lock on an item if the requested lock is compatible with locks already held on the item by other transactions.
- Any number of transactions can hold shared locks on an item,
 - but if any transaction holds an exclusive on the item no other transaction may hold any lock on the item.
- If a lock cannot be granted, the requesting transaction is made to wait till all incompatible locks held by other transactions have been released. The lock is then granted.

Lock-Based Protocols

- A lock is a mechanism to control concurrent access to a data item
- Data items can be locked in two modes:
 1. **exclusive** (X) *mode*. Data item can be both read as well as written. X-lock is requested using **lock-X** instruction.
 2. **shared** (S) *mode*. Data item can only be read. S-lock is requested using **lock-S** instruction.
- Lock requests are made to concurrency-control manager. Transaction can proceed only after request is granted.

Lock-Based Protocols (Cont.)

- Example of a transaction performing locking:
 T_2 : **lock-S**(A);
 read (A);
 unlock(A);
 lock-S(B);
 read (B);
 unlock(B);
 display(A+B)
- Locking as above is not sufficient to guarantee serializability — if A and B get updated in-between the read of A and B, the displayed sum would be wrong.
- A **locking protocol** is a set of rules followed by all transactions while requesting and releasing locks. Locking protocols restrict the set of possible schedules.

Pitfalls of Lock-Based Protocols

- Consider the partial schedule

T_3	T_4
lock-x (B)	
read (B)	
$B := B - 50$	
write (B)	
	lock-s (A)
	read (A)
	lock-s (B)
lock-x (A)	

- Neither T_3 nor T_4 can make progress — executing **lock-S(B)** causes T_4 to wait for T_3 to release its lock on B , while executing **lock-X(A)** causes T_3 to wait for T_4 to release its lock on A .
- Such a situation is called a **deadlock**.
 - To handle a deadlock one of T_3 or T_4 must be rolled back and its locks released.

The Two-Phase Locking Protocol

- This is a protocol which ensures conflict-serializable schedules.
- Phase 1: Growing Phase
 - transaction may obtain locks
 - transaction may not release locks
- Phase 2: Shrinking Phase
 - transaction may release locks
 - transaction may not obtain locks
- The protocol assures serializability. It can be proven that the transactions can be serialized in the order of their **lock points** (i.e., the point where a transaction acquired its final lock).

Pitfalls of Lock-Based Protocols (Cont.)

- The potential for deadlock exists in most locking protocols. Deadlocks are a necessary evil.
- Starvation** is also possible if concurrency control manager is badly designed. For example:
 - A transaction may be waiting for an X-lock on an item, while a sequence of other transactions request and are granted an S-lock on the same item.
 - The same transaction is repeatedly rolled back due to deadlocks.
- Concurrency control manager can be designed to prevent starvation.

The Two-Phase Locking Protocol (Cont.)

- Two-phase locking *does not* ensure freedom from deadlocks.
- Cascading roll-back is possible under two-phase locking. To avoid this, follow a modified protocol called **strict two-phase locking**. Here a transaction must hold all its exclusive locks till it commits/aborts.
- Rigorous two-phase locking** is even stricter: here *all* locks are held till commit/abort. In this protocol transactions can be serialized in the order in which they commit.

The Two-Phase Locking Protocol (Cont.)

- There can be conflict serializable schedules that cannot be obtained if two-phase locking is used.
- However, in the absence of extra information (e.g., ordering of access to data), two-phase locking is needed for conflict serializability in the following sense:

Given a transaction T_i that does not follow two-phase locking, we can find a transaction T_j that uses two-phase locking, and a schedule for T_i and T_j that is not conflict serializable.

Lock Conversions

- Two-phase locking with lock conversions:
 - First Phase:
 - can acquire a lock-S on item
 - can acquire a lock-X on item
 - can convert a lock-S to a lock-X (upgrade)
 - Second Phase:
 - can release a lock-S
 - can release a lock-X
 - can convert a lock-X to a lock-S (downgrade)
- This protocol assures serializability. But still relies on the programmer to insert the various locking instructions.

Automatic Acquisition of Locks

- A transaction T_i issues the standard read/write instruction, without explicit locking calls.
- The operation **read**(D) is processed as:
 - if** T_i has a lock on D
 - then**
 - read(D)
 - else begin**
 - if necessary wait until no other transaction has a **lock-X** on D
 - grant T_i a **lock-S** on D ;
 - read(D)
 - end**


Automatic Acquisition of Locks (Cont.)

- **write**(D) is processed as:
 - if** T_i has a **lock-X** on D
 - then**
 - write(D)
 - else begin**
 - if necessary wait until no other trans. has a lock on D ,
 - if T_i has a **lock-S** on D
 - then**
 - upgrade** lock on D to **lock-X**
 - else**
 - grant T_i a **lock-X** on D
 - write(D)
 - end;**
- All locks are released after commit or abort

Implementation of Locking

- A **lock manager** can be implemented as a separate process to which transactions send lock and unlock requests.
- The lock manager replies to a lock request by sending a lock grant messages (or a message asking the transaction to roll back, in case of a deadlock).
- The requesting transaction waits until its request is answered.
- The lock manager maintains a data-structure called a **lock table** to record granted locks and pending requests.
- The lock table is usually implemented as an in-memory hash table indexed on the name of the data item being locked.

Lock Table




- Black rectangles indicate granted locks, white ones indicate waiting requests
- Lock table also records the type of lock granted or requested
- New request is added to the end of the queue of requests for the data item, and granted if it is compatible with all earlier locks
- Unlock requests result in the request being deleted, and later requests are checked to see if they can now be granted
- If transaction aborts, all waiting or granted requests of the transaction are deleted
 - lock manager may keep a list of locks held by each transaction, to implement this efficiently

Graph-Based Protocols

- Graph-based protocols are an alternative to two-phase locking.
- Impose a partial ordering \rightarrow on the set $\mathbf{D} = \{d_1, d_2, \dots, d_h\}$ of all data items.
 - If $d_i \rightarrow d_j$ then any transaction accessing both d_i and d_j must access d_i before accessing d_j .
 - Implies that the set \mathbf{D} may now be viewed as a directed acyclic graph, called a *database graph*.
- The *tree-protocol* is a simple kind of graph protocol.

Tree Protocol

1. Only exclusive locks are allowed.
2. The first lock by T_i may be on any data item. Subsequently, a data Q can be locked by T_i only if the parent of Q is currently locked by T_i .
3. Data items may be unlocked at any time.
4. A data item that has been locked and unlocked by T_i cannot subsequently be relocked by T_i .



Graph-Based Protocols (Cont.)

- The tree protocol ensures conflict serializability as well as freedom from deadlock.
- Unlocking may occur earlier in the tree-locking protocol than in the two-phase locking protocol.
 - shorter waiting times, and increase in concurrency
 - protocol is deadlock-free, no rollbacks are required
- Drawbacks**
 - Protocol does not guarantee recoverability or cascade freedom
 - Need to introduce commit dependencies to ensure recoverability
 - Transactions may have to lock data items that they do not access.
 - increased locking overhead, and additional waiting time
 - potential decrease in concurrency
- Schedules not possible under two-phase locking are possible under tree protocol, and vice versa.

Deadlock Handling

- System is deadlocked if there is a set of transactions such that every transaction in the set is waiting for another transaction in the set.
- Deadlock prevention** protocols ensure that the system will *never* enter into a deadlock state. Some prevention strategies:
 - Require that each transaction locks all its data items before it begins execution (predeclaration).
 - Impose partial ordering of all data items and require that a transaction can lock data items only in the order specified by the partial order (graph-based protocol).

Deadlock Handling

- Consider the following two transactions:

T_1 : write (X)	T_2 : write(Y)
write(Y)	write(X)
- Schedule with deadlock

T_1	T_2
lock-X on A write (A)	
	lock-X on B write (B)
wait for lock-X on B	wait for lock-X on A

More Deadlock Prevention Strategies

- Following schemes use transaction timestamps for the sake of deadlock prevention alone.
- wait-die** scheme — non-preemptive
 - older transaction may wait for younger one to release data item. Younger transactions never wait for older ones; they are rolled back instead.
 - a transaction may die several times before acquiring needed data item
- wound-wait** scheme — preemptive
 - older transaction *wounds* (forces rollback) of younger transaction instead of waiting for it. Younger transactions may wait for older ones.
 - may be fewer rollbacks than *wait-die* scheme


Deadlock prevention (Cont.)

- Both in *wait-die* and in *wound-wait* schemes, a rolled back transaction is restarted with its original timestamp. Older transactions thus have precedence over newer ones, and starvation is hence avoided.
- Timeout-Based Schemes:**
 - a transaction waits for a lock only for a specified amount of time. After that, the wait times out and the transaction is rolled back.
 - thus deadlocks are not possible
 - simple to implement; but starvation is possible. Also difficult to determine good value of the timeout interval.


Deadlock Detection

- Deadlocks can be described as a **wait-for graph**, which consists of a pair $G = (V, E)$,
 - V is a set of vertices (all the transactions in the system)
 - E is a set of edges; each element is an ordered pair $T_i \rightarrow T_j$.
- If $T_i \rightarrow T_j$ is in E , then there is a directed edge from T_i to T_j , implying that T_i is waiting for T_j to release a data item.
- When T_i requests a data item currently being held by T_j , then the edge $T_i \rightarrow T_j$ is inserted in the wait-for graph. This edge is removed only when T_j is no longer holding a data item needed by T_i .
- The system is in a deadlock state if and only if the wait-for graph has a cycle. Must invoke a deadlock-detection algorithm periodically to look for cycles.

Deadlock Detection (Cont.)



Wait-for graph without a cycle



Wait-for graph with a cycle

Deadlock Recovery

- When deadlock is detected:
 - Some transaction will have to be rolled back (made a victim) to break deadlock. Select that transaction as victim that will incur minimum cost.
 - Rollback -- determine how far to roll back transaction
 - Total rollback:** Abort the transaction and then restart it.
 - More effective to roll back transaction only as far as necessary to break deadlock.
 - Starvation happens if same transaction is always chosen as victim. Include the number of rollbacks in the cost factor to avoid starvation