≡                                                    Documentation Settings    ▼

# api-js-local

## POST  add Person

> http://localhost:4000/api/persons

### BODY  raw

```
{
    "first_name": "Rosalia",
    "last_name": "Lara",
    "edad": 40,
    "genero": "F"
}
```

Example Request                                                      add Person

```
curl --location --request POST 'http://localhost:4000/api/persons' \
--data-raw '
{
    "first_name": "Rosalia",
    "last_name": "Lara",
    "edad": 40,
    "genero": "F"
}
'
```

## GET  Get all persons

> http://localhost:4000/api/persons

Documentation Settings  ▼

Example Request

Get all persons

```
curl --location --request GET 'http://localhost:4000/api/persons'
```

## GET  Get One person

http://localhost:4000/api/persons/2

Example Request

Get One person

```
curl --location --request GET 'http://localhost:4000/api/persons/2'
```

## DEL  Delete one person

http://localhost:4000/api/persons/3

Example Request

Delete one person

```
curl --location --request DELETE 'http://localhost:4000/api/persons/3'
```

## PUT  Update one person

https://layo-express-mysql.herokuapp.com/api/persons/1

**BODY** raw

Documentation Settings ▼

```
    {
        "first_name": "Rosalia",
        "last_name": "Sarabia",
        "edad": 40,
        "genero": "F"
    }
```

Example Request
Update one person

```
curl --location --request PUT 'https://layo-express-mysql.herokuapp.com/api/persons/1' \
--data-raw '    {
        "first_name": "Rosalia",
        "last_name": "Sarabia",
        "edad": 40,
        "genero": "F"
    }'
```

## PATCH  Patch one person partial

http://localhost:4000/api/persons/2

## BODY raw

```
{
        "edad": 30,
        "last_name":"Velazquez"
}
```

Example Request
Patch one person partial

```
curl --location --request PATCH 'http://localhost:4000/api/persons/2' \
--data-raw '{
        "edad": 30,
        "last_name":"Velazquez"
```