

Stat 5200: Analysis of Designed Experiments

Jesse Wheeler

Contents

1 Overview	1
2 Completely Randomized Designs	1

1 Overview

Objectives and overview

- This material is based Chapter 3 on the textbook “A First Course in Design and Analysis of Experiments” (Oehlert, 2000).
- Chapter outcomes include:
 - TODO

2 Completely Randomized Designs

Completely Randomized Design

- Completely randomized design (CRD) is the simplest design for comparing treatments and is sometimes the preferred design.
- *Setup*:
 - There are g treatment groups.
 - N experimental units (EU)s available.
 - You want sample sizes of $n_1, n_2, \dots, n_g$, with $\sum_{i=1}^g n_i = N$.
- *Idea*: All possible sub-group composition are equally as likely.

Performing a Completely Randomized Design

- Randomly choose n_1 EU's for treatment 1.
- Randomly choose n_2 EU's for treatment 2.
- ...
- Randomly choose n_{g-1} EU's for treatment $g - 1$.
- The remaining n_g EU's are assigned to treatment g .
- On a computer, this can be done by permuting $1, 2, \dots, N$, and assigning the first n_1 numbers to treatment 1, the next n_2 to treatment 2, etc.

Advantages and Disadvantages

- Advantages
 - Simple to do; all you need is one random permutation.
 - Simple to explain and understand.
 - Simple to analyze.
 - No restrictions on the sample sizes (other designs may restrict n_i).
 - Easy with missing values.
- Disadvantages
 - Not always possible or cost-effective.
 - The accuracy of the experiment depends on variability among the EUs, not just the variability among treatment groups. Thus, it may require more EUs (\$\$\$\$).

Acknowledgments

- Compiled on August 17, 2026 using R version 4.5.0.
- Licensed under the [Creative Commons Attribution-NonCommercial license](#).  Please share and remix non-commercially, mentioning its origin.
- We acknowledge [students and instructors for previous versions of this course / slides](#).

References

Oehlert GW (2000). *A First Course in Design and Analysis of Experiments*. W. H. Freeman. ISBN 0-7167-3510-5. [1](#)