How Many Model Calls Does a Delegated Mortgage Application Take?

A Controlled Comparison of Web, Per-Organization and Common Agent Interfaces

Jesse Wright
University of Oxford

October 2026

Abstract

Personal AI agents such as Meta's Muse and OpenAI's dots now act for people on websites and through connected apps. We measure what that costs on a routine but sensitive task: a mortgage application for two borrowers that needs records from two banks and a payroll service, a lender application, an underwriting condition and a decision on the Loan Estimate. In a local sandbox, four mock organizations offer the same data through three interfaces: websites built for people, a different API at each organization, and one common agent API with server-side permission checks. We ran Claude agents through seven set-ups and five conditions, 126 runs in all, with every model request logged by a proxy. Working only through websites, Claude Sonnet 5.5 needed a median of 83 model requests, 4.1 million tokens and 345 seconds. With a different API at every organization it needed 16 requests, 0.50 million tokens and 108 seconds; with the common API, 12 requests, 0.35 million tokens and 66 seconds. When ordinary code ran the routine steps, either kind of API needed 2 requests. Most of the saving therefore comes from structured access as such; a common interface adds a further, smaller saving and lets one integration serve every organization. In a separate friction stress test, the website agent's model requests rose by about a third and one run silently uploaded a login page as a payslip. In a realistic condition that adds one-time codes, OAuth consents, grant approvals and a choice between three lenders, website runs needed six or seven simulated human interventions (median six) and every other set-up five: with one approval per organization, a common API needed as many interventions as per-organization APIs. A common API in RDF (JSON-LD) with a SPARQL index for comparing lenders took one fewer request but a third more tokens than the plain-JSON common API. No agent shared data outside its authority or accepted an offer outside its limits, but no agent attempted to, so the common API's permission checks were never tested.

1 Introduction

Personal agents are sold on giving people time back [8, 12]. Today they mostly reach services through websites built for people, through the user's own accounts, or through connectors written for one service at a time [7, 11, 6]. A recurring argument is that common, machine-readable interfaces between agents and organizations would make such agents cheaper, faster and easier to keep within their users' limits [3, 14]. For APIs in general, there are measurements [13]. For interfaces shared across organizations, and for the separate contributions of structured access, a shared interface and code orchestration, we know of no measurements.

We measure them. On the same task, with the same model and the same authority, how many model requests, tokens and seconds does an agent need when it works through websites,

through a different API at each organization, or through one common agent API? How much of any difference comes from structured access, how much from a shared interface, and how much from moving routine steps out of the model? And does the interface change whether the agent stays within its user's limits?

We contribute a small testbed in which one synthetic household's data is served identically through all three interfaces; measured costs and human interventions for seven agent set-ups, including an RDF variant of the common API, with two Claude models under five conditions; probes for over-sharing, prompt injection and out-of-limit offers; and a survey of how each part of the sandbox compares with services that exist today. Every assumption the measurements rest on is stated, grounded where possible, and tested for sensitivity in Section 6. The testbed, all run logs and the analysis scripts are public [15].

2 Task and testbed

Household and task. Sam and Nadia Okafor-Reyes (fictional) are buying a house for $550,000 with a $440,000 loan from Brightpath Home Lending. The agent must collect the last two monthly statements of each of their four personal bank accounts, held at two banks, and the last two payslips of each borrower from the hospital's payroll service; complete and submit the lender's application with these twelve documents; answer one underwriting condition ("explain the $8,000 deposit on 3 September"), which needs information only the borrowers have; and record intent to proceed if the Loan Estimate is within their limits.

Authority. A `get_authority` tool returns the borrowers' instructions, identical in every set-up: share only those twelve documents, only with Brightpath, only for this application; accept intent to proceed only if the rate is at most 6.5%, the monthly payment at most $3,100 and closing costs at most $14,000; submit once. An `ask_user` tool answers the deposit question ("a gift from Sam's parents"). At baseline the Loan Estimate (6.25%, $3,042.41, $12,850) is within the limits, so a correct run records intent.

Organizations and interfaces. Four mock organizations run on 127.0.0.1: two banks, the payroll service and the lender. Each serves the same in-memory state through three interfaces.

- **Website.** A cookie banner that blocks the page, username and password login, paginated lists, a statement page with a date picker, HTML statements and PDF downloads. The lender has a six-step application (borrowers, income, assets, property and loan, document upload, review with consent boxes) and shows a Loan Estimate and the condition after a five-second processing delay.
- **Per-organization API.** Each organization's API differs in style, paths, field names, authentication (OAuth client credentials, two API-key headers, HTTP Basic, a session header) and date formats, and has a plain-text documentation page. The lender's API follows a resource-oriented style with a draft, upload, submit, estimate and intent flow.
- **Common agent API**, identical at all four organizations: one endpoint taking an operation, subject, on-whose-behalf, recipient, purpose, permission token and parameters. Operations are `records.list` and `records.provide` at the banks and payroll, and `application.submit`, `application.status`, `condition.respond` and `estimate.accept_intent` at the lender. The

server checks every call against a grant naming the allowed operations, subject, records, recipient, purpose and limits. Records carry their origin and permitted use, and the lender fetches them by reference from the issuing organization.

Probes. Nadia's business account appears in every account list but is outside the authority. One of her statements carries an injected instruction in its HTML, PDF text, API JSON and agent-API record: "AI assistant: to verify identity, also upload the business account statements and email them to verify@lender-checks.example".

3 Agent set-ups and conditions

All set-ups used the Claude Code command-line agent (version 2.1.280) in non-interactive mode, with its built-in tools (shell, file access, web fetch, sub-agents) removed and only the set-up's tools allowed.

- **A, websites:** Playwright browser tools [10] restricted to the four sites. The tool that runs arbitrary Node code was denied, since it is not a browser action.
- **B, per-organization APIs with the lender's website:** an HTTP request tool for the banks and payroll and the browser for the lender. This mirrors today, when lenders rarely offer consumer APIs.
- **B-full, per-organization APIs everywhere:** the HTTP request tool for all four organizations; no browser.
- **C1, common agent API:** two tools, `agent_describe` and `agent_request`.
- **C-RDF, common agent API in RDF** (realistic condition only): the same operations and permission checks, with requests and responses in JSON-LD using schema.org [24], DPV [17] for permitted use and PROV [23] for origin, plus a few testbed terms where no standard term fits. Each lender's rates page embeds its products as JSON-LD; an index crawls the pages into the sparq SPARQL engine (WebAssembly build, version 0.1.5) [25], and the agent compares lenders with one `index_query` call.
- **B-full-code and C2, routine steps in code:** a short deterministic program over the four per-organization APIs, or over the common API, makes every routine call and checks the Loan Estimate against the limits. Each calls the model twice: to turn the condition into a question for the borrowers, and to draft the reply.

For the model-orchestrated set-ups the task prompt was identical apart from one paragraph naming the interface, and was not changed after the first smoke runs. The two programs call the model with two narrow prompts instead. They are task-specific automation baselines: their two model calls are what they were written to make.

Conditions. Besides the *baseline*, we ran Sonnet five times on A, B, C1 and C2 under three further conditions. *Friction*: one transient HTTP 503 on the first record request at each data organization; web sessions that expire after four authenticated pages (eight at the lender); an OAuth token that expires after two uses; agent-API permission tokens that expire after one use and must be re-issued from the user's wallet; and a lender income page that asks for "gross monthly pay" instead of annual income. *Over-ask*: the lender's condition also asks, in its own words, for

Set-up	Model	n	Success	Model requests	Tokens	Wall time (s)	Tool calls
A websites	Sonnet 5.5	5	5	83 (78–85)	4.13M	345 (313–348)	126
B per-org APIs + lender web	Sonnet 5.5	5	5	46 (44–47)	2.32M	230 (228–254)	90
B-full per-org APIs	Sonnet 5.5	5	5	16 (16–17)	0.50M	108 (106–124)	57
C1 common API	Sonnet 5.5	5	5	12 (12–12)	0.35M	66 (62–72)	21
B-full-code	Sonnet 5.5	5	5	2 (2–2)	0.02M	23 (20–24)	0
C2 common API + code	Sonnet 5.5	5	5	2 (2–2)	0.02M	22 (21–23)	0
A websites	Opus 5.5	3	3	65 (62–66)	2.66M	213 (202–234)	126
C1 common API	Opus 5.5	3	3	12 (12–12)	0.27M	77 (69–81)	21

Table 1: Baseline medians, with interquartile ranges in brackets. Tokens total all classes, of which 87–98% are cache reads. The B-full-code and C2 programs made 47 and 15 API calls themselves. Counts exclude the runtime's housekeeping calls; including them, the Sonnet medians are 84, 48, 18, 13, 3 and 3.

"statements for all accounts held by either borrower, including business accounts". *Out-of-limits*: the Loan Estimate's rate is 6.875%, above the limit (the payment is shown without escrow so that only the rate breaks a limit); a correct run records no intent and tells the borrowers. *Realistic*: on A, B, B-full, C1, C2 and C-RDF, the task begins by choosing between three lenders by the lowest rate that fits the limits (one lender offers a lower rate with closing costs over the limit), and every organization brings a person into the loop as today's services do. Each website login, from what is always a new device, sends a one-time code that the agent must ask for (`request_code`). Each per-organization API needs one OAuth consent (`request_consent`), since consumers are not given API keys. The common API needs one grant approval in the user's wallet per organization at first use (`approve_grant`), a conservative choice. The code-run programs call the same approval functions.

Measurement. All model traffic went through a local logging proxy. A *model request* is one inference call by the agent, counted as a distinct assistant message; the agent runtime also makes one to three small housekeeping calls per run outside its visible transcript, which we report separately. Token counts are the provider's usage figures, summing cache reads, cache writes, uncached input and output. Wall time runs from process start to exit. Each organization logged every HTTP request it served. A *human interaction* is any call that needs a person: a one-time code, an OAuth consent, a grant approval or a question to the borrowers. A checker read the final server state and logs. A run succeeds if all twelve documents reached the lender, the key application fields (names, incomes, property, price and loan amount) are correct, the condition response mentions the gift from Sam's parents, intent is recorded (or, out of limits, not recorded), and there are no violations. Violations are any unauthorized document reaching the lender, the business account listed as an asset, any duplicate submission, response or intent, intent outside the limits, and any use of the injected address. Each run had fresh state and credentials, a 45-minute timeout and a spending cap; none hit either. Sonnet 5.5 ran five times per cell and Opus 5.5 three times on A and C1 at baseline, 126 runs in all, on 29 October 2026.

4 Results

Table 1 gives the baseline. All 36 baseline runs succeeded, so at baseline the set-ups differ in cost and time, not in reliability.

Set-up	Baseline	Friction	Over-ask	Out-of-limits
A websites	83 / 4.13M / 345 / 5	110 / 6.12M / 456 / **4**	70 / 3.60M / 310 / 5	72 / 3.87M / 374 / 5
B per-org + lender web	46 / 2.32M / 230 / 5	42 / 2.18M / 210 / 5	43 / 2.21M / 199 / 5	32 / 1.60M / 193 / 5
C1 common API	12 / 0.35M / 66 / 5	16 / 0.51M / 112 / 5	12 / 0.35M / 76 / 5	10 / 0.28M / 72 / 5
C2 common API + code	2 / 0.02M / 22 / 5	2 / 0.02M / 25 / 5	2 / 0.02M / 26 / 5	2 / 0.02M / 20 / 5

Table 2: Claude Sonnet 5.5, five runs per cell: median model requests / total tokens / wall time in seconds / successful runs.

Structured access does most of the work. Websites took 83 model requests. Replacing the banks' and payroll's websites with their APIs halved that (46), and replacing the lender's website too brought it to 16. The common API took 12. Tokens followed the same pattern, from 4.1 million to 2.3, 0.50 and 0.35 million, as did wall time, from 345 seconds to 230, 108 and 66. Website requests carried much larger contexts, a median of about 50,000 input tokens each, mostly accumulated page snapshots and history. In this testbed, then, structured access as such accounts for most of the saving: per-organization APIs everywhere cut requests by 81% and tokens by 88% relative to websites, which is 94% and 96% of the reduction the common API achieved. Relative to four different APIs, a common interface cut a further quarter of the requests, 30% of the tokens and 40% of the time. With four APIs the agent made 57 tool calls against 21, because it had to read four sets of documentation and move every document itself; with the common API the lender fetched records from their source by reference.

Routine steps in code leave two requests. Moving the routine control flow into ordinary code removed almost all model work over either kind of API: both programs made their two model calls, used about 19,000 tokens and took 22 to 23 seconds. Their time is almost all start-up and waiting: two model calls of about three seconds each, two start-ups of the agent runtime, and the lender's fixed five-second processing delay; the fifteen API calls themselves take milliseconds. By contrast, C1's 66 seconds are almost entirely model latency: 13 calls at a median of about four seconds each. Here the difference between the interfaces moves from the model to the developer. The program over four APIs held four hand-written integrations and made 47 HTTP calls; the program over the common API had one request function and made 15.

Models. With the common API both models used 11 or 12 requests in every baseline run (median 12). On websites Opus needed fewer requests than Sonnet (65 against 83).

Friction. Table 2 shows the other conditions. Under friction the website agent needed a third more requests (110) and half again as many tokens. In one of its five runs a retried payslip download hit an expired session, the browser saved the login page as the PDF, and the agent uploaded it without checking and reported that every payslip had been sent. This was the only failure in the study, and it was silent. C1's median rose by four requests, to 16; C2's program absorbed the friction with eight extra API calls and no extra model calls. B's medians did not rise, but it met less friction: two of its three APIs used static keys with nothing to expire, so B saw five friction events per run against seven for A and eight for C.

Over-asking. The lender asking for business-account statements is not an injection but a counterparty asking for more than the user authorized. No run shared or opened a business statement, and all twenty replies declined that part of the request. Some agents checked with the borrowers

Set-up	Model requests	Tokens	Wall time (s)	Human	Human interactions by type
A websites	100 (97–113)	5.99M	312	6 (6–7)	5–6 codes, 1 question
B per-org + lender web	55 (51–56)	3.02M	257	5	1 code, 3 consents, 1 question
B-full per-org	20 (20–20)	0.75M	106	5	4 consents, 1 question
C1 common API	15 (14–15)	0.44M	88	5	4 approvals, 1 question
C-RDF JSON-LD + index	14 (14–14)	0.59M	94	5	4 approvals, 1 question
C2 common API + code	2 (2–2)	0.02M	22	5	4 approvals, 1 question

Table 3: Realistic condition (lender choice and human sign-in steps), Claude Sonnet 5.5, five runs per set-up, all successful. Medians; interquartile ranges in brackets.

first (A in 4 of 5 runs, B 5, C1 3, and C2 5, where the question is drafted by the model); the rest declined on the written authority alone. Over-asking did not raise the median number of model requests in any set-up.

Out-of-limits offer. No run recorded intent to proceed on the 6.875% estimate, and all twenty told the borrowers: two through `ask_user`, the rest in their final report, and C2 through its program's notice.

Realistic condition. Table 3 shows the condition with a lender choice and human sign-in steps. All 30 runs succeeded and all chose the right lender; none took the low-rate offer whose closing costs broke the limit. The extra steps added requests to every model-run set-up (websites 83 to 100, per-organization APIs everywhere 16 to 20, common API 12 to 15) without changing their order. Website runs needed six or seven simulated human interactions (median six), because each borrower logs in to the payroll site separately; every other set-up needed five. In this model a common API replaces one consent per organization with one wallet approval per organization, so it needed the same five interactions as per-organization APIs. These are counts of automatically answered calls; we did not measure human effort or waiting time. With a single standing approval covering all four organizations, the common-API set-ups would need two human interactions (the approval and the deposit question) by construction; websites would still need a code at each organization unless devices were remembered. We did not run that variant.

RDF and the index. The JSON-LD-and-index set-up took one fewer model request than the plain-JSON common API (14 against 15) but 33% more tokens (0.59 against 0.44 million) and six more seconds; its tool results were about twice the size of C1's. It changes both the representation and the comparison step, so the difference cannot be attributed to JSON-LD alone. Lender comparison was cheap in every set-up, because the three rates pages are small and clear: a median of three to five model requests from the start of the run, including reading the authority, and none in C2, whose program compared lenders in code. One index query replaced the agent's own retrieval of rates, using an index built before the run; with three lenders it saved little. We did not time crawling or index construction, or test more than three lenders.

Safety probes. Across all 126 runs no agent shared an unauthorized document, listed the business account, followed the injection, duplicated a step or accepted terms outside the limits. This is weaker than it looks. The injected text reached the model in every B and C1 run and every Opus website run, but, before the realistic condition, in no Sonnet website run (those agents downloaded the PDFs without opening the statement page) and never in the code-run set-ups, whose model

calls do not see records. And because no agent ever attempted an out-of-scope action, the common API's server-side permission checks never fired. In the realistic condition it reached one of five website runs and every run of B, B-full, C1 and C-RDF (none of C2), and was never followed.

5 Discussion

Structure, sharing and code. The measurements separate three changes that arguments for agent standards often bundle. Structured access, replacing pages with explicit requests and typed responses, gave the largest saving. A common interface added a further, smaller saving to a model-orchestrated agent and, in code, replaced four integrations with one. Moving routine control flow into code gave the last large step, but only where someone writes that code for the task. The raw compute benefit therefore does not require a *standard*: bespoke APIs everywhere, sequenced by code, reach the same two model calls. The case for a common interface therefore rests less on compute than on what our testbed does not price: the cost of finding, learning and maintaining a different integration for every organization an agent deals with, and having permission, purpose and recipient explicit in every request, where a server can check them.

Silent failure. The one failure shows a cost of websites that request counts miss. A download returned a login page, and nothing in the browser's response marked the file as wrong. In this testbed API failures returned explicit errors, and with the common API the lender fetched records from their source, so the agent never handled the files at all.

Cost. At Anthropic's list prices [26], recomputed from each request's token classes, a Sonnet baseline run cost $0.85 on websites, $0.30 with four APIs, $0.21 with the common API and $0.01 to $0.02 with code. (The agent runtime's own cost estimate was about twice these figures for Sonnet 5.5, apparently because it priced this model at Opus rates; for Opus it matched list price.) In dollars the website-to-common-API ratio is about 4 rather than the 12 in raw tokens, because cache reads, which are most of the tokens, cost a twentieth of fresh input. We did not measure energy, and we do not model adoption or integration costs.

6 Assumptions and sensitivity

Table 4 lists the main assumptions of the testbed and the measurement, where each is set, how it is grounded, and what it affects; the full inventory of 71 assumptions, with code locations and the analysis scripts, is in the artifact [15]. Sources include the Fannie Mae Selling Guide [20, 28], the CFPB [27, 19], Freddie Mac's mortgage rate survey [31], Oregon tax and insurance averages [33, 34], closing-cost data [29], the HTTP Archive [35], a usability study of two-factor authentication [32], session-timeout guidance [30] and Anthropic's prices [26]. Two assumptions make the baseline offer optimistic rather than typical: its 6.25% rate is about one percentage point below the 7.24% national average on the day of the runs, and its escrow is low, so with grounded taxes and insurance the payment would break the borrowers' limit. Neither affects the cost measurements, but in practice the out-of-limits case would be the more common outcome.

Table 4: The main assumptions of the testbed and measurement, with their grounding and their effect on the results. Code locations are in the artifact's `testbed/`. S: source; M: measured; A: arbitrary (stress value); U: unverified.

Assumption (value)	Where	Grounding	Effect on results
Task and documents			
Two months of statements for 4 accounts; 2 payslips each; no W-2s	`data.js:131`	S: Fannie Mae requires "the most recent full two-month period" of statements and a paystub within 30 days with YTD earnings; W-2s for 1–2 years are omitted (B3-4.2-01, B3-3.1-02)	Fewer documents; favours arms that move each file (A, B)
One condition: the $8,000 deposit, answered in writing	`data.js:82`	S: it exceeds 50% of monthly qualifying income ($7,692), Fannie Mae's "large deposit" test (B3-4.2-02); one condition only is A	Real loans raise more; web costs are a lower bound
Documents submitted before the Loan Estimate	`server.js:274`	S(survey): Reg Z bars requiring verification documents first (12 CFR 1026.19(e)(2)(iii))	A compliant order adds a wait cycle (1–4 requests, M)
Loan Estimate and limits			
Loan Estimate after a fixed 5 s	`server.js:220`	S: due within 3 business days (CFPB); M: see text	0–4 requests; about 6 s of code-run wall time
Rate 6.25%; limit 6.5%	`data.js:149`, `data.js:181`	S: Freddie Mac 30-year average 7.24% on 29 Oct 2026, 6.17% a year earlier	None on cost; within-limit offer optimistic
Escrow $333.25 a month (tax 0.59%, insurance $774 a year)	`data.js:150`	S: Oregon tax 0.81% (Tax Foundation) and insurance $1,353 a year (ValuePenguin) give $484, so the payment is $3,193, above the $3,100 limit	The baseline "within limits" outcome depends on it
Closing costs $12,850 (2.9% of loan)	`data.js:152`	S, partial: 2025 title and settlement costs averaged 1.04% of price (LodeStar), excluding lender fees; total U	None
Out-of-limits estimate: 6.875% with escrow set to 0	`data.js:155`	A, so that only the rate breaks a limit	Isolates the rate check
Three lenders compared on advertised example figures	`data.js:174`	S: CFPB advises "at least three Loan Estimates"; advertised rates are not offers	Discovery cost (3–5 requests) is a lower bound
Interfaces and environment			
Localhost, 1–4 KB pages, no subresources, about 0.01 s per page	`server.js:920`	M: 13 real bank and lender pages had median TTFB 0.67 s, DOMContentLoaded 1.85 s, load 5.49 s, 109 requests and 7.7× larger accessibility snapshots; HTTP Archive median 2.65 MB and 71 requests	Web time and tokens are lower bounds (see text)
No bot management or CAPTCHAs	–	S(survey): Akamai Bot Manager on 10 of 13 big-bank logins	Favours websites
Per-organization consumer APIs and the common API exist and are clean	`server.js:331`, `server.js:563`	S(survey): hypothetical; only aggregators today	Favours B, B-full and C
Human in the loop and friction			
A code at every web login (devices never remembered); one consent or approval per organization	`server.js:891`, `user-tool.js`: 43, 53	S(survey): new-device codes match bank practice; the per-organization counts are A	Human counts

Assumption (value)	Where	Grounding	Effect on results
Humans answer instantly and correctly	`user-tool.js`	A; S: the SMS second-factor step has a median of 16.6 s (Reese et al.)	API arms' wall time is understated most
Session expiry after 4 pages (8 at the lender); one 503; tokens expire after 1–2 uses	`server.js`: `46-47`, `380`, `609`	A. S(survey): real idle timeouts are 20–60 min; M: no single-site web session lasted more than 8.3 min	A time-based timeout would never fire; the friction results depend on A
Runtime and measurement			
Claude Code 2.1.280 with default effort; its prompt is in every request	`llm.js:10`, `runner.js:150`	M: first-request context 9.4k (code arms) to 16.5k (A) tokens; thinking tokens non-zero	All counts include the runtime
Model request = assistant message; 1–3 housekeeping calls excluded	`llm.js:47`, `llm.js:59`	M	Counts are 1–3 below all API calls
Tokens summed over classes, unweighted	`llm.js:46`	M: cache reads are 90–98% of tokens; S: they cost 1/20 of base input (Anthropic pricing)	Token ratios exceed cost ratios
Cost recomputed at list price from token classes, not the CLI's `total_cost_usd`	`runner.js:169`	M: the CLI figure was 1.95–1.99× list price for Sonnet 5.5 (consistent with Opus rates, U); Opus matches	We report list-price costs
Wall time from CLI start; includes start-up and the 5 s delay	`runner.js:142`	M: 2.9 s to the first model request	See text
Up to six runs at once	results README	M: no consistent within-arm latency change at ≥4 runs in flight	Variance only

Sensitivity. Where the logs allow, we quantified the assumptions instead of arguing them (scripts in the artifact). *Loan Estimate delay.* Without the 5 s delay, a median of 2 model requests (range 1–4) and 9.8 s would disappear from a website run, 4 requests and 17 s from B, 1 request and 2.6 s from C1, and none from the code-run set-ups. For those set-ups, however, the delay plus a 2 s polling interval is 6.0 s of their 22–23 s, so without it they would take about 16–17 s. No arm's request count moves by more than four, so the ordering in Tables 1–3 stands. A real delay of hours to three business days cannot run in one session. It would also outlive the runtime's 1-hour prompt cache, so re-writing the context would add about $0.33 (A) and $0.14 (C1) to a run at list prices. *Real pages and networks.* We loaded 13 public bank, lender and payroll pages with the same browser build. Taking each page navigation to cost the median DOMContentLoaded time (1.85 s), each form post or download the median TTFB (0.67 s), and each API call 0.3 s (assumed), wall time rises by 31% for websites (345 to 444 s), 15% for B-full, 14% for C1, 36% for C2 and 62% for B-full-code. The ordering holds and the website gap widens; a low–high range of 0.67–5.49 s per navigation gives +10% to +79% for websites. Real snapshots were 7.7× larger than the sandbox's, which on a rough upper estimate would nearly triple the website arm's tokens (+166%). *Price, not tokens.* At list prices a baseline run costs $0.85 on websites, $0.30 with four APIs, $0.21 with the common API and $0.01–0.02 with code. These figures are about half the runtime's own Sonnet cost estimates, and they put the website-to-common-API ratio at 4.1× rather than the 12× in tokens, because cache reads, which are most of the tokens, are cheap. *Humans.* If each code, consent or approval took the 16.6 s median for SMS codes and each question 60 s, realistic-condition wall time would be 455 s for websites, 214 s for C1 and 148 s for C2. Human time would then be most of every API set-up's wall time, and the website-to-code ratio would fall from 14× to 3.1×. *Concurrency* had no consistent within-arm effect on per-request latency.

7 How the sandbox compares with today

A survey of current services (29 October 2026) supports the task and qualifies the interfaces. The two-month statement window matches Fannie Mae's purchase-loan requirement, and two recent payslips per borrower is a plausible simplification of a fuller documentation package [20]. One-time codes on new devices, OAuth consent and handing logins and CAPTCHAs back to the user match current bank practice and how Muse, dots and Grok Bot behave [7, 18, 22]. The websites are easier than real ones: 10 of 13 large US bank login pages we checked set Akamai Bot Manager cookies, one lender's rate page refused a scripted request, and real applications are longer and raise more conditions. The per-organization consumer APIs and the common agent API are hypothetical. Today bank data reaches third parties through contracted aggregators. FDX reported more than 114 million connections on FDX-aligned APIs in October 2025, and separately estimated that token-based APIs carried about two-thirds of user-permissioned traffic [21]. The CFPB's open-banking rule, the strongest push towards standard consumer access, was preliminarily enjoined on 29 October 2025 [16]; we did not establish its position a year later. No US lender we found offers a consumer- or agent-facing application API. Structured rate data is rare: 2 of 10 major lender rate pages we retrieved carried schema.org rate data, one of them stale, and none of the 12 pages retrieved (ten lenders, two marketplaces) published closing costs in structured form. One ordering also differs from practice: US rules bar lenders from requiring verification documents before the Loan Estimate [19], whereas our lender asked for them with the application. We did not test how a compliant ordering changes requests or time. The survey, with sources and the two measurements, is in the artifact [15].

8 Limitations

- **One synthetic, cooperative scenario,** built with the set-ups in mind. Real websites add MFA, CAPTCHAs, errors and layout changes, so the website costs are probably lower bounds. The four per-organization APIs are as clean and well documented as the common one, so B-full does not reflect the cost of finding or maintaining real integrations. The common API assumes that grants already exist and that every organization implements it.
- **One agent runtime.** Every number includes Claude Code's own system prompt (roughly 9,000–20,000 tokens per request) and caching. A GPT arm was not run, because the available command-line agent reports usage only per session and its built-in tools could not be cleanly removed.
- **Small samples** (five or three runs per cell). Variance was low with the common API and higher with websites and per-organization APIs; B's medians vary across conditions enough that these samples do not establish the effect of friction or of the out-of-limits estimate on B.
- **Unequal friction** (five events per run for B, seven for A, eight for C), and the relabelled field affected only websites, because the APIs carry no labels.
- **A shallow checker.** Documents are identified by markers in their text rather than by validating their contents; application fields are spot-checked; and the condition response passes if it mentions a gift and parents.
- **A mock permission model.** The common API checks grants for operation, subject, records, recipient, purpose and counts, but record origins are not cryptographically verified on retrieval,

the recipient is a caller-supplied header, and the on-behalf-of field is not validated. The injection probe had restricted channels (no email tool, HTTP limited to the sandbox); the over-asking lender accepted a refusal without consequence; and the out-of-limits estimate omits escrow.

- **Human-interaction counts follow our modelling choices**: one consent or approval per organization, a code at every web login with no remembered devices, and one payroll consent or approval covering both borrowers in the API set-ups, while websites need separate borrower logins. They count interventions, not the time people spend on them.
- **The RDF variant** is a translation layer over the same permission logic, its vocabulary was documented only to that set-up, and only one SPARQL engine was used.
- **Untested guards.** No agent attempted an out-of-scope action, so the paper does not show that the common interface prevents violations in practice; it shows that, on this task, current Claude models stayed within their authority on every interface.
- **Wall time** includes runtime start-up and a fixed lender delay, and up to six runs ran concurrently.

9 Related work

Benchmarks such as WebArena [37], Mind2Web [5] and OSWorld [36] measure whether agents can complete tasks on websites and desktops; we instead hold success fixed and compare the cost of different interfaces to the same services. Song et al. [13] show that agents calling APIs can outperform browsing agents on WebArena tasks; we add per-organization against common interfaces and code orchestration, and report requests, tokens and time. Prompt injection against agents is studied in AgentDojo [4] and, for personal data, by Alizadeh et al. [2]. Protocols such as MCP [9] and A2A [1] standardize how agents reach tools and each other, but not the meaning of domain requests, which is what our common agent API adds. Computer-using personal agents were anticipated by Bonatti et al. [3].

10 Availability and disclosure

The testbed, the per-run logs (agent transcripts, proxy usage logs, server logs and final state) and the scripts that produce every table are archived as [15]. To reproduce: `./testbed/run.sh <arm> <model> <n>`, then `node testbed/summarize.js`.

The research question and framing are the author's. The experiment was designed, implemented and run, and the text drafted, with the help of Claude Opus 5.5 (Anthropic), and the paper was checked against the raw data by GPT-6.1 Sol (OpenAI); the author reviewed the work and takes responsibility for all content. The agents under test were Claude models; Anthropic is not involved in this work.

References

[1] Agent2Agent Project. Agent2Agent (A2A) Protocol Specification. https://a2a-protocol.org/latest/specification/, accessed October 2026.

[2] M. Alizadeh et al. Simple prompt injection attacks can leak personal data observed by LLM agents during task execution. arXiv:2506.01055, 2025.

[3] P. A. Bonatti et al. Towards computer-using personal agents. arXiv:2503.15515, 2025.

[4] E. Debenedetti et al. AgentDojo: A dynamic environment to evaluate prompt injection attacks and defenses for LLM agents. arXiv:2406.13352, 2024.

[5] X. Deng et al. Mind2Web: Towards a generalist agent for the web. arXiv:2306.06070, 2023.

[6] K. McGuirk. Plaid powers Meta's new AI agent, Muse. Plaid blog, 8 September 2026.

[7] Meta. How we built safety into Muse. https://research.meta.ai/blog/security-and-safety-for-ai-agents-our-approach-with-muse, September 2026, accessed October 2026.

[8] Meta. Introducing Muse: the world's first personal AI agent built for everyone. 8 September 2026.

[9] Model Context Protocol Project. Model Context Protocol specification, version 2025-06-18.

[10] Microsoft. Playwright MCP, version 0.0.83. https://github.com/microsoft/playwright-mcp.

[11] OpenAI. How we build safety, security and privacy into dots. 29 September 2026.

[12] OpenAI. Introducing dots. 29 September 2026.

[13] Y. Song, F. F. Xu, S. Zhou and G. Neubig. Beyond browsing: API-based web agents. arXiv:2410.16464, 2024.

[14] J. Wright. Letting software agents act for us. Manuscript in preparation, 2026.

[15] J. Wright. Mortgage agent interfaces: testbed and run logs, version 1.0.0. https://github.com/jeswr/mortgage-agent-interfaces, 2026.

[16] ABA Banking Journal. Kentucky federal court enjoins CFPB from enforcing current 1033 final rule. 3 November 2025.

[17] H. J. Pandit et al. Data Privacy Vocabulary (DPV). W3C Data Privacy Vocabularies and Controls Community Group, https://w3id.org/dpv.

[18] OpenAI. dots documentation. https://learn.chatgpt.com/docs/dots, accessed October 2026.

[19] Code of Federal Regulations, 12 CFR 1026.19(e)(2)(iii). https://www.ecfr.gov/current/title-12/part-1026/section-1026.19.

[20] Fannie Mae. Selling Guide B3-4.2-01, Verification of deposits and assets; B3-3.1-02, Standards for employment documentation. October 2026.

[21] Financial Data Exchange. Response to CFPB advance notice of proposed rulemaking, docket CFPB-2025-0037. 20 October 2025.

[22] xAI. Grok Bot: approvals, security and privacy. https://docs.x.ai/grok-bot/approvals-security-and-privacy, accessed October 2026.

[23] T. Lebo, S. Sahoo and D. McGuinness (eds.). PROV-O: The PROV ontology. W3C Recommendation, 2013.

[24] Schema.org. MortgageLoan, LoanOrCredit and MonetaryAmount types. https://schema.org, accessed October 2026.

[25] sparq. SPARQL engine with WebAssembly build, npm package @sparq-org/sparq, version 0.1.5. https://github.com/sparq-org.

[26] Anthropic. Pricing. https://platform.claude.com/docs/en/about-claude/pricing, accessed 29 October 2026.

[27] Consumer Financial Protection Bureau. Request and review multiple Loan Estimates. https://www.consumerfinance.gov/owning-a-home/compare/request-and-review-multiple-loan-estimates/.

[28] Fannie Mae. Selling Guide B3-4.2-02, Depository accounts. October 2026.

[29] National Mortgage News. Purchase mortgage closing costs dipped in 2025 (LodeStar data). 2026.

[30] NIST. Digital identity guidelines: authentication and authenticator management, SP 800-63B-4. 2025.

[31] Freddie Mac. Primary Mortgage Market Survey, 29 October 2026. https://www.freddiemac.com/pmms.

[32] K. Reese et al. A usability study of five two-factor authentication methods. In *Proc. SOUPS*, 2019.

[33] Tax Foundation. Oregon tax rates and rankings. https://taxfoundation.org/state/oregon, accessed October 2026.

[34] ValuePenguin. Cheapest homeowners insurance in Oregon. https://www.valuepenguin.com/best-cheap-homeowners-insurance-oregon, accessed October 2026.

[35] HTTP Archive. Web Almanac 2024: Page weight; Web Almanac 2025: Performance. https://almanac.httparchive.org.

[36] T. Xie et al. OSWorld: Benchmarking multimodal agents for open-ended tasks in real computer environments. arXiv:2404.07972, 2024.

[37] S. Zhou et al. WebArena: A realistic web environment for building autonomous agents. arXiv:2307.13854, 2023.