

6. Auxiliary Equipment.**6.1 Y Table for Roughing Mill to feed Top passes automatic**

Length : 10 M (approx.)

Roller Barrel Length: 1200 mm

Roller Spacing : app. 800 mm

Frame : Fabricated from Channels

Drive- Electro- mechanical Group Driven with Chain and Sprocket Linear Speed-
App. 3 m/sec,

Roller Neck Bearings : Antifriction Spherical Roller Bearing

6.2 Fix Roller Table for Roughing Mill to feed Bottom passes automatic

Roller Diameter: 273 mm Low alloy steel seamless pipe

Roller Barrel Length: 1200 mm

Roller Spacing : app. 800 mm

Frame : Fabricated from Channels

Drive- Electro- mechanical Group Driven with Chain and Sprocket Linear Speed-
App. 3 m/sec,

Roller Neck Bearings : Antifriction Spherical Roller Bearing

6.3 Approach Roller Table to 1st Continuous Mill (Extension Roller Table)

Length -15 m (App.)

Roller Diameter- 246 mm low alloy steel seamless pipe

Barrel length- 700 mm

Drive : Group driven with chain & sprocket – 2 Nos.

With Electric Motor

Roll Neck Bearings : Anti Friction Pillow Blocks

6.4 Pinch roll Before Quenching Box

Nominal diameter- 300 mm

Barrel length- 100 mm

Motor : DC Motor with drive

Drive : With reduction gearbox and carbon shaft

Pneumatic by operation of Top Roll

Lubrication : Splash Oil

Drive Coupling : Flexible Gear Coupling

Gears & Shaft Material : Heat Treatment Steel

Entry & Exit Guides : Steel Fabricated



6.5 Pinch roll after Quenching Box

Nominal diameter- 300 mm
Barrel length- 100 mm
Motor : DC Motor with drive
Drive : with reduction gearbox and cardon shaft
Pneumatic by operation of Top Roll
Lubrication : Splash Oil
Drive Coupling : Flexible Gear Coupling
Gears & Shaft Material : Heat Treatment Steel
Entry & Exit Guides : Steel Fabricated

6.6 Dividing Shear for, Dia 8mm to Dia 32 mm (TMT)

Type : Direct Driven Dividing Shear (Steel Fabricated)
TMT Bar to be Cut : 10mm to 32mm
Bar Speed : Max. 16 m/s
Motor : DC Motor with drive & Base Plate
Shear with Lubrication Piping, Oil Supply System, Bar Shifter,
Delivery Guide Trough & Valve Stand
Gears : Case Hardened & Ground with Surface Hardness HRC 58-60
Shafts : Heat Treated Steel
Blades : Heat Treated Steel (46-50 HRC)

6.7 Start/ Stop type Crop & Cobble Shear – 2 Nos.

For Hot Material Cutting (Temp. 850°C to 1050°C)
Type : Direct Driven Dividing Shear (Steel Fabricated)
Motor : DC Motor with drive & Base Plate
Low Speed Start / Stop Shear with Lubrication Piping, Oil Supply System,
Delivery Guide Trough
Gears : Case Hardened & Ground with Surface Hardness HRC 58-60
Shafts : Heat Treated Steel
Blades : Heat Treated Steel (46-50 HRC)
shall be installed in between stand # C-2 & C-3.

6.8 Tail Breaking Pinch Rolls – 2 Nos.

Nominal diameter- 300 mm
Barrel length- 100 mm
Motor : DC Motor with drive
Drive : With reduction gearbox and cardon shaft
Pneumatic by operation of Top Roll
Lubrication : Splash Oil
Drive Coupling : Flexible Gear Coupling
Gears & Shaft Material : Heat Treatment Steel
Entry & Exit Guides : Steel Fabricated



6.9 Lubrication Systems – 4 Nos.

- Duplex Oil Lubrication System – 3 Nos.
- Technical Specifications:
 - a. Reservoir 4500 Ltr - 1 No.
 - b. Oil Pump 300 Lpm - 1 No.
 - c. Electric Motor 10 Hp - 2 Nos.
(1 No. Working & 1 No. Stand By)
- For above:
 - a. Oil Filter Duplex Micron 149 - 1 Set
 - b. Oil Cooler 30000K Cal - 1 No.
 - c.
- Instruments:
 - a. Pressure Gauge- 2 Nos.
 - b. Pressure Switches- 1 No.
 - c. Temperature Gauges- 2 Nos.
 - d. Diff Pressure Switch- 1 No.
 - e. Level Switch- 1 No.
 - f. Level Gauge- 1 Set
- Oil Lubrication System for Continuous Shear – 1 No.

6.10 Roller Guide Box with Holder 7 Nos.**6.11 Roller Twist Guide 16 Nos.****6.12 Funnels 1 Set****6.13 Static Guides 1 Set****6.14 Water pump 2 Nos.**