

10. Bar Finishing, Bundling (Packing Bed)**10.1 Cold Shear Run – Out Roller Table (Gauge Conveyor)**

Purpose : Convey the material to bar transfer run-in roller table

Total Length : 26000mm

Table Length (C/C to end rollers) : 24000mm

Roller Spacing : 1200mm

Rollers : Diameter 190mm,

Barrel Length – 800mm,

Speed : 1.9 m/sec

Frame : Steel Fabricated

Drive : Group Driven with chain & sprocket through reduction gear box

Roller Neck Bearings : Pillow Blocks

Disappearing Stopper : 2 no. of pneumatically operated disappearing stoppers shall be installed at the exit of cold shear run-out roller table to stop the bar at 6/12 m from cold shear

10.2 Packing Bed

1) Size: 12 MW x 7.0 ML

2) Transfer Inlet-Arm unit x 12 M:

A) Main Shaft: Ø75 x 12 ML

B) Main drive motor: AC-10 HP x 4P x 1/10

C) Main Wrom Gear Reducer: A-200 x 1/30

D) Gear coupling: TY –SB- 150 x 2

3) Conveyor chain

4) Sprocket

5) Conveyor chain driven unit x 12ML

A) Main Shaft: Ø65 x 12ML

B) Main drive motor: AC –10HP x 4P x 1/10

C) Main Wrom Gear Reducer

D) Gear Coupling



10.3 Semi Automatic Tying Machine - 2 Nos.

- Tying Machines are for semi automatic tying of round bundles of bar.
- The Machines are fitted on a frame which is located in the line of roller table and the position is fixed.
- The tying material is short bars has been cut to 600mm in length and are fed through the machine manually.
- The Tying unit makes a twisted circle knot by means of a special head driven by an electrical motor and it is controlled by limit switches and cylinder moving up and down.
- The bundles are well tightened by means of two special arms making it almost circular.
- Electrical panel and PLC unit located on the pulpit is also in the scope of supply

Bundle dimensions	: Dia 200 – 400mm
Bundle Weight	: 2 Ton
Tying Material	: Short bars Dia 8 to 12mm
Bundle Forming Device	: Rotating Arms
Twisted Head	: 1 No. Electromechanically Drive
Tying Period (5 Ties)	: 85 sec
Tip Laying Rolls	: 1 No.



10.4 Roller Conveyor

- 1) Total Length = 19,000 (mm)
- 2) V-roller before bundling machine = 5,000 (mm)
 - 2-1) Conveyor drive unit:
 - i. Drive gear motor: AC-7.5 HP x 4P x 1/19
 - ii. Conveyor roller: Ø216.3 x 450W
 - iii. Coupling: RF-265
 - iv. Roller Chain & Sprocket: RS 100
 - 2-2) Free V-roller unit:
 - a) V-roller: Ø 89.1 x 406W
 - b) Bearing: 6207Z
 - 2-3) Bundle are drive unit:
 - a) Driver gear motor: AC-5HP x 4P x 1/19
 - b) Conveyor roller: Ø216.3 x 450W
 - c) Roller Chain & Sprocket: RS100
 - 2-4) Clamp by air cylinder: TC- Ø250 x 400 ST
- 3) Roller Conveyor after bundling = 14,000 (mm)
 - 3-1) Conveyor drive unit:
 - v. Driver gear motor: AC-7.5 HP x 4P
 - vi. Conveyor roller: Ø267.4 x 600W
 - 3-2) Clamp by air cylinder: TC- Ø250 x 400 ST
 - 3-3) Stopper: TC- Ø250 x 530ST

