

10. Bar Finishing, Bundling & Tying Machine (Packing Bed)**10.1 Cold Shear Run – Out Roller Table (Gauge Conveyor)**

Purpose : Convey the material to bar transfer run-in roller table

Total Length : 26000mm

Table Length (C/C to end rollers) : 24000mm

Roller Spacing : 1200mm

Rollers : Diameter 190mm,

Barrel Length – 800mm,

Speed : 1.9 m/sec

Frame : Steel Fabricated

Drive : Group Driven with chain & sprocket through reduction gear box

Roller Neck Bearings : Pillow Blocks

Disappearing Stopper : 2 no. of pneumatically operated disappearing stoppers shall be installed at the exit of cold shear run-out roller table to stop the bar at 6/12 m from cold shear

10.2 Packing Bed

1) Size: 12 MW x 7.0 ML

2) Transfer Inlet-Arm unit x 12 M:

A) Main Shaft: Ø75 x 12 ML

B) Main drive motor: AC-10 HP x 4P x 1/10

C) Main Wrom Gear Reducer: A-200 x 1/30

D) Gear coupling: TY –SB- 150 x 2

3) Conveyor chain

4) Sprocket

5) Conveyor chain driven unit x 12ML

A) Main Shaft: Ø65 x 12ML

B) Main drive motor: AC –10HP x 4P x 1/10

C) Main Wrom Gear Reducer

D) Gear Coupling

10.3 Roller Conveyor

1) Total Length = 19,000 (mm)

2)V-roller before bundling machine = 5,000 (mm)

2-1) Conveyor drive unit:

i. Drive gear motor: AC-7.5 HP x 4P x 1/19

ii. Conveyor roller: Ø216.3 x 450W

iii. Coupling: RF-265

iv. Roller Chain & Sprocket: RS 100

2-2) Free V-roller unit:

a) V-roller: Ø 89.1 x 406W

b) Bearing:6207Z



2-3) Bundle are drive unit:

- a) Driver gear motor: AC-5HP x 4P x 1/19
- b) Conveyor roller: Ø216.3 x 450W
- c) Roller Chain & Sprocket: RS100

2-4) Clamp by air cylinder: TC- Ø250 x 400 ST

3) Roller Conveyor after bundling -= 14,000 (mm)

3-1) Conveyor drive unit:

- v. Driver gear motor: AC-7.5 HP x 4P
- vi. Conveyor roller: Ø267.4 x 600W

3-2) Clamp by air cylinder: TC- Ø250 x 400 ST

3-3) Stopper: TC- Ø250 x 530ST

10.4 Pneumatic Tying Machine - 2 Nos.

