

12. CENTRAL LUBRICATION OIL SYSTEMS

1. Four (4) Nos. Central Oil Lubrication System will be installed for forced feed lubrication of reduction gearboxes of the stands & shears

System #1 : To serve the lubrication requirement of bearings and gears of:
- Roughing Mill Gear Boxes

System # 2
Function : To serve the lubrication requirement of bearings and gears of:
- Gear Boxes Mill Stands C1 – C6
- Crop Cum Cobble Shear #1

System # 3
Function : To serve the lubrication requirement of bearings and gears of:
- Gear Boxes Mill Stands C7 – C14
- Crop Cum Cobble Shear #2

System # 4
Function : To serve the lubrication requirement of bearings and gears of:
- High Speed Pinch Rolls
- Slow Speed Pinch Rolls
- Dividing Shears
- Tail brake Pinch Rolls

System # 5
Function : To serve the lubrication requirement of bearings and gears of:
- Continuous Shear

Each system completes with:

- Oil tank complete with electrical heaters, level gauges, ventilator, inlet, outlet & drain connections. Tank capacity about 20 minutes of system flow.
- Working & standby motorized screw type pumps.
- Duplex Filters of suitable micron elements
- Plate type Heat Exchanger.
- Protection equipment & indicators such as Thermostats, pressure gauges, pressure switches, temperature indicators & switches, set of alarms & securities.



2. Air-oil Lubrication System One (1) No.

Function : One (1) for Roll neck bearings and roller guides of Continuous mill stands.

Technical Features:

Air Oil lubrication complete with:

- Oil tank with level gauges & heaters
- Pumps and motors complete with non return valves, unloading valves and suction filter.
- Delivery Filters
- Protection equipment and indicators such as thermostats, manometers, gauges and pressure switch, oil level indicator and alarms etc.

