



HUST

ĐẠI HỌC BÁCH KHOA HÀ NỘI
HANOI UNIVERSITY OF SCIENCE AND TECHNOLOGY

ONE LOVE. ONE FUTURE.



ĐẠI HỌC
BÁCH KHOA HÀ NỘI
HANOI UNIVERSITY
OF SCIENCE AND TECHNOLOGY

Applied Algorithm Lab

Balanced course assignment

ONE LOVE. ONE FUTURE.

Balanced course assignment

- Assign courses to teachers s.t. time-conflict and preference conditions
- **Input & Constraints:** m teachers $T = \{1, 2, \dots, m\}$ and n courses $C = \{1, 2, \dots, n\}$.
 - Each teacher $t \in T$ has a preference list which is courses he/she can teach.
 - There is a list of pairs of conflicting two courses that cannot be assigned to the same teacher.
 - The load of a teacher is the number of courses assigned to her/him.
- **Objective:** Minimize the maximum load of a teacher.
- **Output:** The maximum load, or -1 for non-existing cases.

Balanced course assignment

- Example

stdin	stdout
4 12	3
5 1 3 5 10 12	
5 9 3 4 8 12	Explain: Courses of teachers:
6 1 2 3 4 9 7	1: 1 10 12
7 1 2 3 5 6 10 11	2: 3 4 8
5	3: 2 7 9
1 2	4: 5 6 11
1 3	
1 5	
2 4	
2 5	

Balanced course assignment

- Idea to solve: Backtracking and Branch and bound
 - To store the solution: An array Sol[N].
 - $Sol[i] = j$ iff we arrange teacher j teaches subject i
 - To compare the objective: $nbTeach[j]$ = number of subjects teacher j teaches
 - A variable maxLoad to store current solution's maximum load
 - programming: write functions:
 - `void Try(int k)` // select teacher for course k
 - `bool check(int j, int k)` // check if teacher j can teach course k
 - `void solution()` // change the current solution if find a better
 - Branch and bound (in Try()): if one teacher has $nbTeach[]$ larger than maxLoad: move to the next branch.

A large graphic on the left side of the slide. It features a dark blue background with a circular pattern of red dots of varying sizes, creating a sense of depth and movement. The word "HUST" is centered within this graphic in a white, bold, sans-serif font.

HUST

THANK YOU !