

ClearPath Analyzer

Repo-backed overview of the real estate deal analysis app in `apps/analyzer`.

WHAT IT IS

A Next.js web app that analyzes real estate investment deals from an address or Zillow-style property search flow. It estimates ARV, rehab cost, rent, cash flow, flip profit, and MAO, then stores analyses and lead data in Supabase.

WHO IT'S FOR

Primary persona: residential real estate investors evaluating flip or buy-and-hold deals, with added emphasis on Cook County prospects that can route into ClearPath's service business.

```
<div class="section">
  <h2>What it does</h2>
  <ul>
    <li>Searches by address with Google Places autocomplete
    on the landing page.</li>
    <li>Calculates ARV, rehab range, rent, cash flow, flip
    profit, ROI, and MAO.</li>
    <li>Uses nearby sold comps and nearby rent listings
    when Zillow data is available, with formula fallbacks.</li>
    <li>Gates the full results behind email capture and
    saves leads to Supabase.</li>
    <li>Shows saved analyses for signed-in users on a
    dashboard.</li>
    <li>Publishes an insights page that aggregates recent
    analyses.</li>
    <li>Exports a 1-page deal sheet or a fuller HTML/PDF
    report.</li>
  </ul>
</div>
```

HOW IT WORKS

- **Frontend:** Next.js App Router pages in `src/app` render the landing page, results flow, dashboard, insights, share page, and widget page.
- **Input:** The home page opens a config modal after address selection, then posts deal inputs to `/api/analyze`.
- **Data fetch:** `src/lib/propertyData.ts` calls a RapidAPI Zillow scraper for subject details, sold comps, and rentals; if `RAPIDAPI_ZILLOW_KEY` is missing or calls fail, it falls back to Cook County-flavored stub data.
- **Calculation layer:** `/api/analyze` combines fetched property data with configurable defaults from Supabase `system_defaults` to compute ARV, rehab, rental, flip, and signal outputs.
- **Persistence:** The analyze route inserts analyses into Supabase; `/api/leads` upserts captured emails into `leads`; `/api/events` stores analytics events.
- **User loop:** Results are cached in browser session storage for the results page, and authenticated users can attach saved analyses to their Supabase user ID for the dashboard.

HOW TO RUN

1. From `apps/analyzer`, install dependencies: `npm install`.
2. Create `.env.local` with `NEXT_PUBLIC_SUPABASE_URL`, `NEXT_PUBLIC_SUPABASE_ANON_KEY`, and `SUPABASE_SERVICE_ROLE_KEY`.
3. Optional for live property/comps/rent data: add `RAPIDAPI_ZILLOW_KEY`; otherwise the app uses stub property data.
4. Run the app with `npm run dev` and open `http://localhost:3000`.

```
<div class="section">
  <h2>Repo gaps</h2>
  <ul>
    <li><strong>Production deployment URL:
    </strong> Not found in repo.</li>
    <li><strong>Supabase local start
    command/config:</strong> Migration files
    exist, but a repo-level local bootstrap
    command was not found.</li>
    <li><strong>Asset Group app runtime
    details:</strong> Not included in this summary
    because this page focuses on the analyzer app.
    </li>
  </ul>
</div>
```