



University of
Strathclyde

Interoperability and semantics in RDF representations of FRBR, FRAD and FRSAD

Gordon Dunsire

Presented at the Cologne Conference on Interoperability
and Semantics in Knowledge Organization “Concepts in
Context”

19-20 July 2010



Background (1)

- ✧ Functional Requirements for Bibliographic Records (FRBR) published in 1998
 - ✧ Developed by a Study Group of the International Federation of Library Associations and Institutions (IFLA)
 - ✧ Incomplete – did not address “authorities”
 - ✧ Entities used as access points to bibliographic records
- ✧ Functional Requirements for Authority Data (FRAD) published in 2009
 - ✧ Incomplete – did not address subject authorities

Background (2)

- ✧ Functional Requirements for Subject Authority Data (FRSAD)
 - ✧ Next presentation ...
- ✧ IFLA's FRBR Review Group will develop a consolidated model from the FR “family”
 - ✧ Process is now underway
 - ✧ Will be informed by the analysis required for Semantic Web compatibility (representation in RDF)

Background (3)

- ✧ RDA: resource description and access is based on FRBR and FRAD
 - ✧ Bibliographic metadata content guidelines
- ✧ DCMI RDA Task Group asked to develop an RDF representation of RDA
 - ✧ Following the “London” meeting in April 2007
- ✧ Stimulated creation of “FRBR namespaces project”
 - ✧ To develop RDF representation of FRBR

Background (4)

- ✧ At the same time ... Consolidated edition of International Standard Bibliographic Description (ISBD) in development
 - ✧ Structure and content guidelines
 - ✧ ISBD/XML Study Group to develop an XML representation of ISBD
 - ✧ Decision to use RDF/XML
- ✧ IFLA Namespaces Task Group set up to identify requirements/options for support of IFLA standards in the Semantic Web
 - ✧ Report submitted; further discussion in Aug 2010

Methodology (1)

- ✧ NSDL Metadata Registry used for basic representation in RDF
 - ✧ Same approach as RDA
 - ✧ URI assignment; labels, definition, scope note, property range and domain
- ✧ FR family are entity-relationship models
 - ✧ Entity => RDF Class
 - ✧ E.g. FRBR Work
 - ✧ Entity attribute => RDF property
 - ✧ E.g. FRBR has-intended-audience
 - ✧ Entity-entity relationship => RDF property
 - ✧ E.g. FRBR is-realized-through (Work-Expression)

Methodology (2)

- ✧ Terminology of labels, definitions and scope notes based as closely as possible on source documentation
 - ✧ E.g. Property label = “has” + attribute name
- ✧ Classes and properties declared for prior model(s) re-used in current model
 - ✧ E.g. FRAD re-uses URIs from FRBR namespace
 - ✧ E.g. FRBR Expression; FRBR has-key
- ✧ No re-use of RDF resources from external community namespaces such as FOAF
 - ✧ Equivalences may be established later

Methodology (3)

- ✧ FR attribute properties have domain but no range
 - ✧ Required by the model for extensibility
 - ✧ E.g. FRBR has-key (domain = Work)
- ✧ Relationship properties have domain and range
 - ✧ E.g. FRBR is-realized-through (domain = Work; range = Expression)

General, non-technical issues

- ✧ Consistency within documentation
 - ✧ Written for human consumption; evidence of variable phrasing to make it more readable
 - ✧ E.g. “prior”, “preceding”, “first”
- ✧ Consistency of labels of RDF resources
 - ✧ E.g. “has a reproduction” (regular) vs “has reproduction” (irregular)
- ✧ Documentation refers to sub-types of entity
 - ✧ E.g. “musical work”, “serial”
 - ✧ First pass: sub-type => sub-class
 - ✧ But wrong due to semantic overlap

Opaque URIs

- ✧ Opaque URIs are used
 - ✧ E.g. `http://iflastandards.info/ns/fr/frbr/frbrer/1001`
 - ✧ `frbrer:1001`
 - ✧ **Not** `http://iflastandards.info/ns/fr/frbr/frbrer/Work`
 - ✧ **not** `frbrer:Work`
- ✧ IFLA operates in a multilingual environment
 - ✧ Anglophone bias avoided
 - ✧ Labels, etc. in English (@en), but no problem in accommodating translations
- ✧ Allows subsequent changes to alternative and preferred labels without causing confusion (**URI must not change**)

Semantic issues

- ✧ Do differences in documentation reflect real semantic differences?
- ✧ Close examination and detailed discussion required
 - ✧ Example (minor): Work
 - ✧ FRBR: “A distinct intellectual or artistic creation.”
 - ✧ FRAD: “A distinct intellectual or artistic creation (i.e., the intellectual or artistic content).”
 - ✧ Example (major): Person
 - ✧ FRBR: “An individual.”
 - ✧ FRAD: “An individual or a persona or identity established or adopted by an individual or group.”

Ontological issues (1)

- ✧ Source documentation only identifies pairs of inverse properties
 - ✧ For relationship properties only
 - ✧ E.g. is-realization-of/is-realized-through
 - ✧ Attribute properties are not inverted because instance triple objects are assumed to be literals
- ✧ Analysis of transitive, asymmetric, disjoint, etc. property types required
 - ✧ E.g. has-an-alternate is symmetric (implies the inverse is-an-alternate-to is redundant)
- ✧ All FRBR classes are mutually disjoint

Ontological issues (2)

- ✧ Relationships between separate FR models are likely to be declared with equivalence and hierarchical properties
 - ✧ E.g. owl:sameAs, rdfs:subClassOf
 - ✧ E.g. FRAD class Corporate Body seems to be a sub-class of FRBR Corporate Body
- ✧ Likely to be published as an addendum to the existing FR models
- ✧ Will inform the consolidated model
 - ✧ Which may also require additional classes and properties

RDA issues (1)

- ✧ DCMI RDA Task Group has declared parallel FRBR classes within RDA namespace
 - ✧ Could not wait for FRBR RDF resources to be approved
 - ✧ RDA to decide whether to substitute FRBR namespace resources, or declare equivalence
- ✧ Conflict with FRBR in RDA implementation scenarios?
 - ✧ RDA Manifestation “embodies” Work and Expression; FRBR allows only Expression

RDA issues (2)

- ✧ FRBR identifies sets of entities (classes) as Groups 1, 2 and 3, but not intended to be super-classes
 - ✧ They simplify the entity-relationship diagrams
 - ✧ But relationships are to be interpreted as being between individual entities and not the group
 - ✧ So sets of relationships are required
- ✧ RDA is discussing the declaration of such super-classes to simplify and reduce the properties
 - ✧ As in the Davis/Newman version of FRBR (2005)

ISBD

- ✧ ISBD has only one class (implied)
 - ✧ Resource: likely to be a super-class of FRBR Work, Expression, Manifestation, and Item
- ✧ Attribute properties, but no relationship properties (between Resources)
 - ✧ No range assumed; no inverse properties
 - ✧ To do: Mapping to FRBR properties
- ✧ ISBD Content form and media type mapped to RDA content and carrier types (all controlled vocabularies)
 - ✧ Via RDA/ONIX framework for resource categorization

Improving interoperability

- ✧ At least 3 namespaces in Libraryland will have RDF representations of attributes and relationships
 - ✧ FRBR/consolidated; ISBD; RDA
 - ✧ Interoperability will improve the quality and quantity of linked-data instances
- ✧ Interoperability should be improved by:
 - ✧ The Vocabulary Mapping Framework matrix
 - ✧ Coherent and consistent management environment of IFLA namespaces
 - ✧ Output of W3C Library Linked Data Incubator Group.

Thank you

- ✧ gordon@gordondunsire.com
- ✧ FRBR Review Group
 - ✧ <http://www.ifla.org/en/frbr-rg>
- ✧ ISBD Review Group
 - ✧ <http://www.ifla.org/en/isbd-rg>
- ✧ NSDL Metadata Registry
 - ✧ <http://metadataregistry.org/>
- ✧ Vocabulary Mapping Framework matrix
 - ✧ <http://cdlr.strath.ac.uk/VMF/documents.htm>
- ✧ Library Linked Data Incubator Group
 - ✧ <http://www.w3c.org/2005/Incubator/ld/>