Boolean

```
True or False, first letter should be in capital
```

Operators

| Assignment Operators

```
Operators which store and assign value to a variable/assignment
```

Examples

Operator	Example	Same As
=	x = 5	x = 5
+=	x += 3	x = x + 3
-=	x -= 3	x = x - 3
*=	x *= 3	x = x * 3
/=	x /= 3	x = x / 3
%=	x %= 3	x = x % 3
//=	x //= 3	x = x // 3
**=	x **= 3	x = x ** 3
&=	x &= 3	x = x & 3
|=	x |= 3	x = x | 3
^=	x ^= 3	x = x ^ 3
>>=	x >>= 3	x = x >> 3
<<=	x <<= 3	x = x << 3

&= -> bitwise AND, compares two numbers bit-by-bit and returns a number whose bits are 1 only where both inputs have 1.
|= -> bitwise OR, it updates a number by turning on any bits that are 1 in either number.
^= -> XOR, exclusive OR, only OR, no ANd
">>" -> moves all bits of a number to the right by some positions
"<<" -> moves all bits of a number to the left by some positions.

| Arithmetic Operators

+, -, * *, /,
% -> modulus

** -> exponentiation
// -> floor division

| Comparison Operators

Operator	Name	Example
==	Equal	x == y
!=	Not equal	x != y
>	Greater than	x > y
<	Less than	x < y
>=	Greater than or equal to	x >= y
<=	Less than or equal to	x <= y

is -> returns True if both are the same object
is not -> returns True if both are different objects
in -> returns True if in queried list contain a specific value
not in -> the opposite for in

| Logical Operators

and, or, not