Assignment 1: Backpropagation, 8-3-8 network

Authors:
Jessica Tambo Epoh (i6436881)
Vlad Stefan (i6342904)

Software description and how to use it

What this notebook does

This notebook implements a small neural network, using only NumPy for the math (no Keras, PyTorch or other deep learning libraries).

The network has three layers:

- 8 input nodes
- 3 hidden nodes + bias
- 8 output nodes + bias

It is trained on the 8 one-hot examples (seven 0s and one 1), and the target output is the same as the input. Because the hidden layer has only 3 nodes, the network must learn a compressed representation of the 8 inputs.

Requirements

- Python 3
- NumPy
- Matplotlib

How to run

Open the notebook and choose **Kernel** → **Restart & Run All**. The two experiment cells train 90 and 70 networks, so each takes about 1–2 minutes.

Structure of the notebook

1. **Setup:** imports, sigmoid function, training data
2. **8-3-8 network:** one forward pass, one backpropagation step, to show the cost decreasing, then the full training loop
3. **Training function:** the same steps packed into `train_network()`, used for all experiments
4. **Experiments:** learning rate, starting weight size, cost plot
5. **Interpretation:** hidden activations and learned weights

Implementation choices

- **Activation function:** sigmoid, g(z) = 1 / (1 + e^(−z))
- **Cost function:** least squares, J = 1/(2m) · Σ ||h(x) − y||^2
- **Biases** are stored as separate vectors (`b1` , `b2`) instead of as an extra column inside the weight matrix Θ.
- **Full-batch gradient descent:** in each epoch, all 8 examples are used and the weights are updated once with the average gradient.
- **No weight decay** (λ = 0).
- **Weights** start as small random numbers from a normal distribution; biases start at 0.
- **Convergence:** we say the network has converged at the first epoch where (1) for every example, the largest output is in the correct position, and (2) the cost J is below `tol` (default 0.01).

How to use the training function

```
converged_at, history, A1 = train_network(lr=2.0, seed=0,
init_scale=0.5,
                                          max_epochs=20000,
tol=0.01)
```

Parameter	Meaning
`lr`	learning rate (step size of gradient descent)
`seed`	fixes the random starting weights, so results are reproducible
`init_scale`	standard deviation of the random starting weights
`max_epochs`	maximum number of training epochs
`tol`	cost threshold used in the convergence check

It returns the epoch where the network converged (`None` if it never did), the cost at every epoch, and the final hidden activations.

In [33]:
```
import numpy as np
import time
import matplotlib.pyplot as plt
```

Forward propagation

Activation function: Every hidden and output neuron uses the sigmoid, g(z) = 1 / (1 + e^(−z)). It squashes any number into the range 0 to 1, so each neuron's output can be read as probability.
Its derivative is g′(z) = g(z)(1 − g(z)), which we use in backpropagation.

Training data: `X = np.eye(8)` gives the 8 one-hot examples (one row per example). The target `Y` is the same as the input, because the network must reproduce it.

Weight initialisation: The weights `W1` (8 × 3) and `W2` (3 × 8) start as small random numbers from a normal distribution (standard deviation 0.5), and the biases `b1`, `b2` start at 0.
The weights must be random and not all equal, otherwise all hidden neurons would learn exactly the same thing.
The seed makes the random start reproducible.

Forward pass: The input goes through the network layer by layer:

1. Hidden layer: `A1 = g(X·W1 + b1)`. Each hidden neuron takes a weighted sum of the inputs, adds its bias, and applies the sigmoid.
2. Output layer: `A2 = g(A1·W2 + b2)`. The same, using the hidden outputs as input.

Because we use matrices, one line computes all neurons of a layer for all 8 examples at once.

Cost: We measure how wrong the network is with $J = 1/(2m) \cdot \Sigma \, ||A2 - Y||^2$, where $m = 8$ is the number of examples. Before training, all outputs are close to 0.5 and the cost is about 1.165: the network has not learned anything yet.

In [34]:
```python
def sigmoid(z):
    # sigmoid activation function
    return 1 / (1 + np.exp(-z))

# the 8 examples
X = np.eye(8)
Y = X.copy()     #target

# random starting weights and zero biases
rng = np.random.default_rng(0)
W1 = rng.normal(0, 0.5, (8, 3))   # input (8) -> hidden (3)
b1 = np.zeros(3)
W2 = rng.normal(0, 0.5, (3, 8))   # hidden (3) -> output (8)
b2 = np.zeros(8)

# Forward propagation
A1 = sigmoid(X @ W1 + b1)    # hidden values
A2 = sigmoid(A1 @ W2 + b2)   # output guesses

np.set_printoptions(precision=2, suppress=True)
print("Hidden values (8 examples x 3 hidden neurons):")
print(A1)
print("\nOutput guesses (8 examples x 8 outputs):")
print(A2)
m = X.shape[0]
J = 0.5 * np.sum((A2 - Y) ** 2) / m
print("\nCost:", J)
```

```
Hidden values (8 examples x 3 hidden neurons):
[[0.52 0.48 0.58]
 [0.51 0.43 0.55]
 [0.66 0.62 0.41]
 [0.35 0.42 0.51]
 [0.24 0.47 0.35]
 [0.41 0.43 0.46]
 [0.55 0.63 0.48]
 [0.66 0.42 0.54]]

Output guesses (8 examples x 8 outputs):
[[0.46 0.64 0.56 0.52 0.45 0.48 0.59 0.71]
 [0.46 0.64 0.56 0.51 0.45 0.49 0.58 0.69]
 [0.5  0.62 0.52 0.49 0.43 0.49 0.55 0.69]
 [0.45 0.63 0.56 0.53 0.46 0.48 0.59 0.68]
 [0.46 0.6  0.55 0.53 0.46 0.49 0.58 0.66]
 [0.47 0.62 0.55 0.52 0.46 0.49 0.57 0.68]
 [0.47 0.64 0.55 0.51 0.43 0.49 0.58 0.71]
 [0.48 0.64 0.54 0.5  0.45 0.49 0.56 0.68]]

Cost: 1.1654551995739066
```

One backpropagation step

We first show a single backpropagation step on its own, before the full training loop. We built the network step by step, following the same order as the lecture: first the forward pass, then the errors of the output and hidden neurons, then the weight update. Splitting the problem into these smaller tasks made it easier to understand and check each part separately. Showing one step also lets us see directly that the cost decreases after a single update. The backpropagation step finds out how much each weight contributed to the error, so that we can change each weight in the direction that reduces the cost.

Error of the output neurons: `d_out = (A2 − Y) · A2(1 − A2)` This is (how wrong the output is) × (the derivative of the sigmoid). The derivative tells how much the neuron can still change: it is largest at 0.5 and almost zero when the neuron is close to 0 or 1.

Error of the hidden neurons: `d_hid = (d_out · W2ᵀ) · A1(1 − A1)` The hidden neurons have no target, so we cannot compare them with a correct answer. Instead, the output errors are sent backwards through the weights `W2`: a hidden neuron with a strong connection to a wrong output gets a big share of the blame. This is again multiplied by the sigmoid derivative.

Gradients and update: The gradient of a weight is (error of the neuron it goes into) × (value of the neuron it comes from), averaged over the m examples:

- `W2` gradient: `A1ᵀ · d_out / m`
- `W1` gradient: `Xᵀ · d_hid / m`

The Bias: The bias of a neuron works like a weight on an input that is always 1, so its gradient is just the average error of that neuron: `d_out.mean()` and `d_hid.mean()`.

Every parameter is then updated with gradient descent: new value = old value − learning rate × gradient. All gradients are computed first and only then applied, in order to

guarantee a simultaneous update.

After this single step, the cost drops from 1.17 to 0.89.

In [35]:
```
lr = 2.0         # learning rate
# delta of the output
d_out = (A2 - Y) * A2 * (1 - A2)

# delta of the hidden
d_hid = (d_out @ W2.T) * A1 * (1 - A1)

# update every weight
W2 -= lr * (A1.T @ d_out) / m
b2 -= lr * d_out.mean(axis=0)
W1 -= lr * (X.T @ d_hid) / m
b1 -= lr * d_hid.mean(axis=0)

# forward propagation with the new weights and check the cost
A1 = sigmoid(X @ W1 + b1)
A2 = sigmoid(A1 @ W2 + b2)
J = 0.5 * np.sum((A2 - Y) ** 2) / m
print("J after:", J)
```

```
J after: 0.8929764552310329
```

Training loop

Training simply repeats the forward pass and the backpropagation step many times. One epoch = all 8 examples are passed forward once, followed by one weight update.
We train for 20,000 epochs with learning rate 2 and print the cost at a few moments: it keeps decreasing, from 0.89 to 0.0012.

In [36]:
```
for epoch in range(1, 20001):
    # forward
    A1 = sigmoid(X @ W1 + b1)
    A2 = sigmoid(A1 @ W2 + b2)
    J = 0.5 * np.sum((A2 - Y) ** 2) / m

    if epoch in (1, 100, 1000, 5000, 10000, 20000):
        print(f"epoch {epoch:>5}   J = {J:.4f}")

    # backward
    d_out = (A2 - Y) * A2 * (1 - A2)
    d_hid = (d_out @ W2.T) * A1 * (1 - A1)
    W2 -= lr * (A1.T @ d_out) / m
    b2 -= lr * d_out.mean(axis=0)
    W1 -= lr * (X.T @ d_hid) / m
    b1 -= lr * d_hid.mean(axis=0)
```

```
epoch     1   J = 0.8930
epoch   100   J = 0.4218
epoch  1000   J = 0.0622
epoch  5000   J = 0.0056
epoch 10000   J = 0.0025
epoch 20000   J = 0.0012
```

Training function

`train_network()` contains exactly the same steps as above (initialisation, forward pass, backpropagation, update), packed into one function so that we can run many experiments with different parameters. It also records the cost at every epoch and the first epoch where the network converged. In the cell below, it reproduces the result of the step-by-step version.

In [37]:
```
def train_network(lr=2.0, seed=0, init_scale=0.5, max_epochs=20000, tol=0.01):
    # seed fixes the random starting weights, so results are reproducible
    # init_scale is the standard deviation of the random starting weights
    # max_epochs is the maximum number of training epochs
    rng = np.random.default_rng(seed)
    W1 = rng.normal(0, init_scale, (8, 3)); b1 = np.zeros(3)
    W2 = rng.normal(0, init_scale, (3, 8)); b2 = np.zeros(8)
    m = X.shape[0]
    history, converged_at = [], None

    for epoch in range(1, max_epochs + 1):
        # forward
        A1 = sigmoid(X @ W1 + b1)
        A2 = sigmoid(A1 @ W2 + b2)
        J = 0.5 * np.sum((A2 - Y) ** 2) / m
        history.append(J)
        # converged = first epoch where all guesses are correct and cost is
below tolerance
        if converged_at is None and np.all(A2.argmax(1) == Y.argmax(1)) and J <
tol:
            converged_at = epoch
        # backward
        d_out = (A2 - Y) * A2 * (1 - A2)
        d_hid = (d_out @ W2.T) * A1 * (1 - A1)
        W2 -= lr * (A1.T @ d_out) / m;  b2 -= lr * d_out.mean(axis=0)
        W1 -= lr * (X.T @ d_hid) / m;   b1 -= lr * d_hid.mean(axis=0)

    A1 = sigmoid(X @ W1 + b1)   # final hidden values
    return converged_at, history, A1
```

In [38]:
```
start = time.time()
converged_at, history, A1 = train_network(lr=2.0, seed=0)

print("Converged at epoch:", converged_at)
print("Time:", round(time.time() - start, 2), "seconds")
print("Final J:", history[-1])
print("\nHidden code (rounded):\n", np.round(A1).astype(int))
```

```
Converged at epoch: 3131
Time: 1.48 seconds
Final J: 0.0011739472915837468

Hidden code (rounded):
 [[1 0 0]
 [1 0 1]
 [1 1 0]
 [0 0 1]
 [0 1 0]
 [0 0 0]
 [0 1 1]
 [1 1 1]]
```

Learning performance

To check whether the network learns reliably, we ran two experiments. For every setting we trained 10 networks with different starting weights (different random seeds), each for at most 20,000 epochs. One epoch = all 8 examples shown once, followed by one weight update.

Experiment 1: Learning rate

We tested learning rates from 0.1 to 100, with starting weight size 0.5.

In [39]:
```python
learning_rates = [0.1, 0.5, 1, 2, 5, 10, 20, 50, 100]
seeds = range(10)   # 10 different random starts for each learning rate

print("learning rate | converged (out of 10) | average epochs")
for lr in learning_rates:
    results = []
    for seed in seeds:
        converged_at, history, A1 = train_network(lr=lr, seed=seed)
        results.append(converged_at)

    # the runs that converged
    ok = [r for r in results if r is not None]
    avg = round(np.mean(ok)) if ok else "-"
    print(f"{lr:>13} | {len(ok):>21} | {avg}")
```

```
learning rate | converged (out of 10) | average epochs
          0.1 |                     0 | -
          0.5 |                    10 | 13319
            1 |                    10 | 6659
            2 |                    10 | 3330
            5 |                    10 | 1338
           10 |                    10 | 669
           20 |                    10 | 376
           50 |                    10 | 4121
          100 |                     0 | -
```

- 0.1: too small, the steps are so small that the network does not reach the convergence threshold within 20,000 epochs.
- 0.5 to 20: the network converges for every seed. Doubling the learning rate roughly halves the number of epochs needed.

- 50: too large, the network still converges, but it is much slower again, because the large steps overshoot the minimum.
- 100: the network never converges.
  So with any learning rate between 0.5 and 50 it learned the task for all 10 random starts.
  With learning rate 2 and seed 0, the network converged after 3131 epochs.
  One training run of 20,000 epochs took about 1.5 seconds on our computer, so reaching convergence, 3131 epochs, takes roughly 0.2 seconds.

Experiment 2: Size of the starting weights

The starting weights are drawn from a normal distribution with standard deviation `init_scale`. We tested values from 0 (all weights start at zero) to 5, with learning rate 5.

In [40]:
```
init_scales = [0, 0.01, 0.1, 0.5, 1, 2, 5]

print("starting weight size | converged (out of 10) | average epochs")
for scale in init_scales:
    results = []
    for seed in range(10):
        converged_at, history, A1 = train_network(lr=5, seed=seed,
init_scale=scale)
        results.append(converged_at)

    ok = [r for r in results if r is not None]
    avg = round(np.mean(ok)) if ok else "-"
    print(f"{scale:>20} | {len(ok):>21} | {avg}")
```

```
starting weight size | converged (out of 10) | average epochs
                   0 |                    10 | 14580
                0.01 |                    10 | 1816
                 0.1 |                    10 | 1570
                 0.5 |                    10 | 1338
                   1 |                    10 | 1373
                   2 |                    10 | 1792
                   5 |                     5 | 7917
```

- 0.01–2: always converges, fastest around 0.5.
- 5: only half of the networks converged, and slowly. With large weights the sigmoid neurons start close to 0 or 1, where their slope a(1 − a) is almost zero. The gradients are then tiny, so the neurons are almost frozen and learn very slowly.
- All weights 0 :if every weight starts at the same value, all three hidden units compute exactly the same thing.
  They then receive exactly the same error signal during backpropagation, so they get the same updates and stay identical.
  In theory, the network then behaves as if it had only one hidden unit, and one unit is not enough to tell 8 inputs apart.
  This is called the symmetry problem, and it is the reason why weights are normally initialised randomly, symmetry breaking.

In our run, the network still converged, but it needed 14580 epochs, about 10 times more than with small random weights, 1338 epochs for size 0.5. The hidden activations, printed in the cell below, explain why.

In [41]:
```
converged_at, history, A1 = train_network(lr=5, seed=0, init_scale=0)
print("Hidden values when all weights start at 0:\n", A1)
```


```
Hidden values when all weights start at 0:
 [[0.   0.   0.6 ]
 [0.26 0.26 0.  ]
 [0.03 0.03 0.24]
 [0.18 0.18 0.93]
 [1.   1.   0.27]
 [0.72 0.72 0.  ]
 [0.64 0.64 1.  ]
 [1.   1.   0.72]]
```

Hidden units 1 and 2 have exactly the same value for every input, so they never separated.
Hidden unit 3, however,became different. Since nothing in the code is random when all weights are 0, this difference most likely comes from tiny rounding errors in the computer's calculations, which broke the symmetry by accident.
Backpropagation then slowly made this tiny difference bigger. As a result, the network had effectively only two different hidden units instead of three. It still managed to separate the 8 inputs, but only by using in-between values, such as 0.26 and 0.72 instead of a clean on/off code, which is harder and therefore much slower to learn.
The seed has no effect here: with a starting weight size of 0, every weight is exactly 0, no matter the seed. All 10 runs were therefore the same network, which is why all 10 gave the same result. To sum up the first two columns, hidden units 1 and 2, are identical in every row, while the third column is different.

Conclusion: the weights must start small and random, to break the symmetry between hidden units without saturating the sigmoid.

In [42]:
```
plt.figure(figsize=(8, 5))
for lr in [0.5, 2, 20, 50]:
    converged_at, history, A1 = train_network(lr=lr, seed=0)
    plt.plot(history, label=f"learning rate {lr}")

plt.yscale("log")   # log scale: makes small costs visible (explained below)
plt.axhline(0.01, color="gray", linestyle="--", label="convergence threshold
(tol = 0.01)")
plt.xlabel("Epoch")
plt.ylabel("Cost J (log scale)")
plt.title("Cost during training for different learning rates")
plt.legend()
plt.grid(True, alpha=0.3)
plt.show()
```



Cost during training

The plot shows the cost J for four learning rates (seed 0). The y-axis uses a log scale so that small costs remain visible. The dashed line is the convergence threshold (J = 0.01).

- lr = 20 drops fastest and crosses the threshold almost immediately.
- lr = 2 decreases steadily and crosses it at around 3,000 epochs.
- lr = 0.5 is slow and needs about 12,500 epochs.
- lr = 50 shows flat plateaus with sudden spikes: the network is stuck, overshoots, and gets stuck again. After about 4,000 epochs it suddenly finds a good direction and the cost drops quickly.

Interpretation of the learned weights

We now look inside the network trained: learning rate 2, seed 0.
First we look at the activations of the 3 hidden units for each of the 8 inputs, then at the weights themselves.

In [43]:
```
# outputs of the trained network
A1 = sigmoid(X @ W1 + b1)    # hidden values of the trained network
A2 = sigmoid(A1 @ W2 + b2)   # outputs of the trained network
print("Outputs of the trained network:\n", A2)

print("\nHidden values:\n", A1)
print("\nRounded hidden code:")
for i in range(8):
    print(f"input {i}  ->  {np.round(A1[i]).astype(int)}")
```

```
Outputs of the trained network:
 [[0.97 0.02 0.02 0.   0.   0.02 0.   0.  ]
 [0.01 0.97 0.   0.01 0.   0.   0.   0.03]
 [0.02 0.   0.97 0.   0.02 0.   0.   0.02]
 [0.   0.02 0.   0.97 0.   0.02 0.02 0.  ]
 [0.   0.   0.03 0.   0.96 0.02 0.02 0.  ]
 [0.02 0.   0.   0.02 0.03 0.96 0.   0.  ]
 [0.   0.   0.   0.02 0.02 0.   0.97 0.02]
 [0.   0.01 0.02 0.   0.   0.   0.02 0.96]]

Hidden values:
 [[0.99 0.23 0.02]
 [0.9  0.01 0.96]
 [0.78 0.99 0.01]
 [0.01 0.22 0.99]
 [0.01 0.59 0.01]
 [0.2  0.   0.15]
 [0.02 0.99 0.81]
 [0.99 0.98 0.99]]

Rounded hidden code:
input 0  ->  [1 0 0]
input 1  ->  [1 0 1]
input 2  ->  [1 1 0]
input 3  ->  [0 0 1]
input 4  ->  [0 1 0]
input 5  ->  [0 0 0]
input 6  ->  [0 1 1]
input 7  ->  [1 1 1]
```

After training, every output is close to 1 in the correct position (about 0.96–0.97) and close to 0 everywhere else, so the output is almost exactly the identity matrix: the network has learned to reproduce all 8 input patterns.

The hidden layer learned a binary-like code

Most hidden activations are close to 0 or 1, so each hidden unit behaves almost like an on/off switch. With 3 switches there are exactly 2 × 2 × 2 = 8 possible patterns, and the network uses every pattern exactly once.

Why every input needs a different code: the output layer only receives the 3 hidden values, it never sees the original input. If two inputs produced the same hidden pattern, the output layer would receive exactly the same information for both and could not know which output to switch on. To reproduce all 8 inputs correctly, every input must therefore get its own pattern. With only 3 hidden units, this forces the network to use all 8 combinations.

The code is not ordinary binary counting: input 0 gets `1 0 0`, not `0 0 0`. Which input gets which pattern is arbitrary, and depends on the random starting weights.

The code is binary-like, but not perfectly binary: some values are clearly not 0 or 1. For example, input 4 has a middle value of 0.59, and input 5 has 0.20 and 0.15. The network does not need perfect 0s and 1s: the codes only need to be different enough for the output layer to tell them apart. Our all-zero experiment showed the extreme case of this,

where the network used in-between values such as 0.26 and 0.72 instead of an on/off code.

In [44]:
```
np.set_printoptions(precision=1, suppress=True)
print("W1 (input -> hidden), one row per input:\n", W1)
print("\nW2 (hidden -> output), one column per output:\n", W2)
np.set_printoptions(precision=2, suppress=True)
```

```
W1 (input -> hidden), one row per input:
 [[ 5.  -1.4 -3.9]
 [ 2.5 -5.   3.3]
 [ 1.5  4.8 -4.5]
 [-4.7 -1.5  4.4]
 [-4.9  0.1 -4.9]
 [-1.1 -6.  -1.6]
 [-3.9  5.   1.5]
 [ 5.   3.8  5.1]]

W2 (hidden -> output), one column per output:
 [[  9.9   6.1   3.7 -10.1 -12.   -5.4  -8.4   6.2]
 [ -6.9  -9.6  10.4  -7.4   4.8 -15.1  10.4   6.3]
 [ -8.9   6.2  -8.4   8.6 -11.4  -5.8   3.8   5.9]]
```

The weights: W1 is a code book, W2 is a decoder

W1 (input → hidden): Each input contains a single 1 and seven 0s, so input i only "activates" row i of W1: all other rows are multiplied by 0. Row i of W1 therefore directly determines the hidden code of input i. A positive weight switches the hidden unit on, a negative weight switches it off:

Input	Row of W1	Signs	Hidden code
0	5.0, −1.4, −3.9	+ − −	1 0 0
1	2.5, −5.0, 3.3	+ − +	1 0 1
3	−4.7, −1.5, 4.4	− − +	0 0 1
7	5.0, 3.8, 5.1	+ + +	1 1 1

So W1 stores one 3-bit code per input. The size of the weight also matters. Input 4 has a middle weight of only 0.1, which is why its middle hidden value (0.59) is the least clear of all.

W2 (hidden → output): Each column of W2 belongs to one output unit. The signs of each column match the code of the input that output should reproduce:

Output	Column of W2	Signs	Matches code of input
0	9.9, −6.9, −8.9	+ − −	0 (1 0 0)
1	6.1, −9.6, 6.2	+ − +	1 (1 0 1)
4	−12.0, 4.8, −11.4	− + −	4 (0 1 0)
7	6.2, 6.3, 5.9	+ + +	7 (1 1 1)

Each output unit has learned a template of its own code: positive weights where its code has a 1, negative weights where its code has a 0. It only gets a large positive input when the hidden pattern matches its template, so it lights up for its own input and stays off for all others.

Together, the network works as an encoder–decoder: W1 compresses the 8 inputs into a 3-dimensional code, and W2 decodes that code back into the original input. This is an example of what the lecture calls a latent representation: a hidden, compressed description of the data that the network discovers by itself.

Conclusion

We implemented an 8-3-8 neural network with backpropagation from scratch, using only NumPy. The network learned to reproduce all 8 one-hot inputs.

Learning is reliable: for every learning rate between 0.5 and 50, all 10 random starts converged. A learning rate around 20 was fastest (376 epochs on average), while values that were too small (0.1) or too large (100) did not converge. The starting weights must be small and random: too large weights saturate the sigmoid and slow learning down, and all-zero weights create a symmetry problem between the hidden units.

Looking inside the trained network, the 3 hidden units learned a binary-like code, using all 8 possible on/off patterns. W1 acts as a code book that assigns a code to each input, and W2 acts as a decoder that turns the code back into the original input. The network discovered this compressed representation entirely by itself.

LLM Usage and Extra Reading

We used a Large Language Model (LLM), specifically Claude, as a supporting tool to clarify theoretical concepts, assist in debugging parts of the code, and to correct grammatical errors and refine the language of the report. The overall design and the final implementation were carried out by us,compared each line with the lecture formulas, and all LLM suggestions were critically evaluated and tested before being used.
Besides the lecture slides, we used the "Backprop Help" document provided by the course.

Team Contributions

Author	Code	Report	Video
Jessica Tambo Epoh	writing the training function, writing and checking the experiments, reviewing and editing rest of the code	Part 2: experiments and plot, Part 3: interpretation of the hidden layer and weights,conclusion, proofreading	50%
Vlad Stefan	building the forward pass, backprop step and training	Part 1: software description (README),code explanations (forward and backward pass), proofreading	50%

Author	Code	Report	Video
	loop, reviewing and editing rest of the code		