

# pandoc-emphasize-code

## Contents

Usage . . . . .	1
Syntax . . . . .	2
Rendering to HTML . . . . .	2
Rendering with LaTeX . . . . .	3
Regular Highlighting . . . . .	3
Install . . . . .	4
From Hackage . . . . .	4
Build . . . . .	4
Run . . . . .	4
Changelog . . . . .	5
License . . . . .	5

## Usage

Often when working with code examples in documentation, printed or web hosted, or in presentation slideshows, you might want to emphasize parts of a code snippet.

You can get away with manually writing the target markup, in LaTeX or raw HTML, but if you want to render the same document in multiple output formats, this gets really tedious. Also, having to write the markup by hand can be error prone.

This filter lets you specify *ranges* of a code block to emphasize, and have the filter generate the appropriate markup for you. It recognizes code blocks with the `emphasize` attribute present:

```
{ . haskell emphasize=2:3-2:14,3:3-3:12 }
myFunc = do
  newStuffHere
  andThisToo notThis
  notSoRelevant
```

In the example above, the identifier `newStuffHere` and `andThisToo` will be emphasized.

Currently, the following output formats are supported:

- HTML (html and html5)
- LaTeX (latex and beamer)
- GitHub-Flavored Markdown (markdown\_github)

## Syntax

The value of the `emphasize` attribute is a comma-separated list of *ranges*. A *range* consists of two positions, separated by a dash. A *position* consists of a *line number* and a *column number*, separated by a colon.

The syntax can be described in EBNF, like so:

```
line number    = natural number;
column number  = natural number;
position       = line number, ":", column number;
range          = position, "-", position;
ranges         = range, { ("", range) };
```

(\* definition of natural number excluded for brevity \*)

There must be at least one range in the comma-separated list. A range can span multiple lines.

## Rendering to HTML

The code block above would render HTML output like the following (lines broken for readability):

```
<pre class="haskell"><code>myFunc = do<br>
  <mark>newStuffHere</mark><br>
  <mark>andThisToo</mark> notThis<br>
  notSoRelevant</code></pre>
```

When rendering HTML5, the markup can be styled using CSS:

```
code mark {
  font-weight: bold;
  font-style: normal;
}
```

The `html` output format (not `html5`) uses `<em>` tags instead of `<mark>` tags.

```
code em {
  font-weight: bold;
  font-style: normal;
}
```

By default, if no custom styling is applied, emphasized ranges in HTML will be rendered in italic type. With the CSS rule from above, it will instead look something like this:

```
myFunc = do
  newStuffHere
  andThisToo notThis
  notSoRelevant
```

Note that there is no additional syntax highlighting when emphasizing code and rendering to HTML, as there is no way to use Pandoc's highlighter and embed custom HTML tags. You might be able to add that using a Javascript highlighter running on the client.

## Rendering with LaTeX

When rendering using LaTeX, two things are required:

- The `listings` package needs to be included.
- You need to define a `CodeEmphasis` command, styling the emphasized code in `lstlistings`.

If you're not using a custom LaTeX template, you can use the YAML front matter in a Markdown source file to add the requirements:

```
header-includes:
- \usepackage{listings}
- \lstset{basicstyle=\ttfamily}
- \newcommand{\CodeEmphasis}[1]{\textcolor{red}{\textit{#1}}}
```

**NOTE:** When rendering as Beamer slides, any frame including an emphasized block must be marked as `fragile`:

```
## My Slide {.fragile}
```

```
{.haskell emphasize=2:3-2:14,3:3-3:12}
myFunc = do
  newStuffHere
  andThisToo notThis
  notSoRelevant
```

## Regular Highlighting

You can still use regular Pandoc highlighting (the *skylighting* library):

```
{.haskell}
myFunc = do
```

```
newStuffHere
andThisToo notThis
notSoRelevant
```

It gives you all the nice colors:

```
myFunc = do
  newStuffHere
  andThisToo notThis
  notSoRelevant
```

The drawback is that you have two different highlighting systems now, one for emphasized code, one for regular code blocks.

## Install

Executables for Linux and macOS are available in the Releases page.

### From Hackage

If you'd rather install using cabal or stack, you can use the following command:

```
cabal install pandoc-emphasize-code
```

The package is available at Hackage.

## Build

Requirements:

- Cabal or Stack, either works.

To install from sources, run:

```
git clone git@github.com:owickstrom/pandoc-emphasize-code.git
cd pandoc-emphasize-code
stack setup
stack install
```

## Run

If you have installed from sources, and you have `~/ .local/bin` on your PATH, you can use the filter with Pandoc like so:

```
pandoc --filter pandoc-emphasize-code input.md output.html
```

## Changelog

- **0.2.0**
  - Use Lucid to render HTML, fixes issue #1
- **0.1.1**
  - Restructured modules
  - Separated pretty printer
  - Better error messages
  - Improved validation
  - Documentation styling improvements
- **0.1.0**
  - First release
  - Support for multiple ranges
  - Rendering support for HTML, Markdown, and LaTeX

## License

Mozilla Public License Version 2.0