1. Sample section

Variant A: Editor tab

The converter starts here. The function reads the file and writes the PDF:

src/main.py

```
def main():
    args = parse_args()
    for path in args.files:
        convert(path)
```

Bloque de código 1.1: Main entry point

A config file with a dark theme on the block:

config/export.json

```
{ "printBackground": true, "pageSize": "A4" }
```

Bloque de código 1.2: Export settings

A long path, to check how the header wraps or cuts:

src/very/deep/package/structure/with/a/long/module_name_here.py

```
VALUE = 42
```

Bloque de código 1.3: Deep module

A block with no file name, for comparison:

```
md-to-pdf informe.md
```

Bloque de código 1.4: Shell command

1. Sample section

Variant A2: Tab, lighter shade + accent line

The converter starts here. The function reads the file and writes the PDF:

src/main.py

```
def main():
    args = parse_args()
    for path in args.files:
        convert(path)
```

Bloque de código 1.1: Main entry point

A config file with a dark theme on the block:

config/export.json

```
{ "printBackground": true, "pageSize": "A4" }
```

Bloque de código 1.2: Export settings

A long path, to check how the header wraps or cuts:

src/very/deep/package/structure/with/a/long/module_name_here.py

```
VALUE = 42
```

Bloque de código 1.3: Deep module

A block with no file name, for comparison:

```
md-to-pdf informe.md
```

Bloque de código 1.4: Shell command

1. Sample section

Variant A3: Tab, sans font, folder dimmed

The converter starts here. The function reads the file and writes the PDF:

src/**main.py**

```
def main():
    args = parse_args()
    for path in args.files:
        convert(path)
```

Bloque de código 1.1: Main entry point

A config file with a dark theme on the block:

config/**export.json**

```
{ "printBackground": true, "pageSize": "A4" }
```

Bloque de código 1.2: Export settings

A long path, to check how the header wraps or cuts:

src/very/deep/package/structure/with/a/long/**module_name_here.py**

```
VALUE = 42
```

Bloque de código 1.3: Deep module

A block with no file name, for comparison:

```
md-to-pdf informe.md
```

Bloque de código 1.4: Shell command

1. Sample section

Variant A4: Tab on a tab strip (editor window)

The converter starts here. The function reads the file and writes the PDF:

src/main.py

```
def main():
    args = parse_args()
    for path in args.files:
        convert(path)
```

Bloque de código 1.1: Main entry point

A config file with a dark theme on the block:

config/export.json

```
{ "printBackground": true, "pageSize": "A4" }
```

Bloque de código 1.2: Export settings

A long path, to check how the header wraps or cuts:

src/very/deep/package/structure/with/a/long/module_name_here.py

```
VALUE = 42
```

Bloque de código 1.3: Deep module

A block with no file name, for comparison:

```
md-to-pdf informe.md
```

Bloque de código 1.4: Shell command

1. Sample section

Variant B: Full-width title bar

The converter starts here. The function reads the file and writes the PDF:

src/main.py

```
def main():
    args = parse_args()
    for path in args.files:
        convert(path)
```

Bloque de código 1.1: Main entry point

A config file with a dark theme on the block:

config/export.json

```
{ "printBackground": true, "pageSize": "A4" }
```

Bloque de código 1.2: Export settings

A long path, to check how the header wraps or cuts:

src/very/deep/package/structure/with/a/long/module_name_here.py

```
VALUE = 42
```

Bloque de código 1.3: Deep module

A block with no file name, for comparison:

```
md-to-pdf informe.md
```

Bloque de código 1.4: Shell command

1. Sample section

Variant B2: Bar in the theme's color, slightly lighter

The converter starts here. The function reads the file and writes the PDF:

src/main.py

```
def main():
    args = parse_args()
    for path in args.files:
        convert(path)
```

Bloque de código 1.1: Main entry point

A config file with a dark theme on the block:

config/export.json

```
{ "printBackground": true, "pageSize": "A4" }
```

Bloque de código 1.2: Export settings

A long path, to check how the header wraps or cuts:

src/very/deep/package/structure/with/a/long/module_name_here.py

```
VALUE = 42
```

Bloque de código 1.3: Deep module

A block with no file name, for comparison:

```
md-to-pdf informe.md
```

Bloque de código 1.4: Shell command

1. Sample section

Variant B3: Window bar with three dots

The converter starts here. The function reads the file and writes the PDF:

src/main.py

```
def main():
    args = parse_args()
    for path in args.files:
        convert(path)
```

Bloque de código 1.1: Main entry point

A config file with a dark theme on the block:

config/export.json

```
{ "printBackground": true, "pageSize": "A4" }
```

Bloque de código 1.2: Export settings

A long path, to check how the header wraps or cuts:

src/very/deep/package/structure/with/a/long/module_name_here.py

```
VALUE = 42
```

Bloque de código 1.3: Deep module

A block with no file name, for comparison:

```
md-to-pdf informe.md
```

Bloque de código 1.4: Shell command

1. Sample section

Variant B4: Light bar, folder dimmed, file bold, outlined

The converter starts here. The function reads the file and writes the PDF:

src/**main.py**

```
def main():
    args = parse_args()
    for path in args.files:
        convert(path)
```

Bloque de código 1.1: Main entry point

A config file with a dark theme on the block:

config/**export.json**

```
{ "printBackground": true, "pageSize": "A4" }
```

Bloque de código 1.2: Export settings

A long path, to check how the header wraps or cuts:

src/very/deep/package/structure/with/a/long/**module_name_here.py**

```
VALUE = 42
```

Bloque de código 1.3: Deep module

A block with no file name, for comparison:

```
md-to-pdf informe.md
```

Bloque de código 1.4: Shell command