# 1. Sample section

**Variant A: Editor tab**

The converter starts here. The function reads the file and writes the PDF:

src/main.py

```
def main():
    args = parse_args()
    for path in args.files:
        convert(path)
```

*Bloque de código 1.1: Main entry point*

A config file with a dark theme on the block:

config/export.json

```
{ "printBackground": true, "pageSize": "A4" }
```

*Bloque de código 1.2: Export settings*

A long path, to check how the header wraps or cuts:

src/very/deep/package/structure/with/a/long/module_name_here.py

```
VALUE = 42
```

*Bloque de código 1.3: Deep module*

A block with no file name, for comparison:

```
md-to-pdf informe.md
```

*Bloque de código 1.4: Shell command*

# 1. Sample section

**Variant B: Full-width title bar**

The converter starts here. The function reads the file and writes the PDF:

src/main.py

```
def main():
    args = parse_args()
    for path in args.files:
        convert(path)
```

*Bloque de código 1.1: Main entry point*

A config file with a dark theme on the block:

config/export.json

```
{ "printBackground": true, "pageSize": "A4" }
```

*Bloque de código 1.2: Export settings*

A long path, to check how the header wraps or cuts:

src/very/deep/package/structure/with/a/long/module_name_here.py

```
VALUE = 42
```

*Bloque de código 1.3: Deep module*

A block with no file name, for comparison:

```
md-to-pdf informe.md
```

*Bloque de código 1.4: Shell command*

# 1. Sample section

**Variant C: Comment line inside the box**

The converter starts here. The function reads the file and writes the PDF:

```src/main.py
def main():
    args = parse_args()
    for path in args.files:
        convert(path)
```

*Bloque de código 1.1: Main entry point*

A config file with a dark theme on the block:

```config/export.json
{ "printBackground": true, "pageSize": "A4" }
```

*Bloque de código 1.2: Export settings*

A long path, to check how the header wraps or cuts:

```src/very/deep/package/structure/with/a/long/module_name_here.py
VALUE = 42
```

*Bloque de código 1.3: Deep module*

A block with no file name, for comparison:

```
md-to-pdf informe.md
```

*Bloque de código 1.4: Shell command*

# 1. Sample section

**Variant D: Corner badge**

The converter starts here. The function reads the file and writes the PDF:

src/main.py

```
def main():
    args = parse_args()
    for path in args.files:
        convert(path)
```

*Bloque de código 1.1: Main entry point*

A config file with a dark theme on the block:

config/export.json

```
{ "printBackground": true, "pageSize": "A4" }
```

*Bloque de código 1.2: Export settings*

A long path, to check how the header wraps or cuts:

src/very/deep/package/structure/with/a/long/module_name_here.py

```
VALUE = 42
```

*Bloque de código 1.3: Deep module*

A block with no file name, for comparison:

```
md-to-pdf informe.md
```

*Bloque de código 1.4: Shell command*

# 1. Sample section

**Variant E: Plain label above, no box**

The converter starts here. The function reads the file and writes the PDF:

File: `src/main.py`

```
def main():
    args = parse_args()
    for path in args.files:
        convert(path)
```

*Bloque de código 1.1: Main entry point*

A config file with a dark theme on the block:

File: `config/export.json`

```
{ "printBackground": true, "pageSize": "A4" }
```

*Bloque de código 1.2: Export settings*

A long path, to check how the header wraps or cuts:

File: `src/very/deep/package/structure/with/a/long/module_name_here.py`

```
VALUE = 42
```

*Bloque de código 1.3: Deep module*

A block with no file name, for comparison:

```
md-to-pdf informe.md
```

*Bloque de código 1.4: Shell command*