


5-3-1 [OHU] A 40 kg aluminum block at 90°C is dropped into an insulated tank that contains 0.5 m³ of liquid water at 20°C. Determine the equilibrium temperature.

SOLUTION



Given:

$$c_1 = 0.9 \frac{\text{kJ}}{\text{kg} \cdot \text{K}};$$

$$c_2 = 4.184 \frac{\text{kJ}}{\text{kg} \cdot \text{K}};$$

State-1 (given T_1, m_1)

State-2 (given T_2, v_2):

$$m_2 = \frac{V}{v} = \frac{0.5}{0.001} = 500 \text{ kg};$$

The energy balance on the system can be expressed as

$$E_{\text{in}} - E_{\text{out}} = \Delta E_{\text{system}};$$

$$\Rightarrow 0 = \Delta U;$$

The total internal energy if the system can be expressed as

$$\Delta U_{\text{system}} = \Delta U_{\text{Al}} + \Delta U_{\text{water}};$$

$$\Rightarrow 0 = [m_1 c_1 (T_3 - T_1)]_{\text{Al}} + [m_2 c_2 (T_3 - T_2)]_{\text{water}};$$

$$\Rightarrow 0 = [(40)(0.9)(T_3 - 90)] + [(500)(4.184)(T_3 - 20)];$$

$$\Rightarrow T_3 = 21.18^\circ\text{C}$$


TEST Solution:

Launch the SL/SL non-uniform non-mixing closed process system TESTcalc to verify the solution. The TEST-code for this problem can be found in the TEST-Pro site at www.thermofluids.net

This work is protected by United States copyright laws and is provided solely for the use of instructors in teaching their courses and assessing student learning. Dissemination or sale of any part of this work (including on the World Wide Web) will destroy the integrity of the work and is not permitted.

5-3-2 [OHC] In the problem described above, determine the entropy generated during the process.

SOLUTION



Given:

$$c_1 = 0.9 \frac{\text{kJ}}{\text{kg} \cdot \text{K}};$$

$$c_2 = 4.184 \frac{\text{kJ}}{\text{kg} \cdot \text{K}};$$

State-1 (given T_1, m_1)

State-2 (given T_2, v_2):

$$m_2 = \frac{V}{v} = \frac{0.5}{0.001} = 500 \text{ kg};$$

The energy balance on the system can be expressed as

$$E_{\text{in}} - E_{\text{out}} = \Delta E_{\text{system}};$$

$$\Rightarrow 0 = \Delta U;$$

The total internal energy if the system can be expressed as

$$\Delta U_{\text{system}} = \Delta U_{\text{Al}} + \Delta U_{\text{water}};$$

$$\Rightarrow 0 = [m_1 c_1 (T_3 - T_1)]_{\text{Al}} + [m_2 c_2 (T_3 - T_2)]_{\text{water}};$$

$$\Rightarrow 0 = [(40)(0.9)(T_3 - 90)] + [(500)(4.184)(T_3 - 20)];$$

$$\Rightarrow T_3 = 21.18^\circ \text{C};$$

The entropy balance can be expressed as

$$S_{\text{gen,univ}} = \Delta S - \frac{Q}{T_B};$$

$$\Rightarrow S_{\text{gen,univ}} = m_1 c_1 \ln \frac{T_3}{T_1} + m_2 c_2 \ln \frac{T_3}{T_2};$$

$$\Rightarrow S_{\text{gen,univ}} = (40)(0.9) \ln \frac{(294.18)}{(363)} + (500)(4.184) \ln \frac{(294.18)}{(293)};$$

$$\Rightarrow S_{\text{gen,univ}} = -7.56 + 8.404;$$

$$\Rightarrow S_{\text{gen,univ}} = 0.848 \frac{\text{kJ}}{\text{K}}$$


TEST Solution:

Launch the SL/SL non-uniform non-mixing closed process system TESTcalc to verify the solution. The TEST-code for this problem can be found in the TEST-Pro site at www.thermofluids.net

This work is protected by United States copyright laws and is provided solely for the use of instructors in teaching their courses and assessing student learning. Dissemination or sale of any part of this work (including on the World Wide Web) will destroy the integrity of the work and is not permitted.

5-3-3 [OHV] A 25 kg aluminum block initially at 225°C is brought into contact with a 25 kg block of iron at 150°C in an insulating enclosure. Determine (a) the equilibrium temperature, (b) and the total entropy change for this process.

SOLUTION



Given:

$$c_1 = 0.9 \frac{\text{kJ}}{\text{kg} \cdot \text{K}};$$

$$c_2 = 0.45 \frac{\text{kJ}}{\text{kg} \cdot \text{K}};$$

State-1 (given T_1, m_1)

State-2 (given T_2, m_2)

The energy balance on the system can be expressed as

$$E_{\text{in}} - E_{\text{out}} = \Delta E_{\text{system}};$$

$$\Rightarrow 0 = \Delta U;$$

(a) The total internal energy if the system can be expressed as

$$\Delta U_{\text{system}} = \Delta U_{\text{Al}} + \Delta U_{\text{Fe}};$$

$$\Rightarrow 0 = [m_1 c_1 (T_3 - T_1)]_{\text{Al}} + [m_2 c_2 (T_3 - T_2)]_{\text{Fe}};$$

$$\Rightarrow 0 = [(25)(0.9)(T_3 - 225)] + [(25)(0.45)(T_3 - 150)];$$

$$\Rightarrow T_3 = 200^\circ\text{C}$$

(b) The entropy balance can be expressed as

$$S_{\text{gen,univ}} = \Delta S - \frac{Q}{T_B}^0;$$

$$\Rightarrow S_{\text{gen,univ}} = m_1 c_1 \ln \frac{T_3}{T_1} + m_2 c_2 \ln \frac{T_3}{T_2};$$

$$\Rightarrow S_{\text{gen,univ}} = (25)(0.9) \ln \frac{(473)}{(498)} + (25)(0.45) \ln \frac{(473)}{(423)};$$

$$\Rightarrow S_{\text{gen,univ}} = -1.15 + 1.256;$$

$$\Rightarrow S_{\text{gen,univ}} = 0.097 \frac{\text{kJ}}{\text{K}}$$


TEST Solution:

Launch the SL/SL non-uniform non-mixing closed process system TESTcalc to verify the solution. The TEST-code for this problem can be found in the TEST-Pro site at www.thermofluids.net

This work is protected by United States copyright laws and is provided solely for the use of instructors in teaching their courses and assessing student learning. Dissemination or sale of any part of this work (including on the World Wide Web) will destroy the integrity of the work and is not permitted.

5-3-4 [OHQ] A half kg bar of iron, initially at 782°C, is removed from an oven and quenched by immersing it in a closed tank containing 10 kg of water initially at 21°C. Heat transfer from the tank can be neglected. Determine (a) the equilibrium temperature, (b) and the total entropy change for this process.

SOLUTION



Given:

$$c_1 = 0.45 \frac{\text{kJ}}{\text{kg} \cdot \text{K}};$$

$$c_2 = 4.184 \frac{\text{kJ}}{\text{kg} \cdot \text{K}};$$

State-1 (given T_1, m_1)

State-2 (given T_2, m_2)

The energy balance on the system can be expressed as

$$E_{\text{in}} - E_{\text{out}} = \Delta E_{\text{system}};$$

$$\Rightarrow 0 = \Delta U;$$

(a) The total internal energy if the system can be expressed as

$$\Delta U_{\text{system}} = \Delta U_{\text{Fe}} + \Delta U_{\text{water}};$$

$$\Rightarrow 0 = [m_1 c_1 (T_3 - T_1)]_{\text{Fe}} + [m_2 c_2 (T_3 - T_2)]_{\text{water}};$$

$$\Rightarrow 0 = [(0.5)(0.45)(T_3 - 782)] + [(10)(4.184)(T_3 - 21)];$$

$$\Rightarrow T_3 = 25.07^\circ \text{C}$$

(b) The entropy balance can be expressed as

$$S_{\text{gen,univ}} = \Delta S - \frac{Q}{T_B}^0;$$

$$\Rightarrow S_{\text{gen,univ}} = m_1 c_1 \ln \frac{T_3}{T_1} + m_2 c_2 \ln \frac{T_3}{T_2};$$

$$\Rightarrow S_{\text{gen,univ}} = (0.5)(0.45) \ln \frac{(298.07)}{(1055)} + (10)(4.184) \ln \frac{(298.07)}{(294)};$$

$$\Rightarrow S_{\text{gen,univ}} = -0.284 + 0.575;$$

$$\Rightarrow S_{\text{gen,univ}} = 0.291 \frac{\text{kJ}}{\text{K}}$$


TEST Solution:

Launch the PC/SL non-uniform non-mixing closed process system TESTcalc to verify the solution. The TEST-code for this problem can be found in the TEST-Pro site at www.thermofluids.net

This work is protected by United States copyright laws and is provided solely for the use of instructors in teaching their courses and assessing student learning. Dissemination or sale of any part of this work (including on the World Wide Web) will destroy the integrity of the work and is not permitted.

5-3-5 [OHY] A 15 kg block of copper at 100°C is dropped into an insulated tank that contains 1 m³ of liquid water at 20°C. Determine (a) the equilibrium temperature (b) the entropy generated in this process.

SOLUTION



Given:

$$c_1 = 0.386 \frac{\text{kJ}}{\text{kg} \cdot \text{K}};$$

$$c_2 = 4.184 \frac{\text{kJ}}{\text{kg} \cdot \text{K}};$$

State-1 (given T_1, m_1)

State-2 (given T_2, v_2):

$$m_2 = \frac{V}{v} = \frac{1}{0.001} = 1000 \text{ kg};$$

The energy balance on the system can be expressed as

$$E_{\text{in}} - E_{\text{out}} = \Delta E_{\text{system}};$$

$$\Rightarrow 0 = \Delta U;$$

(a) The total internal energy if the system can be expressed as

$$\Delta U_{\text{system}} = \Delta U_{\text{Cu}} + \Delta U_{\text{water}};$$

$$\Rightarrow 0 = [m_1 c_1 (T_3 - T_1)]_{\text{Cu}} + [m_2 c_2 (T_3 - T_2)]_{\text{water}};$$

$$\Rightarrow 0 = [(15)(0.386)(T_3 - 100)] + [(1000)(4.184)(T_3 - 20)];$$

$$\Rightarrow T_3 = 20.11^\circ \text{C}$$

(b) The entropy balance can be expressed as

$$S_{\text{gen,univ}} = \Delta S - \frac{Q}{T_B} ;$$

$$\Rightarrow S_{\text{gen,univ}} = m_1 c_1 \ln \frac{T_3}{T_1} + m_2 c_2 \ln \frac{T_3}{T_2} ;$$

$$\Rightarrow S_{\text{gen,univ}} = (1000)(4.184) \ln \frac{(293.11)}{(293)} + (15)(0.386) \ln \frac{(293.11)}{(373)} ;$$

$$\Rightarrow S_{\text{gen,univ}} = 1.570 - 1.396 ;$$

$$\Rightarrow S_{\text{gen,univ}} = 0.174 \frac{\text{kJ}}{\text{K}}$$


TEST Solution:

Launch the PC/SL non-uniform non-mixing closed process system TESTcalc to verify the solution. The TEST-code for this problem can be found in the TEST-Pro site at www.thermofluids.net

This work is protected by United States copyright laws and is provided solely for the use of instructors in teaching their courses and assessing student learning. Dissemination or sale of any part of this work (including on the World Wide Web) will destroy the integrity of the work and is not permitted.

5-3-6 [OHF] An unknown mass of iron at 80°C is dropped into an insulated tank that contains 0.1 m³ of liquid water at 20°C. Meanwhile, a paddle wheel driven by a 200 W motor is used to stir the water. When equilibrium is reached after 20 min, the final temperature is 25 °C. Determine (a) the mass of the iron block. (b) *What-if scenario:* How would the answer in part (a) change if the iron block was at 150 °C at the time of dropping.

SOLUTION



Given:

$$c_1 = 0.45 \frac{\text{kJ}}{\text{kg} \cdot \text{K}};$$

$$c_2 = 4.184 \frac{\text{kJ}}{\text{kg} \cdot \text{K}};$$

State-1 (given T_1)

State-2 (given T_2, v_2):

$$m_2 = \frac{V}{v} = \frac{0.1}{0.001} = 100 \text{ kg};$$

The energy balance on the system can be expressed as

$$E_{\text{in}} - E_{\text{out}} = \Delta E_{\text{system}};$$

$$\Rightarrow 0 = \Delta U;$$

$$(a) \quad \cancel{Q}^0 = [m_1 c_1 (T_3 - T_1)]_{\text{Fe}} + [m_2 c_2 (T_3 - T_2)]_{\text{water}} + W_{\text{ext}};$$

$$\Rightarrow 240 = [m_1 (0.45)(25 - 80)] + [(100)(4.184)(25 - 20)];$$

$$\Rightarrow m_1 = 74.74 \text{ kg}$$

TEST Solution and What-if Scenario:

Launch the SL/SL non-uniform non-mixing closed process system TESTcalc to verify the solution and conduct the what-if study. The TEST-code for this problem can be found in the TEST-Pro site at www.thermofluids.net.

This work is protected by United States copyright laws and is provided solely for the use of instructors in teaching their courses and assessing student learning. Dissemination or sale of any part of this work (including on the World Wide Web) will destroy the integrity of the work and is not permitted.