

No. : 202632135



Proposal

**CNC PRESS BRAKE BRAND:
MEKOTEK MODEL: MKT 32135**

Prepared by:

Osman Boydas 562-350-2071

KAIMEC LLC.

1231 EDINGER AVE.
CA 92780

GENERAL VIEW OF THE PRESS BRAKE



MAJOR SPECS and ACCESSORIES INCLUDED

- Bending Length : 10' 6" (3,200mm)
- Bending force : 1,300kN / 135T
- 6 AXIS : Y1-Y2-X-R-Z1-Z2
- CNC Auto Crowning
- X:650 mm Backrest Axis
- Back Gauge Servo Motors
- Back Gauge Reducer
- Rexroth Hydraulic System (German)
- Cybelec 15 (CybTouch 15) CNC Control Unit
- Servo system
- Hydraulic System - Rexroth (German)
- Servo System -Inovance
- Magnetic Ruler - Givi (Italian)
- Front Safety Barrier - DSP A200 (Italian)
- Oil Pump - First
- Euro type Punch - Upper Mold -H100/R03
- Punch Holder Type - Easy Latch Change
- Eurotype Bottom Mold- 4 SIDED
- Electric Components - Schneider
- Double Foot Pedal
- Stainless Oil Tank
- Protection Hood with Safety Switch
- Front and Rear Operation LED
- Sliding Front Arm Support System
- Incoming voltage 220-240 or 480volt
- Transformer 480to 380v.
- Installation And Training

TECHNICAL SPECIFICATIONS		
Bending Force	1,350kN	303,450 lbf
Bending Tonnage	135T	149 US tons
Bending Length	3,200mm	126 in (10.5 ft)
Workbench Height	900mm	35.4 in
Column Spacing	2,500mm	98.4 in
Throat Depth	400mm	15.7 in
Slide Stroke	200mm	7.87 in
Maximum Opening Height	470mm	18.5 in
Rapid Descent Speed	180mm/s	7.09 in/s
Return Speed	140mm/s	5.51 in/s
Working Speed	10mm/s	0.39 in/s
Rear Gear (X-axis) Stroke	550mm	21.65 in
Max Operating Speed (X-axis)	400mm/s	15.75 in/s
X-axis Positioning Accuracy	± 0.05mm	± 0.002 in
X-axis Repeat Positioning Accuracy	± 0.02mm	± 0.0008 in
Y-axis Positioning Accuracy	± 0.02mm	± 0.0008 in
Y-axis Repeat Positioning Accuracy	± 0.01mm	± 0.0004 in
R-axis Stroke	150mm	5.91 in
Max Operating Speed (R-axis)	100mm/s	3.94 in/s
Working Accuracy	± 0.2mm/m, Angle: ± 0.5°/m	± 0.002 in/ft, Angle: ± 0.5°/m
Number of CNC Axes	4 + 2	4 + 2
Main Motor Power	11KW	14.75 HP
Fuel Tank Capacity	200L	52.8 gal
Machine Dimensions (L×W×H)	4000 × 1750 × 2860mm	157.5 × 68.9 × 112.6 in
Machine Weight	8,300kg	18,300 lbs

Main Configuration	
Control system	CT15
Hydraulic system valve group	Rexroth
Servo motor	Inovance
Oil pump	First (U.S.)
Oil cylinders	HY
Main motor	Inovance
Compensation method	DSP protection
Control axes	4 axis
Magnetic grid ruler	Givi (Italy)
X-axis linear guide	HIWIN
X-axis linear rod	HIWIN
Electrical components	Schneider
Fixture	Double sided quick clamp
Compensation workbench	SRJM
Safety light curtain	DSP/A200 (Including black bracket)
Protective doors	Installed protective doors
Standard Configuration	
CNC System	1 set
Positioning gear fingers	4 pcs
Standard upper molds	1 set
Standard lower mold	1 set
Pedal switches	1 set
Toolboxes	1 set



4. Price

DESCRIPTION	
Model: MKT 32135	\$105,000.00

Warranty	24 months warranty on all parts to include the fiber laser source
Shipment	In 10 days after PO date (from manufacturer)
Payment	Our standard payment terms are 30% deposit required with purchase; balance due prior to shipping
Sales Tax	Will be added to the invoices (not included in the prices)
Terms	FOBTUSTIN, CA