

FIBER LASER CUTTING MACHINES



FLO 1530 (5x10FT)

**MADE IN EUROPE
HIGH QUALITY
HIGH SPEED
HIGH ACCURACY**

FIBER LASER CUTTING MACHINES



Cutting Thickness	1kW to 30kW
Carbon Steel	10 mm (3/8") to 70mm (2-3/4")
Stainless Steel	3 mm (1/8") to 40mm (1-9/16")
Aluminum	2 mm (1/16") to 30mm (1-3/16")
Brass	2 mm (1/16") to 20mm (3/4")

Available Sizes
1500 x 3000mm (5 x 10 ft)
2000 x 4000mm (6.5 x 13 ft)
2500 x 6000mm (6.5 x 20 ft)

Laser Power
FLO Models: 1 to 4kW
FLC Models: 1 to 30kW

MATERIALS CAN BE CUT



**Carbon
Steel**



Brass

**Stainless
Steel**



Copper




Titanium



Mild Steel

Aluminum



Iron



OPEN TYPE FIBER LASERS

Available Sizes

1500 x 3000mm (5 x 10 ft)

2000 x 4000mm (6.5 x 13 ft)

2500 x 6000mm (6.5 x 20 ft)





OPEN
TYPE FIBER
LASER CUTTING
MACHINES

FLO-1530 (5x10ft)

Cutting Thickness	1000 w	2000 w	3000 w
Carbon Steel	10mm (3/8")	14mm (9/16")	16mm (5/8")
Stainless Steel	3 mm (1/8")	5 mm (3/16")	6 mm (1/4")
Aluminium	2 mm (1/16")	4 mm (1/8")	5 mm (3/16")
Brass	2 mm (1/16")	4 mm (1/8")	5 mm (3/16")

SPECIFICATIONS

Working Area	1500 x 3000 mm (5 x 10 ft) / option (2000x4000mm (6.5 x 13ft))
Loading Capacity	800 kg (1750 lbs)
X-Y Axis Travel	1520 x 3030 mm (5 x 10 ft)
Z Axis Travel	100 mm (3.94")
X-Y-Z Axis Guideway	4 Point Ball Caged
X-Y Axis Drive System	Rack
Z Axis Drive System	Ballscrew
X-Y Axis Speed	80 m/min (3150 ipm)
Z Axis Speed	30 m/min (1180 ipm)
X-Y Position Accuracy	0.05 mm (0.002")
X-Y Repeatatability Accuracy	0.03 mm (0.001")
Laser Source	JPT / Han's
Laser Source Output Power CNC	1000 / 2000 / 3000 W
Control System	Fscut / Cypcut
Laser Cutting Head	Raytools / BOCI / WSX
Assist Gasses	Air / Oxygen / Nitrogen
Cooling Type	Water Cooling
Machine Weight	2300 kg (5100 lbs)
Machine Dimensions (W x L x H)	2355 x 4302 x 1980 mm (7.7 x 14.1 x 6.5 ft)
Graphic Format	dwg / dxf / stp
Electricity	220 or 380 Volt / 3 phase / 60 Hz
Certifications	CE / ISO / FDA
Warranty	2 Years



OPEN TYPE
DUAL-TABLE
FIBER LASER
CUTTING
MACHINES

FLO-D-1530

5x10ft

Cutting Thickness	1000 w	2000 w	3000 w
Carbon Steel	10mm (3/8")	14mm (9/16")	16mm (5/8")
Stainless Steel	3 mm (1/8")	5 mm (3/16")	6 mm (1/4")
Aluminium	2 mm (1/16")	4 mm (1/8")	5 mm (3/16")
Brass	2 mm (1/16")	4 mm (1/8")	5 mm (3/16")

SPECIFICATIONS

Working Area	1500 x 3000 mm (5 x 10 ft)
Loading Capacity	1200 kg (2650 lbs)
X-Y Axis Travel	1520 x 3030 mm (5 x 10 ft)
Z Axis Travel	100 mm (3.94")
X-Y-Z Axis Guideway	4 Point Ball Caged
X-Y Axis Drive System	Rack
Z Axis Drive System	Ballscrew
X-Y Axis Speed	80 m/min (3150 ipm)
Z Axis Speed	30 m/min (1180 ipm)
X-Y Position Accuracy	0.05 mm (0.002")
X-Y Repeatatability Accuracy	0.03 mm (0.001")
Laser Source	JPT / Han's
Laser Source Output Power	1000 / 2000 / 3000 W
CNC Control System	Fscut / Cypcut
Laser Cutting Head	Raytools / BOCI / WSX
Assist Gasses	Air / Oxygen / Nitrogen
Cooling Type	Water Cooling
Machine Weight	4500 kg (9900 lbs)
Machine Dimensions (W x L x H)	2355 x 8580 x 1980 mm (7.7 x 28.1 x 6.5 ft)
Graphic Format	dwg / dxf / stp
Electricity	220 or 380 Volt / 3 phase / 60 Hz
Certifications	CE / ISO / FDA
Warranty	2 Years



OPEN TYPE
SHEET/ PLATE
AND
PIPE/PROFILE
CUTTING LASER

5x10ft

FLO-P-1530

Cutting Thickness	1000 w	2000 w	3000 w
Carbon Steel	10mm (3/8")	14mm (9/16")	16mm (5/8")
Stainless Steel	3 mm (1/8")	5 mm (3/16")	6 mm (1/4")
Aluminium	2 mm (1/16")	4 mm (1/8")	5 mm (3/16")
Brass	2 mm (1/16")	4 mm (1/8")	5 mm (3/16")

SPECIFICATIONS

Working Area	1500 x 3000 mm (5 x 10 ft)
Loading Capacity	800 / 350 kg (1750 / 770 lbs)
X-Y Axis Travel	1520 x 3030 mm (5 x 10 ft)
Z Axis Travel	400 mm (15.7")
X-Y-Z Axis Guideway	4 Point Ball Caged
X-Y Axis Drive System	Rack
Z Axis Drive System	Ballscrew
X-Y Axis Speed	80 m/min (3150 ipm)
Z Axis Speed	30 m/min (1180 ipm)
X-Y Position Accuracy	0.05 mm (0.002")
X-Y Repeatability Accuracy	0.03 mm (0.001")
Max. Profile Length	6100 mm (20 ft)
Max. Pipe / Profile Dimensions	Ø 220 mm (8.7")
Laser Source	JPT / Han's
Laser Source Output Power CNC	1000 / 2000 / 3000 W
Control System	Fscut / Cypcut / Tube Pro
Laser Cutting Head	Raytools / BOCI / WSX
Assist Gasses	Air / Oxygen / Nitrogen
Cooling Type	Water Cooling
Machine Weight	4100 kg (9000 lbs)
Machine Dimensions (W x L x H)	3200 x 8150 x 1980 mm (10.5 x 26.7 x 6.5 ft)
Graphic Format	dwg / dxf / stp
Electricity	220 or 380 Volt / 3 phase / 60 Hz
Certifications	CE / ISO / FDA
Warranty	2 Years

CLOSE TYPE FIBER LASERS



FLC 1530
(5x10ft)



FLC 2040
(6.5x13ft)



FLO 2060
(6.5x20ft)

FLC-1530

(5x10ft)

FULLY ENCLOSED
DUAL TABLE FIBER
LASER
CUTTING MACHINES



SPECIFICATIONS

Working Area	1500 x 3000 mm (5 x 10 ft)
Loading Capacity	1200 kg (2650 lbs)
X-Y Axis Travel	1520 x 3030 mm (5 x 10 ft)
Z Axis Travel	300 mm (11.8")
X-Y-Z Axis Guideway	4 Point Ball Caged
X-Y Axis Drive System	Rack
Z Axis Drive System	Ballscrew
X-Y Axis Speed	80 m/min (3150 ipm)
Z Axis Speed	30 m/min (1180 ipm)
X-Y Position Accuracy	0.05 mm (0.002")
X-Y Repeatatability Accuracy	0.03 mm (0.001")
Table Change Time	10 sec
Laser Source	JPT / Han's
Laser Source Output Power	1 / 2 / 3 / 4 / 6 / 8 / 12 / 20 kW
CNC Control System	Fscut / Cypcut
Laser Cutting Head	Raytools / BOCI / WSX
Assist Gasses	Air / Oxygen / Nitrogen
Cooling Type	Water Cooling
Machine Weight	8500 kg (18.750 lbs)
Machine Dimensions (W x L x H)	2698 x 9175 x 2560 mm (8.8 x 30 x 8.4 ft)
Graphic Format	dwg / dxf / stp
Electricity	220 or 380 Volt / 3 phase / 60 Hz
Certifications	CE / ISO / FDA
Warranty	2 Years

Cutting Thickness	1000 w	2000 w	3000 w	4000 w	6000 w	8000 w	12000 w	20000 w
Carbon Steel	10mm (3/8")	14mm (9/16")	16mm (5/8")	10mm (3/8")	22mm (7/8")	25 mm (1")	30mm (19/16")	45mm (29/16")
Stainless Steel	3mm (1/8")	5mm (3/16")	6mm (1/4")	10mm (3/8")	20mm (13/16")	25 mm (1")	25mm (1")	40mm (25/16")
Aluminium	2mm (1/16")	4mm (1/8")	5mm (3/16")	8mm (5/16")	10mm (3/8")	20 mm (13/16")	25mm (1")	30mm (19/16")
Brass	2mm (1/16")	4mm (1/8")	5mm (3/16")	8mm (5/16")	8mm (5/16")	12mm (1/2")	12mm (1/2")	18mm (11/16")

FLC-P-1530

(5x10ft)

FULLY ENCLOSED
SHEET / PLATE & TUBE/PROFILE
FIBER LASER CUTTING MACHINE



SPECIFICATIONS

Working Area	1500 x 3000 mm (5 x 10 ft)
Loading Capacity (Ø 220)	1200 / 350 kg (2650 / 750 lbs)
Loading Capacity (Ø 350)	1200 / 800 kg (2650 / 1750 lbs)
X-Y Axis Travel	1520 x 3030 mm (5 x 10 ft)
Z Axis Travel	350 mm (13.8")
X-Y-Z Axis Guideway	4 Point Ball Caged
X-Y Axis Drive System	Rack
Z Axis Drive System	Ballscrew
X-Y Axis Speed	80 m/min (3150 ipm)
Z Axis Speed	30 m/min (1180 ipm)
X-Y Position Accuracy	0.05 mm (0.002")
X-Y Repeatatability Accuracy	0.03 mm (0.001")
Table Change Time	10 sec
Max. Profile Dimensions	Ø350 / Ø220 (13.8" / 8.6")
Laser Source	JPT / Han's
Laser Source Output Power	1 / 2 / 3 / 4 / 6 / 8 / 12 / 20 kW
CNC Control System	Fscut / Cypcut
Laser Cutting Head	Raytools / BOCI / WSX
Assist Gasses	Air / Oxygen / Nitrogen
Cooling Type	Water Cooling
Machine Weight	10000 kg (22000 lbs)
Machine Dimensions (W x L x H)	4400 x 10000 x 2560 mm (14.4 x 32.8 x 8.4 ft)
Graphic Format	dwg / dxf / stp
Electricity	220 or 380 Volt / 3 phase / 60 Hz
Certifications	CE / ISO / FDA
Warranty	2 Years

Cutting Thickness	1000 w	2000 w	3000 w	4000 w	6000 w	8000 w	12000 w	20000 w
Carbon Steel	10mm (3/8")	14mm (9/16")	16mm (5/8")	10mm (3/8")	22mm (7/8")	25 mm (1")	30mm (19/16")	45mm (29/16")
Stainless Steel	3mm (1/8")	5mm (3/16")	6mm (1/4")	10mm (3/8")	20mm (13/16")	25 mm (1")	25mm (1")	40mm (25/16")
Aluminium	2mm (1/16")	4mm (1/8")	5mm (3/16")	8mm (5/16")	10mm (3/8")	20 mm (13/16")	25mm (1")	30mm (19/16")
Brass	2mm (1/16")	4mm (1/8")	5mm (3/16")	8mm (5/16")	8mm (5/16")	12mm (1/2")	12mm (1/2")	18mm (11/16")

FLP-6035

PIPE / PROFILE FIBER LASER
CUTTING MACHINE



Cutting Thickness	1000 w	2000 w	3000 w
Carbon Steel	10mm (3/8")	14mm (9/16")	16mm (5/8")
Stainless Steel	3 mm (1/8")	5 mm (3/16")	6 mm (1/4")
Aluminium	2 mm (1/16")	4 mm (1/8")	5 mm (3/16")
Brass	2 mm (1/16")	4 mm (1/8")	5 mm (3/16")

SPECIFICATIONS

Loading Capacity	850 kg (1875 lbs)
Z Axis Travel	440 mm (17.3")
X-Y-Z Axis Guideway	4 Point Ball Caged
X-Y Axis Drive System	Rack
Z Axis Drive System	Ballscrew
X-Y Axis Speed	80 m/min (3150 ipm)
Z Axis Speed	30 m/min (1180 ipm)
X-Y Position Accuracy	0.05 mm (0.002")
X-Y Repeatatability Accuracy	0.03 mm (0.001")
Max. Profile Lenght	6100 mm (20 ft)
Max. Profile Dimensions	Ø 350 mm (13.8")
Laser Source	JPT / Han's
Laser Source Output Power	1000 / 2000 / 3000 W
CNC Control System	Fscut
Laser Cutting Head	Raytools / BOCI / WSX
Assist Gasses	Air / Oxygen / Nitrogen
Cooling Type	Water Cooling
Machine Weight	7000 kg (15430 lbs)
Machine Dimensions (W x L x H)	2560 x 11102 x 2671 mm (8.4 x 36.4 x 8.8 ft)
Graphic Format	dwg / dxf / stp
Electricity	220 or 380 Volt / 3 phase / 60 Hz
Certifications	CE / ISO / FDA
Warranty	2 Years



KAIMEC
MACHINES

1231 Edinger Avenue Tustin, CA 92780

Phone: (714)258-8526

General Inquiry: sales@kaimec.com

