INDUSTRIAL STRENGTH SOFTWARE SERVICES
TECHNICAL REPORT · JK-TR-001 · REV 0.1

JOTAKEY

A FORMALLY SPECIFIED FIDO2 SECURITY KEY

AUTHOR
Javier Fernandez

CONTACT
jfernand@me.com

ISSUED
2026-10-14

(C) JAVIER FERNANDEZ @ JOTASOFT 2026

ABSTRACT

Jotakey is a hardware security key, in the family of the YubiKey, with firmware written in Rust. It runs on its own board, the jotakey key (an STM32L432 microcontroller with an OPTIGA Trust M secure element), and on an Espressif ESP32-C6 DevKit.

We explain from first principles how FIDO2, WebAuthn and **passkeys** work, and why they defeat phishing where passwords and one-time codes fail. We also document the design of Jotakey: its threat model, key hierarchy, transports, and the honest limits of each platform against an attacker who holds the device. Finally, we describe how the device is **assured**: Unit and property tests, coverage-guided fuzzing, mutation testing, and test firmware. Formal verification in the Lean 4 theorem prover is also covered. We assume no prior knowledge of formal methods.

DOCUMENT CONTROL

STATUS	MVP firmware on the ESP32-C6: CTAP 2.0, non-resident credentials, USB (via bridge) and BLE. Jotakey key: hardware 0.3.0; firmware written, tested against a simulated OPTIGA, not yet run on a board
HARDWARE	Jotakey key, hardware 0.3.0 (STM32L432KC + OPTIGA Trust M V1, USB-A); Espressif ESP32-C6-DevKitC-1 / M-1
REPOSITORY	`crates/` (Rust), `formal/` (Lean 4), `docs/` (this report)
NORMATIVE RULES	`AGENTS.md` — security invariants 1–9

1 Goals and threat model 4
1.1 Project scope 4
1.2 Correctness 4
1.3 Threat model 4
1.4 Security invariants 6
2 Cryptography primer 6
2.1 Hash functions 6
2.2 Message authentication codes 6
2.3 Digital signatures: ECDSA on P-256 6
2.4 Protecting a PIN in transit 7
2.5 Randomness 7
2.6 Constant time 7
3 From passwords to passkeys 8
3.1 The limitations of passwords 8
3.2 Public-key login 8
3.3 A short history of FIDO 8
3.4 Passkeys 8
3.5 The three parties 9
4 WebAuthn: the two ceremonies 9
4.1 Registration 9
4.2 The RP ID 10
4.3 authenticatorData 10
4.4 Authentication 11
4.5 Attestation 11
5 CTAP2: talking to the authenticator 11
5.1 CBOR 11
5.2 Commands 12
5.3 CTAPHID: CTAP over USB 12
5.4 FIDO over BLE 13
6 Jotakey's architecture 13
6.1 The ESP32-C6 board; USB limitations. 13
6.2 Software layers 14
6.3 The jotakey key's firmware 15
6.4 The key hierarchy 16
6.5 Credential IDs. Keys by derivation 17
6.6 Persistent state 17
6.7 User experience 18
6.8 The USB bridge 18
6.9 Looking at keys: the explorer 22
7 Hardware security 25
7.1 ESP32-C6 features 25
7.2 Provisioning 26
7.3 Side channels 26
7.4 Fault injection attack 26
7.5 The jotakey key. STM32 + security controller 27
7.6 The jotakey key board 29
8 Testing 31
8.1 Unit, scenario and property tests 31
8.2 Fuzzing 31
8.3 Mutation testing 35
8.4 On-device test firmware 36
8.5 End to end 37
8.6 Static checks 37
9 Formal verification 37
9.1 Proofs vs. tests 37
9.2 The landscape of techniques 38

9.3 Lean 4 primer 38
9.4 Modelling 40
9.5 Case study: CBOR has exactly one encoding 40
9.6 Case study: the security state machines 40
9.7 Closing the gap between model and code 42
9.8 Differential testing, step by step 42
9.9 What remains trusted 45
9.10 Working with the proofs 45
10 The proofs 45
10.1 Before you start 49
10.2 Bytes and numbers 49
10.3 CBOR heads 50
10.4 The strict validator 53
10.5 CTAPHID reassembly 53
10.6 The authenticator state machine 54
10.7 Credential IDs 56
10.8 PIN lockout 57
10.9 When a touch counts 57
10.10 The record log under power loss 58
10.11 The OPTIGA session 59
10.12 What the proofs leave out 60
10.13 Rust and Lean names 60
11 Roadmap 63
11.1 Full CTAP 2.1 passkeys 63
11.2 Hardware 64
11.3 Assurance 65
A Invariant traceability 65
B Repository map 66
C Getting started 66
D Glossary 67
E References 67

01 GOALS AND THREAT MODEL

1.1 PROJECT SCOPE

A **security key** is a small device that holds private keys and uses them to prove the holder's identity to websites, without ever letting those keys out. You plug it in (or bring it close, or pair it over Bluetooth), the browser asks it to sign a challenge, a light blinks, you touch it, and you are logged in. The YubiKey is the best-known example.

Jotakey does the same job on two platforms. **jotakey** is its own hardware: a USB-A dongle with an STM32L432 microcontroller, which talks to the computer directly as a USB security key, and an Infineon **OPTIGA Trust M** secure element, which holds the root secret. A capacitive touch pad is its "touch" sensor and a red LED its only display (`hardware/HARDWARE.md`).

The **ESP32-C6 DevKit** is an inexpensive, commonly available, open development board: a 160 MHz RISC-V microcontroller with Wi-Fi 6, Bluetooth LE and 802.15.4 radios, 512 KiB of SRAM and 4–8 MiB of flash. It has two USB-C ports and two buttons, **BOOT** and **RESET**, plus one addressable RGB LED; Jotakey uses the BOOT button as its touch sensor. The DevKit has no secure element and needs a host bridge for USB (§6.1), so it serves as the development platform, and jotakey is the device to carry.

PROTOCOL	FIDO2: CTAP 2.0 authenticator, WebAuthn-compatible
ALGORITHMS	ES256 (ECDSA P-256 with SHA-256), HMAC-SHA256, HKDF-SHA256
TRANSPORTS	CTAPHID over USB (native on the key; through a host bridge on the C6), FIDO over BLE (C6)
CREDENTIALS	Non-resident ("server-side") credentials, unlimited in number
USER PRESENCE	Touch pad (key) or BOOT button (C6), debounced, fresh press required for every signature
ROOT OF TRUST	OPTIGA Trust M secure element (key); eFuse HMAC key (C6)
LANGUAGE	Rust, `no_std` , no heap in the protocol core, no `unsafe` in the core
VERIFICATION	Lean 4 models and proofs of the security-critical state machines

1.2 CORRECTNESS

A user believes they are protected when using this device. There are three ways in which this trust would be broken:

1. **Key compromise.** If an attacker learns a credential's private key, they can log in as the user from anywhere, forever, and the user cannot tell.
2. **Silent use.** If the key can be made to sign without the user's knowledge (no touch, or a touch meant for something else), an attacker who controls the computer can log in to any account registered with the key.
3. **Denial of service, and confusion.** Crashes, lockups or ambiguous parsing let a malicious host wedge the device, or worse, make two components disagree about what was signed.

The rest of this report is about making these failures impossible by construction where we can, unlikely where we cannot, and **documented** everywhere.

1.3 THREAT MODEL

We assume a strong attacker.

ATTACKER	CAPABILITIES	OUTCOME FOR JOTAKEY
Phishing site	Lures the user to `examp1e.com` and relays their login to `example.com` .	**Defeated.** Credentials are bound to the RP ID. The browser enforces the origin; the key enforces the binding (§4.3, invariant 3).
Malware on the host	Full control of the computer and browser: can send any CTAP message at any time, read every response.	**Contained.** It cannot extract keys. It can ask for signatures, but each one needs a fresh physical touch (invariant 1). It can trick the user into touch-

ATTACKER	CAPABILITIES	OUTCOME FOR JOTAKEY
		ing for the wrong site. That is inherent to every security key without a display.
Malicious USB/BLE peer	Sends malformed, oversized or out-of-order frames.	**Defeated.** Total parsers, bounded buffers, strict canonical CBOR, channel isolation (invariants 4–5). Verified by fuzzing and Lean proofs.
Network eavesdropper	Sees all WebAuthn traffic between browser and website.	**Irrelevant.** Only public keys and signatures over fresh challenges travel.
Database breach at the RP	Steals every stored public key and credential ID.	**Irrelevant.** Public keys cannot be used to log in; credential IDs are useless without the device's root key.
Thief, casual	Holds the device for minutes, no lab.	**Defeated with a PIN; partially without.** With a PIN set, every login that asks for user verification needs it, and the key blocks after 8 wrong guesses (3 per power cycle, invariant 10). Without a PIN, or where a site asks only for presence, the thief can log in where the user only needs a security key. Accounts that also require a password stay safe.
Thief, laboratory	Decapsulation, voltage/EM fault injection, power analysis.	**Jotakey key: partially defeated.** The root secret and the counter stay in the OPTIGA secure element (EAL6+ hardware). A thief who breaks the STM32 can **use** the key while holding it, and copy a credential only if they also obtain its ID from the website; they cannot copy the key as a whole (§7.5). **ESP32-C6: not defeated.** Published attacks bypass secure boot and flash encryption on this chip family (§7.4).
Supply chain	Tampered board or toolchain before provisioning.	**Out of scope** for the MVP; partially mitigated by reproducible builds and secure boot.

SUMMARY

Jotakey is a strong defence against **remote** attackers: phishing, malware and network attackers, which are the most common. Against a well-equipped attacker with physical possession, the two platforms differ. **jotakey** keeps its root secret in a certified secure element, so a stolen key cannot be cloned as a whole, although an attacker who breaks its microcontroller can use it while they hold it. The ESP32-C6 has no secure element and gives its secrets up as stated in the threat model, in `AGENTS.md`, and in the roadmap.

1.4 SECURITY INVARIANTS

The design is centered around ten invariants. They are written in `AGENTS.md` (normative for anyone changing the code). Each is enforced in code and checked by tests. Where marked ⊢, they are also proved in Lean. Appendix A traces each invariant to its implementation, tests and theorems.

#	INVARIANT	LEAN
1	No signature carrying the UP flag without a user-presence event consumed within the same command.	⊢
2	The signature counter strictly increases, across power loss.	⊢
3	A credential ID unwraps only for the relying party it was minted for.	⊢
4	Parsers are total and bounded: every input yields a result, never a crash.	⊢
5	CTAPHID channels are isolated from each other.	⊢
6	Reset only within 10 s of power-up, and only with a touch.	⊢
7	Fail closed: failed self tests disable the authenticator permanently.	⊢
8	The root secret never leaves its hardware key store (OPTIGA or eFuse HMAC); secrets are zeroized, never logged.	
9	No secret-dependent branches or memory accesses in our code.	
10	At most 8 wrong PINs between correct ones, 3 per power cycle; every attempt is counted durably before the PIN is compared.	⊢

02 CRYPTOGRAPHY PRIMER

FIDO2 uses a handful of standard primitives. This chapter explains just enough of each to follow the rest of the report. No mathematics beyond arithmetic is required.

2.1 HASH FUNCTIONS

A **hash function** such as SHA-256 maps any input to a fixed 32-byte **digest**. It is easy to compute and, as far as anyone knows, impossible to run backwards. It is also infeasible to find two inputs with the same digest (a **collision**). Hashes are used as compact, tamper-evident fingerprints. WebAuthn hashes the RP ID (`rpIdHash`) and the client data (`clientDataHash`), and the authenticator signs those hashes, not the raw data.

2.2 MESSAGE AUTHENTICATION CODES

A **MAC** is a hash with a secret key: `HMAC-SHA256(key, message)` produces a tag that only someone holding `key` can compute. Changing a single bit of the message changes the tag unpredictably. Jotakey uses HMAC in two ways:

- to **derive** independent keys from one root key, with a different label for each purpose (`"jotakey/tag/v1"`, `"jotakey/seed/v1"`);
- to **authenticate** credential IDs, so the device can recognise its own IDs and reject forged or foreign ones (§6.4).

HKDF (RFC 5869) is a standard construction built from HMAC. It turns key material plus a salt and a context string into as many independent-looking bytes as needed. Jotakey uses it to derive each credential's private key.

2.3 DIGITAL SIGNATURES: ECDSA ON P-256

A **signature scheme** has a private key, which signs, and a public key, which verifies. Anyone can check a signature, but only the private-key holder can produce one. WebAuthn's default algorithm, **ES256**, is ECDSA over the NIST P-256 elliptic curve with SHA-256.

- A **private key** is a random number d with $1 \le d < n$, where $n \approx 2^{256}$ is the order of the curve.
- The **public key** is the point $Q = d \cdot G$: the fixed generator point G "added to itself" d times. Computing Q from d is fast. Recovering d from Q is the elliptic curve discrete logarithm problem, believed infeasible.
- To **sign** a hash z, pick a secret one-time number k (the **nonce**), compute the point $k \cdot G$, and from it two numbers (r, s). Verification checks an equation using only Q.

> THE NONCE
> If two signatures ever share the same k, or if k is even slightly predictable, simple algebra recovers the private key. This is how Sony's PlayStation 3 signing key leaked in 2010.
>
> Jotakey therefore uses **hedged** nonces (RFC 6979 §3.6): k is derived deterministically from the private key and the message, **and** mixed with 32 fresh bytes from the hardware random number generator. A broken RNG cannot cause nonce reuse, because the deterministic part protects. A fault attack that skips or repeats part of the computation cannot exploit determinism, because the random part protects. The known-answer self test checks the deterministic path against the RFC's published vector at every boot.

2.4 PROTECTING A PIN IN TRANSIT

The PIN (§6.5) travels from the computer to the key over USB, where other software on the computer can watch it. CTAP's **PIN/UV auth protocol two** first agrees a secret, then uses it to encrypt and authenticate:

- **ECDH (elliptic-curve Diffie–Hellman).** Each side has a P-256 key pair and sends the other its public key. Each multiplies its own secret scalar by the other's public point; both arrive at the same point, which an eavesdropper who saw only the public keys cannot compute. The authenticator's key pair lasts one power cycle; the computer's lasts one command.
- **HKDF** turns the shared point's x-coordinate into two independent 32-byte keys: one for HMAC, one for AES.
- **AES-256-CBC** encrypts the PIN (padded to 64 bytes) and, later, the token the key hands back. A fresh random IV goes in front of every ciphertext. No padding scheme is needed because every message is a whole number of 16-byte blocks.
- **HMAC-SHA256** tags each request, proving that it came from the side that holds the shared secret.

Jotakey's implementation (`pin_protocol.rs`) is checked byte for byte against python-fido2's, an independent implementation that browsers' test suites also use. The AES is RustCrypto's bitsliced software AES, which has no secret-dependent table lookups.

2.5 RANDOMNESS

Keys and nonces need **unpredictable** bits. The ESP32-C6 has a hardware true random number generator (TRNG) fed by thermal noise in the SAR ADC and in the radio. Hardware noise sources can fail: a stuck bit, a broken oscillator, a fault-injection glitch. NIST SP 800-90B specifies two cheap **health tests** that catch such failures continuously:

- **Repetition count test.** The same byte repeated too many times in a row (6, for an assumed 4 bits of entropy per byte) means the source is stuck.
- **Adaptive proportion test.** In each window of 512 bytes, the first byte must not recur 62 or more times. This catches a source that has become biased.

The cutoffs are computed exactly from the binomial distribution for a false-alarm rate of 2^{-20} (see `selftest.rs`). Jotakey runs both tests over 1024 bytes at boot and on every byte it uses afterwards. Any failure permanently disables the authenticator (invariant 7).

2.6 CONSTANT TIME

An attacker who can measure **how long** an operation takes, or how much power it draws, can learn secrets if the code's behaviour depends on them. The classic bug is comparing a secret tag with `==`, which stops at the first differing byte and so leaks how many bytes matched. Jotakey compares tags with `subtle::ConstantTimeEq` and uses the RustCrypto `p256` crate, whose scalar arithmetic is written to be constant-time. Its own code never branches on secret data (invariant 9).

03 FROM PASSWORDS TO PASSKEYS

3.1 THE LIMITATIONS OF PASSWORDS

A password is a **shared secret**: the user knows it and the website stores something derived from it. Every login sends the secret, or something equivalent to it, to whoever is on the other end. That design has three structural flaws:

- **Phishing.** The user cannot reliably tell `example.com` from `examp1e.com`. Whatever they type on the fake site, the attacker replays on the real one. One-time codes from an app or SMS do not help: the fake site relays them in real time.
- **Reuse.** A breach at one site exposes the password everywhere it was reused.
- **Server breaches.** The site's database is a treasure chest of password hashes, which attackers crack offline.

3.2 PUBLIC-KEY LOGIN

Public-key authentication removes the shared secret. At registration, a fresh key pair is created **for that one site**. The site stores the public key. At login, the site sends a random **challenge**, and the user's device signs it with the private key. The private key never leaves the device, and the site stores nothing worth stealing.

That alone does not stop phishing: a fake site could relay the challenge too. FIDO adds the missing piece. The **browser**, which reliably knows which site it is talking to, includes the site's origin in what is signed. The **authenticator** only uses a credential for the site it was created for. A signature obtained on `examp1e.com` names `examp1e.com`, and `example.com` rejects it. Domain phishing cannot work.

> **THE PROTOCOL, INSTEAD OF THE USER, IS THE LAST LINE OF DEFENCE AGAINST PHISHING**

3.3 A SHORT HISTORY OF FIDO

YEAR	MILESTONE
2012	The **FIDO Alliance** is founded (PayPal, Lenovo, Nok Nok Labs, Validity, Infineon, Agnitio; Google and Yubico join in 2013).
2014	**U2F** (Universal 2nd Factor): a USB key as a second factor next to the password. Google deploys it internally; in 2018 it reports that no employee account had been phished since security keys became mandatory in early 2017.
2018	**FIDO2** = W3C **WebAuthn** (browser API, Recommendation in 2019) + **CTAP2** (Client-to-Authenticator Protocol). Adds resident (discoverable) credentials, user verification by PIN or biometrics, and passwordless login.
2021	**CTAP 2.1**: credential management, PIN protocol v2, hmac-secret, enterprise attestation.
2022	Apple, Google and Microsoft commit to **passkeys**: FIDO credentials synchronised across a user's devices by the platform.
2023–25	**CTAP 2.2**: the **hybrid** transport (scan a QR code, phone acts as authenticator over BLE plus a cloud relay); passkeys become the default sign-in option on major sites.

3.4 PASSKEYS

"Passkey" is the user-facing name for a **discoverable FIDO credential**. The word covers two deployment models with very different security properties:

	SYNCED PASSKEY	DEVICE-BOUND PASSKEY
Where the key lives	In the platform's cloud keychain (iCloud Keychain, Google Password Manager, 1Password …), end-to-end encrypted, copied to all the user's devices.	In one hardware authenticator (a security key or a TPM), never copied.

	SYNCED PASSKEY	DEVICE-BOUND PASSKEY
Survives losing the device	Yes	No; register a backup key.
Trust anchor	The platform account and its recovery process.	Possession of the physical device.
Typical use	Consumer accounts	High-assurance accounts, administrators, regulated environments.

Jotakey is a **device-bound** authenticator. The MVP implements **non-discoverable** credentials: the website must name the credential (send its ID) at login. This is how security keys work as a second factor, and how many enterprise deployments use them. **Discoverable** credentials, where the device stores the user handle so the website does not need to send an ID ("username-less" passkeys), are the first item on the roadmap (§11).

3.5 THE THREE PARTIES


RELYING PARTY (RP)	The website, e.g. `example.com`. Stores public keys and credential IDs, issues challenges, verifies signatures. Identified by its **RP ID**, a domain.
CLIENT / PLATFORM	The browser plus the operating system. Knows the true origin of the page, builds `clientDataJSON`, talks to authenticators over USB, NFC, BLE or hybrid. Speaks WebAuthn upward and CTAP downward.
AUTHENTICATOR	The key: Jotakey. Holds or derives private keys, checks user presence, signs. Trusts nothing it receives.

THE ROLES IN EVERY FIDO CEREMONY

04 WEBAUTHN: THE TWO CEREMONIES

WebAuthn defines two **ceremonies** (the spec's word for a protocol that includes a human): **registration** creates a credential, **authentication** uses it. Both follow the same pattern: the RP sends a challenge, the browser wraps it, the authenticator signs, and the RP verifies.

4.1 REGISTRATION



REGISTRATION (NAVIGATOR.CREDENTIALS.CREATE)

The browser computes `clientDataJSON`, a small JSON document that records the operation type (`webauthn.create`), the RP's challenge and the **origin** of the page:

CLIENTDATAJSON (BUILT BY THE BROWSER, NEVER BY THE WEBSITE)

```
{"type":"webauthn.create","challenge":"q5sJ…7w","origin":"https://example.com","crossOrigin":false}
```

The authenticator never sees this JSON, only its SHA-256, the `clientDataHash`. It signs over that hash together with its own `authenticatorData`. The RP later checks that the challenge is the one it issued and the origin is its own. A phishing page at `examp1e.com` can relay the challenge, but cannot make the browser write a different origin.

4.2 THE RP ID

Every credential is created for an **RP ID**, a domain such as `example.com`. The browser only lets a page use an RP ID equal to its own host, or a registrable suffix of it: `login.example.com` may use `example.com`, `examp1e.com` may not. The authenticator hashes the RP ID into the credential (Jotakey binds it into the credential ID's authentication tag, §6.4) and refuses to use the credential for any other RP ID. So there are two independent checks: the browser checks origin against RP ID, and the key checks RP ID against credential.

4.3 AUTHENTICATORDATA

Both ceremonies return the same binary structure, which the authenticator builds and signs:

rpIdHash	flags	signCount
32 B · SHA-256(rp.id)	1 B	4 B · big-endian

AUTHENTICATORDATA, ASSERTION FORM: 37 BYTES


aaguid	idLen	credentialId	credentialPublicKey
16 B	2 B	49 B	77 B · COSE_Key

…PLUS ATTESTEDCREDENTIALDATA AT REGISTRATION (JOTAKEY: 181 BYTES IN TOTAL)

BIT	FLAG	MEANING
0	UP	User Present: someone physically interacted with the authenticator. **Jotakey always sets it** (invariant 1).
2	UV	User Verified: PIN or biometric checked. Not supported in the MVP.
3–4	BE/BS	Backup eligible / backed up (synced passkeys). Always 0 for Jotakey.
6	AT	Attested credential data included (registration only).
7	ED	Extension data included. Not used.

The **signature counter** lets an RP detect a cloned authenticator. If an assertion arrives with a counter not larger than the last one seen, two devices may share a key. Jotakey's counter is global, persisted to flash **before** any signature carrying it is released, and proved monotonic in Lean (§9.6).

4.4 AUTHENTICATION



AUTHENTICATION (NAVIGATOR.CREDENTIALS.GET)

The signature covers `authenticatorData ‖ clientDataHash`. The RP verifies it with the public key it stored at registration, checks the UP flag, the RP ID hash, the challenge, the origin, and that the counter increased.

4.5 ATTESTATION

At registration the authenticator can also prove **what kind of device** it is, by signing with a per-model **attestation key** whose certificate chains to the manufacturer. Formats include `packed`, `tpm`, `android-key`, `fido-u2f`, `apple` and `none`. Attestation serves enterprises that must allow only certified models. It costs privacy (keys of one batch are linkable) and requires a certificate authority.

Jotakey uses **packed self-attestation**: the attestation statement is signed with the new credential's own private key. This proves possession of the key and nothing about the device. Most consumer RPs request no attestation (`"none"`) anyway.

05 CTAP2: TALKING TO THE AUTHENTICATOR

WebAuthn is the browser's API. **CTAP**, the Client-to-Authenticator Protocol, is what the browser actually sends to the key. CTAP2 messages are a command byte followed by a **CBOR** map. The answer is a status byte followed by a CBOR map.

5.1 CBOR

CBOR (RFC 8949) is a binary JSON: integers, byte strings, text strings, arrays, maps, booleans. Each item starts with a **head** byte: 3 bits of major type and 5 bits of "additional information". The latter holds a small value directly (0–23) or announces 1, 2, 4 or 8 following bytes.

major	info	argument	payload
3 bits	5 bits	0, 1, 2, 4 or 8 B	…

A CBOR HEAD: MAJOR TYPE 3 (TEXT), LENGTH 11 IN THE LOW BITS, THEN 11 BYTES OF UTF-8

The same value can often be written in several ways: `24` as `0x18 0x18`, as `0x19 0x00 0x18`, and so on. Map keys can appear in any order or twice. For a parser that guards keys, this freedom is dangerous. If the authenticator and some other component disagree about which of two duplicate `rpId` keys counts,

an attacker can show one value to one component and another to the other. CTAP2 therefore requires **canonical** CBOR. Jotakey's decoder rejects everything else:

- every integer, length and count in its shortest form;
- definite lengths only;
- map keys strictly increasing in canonical order (shorter encoding first, then bytewise), which also rules out duplicates;
- no tags, floats or `undefined`; nesting depth at most 4.

The Lean model of this decoder carries two theorems (§9.5). **Round trip**: decoding an encoded head returns exactly the encoded value. **Uniqueness**: anything the decoder accepts is exactly the canonical encoding of what it decoded. A differential test checks that the Rust decoder and the Lean model agree on over 100 000 inputs.

5.2 COMMANDS

BYTE	COMMAND	JOTAKEY MVP
0x01	authenticatorMakeCredential	Yes. ES256 only; `rk` and `uv` options refused. With a PIN token, the UV flag is set.
0x02	authenticatorGetAssertion	Yes. Allow list required (non-resident credentials). With a PIN token, the UV flag is set.
0x04	authenticatorGetInfo	Yes. Versions, AAGUID, options, limits.
0x06	authenticatorClientPIN	Yes, PIN/UV auth protocol two: getPINRetries, getKeyAgreement, setPIN, changePIN, and tokens with the `mc` and `ga` permissions (§6.5). Zero-length `pinUvAuthParam` probes get `PIN_NOT_SET` or `PIN_INVALID` after a touch.
0x07	authenticatorReset	Yes. Within 10 s of power-up, with a touch.
0x08	authenticatorGetNextAssertion	Not needed without resident keys.

AUTHENTICATORGETINFO RESPONSE, AS JOTAKEY SENDS IT (DIAGNOSTIC NOTATION)

```
{ 1: ["FIDO_2_0"],                        ; versions
  3: h'6a6f74616b65792d7630312d63360001',  ; AAGUID
  4: {"rk": false, "up": true, "plat": false,
      "clientPin": false,                  ; true once a PIN is set
      "pinUvAuthToken": true, "makeCredUvNotRqd": true},
  5: 1200,                                 ; maxMsgSize
  6: [2],                                  ; pinUvAuthProtocols
  7: 8,                                    ; maxCredentialCountInList
  8: 49,                                   ; maxCredentialIdLength
  13: 4 }                                  ; minPINLength
```

CTAP allows `getAssertion` with option `up: false`, a **silent** assertion that produces a valid signature without a touch. Clients use it as a **pre-flight**: before asking the user to touch, they find out which credential in their list the key recognises. python-fido2 and browsers rely on it, and an early Jotakey that refused it could register but never sign in. Jotakey therefore answers it, signing at once with the UP flag **clear** in the authenticator data. WebAuthn requires relying parties to reject an assertion without UP, so a silent assertion cannot log anyone in. Every signature that carries UP still needs a fresh touch (invariant 1), and every signature, silent or not, moves the counter.

5.3 CTAPHID: CTAP OVER USB

USB security keys are HID devices, like keyboards. Each report is exactly 64 bytes, so longer messages are split into an **initialization packet** and **continuation packets**:



INITIALIZATION PACKET (57 PAYLOAD BYTES)

CID	SEQ 0–127	DATA
4 B	1 B	59 B

CONTINUATION PACKET (59 PAYLOAD BYTES)

Several applications may talk to the key at once, so CTAPHID multiplexes **channels**, identified by a 4-byte CID that `CTAPHID_INIT` allocates. Only one transaction runs at a time. A packet from another channel during a transaction is answered with `ERR_CHANNEL_BUSY` and must not disturb the transaction in progress. This is **channel isolation** (invariant 5), proved for the Lean model in §9.6. While waiting for the user, the device sends a `KEEPALIVE` with status `UPNEEDED` at least every 100 ms, so the browser can show "touch your security key". `CTAPHID_CANCEL` aborts the wait.

5.4 FIDO OVER BLE

Over Bluetooth Low Energy, the authenticator exposes a GATT service with UUID `0xFFFD` and four characteristics. The host writes request fragments to `fidoControlPoint`. The device answers with notifications on `fidoStatus`. `fidoControlPointLength` sets the fragment size, and `fidoServiceRevisionBitfield` advertises FIDO2 support. Framing works like CTAPHID without channels: an initial fragment `CMD ‖ HLEN ‖ LLEN ‖ DATA`, then `SEQ ‖ DATA`. The link must be encrypted (LE Secure Connections) before the FIDO characteristics accept anything.

06 JOTAKEY'S ARCHITECTURE

6.1 THE ESP32-C6 BOARD; USB LIMITATIONS.

This section concerns the ESP32-C6 DevKit only. The jotakey key's STM32L432 has a general-purpose USB device controller, so the key enumerates as an ordinary FIDO HID device and needs no bridge, on any operating system.

The ESP32-C6 DevKit has two USB-C ports. The one labelled **UART** goes through a USB-to-serial bridge chip to the C6's UART0. The one labelled **USB** is wired to the C6's own USB peripheral. On the C6, that peripheral is the **USB-Serial/JTAG controller**, a fixed-function block implemented entirely in hardware. It can be a serial port and a JTAG debug probe, and nothing else. In particular, it **cannot enumerate as a USB HID device**. Every USB security key is a HID device. (Chips such as the ESP32-S3 have a general USB OTG controller. The C6 does not.)


Jotakey therefore splits USB into two halves. The device speaks the exact CTAPHID protocol, with the same 64-byte reports, but sends them over the serial port inside a small framing layer. On the host, a tiny Linux daemon, `jotakey-bridge`, creates a **virtual** HID device through the kernel's `/dev/uhid` interface and copies reports in both directions. Browsers see an ordinary FIDO security key.

BROWSER / PYTHON-FIDO2	Opens `/dev/hidrawN`, speaks CTAPHID, unaware of the bridge.
LINUX HID CORE	Virtual device created via `/dev/uhid` with the FIDO usage page (0xF1D0).
JOTAKEY-BRIDGE	≈330 lines, std Rust: uhid ⇄ serial, COBS + CRC-32 framing. **Outside the security boundary.**
USB-SERIAL/JTAG	The DevKit's "USB" port: fixed-function serial channel.
FIRMWARE: USB TASK	Deframer → CtapHid → authenticator, and back.

THE USB PATH, TOP TO BOTTOM

> **THE BRIDGE DOES NOT WEAKEN SECURITY**
> FIDO already treats the host as hostile: the authenticator trusts nothing it receives, and every signature needs a touch on the device itself. The bridge runs **on** the host, so it can do nothing that host malware could not do anyway. It never sees key material, only the same CTAP messages any USB host sees. The bridge is Linux-only. The roadmap (§11) lists a small USB-capable co-processor as the path to a standalone, OS-independent device.

The framing on the serial line is simple:



ONE FRAME ON THE SERIAL LINE: 0X00, COBS(REPORT ‖ CRC-32), 0X00

COBS (Consistent Overhead Byte Stuffing) removes every zero byte from the body, so a zero **always** marks a frame boundary. After line noise or a half-written frame, the receiver resynchronises at the next zero. Each frame starts with a zero as well as ending with one, which matters on this board: opening the port resets the C6, and its ROM prints a boot banner on the same USB port. The banner has no zero bytes, so without the leading delimiter it would merge with the first real frame and that reply would be lost. The CRC catches corruption. It is an integrity check, nota security mechanism. Corrupt frames are dropped, and CTAPHID's own timeouts take over. Logs never mix with frames: the firmware prints only to the **UART** port. The two ports have clean roles: "USB" carries the authenticator, "UART" carries diagnostics. §6.7 describes the bridge and the framing in detail.

6.2 SOFTWARE LAYERS

JOTAKEY-CORE	`no_std`, no allocation, `#![forbid(unsafe_code)]`, no `unwrap` / `panic!` / unchecked indexing or arithmetic (enforced by Clippy). CBOR, CTAP2 commands, CTAPHID, BLE framing, serial framing, credential wrapping, power-safe storage, self tests, the OPTIGA driver. **All** bytes from the host, and from the OPTIGA's bus, are interpreted here.
JOTAKEY-FW	ESP32-C6 firmware (esp-hal, embassy, trouBLE). Thin adapters: TRNG, eFuse HMAC key, flash, button, LED, USB-Serial/JTAG, BLE GATT. Implements the core's `Platform` trait.
JOTAKEY-KEY-FW	jotakey key firmware (embassy-stm32, embassy-usb). Thin adapters: RNG, internal flash, touch controller, LED, native USB HID, the OPTIGA's I2C bus and reset line. Implements the same `Platform` trait.
JOTAKEY-TESTFW	On-device test firmware (embedded-test + probe-rs).
JOTAKEY-BRIDGE	Linux host daemon (serial ⇄ uhid).
FORMAL/	Lean 4 models, proofs, and the executable specification (CBOR, presence gate, record log, OPTIGA session and counter).

CRATES AND THEIR TRUST LEVELS

The core is written so that it does not know it runs on a microcontroller. Hardware is reached only through one trait:

CRATES/JOTAKEY-CORE/SRC/PLATFORM.RS (ABRIDGED)

```rust
pub trait Platform {
    fn random_bytes(&mut self, out: &mut [u8]) -> Result<(), PlatformError>;
    fn derive_secret(&mut self, label: SecretLabel, out: &mut [u8; 32]) -> Result<(), PlatformError>;
    fn increment_counter(&mut self) -> Result<u32, PlatformError>;   // persisted before return
    fn rotate_epoch(&mut self) -> Result<(), PlatformError>;
    fn uptime_ms(&self) -> u64;
}
```

User presence is **not** in the trait. Waiting for a button is asynchronous and involves keepalives and cancellation, and none of that belongs inside the protocol logic. Instead, the core is a **resumable state machine**. `Authenticator::process` validates a request completely. If it needs a touch, it parks the validated parameters in a `Pending` value and returns `NeedsUserPresence`. The firmware blinks the LED, sends keepalives, watches the button and the cancel signal, then calls `Authenticator::complete` with `Confirmed`, `Timeout` or `Cancelled`. Signing code is reachable **only** from `complete` under `Confirmed`, which is proven by the Lean model (§9.6).

When a touch counts is itself core code: `presence::PresenceGate`, a small pure state machine the firmware feeds one sensor reading per poll. Both firmwares use it, the C6 with its button and the key with its touch electrode, so the rule exists once, and it is proved in Lean (§10.9) and checked against the model by the differential test.

6.3 THE JOTAKEY KEY'S FIRMWARE

`crates/jotakey-key-fw` runs on the STM32L432KC with embassy-stm32. It was built in two milestones, both so far tested only off the board (against a simulated OPTIGA, §8).

- **Milestone 1.** Native USB full-speed with one HID interface carrying the FIDO report descriptor, so the key enumerates as an ordinary FIDO device with no bridge; the 48 MHz USB clock comes from the internal HSI48 oscillator, trimmed against USB start-of-frame. The RNG peripheral feeds the core's health tests, and any seed or clock error it reports latches the failure. The touch controller (TSC) reads the electrode, and the core's `touch::TouchDetector` turns its counts into touched or not, against a baseline taken at boot. The record logs live in the top 32 KB of internal flash. Logs go over SWD only.
- **Milestone 2.** The OPTIGA Trust M driver (next section): the shielded connection with a live-session check, `DeriveKey` for `derive_secret`, the hardware counter `0xE120` for `increment_counter`, and on-device provisioning. USB moved to an interrupt-priority executor, so that the authenticator's blocking work (about 50 ms per OPTIGA derivation) never stalls it.

A unit that has not been provisioned has no root: it fails its boot probe and stays in the fault state, answering every request with `CTAP1_ERR_OTHER`. The **INSECURE** `dev-key` build, whose root is derived from the chip's unique ID and whose counter is a flash record log, never drives the OPTIGA. It exists to test everything else end to end.

Talking to the OPTIGA

The OPTIGA sits on I2C, and the I2C bus runs over the board's copper, where anyone holding the key can attach a probe. So the driver treats the bus as hostile, exactly like USB: every byte read from it is parsed by total functions in the core (`jotakey_core::optiga`), and nothing it says is believed until the **shielded connection** has authenticated it. The driver is sans-IO, so the firmware only supplies the bus (`I2c` trait: write, read, wait) and the reset line.

APDU (APDU.RS)	Commands `Cmd ‖ Param ‖ Len ‖ Data`: `OpenApplication`, `GetDataObject`, `SetDataObject` (data, metadata, count), `GetRandom`, `DeriveKey`. Responses parsed totally.
SHIELDED CONNECTION (SHIELDED.RS)	Handshake from the binding secret; then every command and response is AES-128-CCM-8 encrypted and authenticated, with sequence numbers. The acceptance rule is proved in Lean (§10.11).
NETWORK / TRANSPORT (LINK.RS)	One header byte: channel, presentation layer present, chaining. Our APDUs always fit one packet; chained packets are refused.
DATA LINK (FRAME.RS, LINK.RS)	Frames `FCTR ‖ LEN ‖ packet ‖ CRC-16`, numbered and acknowledged; damaged or lost frames are sent again, a bounded number of times.
PHYSICAL (PHYSICAL.RS)	Registers at address `0x30`: data, data length, state. A busy OPTIGA does not acknowledge its address, and the master retries for a bounded time.

THE OPTIGA'S PROTOCOL STACK, AS THE MCU SPEAKS IT

The shielded connection. At provisioning the MCU and the OPTIGA come to share a 64-byte **binding secret**. Each session begins with a handshake: the OPTIGA picks a random `RND`, both sides derive session keys `PRF(binding, "Platform Binding" ‖ RND)`, and each proves it holds them by encrypting `RND` and a sequence number. From then on every message carries a sequence number one above the last; the MCU accepts a response only if its number is in a small window above the last one it accepted **and** its tag verifies, and only then moves the window. Any failure ends the session, and a new handshake starts afresh.

The live-session check. The handshake has a weakness: the master contributes no randomness, so the master's half of a session is a function of the OPTIGA's half. Someone who recorded a whole session on the bus can later play the OPTIGA's half back, and the MCU would accept the old session keys and then

the old responses, including an old, lower counter value. Infineon's reference manual says so (§6.6: "the shielded connection does not provide an option to add random challenge/nonce from the host"). So after every handshake the MCU sends a fresh random nonce through the new session, asks the OPTIGA for `PRF(freshness secret, "jotakey/fresh/v1" ‖ nonce)`, and compares the answer with the same PRF computed itself. A recording cannot contain the answer for a nonce that did not exist when it was made. Until the check passes, the session is used for nothing else, and the Lean model proves that rule (§10.11).

The counter. `increment_counter` counts the OPTIGA's counter up by one and reads it back through the session. The OPTIGA has stored the value before it answers, so the value is persisted before any signature carries it (invariant 2). The MCU releases it only if it exceeds every value it released since power-up, so even a misbehaving OPTIGA could not make the key sign with a counter that went back.

Cost. Every `DeriveKey` on a stored secret is what the OPTIGA calls a **security event**: its security monitor allows one per 5 s for free, counts bursts, and slows such operations down once more than 128 have accumulated. A sign-in with a list of five credentials costs six derivations; a burst of registrations could reach the throttle. Each derivation takes about 50 ms.

Provisioning runs on the device in two separate firmware images that a human flashes and confirms by holding the touch pad. `provision` (3 s hold) pairs the two chips: the MCU draws 64 bytes from the OPTIGA's TRNG and 64 from its own, keeps the hash `P` in flash, and writes the binding and freshness secrets derived from `P` to the OPTIGA. These two travel in clear, because no shielded connection exists before them; provisioning happens at the bench. Then, through the new live session, it creates `K_root` from both chips' randomness, so `K_root` never crosses the bus in clear, and sets every access condition: `K_root` and the freshness secret can never be read or changed and work only through the shielded connection, the binding secret can never be read or changed, and the counter starts at 0 with threshold 600 000 and can only count, only through the session. All of that can still be undone, because the OPTIGA lets an object's metadata change while the object's **life cycle state** is below "operational". `provision-lock` (10 s hold) is the one irreversible step: it moves the four objects to operational, which freezes their conditions for good. Until then, someone on the bus could reopen the conditions, so an unlocked unit is a development unit. The automation that builds and tests this project compiles both images and never flashes or runs them (AGENTS.md §4).

6.4 THE KEY HIERARCHY

ROOT (HARDWARE KEY STORE)	The device's one long-term secret. Software can only ask the hardware to **use** it, never read it: the OPTIGA secure element on the key, the eFuse HMAC peripheral on the C6.
EPOCH (FLASH)	32 random bytes, replaced by authenticatorReset. Makes reset possible while the root stays fixed for the device's life.
TAG, SEED (PER CREDENTIAL)	F(root, "jotakey/tag/v1" ‖ epoch ‖ 0x01 ‖ rpIdHash ‖ nonce), F(root, "jotakey/seed/v1" ‖ epoch ‖ rpIdHash ‖ nonce), computed by the hardware for one credential at a time. Zeroized after use.
CREDENTIAL KEY D	HKDF-SHA256(seed, salt = rpIdHash, info = "jotakey/cred/v1" ‖ nonce ‖ ctr) → valid P-256 scalar.

FROM THE HARDWARE ROOT SECRET TO A CREDENTIAL'S PRIVATE KEY

The hardware computes each credential's values from the root directly. The microcontroller therefore never holds a secret that covers more than one credential. That matters on the day an attacker manages to run their own code on it (§7.5). They can then ask the hardware for the values of any credential whose ID they hold, and so use or copy that credential. But there is no key to take away that would let them compute every credential, or mint new ones, on their own computer afterwards.

The two platforms differ only in where the root lives and in the function `F`:

	JOTAKEY KEY	ESP32-C6
Root	`K_root`: 64 bytes in OPTIGA data object `0xF1D0`, type pre-shared secret. Created on the device at provisioning from both	`K_dev`: 256 bits in eFuse BLOCK_KEY0, purpose HMAC_UP, read-protected by hardware.

	JOTAKEY KEY	ESP32-C6
	chips' random generators, then locked: never readable, never changeable, usable only over the encrypted link (§7.5).	
F	TLS 1.2 PRF with SHA-256, run by the OPTIGA's `DeriveKey` command. The Trust M V1 has no HMAC command; its PRF is built from HMAC-SHA256.	HMAC-SHA256 in the HMAC peripheral.
Epoch	STM32 flash, behind readout protection.	Encrypted flash.
Counter	OPTIGA hardware up-counter.	Flash record log (§6.5).

The credential format and its proofs (§9.6) are the same on both platforms: the proofs treat the tag function as a parameter.

> **IN THE CODE**
> `Platform::derive_secret(label, context)` returns `F(root, label ‖ epoch ‖ context)`, and the core only ever passes one credential's context. An earlier version derived two epoch-wide keys, `K_mac` and `K_seed`, and computed every tag and HKDF on the microcontroller: exactly the "key to take away" described above. If the hardware fails while the core checks an ID, the request fails; it never reads as "not our credential".

Nothing secret is ever **stored** in the microcontroller's flash except the epoch (and, on the key, the pairing secret from which the secrets of the link to the OPTIGA derive). The epoch is useless without the root, which the flash never holds.

6.5 CREDENTIAL IDS. KEYS BY DERIVATION

For a non-resident credential the website stores the credential ID and hands it back at login. Jotakey makes the ID carry everything it needs to **re-derive** the private key, and authenticates it so that it cannot be forged:

ver	nonce	tag
0x01	32 random bytes	F(root, "jotakey/tag/v1" ‖ epoch ‖ ver ‖ rpIdHash ‖ nonce)[..16]

JOTAKEY CREDENTIAL ID: 49 BYTES

At `getAssertion`, Jotakey recomputes the tag for the **requesting** RP and compares it in constant time. An ID minted for `example.com` presented by `examp1e.com` fails the check, because the RP ID hash is inside the tag (invariant 3). A forged or foreign ID fails too. The nonce is not secret, and the private key is never in the ID, not even encrypted.

> **PROVED IN LEAN (§9.6)**
> `unwrap_accepts_only_wrapped_ids`: anything `unwrap` accepts is **exactly** `wrap(rp, nonce)` for the recovered nonce. `credential_bound_to_relying_party`: an ID minted for one RP never unwraps at another, **assuming** the MAC does not collide across RPs. That assumption is the cryptographic part. It holds for HMAC-SHA256 and for the TLS PRF built on it, truncated to 128 bits, except with probability $\approx 2^{-128}$, and it is stated explicitly as a hypothesis of the theorem rather than hidden.

6.6 PERSISTENT STATE

On the jotakey key, the signature counter lives in the OPTIGA instead (§7.5): a hardware up-counter that can only increase, survives power loss by construction, and, once the unit is locked, cannot be rolled back even by firmware an attacker controls. The record log described here holds the counter and the epoch on the C6, and the epoch, the PIN record and the pairing secret on the key (plus, in `dev-key` builds, the counter).

On the C6, only two values persist: the signature counter and the epoch. Each lives in its own power-loss-safe **record log** of two flash sectors. A new value is appended as a record `MAGIC ‖ seq ‖ payload ‖ CRC-32` after the last one. When a sector fills, the **other** sector is erased and the record goes there. The sector holding the current value is never erased.

The append operation reads the record back and only reports success once it verifies. The authenticator only releases a signature carrying counter $N + 1$ after that success. If power fails mid-write, the torn record is ignored at the next boot. That is harmless, because nothing carrying $N + 1$ was ever released. A property test cuts power at random byte offsets (including in the middle of a sector erase) across thousands of runs and checks that no confirmed counter value is ever lost or handed out twice. The test firmware repeats the torn-write check on real NOR flash. The algorithm itself is proved in Lean (§10.10): for every way a power cut can leave the flash, a remount never finds a value older than the last one confirmed.

The STM32L4's flash adds one rule: it programs aligned 64-bit double-words, each once between erases, and protects each with ECC. The `Flash` trait therefore states its **programming unit** (4 bytes on the C6, 8 on the key), and records are padded to whole units. On the C6 nothing changes. A double-word whose programming was cut fails its ECC check when read; the key's flash adapter catches that fault (an NMI) and reads it as a torn record, which the log already ignores.

6.7 USER EXPERIENCE

LED	MEANING
off	Idle, healthy.
amber blink	A website is asking: touch BOOT to approve. Times out after 30 s.
blue blink	CTAPHID_WINK: the platform asks the device to identify itself.
short blue flash, once a second	Bluetooth is on and advertising, waiting for a connection: for 120 s after a 3 s hold of BOOT, and again after a disconnect within that time.
solid red	Self test or hardware fault. The authenticator refuses everything until reset; the UART log says why.
magenta at boot	**INSECURE** development build (`dev-key` feature, root key derived from the MAC address).

On the jotakey key, one red LED shows the same states as patterns: a slow blink asks for a touch, a fast blink is a wink, solid on is a fault, and three quick flashes at boot mark a `dev-key` build.


A touch counts only if the button (or, on the key, the electrode) is seen **released** after the request arrived, then held for two consecutive 20 ms polls. A button taped down, or still held from a previous request, never approves anything. Holding BOOT for 3 s while idle turns on BLE for two minutes, so the radio is never exposed without the owner's intent.

6.8 THE USB BRIDGE

§6.1 introduced `jotakey-bridge` in one paragraph. This section describes it completely: what happens to a request on its way from the browser to the chip, what each layer does, what goes wrong and how it recovers, and what a hostile bridge could and could not do. The technique is general. Any microcontroller with a serial port but no USB device controller can appear to Linux as a HID device this way, which makes it useful well beyond Jotakey.

The guiding rule is that the bridge **understands nothing**. It does not parse CTAPHID, CBOR or CTAP. It moves opaque 64-byte reports between two places and checks only that they arrived intact. Every protocol decision is made on the device, by the same core code that is tested, fuzzed and modelled in Lean. The bridge is about 330 lines in total: `main.rs` (127) and `uhid.rs` (202, including tests).

A request's journey



A REQUEST AND ITS ANSWER. MESSAGES LARGER THAN ONE REPORT REPEAT THE TOP HALF PER PACKET.

The browser cannot tell this apart from a USB key. It opens `/dev/hidrawN` and writes 64-byte output reports. The kernel hands each one to the bridge as a `UHID_OUTPUT` event. The bridge wraps the report in a frame and writes it to the serial port. On the chip, the usb task deframes it, checks the CRC, and feeds the report to the `CtapHid` state machine, which reassembles multi-packet messages. A complete request goes to the authenticator task. Replies and keepalives travel the same path backwards: `CtapHid` splits them into reports, the usb task frames them, the bridge unframes them and injects each one into the kernel with `UHID_INPUT2`, and the browser reads it from hidraw.

On the host

`uhid` is a Linux kernel interface for implementing HID devices in user space. A program opens `/dev/uhid` and exchanges fixed-size `struct uhid_event` records with the kernel. To the rest of the system, the result is a normal HID device. It gets a hidraw node, udev sees it, and browsers enumerate it. The bridge uses only a handful of events:

EVENT	DIRECTION	USE IN THE BRIDGE
`UHID_CREATE2`	write	Once at start: name "Jotakey FIDO2 (bridge)", bus USB, VID:PID `1209:0001`, and the report descriptor below.
`UHID_OUTPUT`	read	The host wrote a report. Forwarded to the serial port.
`UHID_INPUT2`	write	Deliver a report from the device to the host.
`UHID_GET_REPORT`, `UHID_SET_REPORT`	read	Feature-report requests, which FIDO does not use. Answered at once with `EIO`, because the kernel waits for a reply.
`UHID_START`, `OPEN`, `CLOSE`, …	read	Notifications. Ignored.
`UHID_DESTROY`	write	On exit (Rust `Drop`), so the virtual key disappears with the bridge.

The **report descriptor** is what makes the device a FIDO key. It declares the FIDO Alliance usage page `0xF1D0`, usage `CTAPHID`, and one 64-byte input and one 64-byte output report, exactly as CTAP 2.0 §8.1.8.2 prescribes. Browsers and libraries look for that usage page, not for a vendor or product ID. systemd's `fido_id` helper recognises the same descriptor and grants the logged-in user access to the hidraw node. The VID:PID pair `1209:0001` is the pid.codes test identifier, suitable for development but not for a product.

The bridge has its own uhid encoder (`uhid.rs`) instead of a crate. The obvious crate, `uhid-virt`, needs `libclang` at build time to generate bindings. The structures are packed, so the encoder is plain byte

arithmetic, with no `unsafe` and no C bindings. Unit tests pin the layout against the kernel's: an event is exactly 4 376 bytes, and the `CREATE2` fields sit at the right offsets. One subtlety: depending on the path a report takes through the kernel, an output report from a device without report IDs can arrive with a leading report-number byte of 0. The bridge accepts 64 or 65 bytes and strips that byte. Anything else is ignored.

On the wire

The serial link is a byte stream, so reports need boundaries. Each report travels as one frame: `COBS(report ‖ CRC-32(report)) ‖ 0x00`. This is the actual frame for the first packet every browser sends, a `CTAPHID_INIT` on the broadcast channel with an 8-byte nonce. It was produced by the core's `serial::encode` and cross-checked against an independent Python implementation:

```
CTAPHID_INIT REQUEST: 64-BYTE REPORT → 70-BYTE FRAME

report   ff ff ff ff 86 00 08 11 22 33 44 55 66 77 88 00 … 00     (49 zero bytes)
          └ CID ──────┘ cmd └len┘ └ nonce ─────────────────┘
CRC-32   a5 9f 94 f7 → appended little-endian: f7 94 9f a5

frame    06 ff ff ff ff 86                  5 data bytes, then a zero
         0a 08 11 22 33 44 55 66 77 88      9 data bytes, then a zero
         01 01 01 … 01                      48 × "no data, then a zero"
         05 f7 94 9f a5                     4 data bytes (the CRC), end of body
         00                                 delimiter
```

COBS (Consistent Overhead Byte Stuffing) removes every zero byte from the body. Each code byte `n` means "copy the next `n − 1` bytes, then output a zero", except at the very end. Because the body never contains `0x00`, a zero on the wire **always** means "end of frame". A receiver that starts listening mid-stream, or sees a corrupted byte, recovers at the next zero. The overhead is bounded: one code byte per 254 data bytes plus the delimiter, so a frame is at most 70 bytes for a 64-byte report.

The **CRC-32** (the ISO-HDLC polynomial used by zlib and Ethernet; check value `CBF43926`) detects corruption: noise, a dropped byte, or two frames merged by a lost delimiter. It is not a security mechanism. Anyone on the host can compute a valid CRC, and nothing here needs to keep the host out, because the device validates every message anyway.

The receiver, `serial::Deframer`, is a 70-byte buffer and a little state. It collects bytes until a zero. Empty frames, which are just idle delimiters, are ignored. A frame that overflows the buffer, fails COBS decoding, has the wrong length or fails the CRC is dropped and counted. Nothing is ever retransmitted. CTAPHID already has timeouts and retries, and duplicating them in the framing layer would only add states. A unit test feeds a log line, a corrupted frame and a good frame in one stream, and checks that exactly the good one comes out. The `serial_deframe` fuzz target (§8.2) mixes garbage, intact frames and corrupted frames by the million, and checks that every report it accepts is exactly what was sent and that no intact frame is lost.

Two properties of the C6's USB-Serial/JTAG port matter for the host side. The baud rate is meaningless, because the data moves at USB full speed whatever the port is told. More importantly, the DTR and RTS control lines are wired to the chip's reset logic (that is how flashing tools reset it), so opening the port the usual way can reboot the authenticator. The bridge opens the port with DTR off and clears RTS.

On the device

On the chip, `crates/jotakey-fw/src/usb.rs` runs one task that waits on four things at once: bytes from the serial port, a reply from the authenticator, a keepalive request, and a 50 ms timer. Incoming bytes go through the `Deframer` into `CtapHid::handle_packet`. `CtapHid` implements channel allocation, reassembly, busy and cancel handling, and transaction timeouts. The timer drives those timeouts even when no bytes arrive. Each outgoing packet `CtapHid` produces is framed and written back.

This placement is intentional. The whole CTAPHID state machine runs on the device, in the core, so channel isolation (invariant 5) is enforced by code the Lean model of §9.6 describes, not by the bridge. A bridge that misbehaved could not break isolation between two host applications. It could only feed the device packets, which any USB host can do.

The firmware has one authenticator and two transports. If a USB request arrives while a BLE request is being processed, the usb task answers `CTAP1_ERR_CHANNEL_BUSY` itself, and the host retries. The firmware

never prints anything on this port. Logs go to the **UART** port only, so the CTAPHID stream contains nothing but frames.

Lifecycle and failure modes

The bridge creates the virtual device once, then loops: open the serial port, pump reports until the port hangs up or fails, wait 500 ms, try again.

SITUATION	WHAT HAPPENS
Board unplugged	The serial port errors and the bridge goes back to waiting. The virtual key **stays**, so the browser still sees a key, but its requests time out. Reports the host writes meanwhile queue in the kernel (uhid buffers a limited number of events) and may be delivered after the board returns.
Board reset or replugged	The bridge reconnects within about 500 ms. The firmware has forgotten all channels, so packets on old channel IDs get `ERR_INVALID_CHANNEL`. Host libraries then send a fresh `CTAPHID_INIT`.
Line noise or a half-written frame	The CRC or COBS check fails, the frame is dropped, the stream resynchronises at the next zero, and CTAPHID timeouts recover the transaction.
Bridge stopped	`UHID_DESTROY` removes the virtual key. If the process is killed outright, the kernel removes it when `/dev/uhid` is closed.
Wrong serial port	The bridge would send frames to some other device. Use the stable name under `/dev/serial/by-id/` (the entry for the Espressif USB JTAG/serial unit) rather than `/dev/ttyACM0`, whose number depends on plug order.
Two bridges on one port	Both read the same stream and each gets part of it. Frames break and are dropped. Run exactly one.

Hostile bridges

The bridge is outside the security boundary, like the rest of the host. Treating it as an attacker gives this picture:

A MALICIOUS OR COMPROMISED BRIDGE CAN…	…BUT IT CANNOT
Drop, delay, reorder or replay any report (denial of service).	Obtain a signature without a touch on the device (invariant 1, proved in §9.6).
Send the device any request of its choosing, for any website.	Learn any private key or root key. Neither ever leaves the chip.
Read all CTAP traffic: relying-party ID hashes, credential IDs, and the user name and display name sent in makeCredential.	Use a credential for another website. IDs are bound to `rpIdHash` (invariant 3).
Pretend to be a security key itself, since it is software that creates HID devices.	Make the device skip its checks. Every message is parsed and validated by the core.

Everything in the left column is also available to any program with root on the host, or to a malicious USB host. That is the threat model FIDO is designed for. The bridge adds no new attack on the key. It is a new place for host-side malware to hide, which is one more reason the roadmap replaces it with a USB co-processor.

> **ACCESS TO /DEV/UHID**
> A process that can write to `/dev/uhid` can create **any** HID device, including a keyboard that types commands. `scripts/99-jotakey.rules` gives the `plugdev` group that access, which is convenient on a development machine. On a shared or long-lived system, run the bridge as a dedicated system user that alone has access to `/dev/uhid` and the serial port, for example as a systemd service, rather than widening a group most users belong to.

Running it

BRIDGE SETUP ON LINUX

```
sudo cp scripts/99-jotakey.rules /etc/udev/rules.d/ && sudo udevadm control --reload
sudo usermod -aG plugdev,dialout "$USER"     # uhid + serial access; log in again
                                              # (the serial group is uucp on Arch)
ls /dev/serial/by-id/                         # find the Espressif USB JTAG/serial entry
just bridge /dev/serial/by-id/usb-Espressif…  # or: cargo run -p jotakey-bridge --release -- <port>
# jotakey-bridge: virtual FIDO device created; waiting for …
# jotakey-bridge: connected to …
```

With the bridge running, `python3 scripts/fido2_check.py`, `just host-tests` and any browser on the machine see the key. Stop the bridge with Ctrl-C.

Testing


PART	EVIDENCE
uhid encoding	Unit tests pin the event size (4 376 bytes) and the `CREATE2` layout to the kernel's, and check `OUTPUT` decoding and the `EIO` replies.
Framing	Round trip of every possible report (property test), all-zero and zero-free reports, corruption and resynchronisation, and the `serial_deframe` fuzz target.
Pump loop	The real `pump` runs between a fake uhid (a datagram socket pair, which keeps event boundaries like `/dev/uhid`) and a pseudo-terminal standing in for the serial port. The test checks one report in each direction, that the idle bridge wakes at most twice in 300 ms (the earlier 5 ms polling loop woke 60 times), and that a hang-up ends the pump so the bridge can reconnect.
Whole path	`jotakey-host-tests` runs a simulated device wired exactly like the usb task (framing → `CtapHid` → authenticator), so every simulated request crosses the real framing code in both directions.
On hardware	Runs with the C6 DevKit: `scripts/fido2_check.py` (python-fido2 as client and relying party), a Chrome registration and sign-in through the demo relying party in `examples/webauthn-topcoat`, and the explorer below all go through it.

The bridge sleeps in `poll(2)` on both file descriptors, the uhid device and the serial port, with no timeout. It wakes only when the host writes a report or the board sends bytes, forwards them at once, and uses no CPU while idle. It needs no timer of its own, because all CTAPHID timeouts run on the device. A hang-up or error on the serial port ends the loop, and the bridge goes back to waiting for the board.

The bridge is **Linux-only**, because `uhid` is a Linux interface; other systems would need their own virtual-HID mechanism.

6.9 LOOKING AT KEYS: THE EXPLORER

Chapter 5 describes what an authenticator says about itself. `jotakey-explorer` exposes that information. It is a terminal program that lists every FIDO key attached to the computer, of any make, and shows what the selected one reports. It is useful for three things: checking that the bridge and the firmware are alive, comparing a Jotakey with other keys, and learning the protocol from real answers instead of tables.



Listing 1: The explorer showing the C6 DevKit through the bridge: rendered from the real device, trimmed to fit the page.

Finding keys

Every HID device describes its reports in a **report descriptor**, a short byte program the kernel exposes in sysfs. A FIDO authenticator declares a top-level application collection with usage page `0xF1D0` (assigned to the FIDO Alliance) and usage `0x01` (CTAPHID). The explorer reads the descriptor of every `/dev/hidrawN` node and keeps those that declare it. This finds keys by what they are, not by who made them: USB keys, Bluetooth keys and the bridge's virtual device all qualify, and a keyboard or mouse never does. Vendor and product IDs, the USB descriptor strings and the physical port come from sysfs too, without touching the device. The list is rescanned every two seconds, so keys can be plugged and unplugged while it runs.

USB and HID descriptors

Before it sends anything, the explorer shows what the kernel learnt when the key was plugged in. The **USB** section comes from the device, configuration, interface and endpoint descriptors in sysfs. A typical FIDO key is a full-speed (12 Mbit/s), bus-powered device whose HID interface has class `03/00/00`: HID, with no boot protocol, because it is not a keyboard. That interface has two interrupt endpoints of 64 bytes, one IN and one OUT, each carrying one CTAPHID packet per transfer, polled every few milliseconds. Keys with OTP or smart-card functions show more interfaces: an OTP function is a second HID interface that pretends to be a boot keyboard and types its codes. The bridge's device is virtual, made through `/dev/uhid`, so it has no USB descriptors; the C6 behind it enumerates as a USB serial port instead.

The **HID report descriptor** section decodes the descriptor item by item, with each item's offset and bytes. It is the same description `jotakey-bridge` registers, and most FIDO keys send it nearly byte for byte:

```
THE BRIDGE'S REPORT DESCRIPTOR

Length         34 bytes
Input report   64 bytes   (the CTAPHID packet size)
Output report  64 bytes   (the CTAPHID packet size)
0000  06 d0 f1   Usage Page (FIDO Alliance)
0003  09 01      Usage (CTAPHID)
0005  a1 01      Collection (Application)
0007  09 20        Usage (Input Report Data)
0009  15 00        Logical Minimum (0)
000b  26 ff 00     Logical Maximum (255)
000e  75 08        Report Size (8)
0010  95 40        Report Count (64)
0012  81 02        Input (Data, Var, Abs)
0014  09 21        Usage (Output Report Data)
  …                 (the same four items again)
001f  91 02        Output (Data, Var, Abs)
0021  c0          End Collection
```

Global items such as Report Size and Report Count set state; **main** items such as Input and Output declare a field with that state; Collection and End Collection group them. The explorer adds up the fields to give each report's length: 8 bits × 64 = 64 bytes each way, the CTAPHID packet size. A descriptor with report IDs adds an ID byte in front of every report; FIDO keys use none, since a CTAPHID packet is a bare 64-byte report. The descriptor comes from the device, so it is untrusted like everything else: a truncated or unbalanced one is shown up to the problem, never trusted past it.

Explorer queries

This tool is **read-only by construction.** It sends only these requests:

REQUEST	WHAT IT RETURNS	TOUCH OR STATE CHANGE
CTAPHID `INIT`	A channel, the CTAPHID protocol version, the device version, and capability bits: WINK, CBOR (CTAP2), NMSG (no U2F).	None
`authenticatorGetInfo`	Everything the key advertises: protocol versions, extensions, AAGUID, options, size limits, algorithms.	None
`authenticatorClientPIN` getPINRetries / getUVRetries	How many wrong PINs or failed fingerprints are left. Sent only if getInfo says a PIN or built-in UV is set up.	None: the counters are read, not spent
U2F `VERSION` (over `CTAPHID_MSG`)	`U2F_V2` if the key also speaks the older protocol. Sent only without the NMSG bit.	None
CTAPHID `WINK`, on `w` only	Nothing; the key blinks so you can tell which one it is.	None
None: sysfs	The USB and HID descriptors above, which the kernel read when the key was plugged in.	None; no I/O to the key at all

Nothing it sends creates or uses a credential, asks for a touch, or changes anything on the key. A test proves this for the Jotakey: it runs the whole query against the simulated device with nobody touching, and checks that every request completes and that the signature counter and the epoch are unchanged.

The answers are untrusted input. Any device can claim to be a FIDO key, so the explorer treats replies as an attacker's bytes, as the firmware treats requests. Its CBOR decoder checks every announced length against the bytes actually received before allocating anything, and it limits nesting. Every read waits in `poll(2)` with a timeout, and each query runs on its own thread, so a silent or misbehaving device cannot freeze the screen.

Reading a Jotakey's answers

FIELD	VALUE	MEANING
Capabilities	`0x0d`	WINK and CBOR set; NMSG set, so no U2F. The MVP is CTAP2-only.
`versions`	`FIDO_2_0`	CTAP 2.0, the MVP. CTAP 2.1 keys also list `FIDO_2_1`.
`aaguid`	`6a6f7461-…0001`	The model identifier, the ASCII text `jotakey-v01-c6` with a version suffix. Relying parties look AAGUIDs up in the FIDO Metadata Service; the explorer recognises the Jotakey's.
`rk`	`false`	No discoverable credentials (passkeys stored on the key). A site must send the credential IDs it holds, as the demo relying party does.
`up`	`true`	The key can test user presence: the touch electrode, or the C6's BOOT button.
`plat`	`false`	A **removable** (roaming) authenticator: it moves between computers, unlike a platform authenticator such as Windows Hello or Touch ID, which is part of one device.
`maxMsgSize`	`1200`	The largest request it accepts (invariant 4).
`maxCredentialCountInList`	`8`	Credential IDs per allow or exclude list.
`maxCredentialIdLength`	`49`	Exactly a Jotakey credential ID: version byte, 32-byte nonce, 16-byte tag (§6.4).

What is missing says as much. There is no `uv` option, so the key has no built-in verification such as a fingerprint reader; the PIN is the only way to verify the user. There is no `algorithms` list, a CTAP 2.1 member: a client learns what a 2.0 key supports only from its answers (the Jotakey accepts ES256 alone). A recent YubiKey shows many more fields: `FIDO_2_1`, `credMgmt`, `remainingDiscoverableCredentials`, a U2F version

and, once a PIN is set, the PIN retry count. Putting the two side by side is a quick tour of the CTAP 2.1 roadmap in chapter 11.

Running it

THE EXPLORER

```
just explore            # interactive; q quits
just explore --dump     # every key's report as plain text, for bug reports
```

Up and down (or `j` / `k`) select a key, or scroll the details once Tab or Enter has moved the focus there. `w` winks the selected key, `x` shows the raw getInfo bytes with their CBOR diagnostic notation, and `r` rescans and asks the selected key again. On a desktop Linux system the logged-in user can already open FIDO devices (systemd grants access to them); elsewhere, `scripts/99-jotakey.rules` shows the udev rule to add.

PART	EVIDENCE
Decoder and discovery	Unit tests: getInfo-shaped CBOR, lying lengths and deep nesting rejected without allocating; report descriptors (FIDO, keyboard, composite, 4-byte usages, nested collections, truncation); a fake sysfs tree.
Against a Jotakey	The full query against the in-process device, with nobody touching: every request completes, the counter and the epoch do not move. A render test draws the screen into ratatui's test backend.
On hardware	`cargo test -p jotakey-explorer --test device -- --ignored` queries and winks every key attached. It passes against the C6 DevKit through the bridge. Other makes are not yet tested on hardware.

Like the bridge, the explorer is Linux-only: it reads hidraw nodes and sysfs.

07 HARDWARE SECURITY

Software can be proved correct. Silicon can be attacked. This chapter describes what the ESP32-C6 offers, how Jotakey uses it, and where it falls short (§7.1–7.4). It then describes the jotakey key, which adds the secure element the C6 lacks (§7.5), and how its board is designed (§7.6).

7.1 ESP32-C6 FEATURES

FEATURE	ROLE IN JOTAKEY
eFuse key blocks (6 × 256 bit)	One-time-programmable. `K_dev` is burned into BLOCK_KEY0 with purpose `HMAC_UP`. Keys with this purpose are read-protected: the CPU cannot read them, only the HMAC peripheral can use them.
HMAC peripheral	Computes HMAC-SHA256 with an eFuse key the CPU never sees. Jotakey's only access to `K_dev`.
Secure Boot v2	The ROM verifies the bootloader's RSA-3072 signature, and the bootloader verifies the app's, against a key digest in eFuse. Only firmware signed by the owner runs.
Flash encryption	XTS-AES encryption of flash contents with an on-chip key generated at first boot. Protects the firmware image and the `jotakey` partition (epoch, counter) against off-chip reading.
TRNG	Hardware entropy from SAR ADC and RF noise; health-tested continuously (§2.5).
JTAG / download-mode fuses	Burned at provisioning so a physical attacker cannot attach a debugger or dump flash through the ROM loader.

7.2 PROVISIONING

Provisioning can only happen once as eFuses cannot be unburned. `scripts/provision.sh` documents every step and **prints** the commands by default. It executes one step at a time, only when a human passes `--execute <step>` and types the chip's MAC address to confirm. `AGENTS.md` forbids automation from ever running it.

1. **Root key.** 32 random bytes generated in RAM (`/dev/shm`), burned with `espefuse.py burn_key BLOCK_KEY0 … HMAC_UP`, then shredded. The key then exists only inside the chip. A better future option is to generate it on the device, so it never touches the host.
2. **Secure Boot v2.** An RSA-3072 signing key kept offline. A signed bootloader built with ESP-IDF, and signed application images.
3. **Flash encryption, release mode.** The key is generated on-chip at first boot, and plaintext reflashing is disabled.
4. **Lockdown.** Disable pad and USB JTAG (the USB **serial** function stays, because it carries the CTAPHID tunnel). Switch ROM download mode to "secure download".

Until step 1 is done, the firmware refuses to operate: the HMAC peripheral rejects an unprovisioned key, the boot self check fails, and the LED goes red. For development, the `dev-key` cargo feature substitutes a software key derived from the MAC address. It is loudly announced at boot and must never hold real credentials.

7.3 SIDE CHANNELS

- **Timing.** All comparisons of secret data are constant-time. Scalar multiplication uses RustCrypto's constant-time implementation in software, rather than the C6's ECC accelerator, whose side-channel behaviour is undocumented.
- **Power and EM.** A microcontroller without dedicated countermeasures leaks information through its power draw. An attacker with an oscilloscope and physical access can, in principle, extract an ECDSA key from enough traces. Hedged nonces reduce, but do not remove, that risk.

7.4 FAULT INJECTION ATTACK

> **PUBLISHED ATTACK: ESPRESSIF ADVISORY AR2023-007**
> In January 2024 Espressif published **AR2023-007**, "Security Advisory Concerning Bypassing Secure Boot and Flash Encryption using CPA and FI attack on ESP32-C3 and ESP32-C6". It combines correlation power analysis with voltage-glitch fault injection. An attacker with physical access and lab equipment can run code before Secure Boot rejects it, and then extract device secrets. Earlier advisories (AR2023-005, CVE-2019-15894) describe similar attacks on the original ESP32. Treat a stolen Jotakey as compromised if the thief is well-resourced, and revoke its credentials at your relying parties.

This is why the threat model (§1.3) marks laboratory attackers as **not defeated**. The standard answer is a **secure element**: a small chip designed and certified (Common Criteria EAL5+/EAL6+) to resist exactly these attacks. It holds the keys and performs the signatures internally, so even full control of the microcontroller does not reveal them.

CANDIDATE	STRENGTHS	CONSIDERATIONS
Microchip ATECC608B	Cheap, I²C, P-256 ECDSA and ECDH in hardware, monotonic counters, widely used.	Small slot count: suits a root key plus derived keys, not many stored keys. Configuration is locked once.
NXP SE050	EAL6+, P-256 and many curves, larger storage, applet model.	More complex driver; NDA-free host library available.
Infineon OPTIGA Trust M	EAL6+, P-256, shielded I²C, monotonic counters.	Smaller key store than SE050.

The jotakey key puts the third of these on its own board, next to an STM32L432 microcontroller (§7.5).

7.5 THE JOTAKEY KEY. STM32 + SECURITY CONTROLLER

The jotakey key (`hardware/HARDWARE.md`) pairs two chips with different jobs. The **STM32L432KC**, an Arm Cortex-M4 at 80 MHz, runs the firmware: USB, CTAP, the touch sensor, the LED and the ECDSA signatures. The **Infineon OPTIGA Trust M V1**, built on Common Criteria EAL6+ certified hardware, keeps the secrets: the root, and the signature counter. The two talk over I²C.

FEATURE	ROLE IN JOTAKEY
OPTIGA data object `0xF1D0`	Holds `K_root` , 64 bytes, as a pre-shared secret. After provisioning its access conditions say: never readable, never changeable, usable only over the shielded connection.
OPTIGA `DeriveKey`	Runs the TLS 1.2 PRF (HMAC-SHA256 inside) over `K_root` and returns the result: one credential's tag or seed (§6.3). About 50 ms each.
OPTIGA monotonic counter `0xE120`	The signature counter (invariant 2). The chip only lets it go up, survives power loss by construction, and freezes it at a threshold set to its rated 600 000 updates.
OPTIGA shielded connection	Encrypts and authenticates the I²C traffic with a 64-byte platform binding secret shared between the two chips. A probe on the bus sees ciphertext; a swapped chip on either side cannot talk to the other. A replayed recording of an old session fails the MCU's live-session check (§6.3).
OPTIGA and STM32 random generators	Both feed every random value, mixed with SHA-512, so one weak generator is not enough to weaken the key. The STM32's generator reports its own health errors (invariant 7).
STM32 readout protection	Level 2 on production units: the debug port, booting from RAM and the factory bootloader are disabled for good, and the flash cannot be read out. The setting is irreversible.

The microcontroller: STM32L432KC

The STM32L432KC is an ultra-low-power Arm Cortex-M4 with a floating-point unit, in a 5 × 5 mm UFQFPN32 package ("K" is the 32-pin package, "C" the 256 KB of flash). The key's firmware is not written yet, so the table says what each feature is for in the design. Features the design does not rely on are marked as candidates. The figures are from the datasheet (DS11451) and the reference manual (RM0394) in `hardware/datasheets` .

FEATURE	ROLE IN JOTAKEY
Cortex-M4F, 80 MHz, MPU	Runs CTAP, the USB stack and the ECDSA P-256 signatures in software (RustCrypto, the same code as on the C6). The memory protection unit can make the stack and data non-executable.
256 KB flash: 128 pages of 2 KB, ECC	Firmware, plus the record logs for the epoch, the pairing secret and the PIN record (§6.6). Error correction fixes single-bit errors and detects double-bit ones in every 64-bit word; the record logs add their own CRC on top.
64 KB SRAM: 48 KB SRAM1 + 16 KB SRAM2	The core does not allocate, so its buffers are fixed: the largest is a 1200-byte message. SRAM2 has hardware parity and can be write-protected in 1 KB pages. Candidate: hold the short-lived per-credential seeds there, where a glitch that flips a bit raises a parity error instead of going unnoticed.
USB 2.0 full speed, crystal-less	The key is a native USB HID device: no bridge. The 48 MHz USB clock comes from the internal HSI48 oscillator, which the clock recovery system (CRS) trims against the host's 1 ms start-of-frame packets, and the D+ pull-up is internal. No crystal, no resistors (`hardware/HARDWARE.md` §2).
Touch sensing controller (TSC)	User presence. Up to 3 channels in this package; the key uses one, the electrode on PB5 with its sampling capacitor on PB4 (group 2). The controller runs the charge-transfer measurement in hardware, with spread spectrum against noise and a max-count error flag for a faulty channel.
True random number generator	An analog noise source post-processed by LFSRs, one 32-bit word every 42 RNG clock cycles. It runs its own health tests (repetition count, too slow a clock) and stops on a **seed error**, which the firmware treats as fatal (invariant 7). ST advises

FEATURE	ROLE IN JOTAKEY
	building an approved DRBG on top for NIST use; Jotakey instead mixes it with the OPTIGA's generator through SHA-512 and runs the same SP 800-90B tests as on the C6.
Readout protection (RDP)	Level 2 on production units: no debug port, no boot from RAM, no factory bootloader, and the option bytes are frozen. The datasheet calls it irreversible. Level 1 alone would not do: it blocks reads through the debugger, but published attacks defeat it on several STM32 families (see "What a physical attacker gets" below).
Write protection (WRP), 2 areas of 2 KB pages	Candidate: set over the firmware before level 2, which freezes the option bytes. The flash controller would then refuse to erase or program those pages, so code an attacker manages to run could not make itself permanent.
Proprietary code readout protection (PCROP)	Execute-only flash: code there can be run, not read, even by the CPU's own data accesses. Of little use here: the firmware is open source, and its secrets are data, not code.
Firewall	Candidate. Three segments (code, flash data, RAM data) that only code entering through a **call gate** can reach; any other access resets the chip. It is only effective with RDP level 2. Putting the OPTIGA driver and the binding secret behind it would keep a bug elsewhere in the firmware from reading the secret. It does not stop a fault-injection attacker, who can bypass it like RDP.
96-bit unique ID	Not to be exposed. A USB serial number lets any program on the computer recognise the same key across sessions and users, so the firmware will report no `iSerialNumber`.
Brown-out reset, 1.71–3.6 V supply	Holds the chip in reset while the supply is below its threshold, at power-up and when it sags. It is not a glitch detector: the supply glitches used in fault injection are typically too short for it to react.
SWD	On five bottom-side test pads for a pogo-pin jig. Disabled for good by RDP level 2.

This part has everything a security key needs on one chip: crystal-less USB, a touch controller and a true random number generator, in a package that fits a 12 mm board, with 256 KB of flash for a Rust firmware carrying a USB stack and P-256. Its sibling, the STM32L442KC, adds an AES accelerator (RM0394, Table 1) and nothing else. Jotakey uses AES only for the PIN protocol, a few blocks per PIN entry, which bitsliced software AES does in constant time (§2.4), so the accelerator would buy nothing. A Cortex-M33 with TrustZone (STM32L5, U5) would isolate parts of the firmware from each other in hardware. The firewall above does a smaller version of that, and neither changes the picture against a laboratory attacker, which is why the secrets live in the OPTIGA.

Provisioning

Provisioning happens on the device itself, from two provisioning builds of the firmware that a human flashes and confirms with a long touch (§6.3 has the details). The secrets are generated on the device and never leave it:

1. **Pair** (`provision` build). Mix 64 bytes from each chip's generator into the pairing secret `P`, keep it in the STM32's flash, and write the binding and freshness secrets derived from it into the OPTIGA (`0xE140`, `0xF1D1`).
2. **Root.** Through the new live session, generate `K_root` from both random generators and write it into `0xF1D0`.
3. **Conditions and counter.** Make `K_root` and the freshness secret never readable, never changeable, usable only over the shielded connection; make the binding secret never readable or changeable; set the counter to 0, its threshold to 600 000, counting only over the shielded connection and never rewritable. The epoch is written at first boot.
4. **Lock the OPTIGA** (`provision-lock` build). Move the four objects' life cycle to operational, which freezes their conditions. Everything before this step can be redone.
5. **Lock the STM32.** A human sets readout protection level 2 with STM32CubeProgrammer, over the SWD test pads. From then on the firmware is frozen: Jotakey keys, like YubiKeys, are not updated in the field. A security fix means a new key. (Signed updates are a roadmap exploration, §11.)

Development boards stop before the last two steps and stay open to the debugger; their OPTIGA conditions can still be reopened by someone on the bus, so they are not secure keys. `AGENTS.md` forbids automation from taking any of the irreversible steps: locking OPTIGA objects or setting readout protection.

What a physical attacker gets

The STM32L432 is an ordinary microcontroller. Fault-injection attacks against STM32 readout protection have been published for several families. So we assume a well-equipped thief can, in the end, run their own code on it, with the pairing secret and the epoch in hand. What they can do at that point:


THEY CAN	THEY CANNOT
Use the key while they hold it, for any credential whose ID they present: the hardware computes its tag and seed on request.	Read `K_root`: the OPTIGA never releases it, and attacks on the OPTIGA itself are what its certification is about.
Copy a credential, if they also obtain its ID from the website (the ID is not secret).	Copy the key as a whole: no secret on the STM32 covers more than one credential, so nothing they take away lets them compute the others or mint new ones.
Make the key unusable (for example, by resetting it).	Roll the signature counter back: it lives in the OPTIGA and only goes up, so relying parties that check it can notice a copied credential.

This is the honest boundary of a two-chip design. A key whose secure element also performed the signatures would close the first row. The Trust M V1 cannot import a derived private key to sign with it, and storing one key per credential would cap the number of credentials. The threat model (§1.3) records the result as **partially defeated**.

The OPTIGA Trust M V3 adds HMAC, HKDF and AES. It was out of stock when the board's parts were chosen, so the key uses the V1, whose TLS PRF does the same job here. The two share a package and pinout, so a later board can switch; `F` would then become HMAC, as on the C6.

7.6 THE JOTAKEY KEY BOARD

The jotakey key is a two-layer board whose own edge is the USB plug. Hardware 0.3.0 is described here (releases are tagged `hw-vX.Y.Z`); `hardware/HARDWARE.md` records the part choices against their datasheets, and `hardware/MANUFACTURING.md` the order.



THE JOTAKEY KEY, HARDWARE 0.3.0, RENDERED FROM THE KICAD DESIGN: 47 × 18 MM, 2.0 MM THICK, BLACK SOLDER MASK. THE BACK IS DRAWN AS SEEN FROM BELOW.

Outline and parts

The narrow end is a USB-A plug: a 12 mm tongue carrying four gold contacts laid out as in the USB 2.0 Series "A" plug drawing, with VBUS and GND longer than the data contacts so they mate first. The board is 2.0 mm thick, so the tongue sits firmly in a receptacle, and the contacts' edge is bevelled. The 18 mm body ends in a semicircle whose centre is the centre of the touch electrode.

REF	PART	ROLE
U1	STM32L432KCU6, QFN-32	The microcontroller: USB full speed without a crystal (its clock is trimmed against the host's USB frames), the touch-sensing controller, I²C to the secure element, ECDSA signing.
U2	OPTIGA Trust M V1, USON-10	The secure element: the root secret, per-credential derivation and the signature counter (§7.5).
U3	XC6206 3.3 V LDO, SOT-23	Power from the USB 5 V.
U4	USBLC6-2SC6, SOT-23-6	ESD protection on D+, D− and VBUS, next to the contacts.
E1	10 mm copper disc	The touch electrode, user presence (invariant 1). The bolt logo is cut out of the copper.
D1	Red LED, 0603	The only display: touch requested, OK, fault.
R6, R7	0 Ω links, 0402	Bring-up: they join the LDO's 3.3 V to the microcontroller's supply and that to the secure element's. Not fitted at assembly: soldered by hand during bring-up, they power the board up one stage at a time.
TP1–5	Test pads, bottom	SWD (DIO, CLK, RST, 3V3, GND) for a pogo-pin jig.
TP6–11	Test pads, bottom	Bring-up: the 5 V supply, the LDO's output, the secure element's rail, and its I²C bus and reset, for a meter or a logic analyser.

Layout decisions

- **The tongue carries contacts and nothing else.** No vias and no copper on its back: it slides against the receptacle's metal shell.
- **One crossing for USB.** The plug has D− on the left; the microcontroller's pins put D− on the right. The two lines cross once, between the ESD chip and the microcontroller, where D+ drops to the back for a few millimetres. The ESD chip sits on the board's axis, and its two identical channels are assigned so the crossing stays off the tongue.
- **The touch electrode follows ST's AN4312.** Nothing on the top layer comes within 4 mm of it except its own trace (the note asks for at least 2 mm, 4–5 mm recommended), which arrives at 45°. Behind it, the back carries a ground hatch of 10 % copper instead of a solid plane, trading a little noise immunity for sensitivity. Keeping that gap is why the board is 47 mm long and not 45.5.
- **The secure element sits in the corner** next to the microcontroller's I²C pins, rotated so its clock, reset and supply pins face the microcontroller.
- **Ground pours on both layers,** tied together under each chip's exposed pad.

Silkscreen

The mask is black, which hides the contrast between copper and bare board. So the bolt cut out of the electrode's copper is also printed in white, exactly over the cut-out. The front names the chips by function (MCU, OPTIGA, LDO, ESD); the reference designators live on the assembly drawing instead, because next to 0402 parts on a board this size they cannot avoid covering pads. The back carries the hardware version, the SWD pad names, and the two places where JLCPCB prints its marks: `JLCJLCJLCJLC` for the order number and a solid block for each board's serial number.

How the board is made

The layout is reproducible from scripts in `hardware/jotakey-key/tools/`, each run with KiCad's own Python or command line. `layout.py` draws the outline and places every part; `route.py` lays down the keep-outs and the hand-routed nets (USB, power, the touch trace, the parts under the microcontroller), lets the Freerouting autorouter connect the rest, and pours the ground; `silk.py` adds the silkscreen; `fab.py` refuses to build unless the schematic and board checks pass, then writes the Gerber, BOM and placement files for

JLCPCB; `render.py` draws the figures above. The hardware version is set in one place, the KiCad project variable `HW_VERSION`, which the title blocks and the back of the board display.

08 TESTING

No single technique catches everything, so Jotakey tests at multiple levels, on top of formal validation.

KIND	WHAT IT CATCHES	WHERE
Unit & scenario tests	Known behaviours, spec examples, every error path.	`crates/*/tests`, `#[cfg(test)]`
Property tests	Laws that must hold for **all** inputs: round trips, bounds, monotonicity.	`proptest` in the core
Fuzzing	Crashes, hangs and invariant violations on inputs nobody imagined.	`fuzz/` (9 targets)
Mutation testing	Gaps in the **tests themselves**: code whose breakage no test notices.	`cargo mutants`
On-device tests	What only silicon can show: the TRNG, the HMAC key, real flash, timing.	`crates/jotakey-testfw`
End-to-end	The whole chain as a relying party sees it.	`crates/jotakey-host-tests`, `scripts/fido2_check.py`, `scripts/fido2_pin_check.py`

8.1 UNIT, SCENARIO AND PROPERTY TESTS

96 tests run on the host (`just test`). Highlights:

- **CBOR:** every integer example from RFC 8949 Appendix A; rejection of non-minimal heads, indefinite lengths, tags, floats, `undefined`, invalid UTF-8, unsorted and duplicate map keys, nesting deeper than 4; huge announced lengths fail fast instead of looping. Properties: head and integer round trips; "accepted heads re-encode to the same bytes"; "the decoder never panics on arbitrary bytes".
- **CTAP:** full register → authenticate flows with signatures verified against the public key parsed from authData; RP binding (`evil.example` gets `NO_CREDENTIALS`); tampered IDs; exclude lists; every option combination; algorithm negotiation; PIN probes; missing and wrongly typed parameters; reset window boundaries; and **fail closed**: a failing RNG, key derivation or counter write yields `CTAP1_ERR_OTHER` and **never** moves the counter.
- **Transports:** CTAPHID at every size boundary (1, 57, 58, 116, 117, 118 … 1200 bytes), channel busy and isolation, resync via INIT, sequence errors, timeouts, keepalives, cancel; BLE at every fragment size from 20 to 512. Two thousand random packet streams check that receive state stays well-formed.
- **Storage:** append and remount across sector switches; a property test that cuts power at random byte offsets, including in the middle of a sector erase, and checks that no confirmed counter value is lost or reissued.
- **Self tests:** known-answer tests for SHA-256, HMAC, HKDF and ECDSA (RFC 6979 §A.2.5), plus **fault injection**: corrupting each KAT result in turn must be detected, exactly as FIPS 140-3 expects a self-test implementation to demonstrate.

8.2 FUZZING

Every byte that reaches the key from the host is chosen by someone who may be an attacker: the browser, the operating system, the bridge, any program that can open the HID device or reach the BLE link. Invariant 4 demands that the parsers handle **every** byte string, not just the ones the specification describes. Unit tests check the inputs their authors thought of. A **fuzzer** generates inputs nobody thought of, by the million, and watches what happens.

Coverage-guided fuzzers

Jotakey uses `cargo fuzz`, which drives **libFuzzer**, the fuzzer built into LLVM. A **fuzz target** is a function that takes a byte slice and feeds it to the code under test. The compiler instruments every branch of the program, so after each run the fuzzer knows which edges of the control-flow graph that input reached. The loop is:

1. PICK	An input from the **corpus**, the set of inputs kept so far (initially the seeds).
2. MUTATE	Flip bits, insert, erase or copy bytes, splice two inputs, write "interesting" values (0, 0xFF, lengths), or insert a **dictionary** entry.
3. RUN	Call the target. Sanitizers and assertions watch every operation.
4. OBSERVE	A crash, panic, timeout or out-of-memory stops the run and saves the input. Otherwise: did this input reach an edge (or an edge count) never seen before?
5. KEEP	If it did, add it to the corpus: it is a stepping stone toward deeper code.

ONE ITERATION OF LIBFUZZER'S LOOP, MILLIONS OF TIMES PER RUN

The fifth step is what makes the search **coverage-guided** rather than random. An input that gets one byte further into a CBOR map is kept, and its mutations get further still. The fuzzer climbs into the program a branch at a time, the way a person learns a format by trial and error, only a million times faster.

Comparison tracing helps it over walls. The instrumentation also records the operands of every comparison the program makes, so when the deframer compares a computed CRC with the one on the wire, the fuzzer learns the value it needed and tries it next. The "recommended dictionary" libFuzzer prints at the end of a run is the record of these values: for the serial target it is full of 4-byte CRCs.

Failure types:

- **Panics.** The core is built with `overflow-checks = true`, so an arithmetic overflow is a panic, not a silent wrap. An out-of-range index, a failed `expect` in the target, or an assertion is also a panic. libFuzzer treats each as a crash.
- **Memory errors.** AddressSanitizer is on. The core has no `unsafe`, so this mostly guards the dependencies and the harness.
- **Hangs and blow-ups.** A run that exceeds the time limit (unbounded loops, invariant 4's "no unbounded recursion") or the memory limit is reported as a failure.

Oracles

A fuzzer only notices what goes obviously wrong. Wrong answers, such as accepting a malformed message, or signing without a touch, or moving the counter twice, pass unnoticed. **Oracles** are assertions in the target that turn a violated property into a crash. They turn fuzzing into a security test instead of a robustness test.

Take `cbor_decode`. "The decoder does not panic" is the obvious property. The oracle adds a stronger one: whatever the strict decoder accepts is re-encoded item by item, and the result must equal the input **byte for byte**. If two different byte strings decoded to the same value, an attacker could produce a second encoding of a signed message, and canonical CBOR exists to rule that out. The oracle is the statement of the Lean theorem `decodeHead_accepts_only_canonical` (§9.5), checked on the real Rust code, which the proof never sees.

The other oracles follow the same idea: each states a security invariant in executable form.

Reaching deep code

Random bytes rarely get far. A CTAPHID request must arrive on an allocated channel in packets whose sequence numbers count up. A serial frame must carry a CRC-32 that random data matches once in four billion tries. A makeCredential must be a well-formed CBOR map with sorted keys before any credential logic runs. A target that only ever hits the first `return Err` tests very little. Four techniques are used to get deeper into the code:

- **Inputs as scripts.** The fuzzer's bytes are read as instructions that **build** a valid outer layer, rather than as the outer layer itself. In `ctaphid_stack` the first byte of each 65-byte record picks the channel (mostly ones already allocated), whether the clock jumps past the packet timeout, and whether the user

touches or times out. The `serial_deframe` input says "send these raw bytes", "send an intact frame of this report" or "send this frame with one byte changed".

- **Templates.** In `ctap_dispatch` an odd first byte means "take a valid makeCredential or getAssertion and overwrite these positions with these values". Every mutation starts one step from a valid request, so the deep validation paths are hit from the first run.
- **A genuine credential.** `ctap_dispatch` registers one credential once (`OnceLock`) and puts its real ID in the getAssertion template, so mutated assertions can **succeed**, and the oracles about successful signatures get exercised.
- **Seeds.** `fuzz/make_seeds.py` writes real transactions in each target's input format to `fuzz/seeds/` (tracked in git): a CTAPHID INIT followed by getInfo or makeCredential, the same over BLE, boot text followed by frames. `just fuzz` hands them to libFuzzer next to the working corpus in `fuzz/corpus/` (not tracked: it is regenerated by fuzzing).

NOT REACHING THE ORACLES

Coverage numbers can look healthy while the important path is never taken. Writing this chapter, we counted what each corpus actually reaches. The `serial_deframe` target had run millions of times without ever accepting a frame: no random input had a valid CRC, so its oracle about accepted frames had never once been evaluated (and was weak anyway: it computed a CRC and threw it away). The CTAPHID corpus never got a request through to the authenticator, and the BLE corpus never produced a successful response. To prevent this, we deploy three things: the script format of `serial_deframe`, a stronger oracle, and seeds. Because of them the serial corpus accepts about 10 000 frames per pass, and the transport targets start from successful makeCredential and getInfo exchanges. To check that the new oracle works, we disabled the deframer's CRC comparison: the fuzzer reported "accepted bytes are not the frame's encoding" within seconds. A fuzz target is code too, and it needs its own test.

The ten targets

Each target runs the real core code against `MockPlatform`, a deterministic stand-in for the hardware: its random numbers come from a seeded generator and its key store is software HMAC, so every crash reproduces exactly. The OPTIGA driver's target runs against `SimOptiga` instead, a software OPTIGA Trust M (`optiga/sim.rs`): the slave side of the registers, the data link, the shielded connection, and the commands and access conditions the key uses, with switches to NACK, damage or drop frames. Its failure switches (`fail_rng`, `fail_counter`, `fail_derive`) are what the unit tests use for the fail-closed paths.

TARGET	INPUT	ORACLE (BEYOND: NO PANIC, NO HANG)	INV.
`cbor_decode`	Raw bytes to the strict CBOR decoder.	Anything accepted re-encodes to **exactly** the input bytes: no value has two encodings.	4
`ctap_dispatch`	`[mode, presence, …]`: a raw request, or byte overwrites of a valid makeCredential/getAssertion template; the presence byte picks touch, timeout or cancel.	The counter moves only on a successful makeCredential/getAssertion, by exactly one. A signature produced after parking needed a confirmed touch; one produced without parking is a getAssertion with the UP flag clear. Success bodies are canonical CBOR with no trailing bytes. Nothing stays parked. Responses are 1 to `MAX_MSG_SIZE` bytes. No single request changes the PIN record or signs with UV.	1, 2, 4, 10
`ctaphid_stack`	Records `[flags, packet(64)]`: channel choice, clock jumps, touch or timeout.	The full USB path: reassembly, the authenticator, fragmentation. Receive state stays within bounds; no request is left unanswered; output is bounded.	4, 5
`ble_stream`	A fragment size, then GATT writes of chosen lengths with clock advances.	The BLE framer and the authenticator together. No notification exceeds the fragment size.	4
`serial_deframe`	A script of raw bytes, intact frames and frames with one byte overwritten.	Every report emitted came from wire bytes that are exactly its encoding (so its CRC was valid and no second encoding is accepted); nothing is emitted before a delimiter; an intact frame always gets through, whatever garbage came before it.	4

TARGET	INPUT	ORACLE (BEYOND: NO PANIC, NO HANG)	INV.
`credential_unwrap`	A tag key, an `rpIdHash` and a candidate credential ID.	An accepted ID is exactly what `wrap` mints for the recovered nonce at that RP; a minted ID always unwraps to its nonce.	3
`pin_protocol`	A key-agreement scalar, the platform's COSE key, then a message.	An accepted key re-encodes to the same key, and a key without extra labels is byte for byte the canonical encoding. `decrypt` accepts exactly `iv ‖ whole blocks`, and re-encrypting under the same IV gives the message back. `verify` accepts only `authenticate`'s tag. Checked with a planted bug (CBC chaining removed): caught on the first seed.	4
`client_pin`	A script: key agreement, setPIN, changePIN, token requests, makeCredential and getAssertion with the token, power cycles, resets, failing storage. The target is a correct platform; the input only chooses what it does.	A plain model of the CTAP 2.1 PIN rules predicts the exact status of every step; the stored retries, mismatch count, token and UV flags must match it. The stored counter must already be one lower when the PIN is first processed. A planted bug that compared before counting was caught.	1, 10
`record_log`	A programming unit (4 or 8) and payload size, then a script of appends, power cuts after a chosen number of steps, and remounts.	A remount never goes below the last confirmed sequence number, and finds that record's payload intact; confirmed numbers strictly increase; with the power on every append succeeds, so the log never breaks the flash's programming rules (whole units, each programmed once), which the mock flash enforces. A planted bug that erases the sector holding the latest record is caught within seconds.	2
`optiga_bus`	A mode, a nonce, a script of counter increments, derivations and new sessions, then a script for an attacker on the I2C bus: per read, pass, flip a bit, replay an earlier read, or NACK. In one mode the attacker sits in front of a simulated OPTIGA; in the other it **is** the bus.	Every counter value the driver returns is the OPTIGA's real value and exceeds the last one; every derived secret is the real `PRF(K_root, input)`; with no OPTIGA behind the bus, no session is ever established. Checked with a planted bug (the sequence-number window removed): found in seconds.	2, 4, 7

The `client_pin` target had its own lesson. Its first oracle compared every status code with the model, and a planted bug that compared the PIN **before** storing the attempt passed it: from the outside the two orders answer identically. What the order protects against is a power cut between the two steps, which no status code shows. The fix was to make the order itself observable: the mock platform notes the stored counter at the moment the PIN is first processed, and the oracle requires it to be one lower already. The planted bug then failed within seconds, and so did the unit test written alongside.

The `serial_deframe` property "an intact frame always gets through" is the regression test for the bridge startup hang of chapter 6: before every frame began with a delimiter, boot text in front of a frame made it undecodable.

Running, reproducing, fixing

```
just fuzz ctap_dispatch          # one target, 5 minutes (just fuzz T SECONDS)
just fuzz-all 120                # every target, 2 minutes each
python3 fuzz/make_seeds.py       # regenerate the seeds after a format change
```

Fuzzing needs a nightly toolchain (for the sanitizers) and `cargo install cargo-fuzz`. When a target fails, libFuzzer stops, prints the panic message and saves the input as `fuzz/artifacts/<target>/crash-<hash>`. Then:

1. **Reproduce:** `cargo +nightly fuzz run <target> fuzz/artifacts/<target>/crash-<hash>` replays exactly that input. `MockPlatform` is deterministic, so it fails the same way every time.

2. **Minimise:** `cargo +nightly fuzz tmin <target> <crash file>` shrinks the input to the smallest one that still fails, usually a handful of bytes that make the bug obvious.
3. **Fix, and keep a unit test.** The minimised input becomes an ordinary test in `jotakey-core`, so the bug stays fixed even when nobody is fuzzing. The serial framing test `boot_text_before_the_first_frame_does_not_swallow_it` is an example.

`cargo +nightly fuzz cmin <target>` prunes a corpus to the inputs that still add coverage, and `cargo +nightly fuzz coverage <target>` produces a line-coverage report of what the corpus reaches. That report is the first thing to look at when a target seems too quiet.

Strengths and weaknesses of fuzzing

- **It finds the inputs nobody imagined.** People who write tests share the blind spots of the people who wrote the code, and are often the same people. The fuzzer has no expectations: it will send a map with 2^{32} announced entries, a continuation packet on a channel that never started, or a frame split across a reboot, because the coverage told it those paths exist.
- **It checks properties, not examples.** One oracle covers every input the fuzzer will ever produce. Adding a property costs a few lines; the fuzzer then tests it millions of times an hour, unattended.
- **It ties the proofs to the code.** The Lean models of chapters 9 and 10 are proved for **all** inputs, but they are models: hand transcriptions of the Rust. The fuzz oracles state the same theorems and check them on the real code (chapter 10 pairs each oracle with its theorem). The two nets have different holes: the proofs cover every input of the model, the fuzzer many inputs of the real implementation.
- **It complements mutation testing.** Mutation testing asks whether the tests notice a broken program. Fuzzing asks whether the program breaks on inputs the tests do not contain. The section below shows the first; the trap above shows a fuzz target that, like a weak test, could not have noticed anything.

The limits are as important:

- **No guarantee.** A fuzzer that finds nothing has found nothing **yet**. It cannot guess a 128-bit tag, and a bug behind such a check is out of its reach; proofs and review cover those.
- **Host only.** Targets run on x86 against the mock platform. The firmware adapters (esp-hal drivers, flash, the HMAC peripheral, and on the key the OPTIGA driver once it exists) are not fuzzed; the on-device tests and end-to-end tests below cover them.
- **Functional properties only.** Timing leaks, power side channels and fault injection are invisible to a fuzzer. Invariant 9 relies on `subtle`, RustCrypto and review.

This is a sample run, two minutes per target from the seeds with no failures:

CBOR_DECODE	CTAP_DISPATCH	CTAPHID_STACK	BLE_STREAM
14.9 M	3.4 M	0.6 M	2.6 M
serial_deframe	credential_unwrap	pin_protocol	client_pin
2.2 M	35.4 M	0.07 M	0.01 M

Executions per run depend on how much code each input reaches: a CTAPHID input carries whole transactions through the authenticator, including ECDSA signatures, while a credential ID check is one HMAC. A `pin_protocol` input costs a full elliptic-curve key agreement, and a `client_pin` script up to 64 operations with several each, which is why those two manage the fewest runs. Longer runs before a release are worth their time, and inputs captured from real browsers through the bridge make good seeds.

8.3 MUTATION TESTING

Mutation testing introduces small changes to the code then runs tests to make sure they fail. `cargo mutants` makes hundreds of small deliberate bugs in the code: it flips `<` to `<=`, deletes a `!`, replaces a function body with a constant, deletes a `match` arm. It then runs the test suite against each one. A mutant that survives is a change to the code that no test notices, indicating a better test is in order.

RUN	MISSED	WHAT CHANGED
First run	61 / 459	Revealed untested boundaries (user-ID length 64/65, reset window at exactly 10 000 ms), optional members whose **type**

RUN	MISSED	WHAT CHANGED
		was never checked, CTAPHID resync corners, status codes only compared with themselves, and self tests whose failure branch could never run.
After fixes	0	New targeted tests; an unreachable branch replaced by a compile-time assertion; dead API removed; fault injection added to the self tests.
Storage added	11	The new record log passed its functional tests, yet its on-flash **format**, CRC rejection and sector-switch schedule were unpinned: mutants that wasted slots or erased too often survived. Fixed with a golden layout test, an erase-count schedule test and corruption tests.
clientPIN added	6 / 696	The token lifetime was tested only through its own constant, the session's `Debug` output not at all, and one buffer size was an equivalent mutant. Fixed with a literal ten-minute test, a `Debug` test, and a compile-time assertion in place of the arithmetic.
Current	**0 / 690**	597 caught, 87 unviable (do not compile), 6 time out (infinite loops, counted as caught).

The policy (`AGENTS.md` §4) is **zero unexplained survivors**. The only excluded class is documented in `.cargo/mutants.toml`: replacing `|` with `^` where the operands are disjoint bit fields (`cmd | 0x80` with `cmd < 0x80`), which produces identical values; one comparison between sequence numbers that are unique by construction; and the mock flash, which is test scaffolding. Mutants that make code loop forever are caught by timeouts.

> **WHY BOTHER, WITH PROOFS AVAILABLE?**
> Mutation testing found that the self tests' failure paths were never exercised: a broken `run_kats` that always returned `Ok` would have passed every test. Proofs about the protocol model would not have noticed either, because the self tests are not part of it. Each net has holes the others cover.

8.4 ON-DEVICE TEST FIRMWARE

Some properties exist only on silicon. For the jotakey key, no board is on the desk yet: USB enumeration, the touch thresholds, the ECC fault on a torn double-word, the OPTIGA on the wire (the simulator is written from the same specifications as the driver, so only a real chip can show that both read them right: frame timing, the checksum's byte order, which the code takes from Infineon's library, the first record's sequence number, the metadata encodings, provisioning end to end) and an on-device test firmware for the STM32 are listed as work for when the first boards arrive. For the C6, `crates/jotakey-testfw` is a separate firmware built with `embedded-test` and run by `probe-rs` through the C6's built-in USB-JTAG. No extra debug probe is needed. Each test is flashed, the chip is reset, the test runs, and pass/fail comes back over semihosting with logs over RTT.

TEST	CHECKS
`known_answer_tests_pass_on_target`	The KATs on the RISC-V target (endianness, compiler, crypto backends).
`injected_faults_are_detected_on_target`	Each injected self-test fault is detected on the target.
`trng_health_and_statistics`	SP 800-90B start-up test; 64 KiB through the continuous tests; byte χ^2 and monobit within $\pm 6\sigma$.
`efuse_root_key_hmac`	HMAC peripheral with eFuse KEY0: deterministic, label-separated. **Skipped with a warning** on unprovisioned boards.
`record_log_on_real_flash`	600 appends across sector switches on real NOR flash; a torn record is ignored; uses a scratch area that never touches production data.
`ctap_register_and_authenticate_on_target`	Full makeCredential + getAssertion on the chip with the real TRNG; the signature verifies; no touch, no signature.

TEST	CHECKS
`ecdsa_timing_budget`	Sign + verify under 400 ms per operation at full clock.
`status_led_accepts_frames`	WS2812 frames via RMT.
`user_presence_button` (interactive)	Press BOOT within 30 s (`--features interactive`).

8.5 END TO END

`jotakey-host-tests` contains a CTAPHID **client** written independently of the device code. It has its own CBOR codec, so a bug that is symmetric in the device's encoder and decoder cannot hide. It also contains relying-party checks as a WebAuthn server would perform them (authData layout, COSE key, packed self-attestation, signatures, counters). The client runs against two devices:

- **the simulator**, an in-process device wired exactly like the firmware's USB task: serial framing → CTAPHID → authenticator, with keepalives while "waiting for the touch". This runs in every `just test` .
- **a real Jotakey** through `jotakey-bridge` and `/dev/hidrawN` (ignored by default; run with `just host-tests` while touching the button when asked).

Finally, `scripts/fido2_check.py` drives the device with Yubico's **python-fido2**, both as client **and** as relying-party server. That is a completely independent implementation of both ends of the protocol. `scripts/fido2_pin_check.py` does the same for the PIN: it sets one, checks that a wrong guess is counted and a right one restores the counter, gets tokens and changes the PIN, all without a touch; with `--touch` it also registers and signs in with user verification required. The PIN protocol's primitives were pinned byte for byte to python-fido2 before any of this ran. On the C6 the device passed every no-touch check on the first run (python-fido2 itself refuses to send a PIN shorter than four characters, so that rule is tested only in Rust), and with `--touch` python-fido2's server accepted a registration and a sign-in with user verification required, UV flag set.

8.6 STATIC CHECKS

- `#![forbid(unsafe_code)]` in the core; Clippy denies `unwrap` , `expect` , `panic!` , unchecked indexing and unchecked arithmetic in shipped core code.
- `overflow-checks = true` in every profile, release included.
- `cargo deny` : no known-vulnerable or yanked crates, allowed licences only, crates.io only. Exceptions are documented with reasons: two unmaintained crates that run only at build time (a proc-macro and a build-script YAML parser) and never ship in the firmware.

09 FORMAL VERIFICATION

This chapter assumes no background in formal methods. It explains what formal verification is, surveys the techniques, teaches enough Lean 4 to read Jotakey's proofs, walks through the main ones, and is explicit about what they do **not** guarantee. Chapter 10 then goes through every theorem in detail.

9.1 PROOFS VS. TESTS

Every test in chapter 8 checks **some** inputs. A fuzzer may run a billion of them, but a CTAP message has more possible values than there are atoms in the universe. As Dijkstra put it in 1970, "program testing can be used to show the presence of bugs, but never to show their absence."

A **formal proof** is different. It is a mathematical argument, checked mechanically by a computer, that a property holds for **every** input, **every** sequence of events, **every** possible state. When we prove "no execution of the authenticator state machine produces a signature without a confirmed touch", we are not sampling executions. We have shown that such an execution cannot exist.

The catch is the word **model**. A proof is about a precise mathematical description of a system. If that description differs from the real system, the proof says nothing about the difference. Much of the craft lies in choosing what to model, and in closing the gap between model and code (§9.7).

> **TESTING SAMPLES BEHAVIOURS. PROOF COVERS ALL OF THEM, FOR THE MODEL IT IS ABOUT.**

9.2 THE LANDSCAPE OF TECHNIQUES

Formal methods form a spectrum, from cheap and automatic to expensive and complete. They are complements, not rivals. Jotakey uses several at once.

TECHNIQUE	WHAT IT DOES	EXAMPLES
Type systems	Rule out whole classes of errors at compile time. Rust's ownership types rule out use-after-free and data races in safe code.	Rust, Haskell, OCaml
Property-based testing	Check a stated property on many random inputs, shrinking failures to a minimal example.	proptest, QuickCheck, Hypothesis
Fuzzing	Coverage-guided random inputs search for crashes and violated assertions.	libFuzzer, AFL++, cargo-fuzz
Model checking	Exhaustively explore every state of a finite (or bounded) model, and produce a counterexample trace if a property fails.	TLA+/TLC, SPIN, CBMC, **Kani** (Rust)
Abstract interpretation	Over-approximate all behaviours to prove the absence of run-time errors.	Astrée (Airbus flight software), MIRAI
Deductive verification	Annotate code with pre/postconditions and invariants; an SMT solver discharges the proof obligations automatically.	Dafny, Why3, Frama-C, **Verus**, **Creusot**, **Prusti**
Interactive theorem proving	Write definitions and proofs in a rich logic; a small kernel checks every step. Most expressive and most laborious.	Rocq (Coq), Isabelle/HOL, **Lean 4**, F*

Landmark results show what the strong end can reach:

- **seL4** (Isabelle/HOL, 2009–): an operating-system microkernel whose C implementation is proved to refine its specification, down to the compiled binary.
- **CompCert** (Coq): a C compiler proved never to miscompile. In a large compiler-testing study, it was the only compiler in which no wrong-code bugs were found in the verified parts.
- **HACL*** and **Fiat-Crypto**: verified cryptographic code now running in Firefox, the Linux kernel, Chrome and BoringSSL.
- **Amazon Web Services**: TLA+ for distributed protocols; the Cedar authorization language, whose specification and proofs are written in Lean.

9.3 LEAN 4 PRIMER

Lean 4 is both a functional programming language and a proof assistant. That duality is exactly what we need: the **same** definitions can be run (as an executable specification) and reasoned about (as mathematics).

Data and functions

Types are defined by listing their constructors, and functions by pattern matching:

DATA AND FUNCTIONS

```
inductive PresenceResult where       -- result of waiting for a touch
  | confirmed | timeout | cancelled

def toLittleEndian : Nat → Nat → List Nat   -- the low `width` bytes, least significant first
  | 0,          _     => []
  | width + 1, value => value % 256 :: toLittleEndian width (value / 256)

#eval toLittleEndian 2 1000          -- [232, 3]
```

Lean insists that every function **terminates** and handles **every** case. A function that could loop or crash is rejected at definition time. For our CBOR decoder that is already a theorem: the definition compiles, so the decoder terminates on every input.

Propositions are types, proofs are programs

The central idea, the **Curry–Howard correspondence**, is that a statement is a type, and a proof of the statement is a value of that type. `2 + 2 = 4` is a type. `rfl` ("by reflexivity") is a value of it. A theorem is a definition whose type is the statement:

A FIRST THEOREM

```
theorem toLittleEndian_length (width value : Nat) :
    (toLittleEndian width value).length = width := by
  induction width generalizing value with
  | zero          => rfl                        -- the empty list has length 0
  | succ width ih => simp [toLittleEndian, ih]   -- one byte, plus `width` by induction
```

The part after `by` is a **tactic script**. Instead of writing the proof term by hand, we issue commands that build it step by step:

TACTIC	WHAT IT DOES
`intro`	Assume the premise of an implication ("suppose P …").
`cases` , `match`	Split into one case per constructor ("either it timed out, or …").
`induction`	Prove for 0 (or `[]`), then for `n+1` assuming `n` (or `x :: xs` assuming `xs`).
`simp`	Rewrite with known equations until the goal simplifies away.
`omega`	Decide linear arithmetic over integers and naturals, including `/` and `%` by constants.
`rfl` , `decide`	Close a goal that holds by computation.
`exact` , `apply`	Use an existing lemma to finish, or reduce, the goal.

Quis custodiet ipsos custodes?

Tactics are elaborate and could contain bugs. That does not matter. Every tactic only **proposes** a proof term, and a small, separate **kernel** type-checks the final term. Only the kernel must be trusted (the "de Bruijn criterion"). Lean also records which **axioms** a proof relies on. `#print axioms` lists them, and `formal/AxiomAudit.lean` checks every Jotakey theorem:

LAKE ENV LEAN AXIOMAUDIT.LEAN (EXCERPT)

```
'Jotakey.Authenticator.signature_requires_confirmed_touch' depends on axioms:
    [propext, Quot.sound]
'Jotakey.Authenticator.trace_signature_counters_increase' depends on axioms:
    [propext, Classical.choice, Quot.sound]
'Jotakey.CtapHid.fragmented_message_is_reassembled' depends on axioms: [propext, Quot.sound]
'Jotakey.Cbor.decodeHead_accepts_only_canonical' depends on axioms: [propext, Quot.sound]
```

These are the three standard axioms of Lean's logic (propositional extensionality, quotient soundness, and choice), the same ones all of mathlib uses. Two markers would mean trouble: `sorryAx` , which records an

unfinished proof, and `Lean.ofReduceBool`, which records a proof that trusts the compiler. Neither appears, and `just lean` fails the build if either ever does.

9.4 MODELLING

A model is a deliberate simplification. Jotakey's models follow three rules:

1. **Mirror the code's structure.** The Lean `receivePacket` function for CTAPHID has the same cases, in the same order, as `CtapHid::handle_packet`. Reviewers can compare them line by line.
2. **Abstract what the property does not depend on.** The authenticator model does not parse CBOR or compute ECDSA. A request arrives already classified as `makeCredential relyingParty`, `getAssertion relyingParty credential`, `rejected` and so on. "No signature without a touch" does not depend on how parsing works, so the parser is not part of that model. (It has its own model, below.)
3. **Make assumptions explicit.** Cryptography cannot be proved in Lean. The credential model takes the MAC as a **parameter**, and any theorem that needs a cryptographic property states it as a hypothesis, visible in the theorem's signature.

9.5 CASE STUDY: CBOR HAS EXACTLY ONE ENCODING

The first model, `formal/Jotakey/Cbor/`, mirrors the decoder of §5.1. The key theorem says that whatever bytes the decoder accepts are **exactly** the canonical encoding of what it returned:

FORMAL/JOTAKEY/CBOR/HEADS.LEAN

```
theorem decodeHead_accepts_only_canonical (bytes : List Nat) (majorType argument : Nat)
    (rest : List Nat)
    (hBytes : ∀ byte ∈ bytes, byte < 256)                    -- these really are bytes
    (h : decodeHead bytes = some (majorType, argument, rest)) : -- the decoder accepted them
    bytes = encodeHead majorType argument ++ rest             -- … so they ARE canonical
```

Read it as: "for every byte list `bytes`, if the decoder accepts it, then it is exactly the canonical encoding of the result, followed by the unread rest." Two different byte strings can therefore never decode to the same head. The ambiguity attacks of §5.1 are impossible for any parser that implements this model.

The proof splits on the width of the argument (immediate, 1, 2, 4 or 8 bytes). In each case it uses a lemma about big-endian numbers, `bigEndian_bytes_roundtrip`: reading `k` bytes as a number and writing the number back as `k` bytes gives the same bytes. The minimality check is what makes the case split work. A value accepted from the 2-byte form is ≥ 256, so `encodeHead` also chooses the 2-byte form. Without that check in the decoder, the theorem would be **false**, and Lean would refuse the proof. That is the point: the proof would not have gone through for a lax decoder.

Its companion, `decodeHead_inverts_encodeHead`, proves the round trip in the other direction. The full validator `skipItem`, which handles maps, key ordering, UTF-8 and depth, is defined in `Cbor.lean`, next to it. Lean's termination checker accepts it, so the decoder provably terminates on every input.

9.6 CASE STUDY: THE SECURITY STATE MACHINES

No signature without a touch, ever

`formal/Jotakey/Authenticator.lean` models `Authenticator::process` and `complete` as pure functions `processRequest` and `completePresence` on a `State` (pending command, signature counter, reset epoch, fault flag), driven by `Event`s: requests and presence results. A **trace** is any list of events, in any order, of any length. The theorems quantify over all of them:

FORMAL/JOTAKEY/AUTHENTICATOR.LEAN

```
-- Invariant 1.
theorem signature_requires_confirmed_touch (state : State) (event : Event)
    (relyingParty counter : Nat)
    (hSigned : (handleEvent state event).2 = .signature relyingParty counter) :
    event = .presence .confirmed ∧ state.faulted = false ∧
      (state.pending = .makeCredential relyingParty ∨
        ∃ credential, state.pending = .getAssertion relyingParty credential)

theorem one_touch_signs_at_most_once (state : State) (first second : PresenceResult)
    (relyingParty counter : Nat) :
    (completePresence (completePresence state first).1 second).2 ≠
      .signature relyingParty counter

-- Invariant 2, over every possible trace.
theorem trace_signature_counters_increase (state : State) (events : List Event) :
    (signatureCounters (runTrace state events).2).Pairwise (· < ·)
```

In words:

- A signature comes **only** from a confirmed presence event that completes a parked makeCredential or getAssertion for **that** relying party, on a healthy device.
- One touch completes at most one command. A second “confirmed” event right after produces nothing.
- In **any** interleaving of requests, touches, timeouts, cancellations and resets, the counters of emitted signatures form a strictly increasing sequence.

`epoch_change_requires_reset_in_window` proves invariant 6 over traces. If the epoch ever changes, the trace contains a reset request that arrived within 10 seconds of power-up. `faulted_stays_faulted_and_never_signs` proves that the fault state of invariant 7 is absorbing.

Channel isolation and exact reassembly

`formal/Jotakey/CtapHid.lean` models the CTAPHID receive path. `receivePackets_ignores_other_channels` proves that any sequence of packets from other channels leaves the owning channel’s transaction exactly as it was. `receivePacket_preserves_well_formed` proves that buffers never exceed the announced length or the 1200-byte limit. `fragmented_message_is_reassembled` proves that a message fragmented the way a host must fragment it is delivered intact:

FORMAL/JOTAKEY/CTAPHID.LEAN

```
theorem fragmented_message_is_reassembled (channel command : Nat) (message : List Nat)
    (hMaxSize : message.length ≤ maxMessageSize) :
    receivePackets .idle (fragmentMessage channel command message) = .busy channel message
```

While writing this proof, Lean pointed out that a hypothesis we had added, `0 < message.length`, was never used. The theorem also holds for empty messages. Proof assistants often teach you something about your own design this way.

Credential binding, with the assumption on the table

FORMAL/JOTAKEY/CREDENTIAL.LEAN

```
theorem unwrap_accepts_only_wrapped_ids (key relyingParty credentialId nonce : List Nat)
    (h : unwrap mac key relyingParty credentialId = some nonce) :
    credentialId = wrap mac key relyingParty nonce ∧ nonce.length = nonceLength

theorem credential_bound_to_relying_party
    (hNoCrossSiteCollision : ∀ key party party' nonce,          -- the cryptographic
      party ≠ party' → mac key party nonce ≠ mac key party' nonce)  -- assumption
    (key relyingParty otherParty nonce : List Nat) (hNonceLength : nonce.length = nonceLength)
    (hDifferentParty : relyingParty ≠ otherParty) :
    unwrap mac key otherParty (wrap mac key relyingParty nonce) = none
```

`unwrap_accepts_only_wrapped_ids` needs no assumption at all: the construction accepts nothing but its own outputs. `credential_bound_to_relying_party` needs the MAC not to collide across relying parties, and

says so in its signature. That division is what a proof should give you: everything that can be established by logic is, and the rest is named.

9.7 CLOSING THE GAP BETWEEN MODEL AND CODE

The proofs are about Lean functions. The device runs Rust. How do we know they agree? There are three increasingly strong answers. Jotakey implements the first two today and plans the third.

1. Faithful transcription and review

Each model mirrors its Rust counterpart's structure (§9.4), and every Rust module states which Lean file models it. Changes to one require changes to the other (`AGENTS.md` §4). This is the weakest link: it relies on human care.

2. Differential testing against an executable specification

Lean definitions are executable. The very functions the CBOR theorems are about are compiled into a program, and a Rust test asks it and the Rust decoder the same 101 536 questions. Every answer must match. Any future change to the Rust decoder that departs from the proved model fails this test. Differential testing does not prove equivalence, but it ties the proofs to the code with a mechanical check rather than review alone. §9.8 shows how it works.

The fuzz targets play a similar role for the other models: their oracles are the theorem statements ("counter moves only on a confirmed signature", "reassembly never exceeds the announced length") checked on the real Rust code.

3. Translating the Rust itself: Aeneas (planned experiment)

Aeneas (Ho & Protzenko, Inria/Microsoft) translates Rust into pure Lean functions, using the **Charon** front end to extract the compiler's internal representation. Rust's ownership discipline is what makes this possible: a program without aliasing of mutable data can be expressed as a pure function that takes a value and returns the updated one. With Aeneas, we would no longer **write** `receivePacket` in Lean. We would **generate** it from `ctaphid.rs` and prove that the generated function refines the hand-written model (or prove the theorems directly about it). That removes link 1 entirely. Microsoft has used this route to verify parts of its Rust cryptography library (SymCrypt).

Aeneas supports a subset of Rust. `jotakey-core` is written to stay close to it: no trait objects, no interior mutability, simple loops with explicit bounds (`AGENTS.md` §4). A few closures remain in the CTAP layer (`find_in_list`, `write_success`). Rewriting them as plain loops is the first step of the experiment. The experiment is recorded in the roadmap. Other tools could close the same gap differently:

TOOL	APPROACH
Aeneas	Rust → pure Lean (or F*, Coq, HOL4); interactive proofs about the translation.
hax	Rust → F* or Rocq; used for the verified ML-KEM in the `libcrux` library.
Verus	Annotated Rust, verified by an SMT solver; good for low-level code with loop invariants.
Kani	Bounded model checking of Rust (CBMC); proves absence of panics and assertion failures for bounded inputs, with no annotations.
Creusot, Prusti	Deductive verification of annotated Rust (Why3 and Viper backends).

Kani is the cheapest next step. It could prove, for all inputs up to a bound, that `Decoder::skip` and `CtapHid::handle_packet` never panic, directly on the Rust code.

9.8 DIFFERENTIAL TESTING, STEP BY STEP

Differential testing gives the same input to two implementations of the same thing and compares their answers. It needs no expected outputs: each implementation is the other's oracle, and any disagreement means at least one of them is wrong. The technique is old (McKeeman named it in 1998), and it is how tools like Csmith found hundreds of bugs in GCC and LLVM by comparing compilers against each other.

Jotakey uses a stronger version. One side is the shipped Rust decoder. The other side is not a second hand-written decoder but **the Lean model itself**, the functions `decodeHead` and `validate` that §9.5 proves theorems about. A test failure therefore means one precise thing: the Rust code does something the proved model does not.

Step 1: the model becomes a program

Lean is a programming language as well as a prover, so the same definitions that appear in the theorems can be compiled. `formal/Main.lean` wraps them in a short program, `jotakey-spec`, that reads one question per line and answers it:


A CONVERSATION WITH JOTAKEY-SPEC

```
head 1817            →  err          0x18 says "1-byte argument", but 0x17 = 23 fits in the
                                      initial byte: non-minimal, rejected
head 1818            →  ok 0 24 2    major 0 (unsigned), value 24, 2 bytes consumed
head 190100          →  ok 0 256 3   2-byte argument 0x0100 = 256
validate a201000200  →  ok 5         map {1: 0, 2: 0}: keys in canonical order
validate a202000100  →  err          map {2: 0, 1: 0}: keys out of order
validate 5f          →  err          indefinite-length byte string: not canonical
```

`head` asks for one CBOR head: major type, argument, and how many bytes it used. `validate` asks whether the input starts with one complete, canonical data item, and how long it is. The program contains no decoding logic of its own. Hex parsing and printing are the only code between the question and the proved definitions.

Step 2: the same questions to Rust

`crates/jotakey-core/tests/differential.rs` asks `Decoder::head` and `Decoder::skip` the same questions and prints the answers in the same format. It starts `jotakey-spec` as a child process, writes every question to its input, reads every answer back, and compares the two strings exactly.



ONE ROUND OF THE DIFFERENTIAL TEST. ALL QUESTIONS ARE SENT IN ONE BATCH.

Agreement means more than “both accepted”. They must agree on the decoded values and on the **number of bytes consumed**. A decoder that accepted the right item but stopped one byte early would leave that byte to be misread as the next item. That is how parser differentials are exploited, so it is checked.

Step 3: questions worth asking

Purely random bytes are almost always rejected in the first byte or two, so they would test little more than the error path. The test builds four families of inputs:

FAMILY	INPUTS	WHAT IT EXERCISES
Generated values	20 000	Random nested arrays, maps, integers, byte and text strings, booleans and null, encoded by the Rust encoder. Half of the integers are boundary values: 0, 23, 24, 255, 256, 65 535, 65 536, $2^{32}-1$, 2^{32}, $2^{63}-1$, 2^{63}, $2^{64}-2$, $2^{64}-1$. These exercise the accepting paths deep inside maps and arrays.
Mutated values	20 000	Each generated value again, with up to two random edits: overwrite a byte, truncate, append, swap two neighbours, or insert a byte known to be dangerous (`5f` indefinite length, `ff` break, `f7` undefined, `c0` tag, `f9` half float, `1c` reserved, `18` one-byte head). These land just beside valid inputs, where bugs live.
Random bytes	10 000	0 to 11 random bytes.

FAMILY	INPUTS	WHAT IT EXERCISES
All heads	768	Every possible initial byte 0x00–0xFF, alone, followed by eight `00` bytes, and followed by eight `ff` bytes. Together these cover every head shape, every width and both extremes of every argument.

Each input is asked both ways, as `head` and as `validate`, which gives 101 536 questions. They take about a quarter of a second. The generator uses a fixed seed, so a failure is reproducible. The test also checks that more than a tenth of the answers are acceptances; at present 80 069 are. Otherwise a broken generator could produce only garbage, both sides would answer `err` to everything, and the test would pass while testing nothing.

Seeing it catch a bug

To check that the test has teeth, we broke the Rust decoder on purpose. In `Decoder::head`, a 2-byte argument must be at least 256, otherwise it should have used one byte. We changed `if v <= 0xFF` to `if v < 0xFF`, a one-character off-by-one that lets exactly one non-canonical encoding through. The differential test failed at once:

```
CARGO TEST -P JOTAKEY-CORE --TEST DIFFERENTIAL

assertion `left == right` failed: Rust and Lean disagree on `validate 3900ff4bc5d540`
  left: "ok 3"
 right: "err"
```

`39` is major type 1 (negative integer) with a 2-byte argument, `00 ff`. That is 255, which fits in one byte, so the encoding is not canonical. The broken Rust accepted it (`ok 3`); the model refused it (`err`). The input came from the "mutated values" family.

The same bug was also caught by a unit test, `rejects_non_minimal_heads`, which checks this exact boundary (`19 00 ff`) by hand. The random property test `accepted_heads_are_canonical` did **not** catch it: random bytes rarely land on a value of exactly 255 after a `39`. Each net has different holes.

What a passing differential test means

A pass means: on 101 536 inputs, chosen to sit on the boundaries, the shipped decoder gives exactly the answers of a function proved to have canonical uniqueness, termination and the round-trip property. It is the strongest link between the proofs and the Rust code that Jotakey has today. It does not mean:

- **Equivalence on all inputs.** The test samples. An input outside the four families could still differ. The Aeneas route of §9.7 would close this gap with a proof.
- **Coverage of the other models.** The CBOR decoder, the presence gate and the record log have executable specifications (`presence` and `append` queries; the record log's power cuts are a relation and are covered by fuzzing instead). The other state-machine models are linked to the Rust code by fuzz oracles that check the theorem statements (chapter 8), not by differential tests.
- **Protection against a shared misreading of the standard.** If the model and the Rust code both misunderstand RFC 8949 in the same way, they agree and the test passes. The theorems help here because they state the intended properties independently of either implementation. Reviewing the model against the standard remains a human job.

The Lean compiler and runtime that build `jotakey-spec` are also trusted, but they would have to fail in a way that exactly mimics a Rust bug for the test to wrongly pass.

Running it takes two commands. Without the spec binary the test reports that it skipped; setting `JOTAKEY_REQUIRE_SPEC=1` turns a missing binary into a failure, which is the right setting for continuous integration.

RUNNING THE DIFFERENTIAL TEST

```
cd formal && lake build jotakey-spec && cd ..
cargo test -p jotakey-core --test differential -- --nocapture
# differential: 101536 CBOR queries agree (80069 accepted)
# differential: 5000 presence sequences agree (3043 confirm)
# differential: 2000 record-log appends agree
# differential: 3000 shielded-session histories agree (4643 responses used)
# differential: 2000 counter sequences agree
```

9.9 WHAT REMAINS TRUSTED

A verified system is only as trustworthy as its **trusted computing base**, the parts that are assumed rather than proved. For Jotakey:

TRUSTED COMPONENT	WHY WE ACCEPT IT, AND MITIGATIONS
Lean kernel + 3 axioms	Small, widely used, independently re-checkable (external checkers exist).
The models' faithfulness	Mirrored structure, review, the differential test, fuzz oracles. Aeneas would remove most of this.
The specification itself	A proof that the code meets a wrong spec is worthless. Our specs are short, written in the vocabulary of the CTAP text, and reviewed against it.
rustc + LLVM	Not verified. Overflow checks stay on in release builds. On-device tests run the actual binary.
RustCrypto `p256`, `sha2`, `hmac`, `hkdf`	Audited, widely deployed; checked at boot against published test vectors.
Cryptographic hardness	ECDLP on P-256, SHA-256 collision resistance. Named explicitly (e.g. `credential_bound_to_relying_party`'s hypothesis).
The silicon	See chapter 7: fault injection is outside what any proof here can address.

9.10 WORKING WITH THE PROOFS

EVERYDAY COMMANDS

```
cd formal && lake build                    # check every proof (seconds)
lake env lean AxiomAudit.lean              # which axioms each theorem uses
lake exe jotakey-spec <<< "validate a10102" # run the executable specification
just lean                                  # build + reject sorry, axioms, native_decide
just diff                                  # Rust vs Lean differential test
```

To change a model, edit the Lean file, run `lake build` and read the first error. Lean shows the exact goal it could not prove, which is usually the precise case your change broke. To **add** a property, state it as a `theorem`. If you get stuck, write `sorry` to continue exploring. Lean itself only warns about `sorry`, but `just lean` **rejects** it, so an unfinished proof cannot pass the project's checks.

10 THE PROOFS

Chapter 9 explained what formal verification is and showed the headline results. This chapter is the companion for reading the proofs themselves. It goes through every theorem in `formal/`, in the order the files are best read, and for each one gives the statement, what it means, how the proof works, and which later theorem relies on it. The source files carry the same explanations in their doc comments (**Proves** and **How**), so the chapter and the code can be read side by side.

There are 85 theorems in eight files. Most are **lemmas**: stepping stones, proved because a bigger proof needs them. Following the dependencies from each lemma to the theorems that use it, we eventually reach theorems that nothing else uses. These are the **key theorems**: the conclusions the whole development exists to establish. There are twenty-four.

KEY THEOREM: WHAT IT SAYS	WHY IT MATTERS
`decodeHead_accepts_only_canonical` · invariant 4 Whatever the decoder accepts is exactly the canonical encoding of what it returned.	No value has two accepted encodings, so two parties can never read the same bytes differently. This removes a whole class of parser-confusion attacks.
`decodeHead_inverts_encodeHead` · invariant 4 Decoding an encoded head returns what was encoded and leaves the rest untouched.	The strictness above does not reject anything legitimate: every canonical head is accepted.
`decodeHead_consumes_input` · invariant 4 Every accepted head consumes at least one byte.	Reading cannot stall in place. This is the basis of the decoder's time bound.
`receivePackets_ignores_other_channels` · invariant 5 Packets on other channels never change a transaction in progress.	Malware talking to the key on its own channel cannot inject into, truncate or abort another program's request.
`receivePackets_preserves_well_formed` · invariant 4 After any packet sequence, buffers are within the announced length and 1200 bytes.	Memory use is bounded by a constant, whatever the host sends. Firmware without a heap needs exactly this.
`fragmented_message_is_reassembled` · functional A correctly fragmented message is delivered intact.	It rules out a model that is "safe" only because it accepts nothing (see below).
`one_touch_signs_at_most_once` · invariant 1 One touch completes at most one command.	Malware cannot queue a second signature behind a touch the user gave for something else.
`trace_signature_counters_increase` · invariant 2 In any sequence of events, signature counters strictly increase.	Relying parties use the counter to detect cloned keys. A repeated or decreasing counter would raise false alarms or hide a clone.
`epoch_change_requires_reset_in_window` · invariant 6 The reset epoch changes only if a reset request arrived in the first 10 s after power-up.	Software on the host cannot wipe every credential remotely. A reset needs the key to be replugged.
`faulted_stays_faulted_and_never_signs` · invariant 7 A faulted device stays faulted and never signs.	Fail closed: after a self-test failure, no signature is produced from possibly broken crypto.
`unwrap_recovers_nonce` · functional A credential ID unwraps, at its own site, to the nonce it was minted with.	Legitimate credentials keep working. This is the anti-vacuity partner of the next theorem.
`credential_bound_to_relying_party` · invariant 3 An ID minted for one relying party is rejected at any other, assuming the MAC does not collide.	Phishing resistance at the credential level: an ID is useless outside the site that created it.
`wrong_pins_between_successes_le_eight` · invariant 10 At most 8 wrong PINs are compared between correct entries, whatever happens in between.	A thief gets 8 guesses at the PIN, not 10 000. Power cycles and interrupted attempts do not add any.
`wrong_pins_in_a_row_le_three` · invariant 10 At most 3 wrong PINs in a row without a power cycle.	Guessing runs at the pace of a human unplugging the key.
`blocked_until_reset` · invariant 10 A blocked PIN accepts nothing until a reset.	The only way past a blocked PIN is a reset, which also ends every credential.
`comparison_needs_a_counted_retry` · invariant 10 A PIN is compared only after a retry was counted for it.	The rule that makes the counter mean something; the Rust side checks the same order.
`press_held_from_the_start_never_confirms` · invariant 1 A button or electrode pressed at every reading since the request never confirms.	A taped-down button, or a finger left on the key after an earlier request, cannot approve anything.
`timeout_at_deadline` · invariant 1 A reading at or past the 30 s deadline times out.	A request waiting for a touch cannot be kept open indefinitely, to catch a touch meant for something else.

KEY THEOREM: WHAT IT SAYS	WHY IT MATTERS
`timeout_is_final` · invariant 1 After one reading past the deadline, every later poll times out, whatever time it reports.	A clock that jumps back cannot reopen a request that already timed out.
`confirmed_strictly_increases` · invariant 2 Through any appends, power cuts and remounts, each confirmed counter value exceeds the previous one.	The persistence step under the counter: pulling the plug at any moment cannot make the key repeat a counter value.
`live_needs_check` · invariants 2, 7 The OPTIGA session is live only if, since the last handshake, a live-session check came back right.	A recorded session replayed on the bus never becomes live, so its old answers are never used.
`used_needs_live` · invariants 2, 7 A response from the OPTIGA is used only in a live session, and only if it authenticated and is in the sequence window.	Nothing a bus attacker forges or replays reaches the authenticator.
`used_strictly_increase` · invariants 2, 7 Within a session, the sequence numbers of the responses used strictly increase.	No response is used twice or out of order, so an old answer cannot stand in for a new one.
`released_strictly_increase` · invariant 2 The counter values the key releases strictly increase, whatever values are read back.	On the key, even an OPTIGA that misbehaved could not make it sign with a counter that went back.

The invariant numbers are those of `AGENTS.md`, §2. Two of the key theorems prove no security invariant: `fragmented_message_is_reassembled` and `unwrap_recovers_nonce`. They are there because safety properties are easy to satisfy by doing nothing. A device that dropped every packet would trivially satisfy channel isolation and bounded memory. A device that rejected every credential ID could never sign for the wrong site. **Functional** theorems like these two show the model also does its job, so the safety theorems are not true for an empty reason.

"Nothing else uses it" is a good way to find the conclusions, but it is not a definition of importance. Seven lemmas deserve the same attention, even though another theorem builds on them:

- `signature_requires_confirmed_touch` **is** invariant 1, the most important property of the device: no signature without a confirmed touch, for the parked relying party. It drops off the key list only because `one_touch_signs_at_most_once` is proved from it.
- `receivePacket_preserves_well_formed` is the statement for a single packet. It matches what each call of the Rust `handle_packet` must preserve, and `receivePackets_preserves_well_formed` extends it to any sequence of packets.
- `epoch_change_requires_confirmed_touch` is the other half of invariant 6: a reset needs a **touch**, as well as the time window.
- `unwrap_accepts_only_wrapped_ids` says that `unwrap` accepts nothing but `wrap`'s own outputs, with no assumption about the MAC at all. `credential_bound_to_relying_party` is a corollary.
- `confirmed_needs_release_then_debounced_press` is the main statement about the presence gate (a confirmation needs a release, then a debounced press, all before the deadline); `press_held_from_the_start_never_confirms` is its corollary.
- `trace_never_loses_confirmed` is the main statement about the record log (the latest record on flash is never below the last confirmed one); `confirmed_strictly_increases` is proved from it.
- `accept_needs_everything` is the shielded session's acceptance rule itself: a response is accepted only with the record header, a sequence number in the window and a tag that verifies, and outside the live-session check only in a live session.

All twenty-four key theorems and these seven are listed in `formal/AxiomAudit.lean`, which checks on every build that they rest only on Lean's three standard axioms (§9.3). The panels below show which theorem is proved from which; key theorems are at the left margin.

WHO USES WHOM: CBOR HEADS (EACH LINE IS PROVED USING THE LINES BELOW IT)

```
decodeHead_inverts_encodeHead
└ readArgument_reads_encoded
   ├ toBigEndian_length — toLittleEndian_length
   └ bigEndian_number_roundtrip — littleEndian_number_roundtrip
decodeHead_accepts_only_canonical
├ reencoded_prefix_restores_bytes
│  └ bigEndian_bytes_roundtrip — littleEndian_bytes_roundtrip
├ prefix_value_fits_width
│  └ fromBigEndian_fits_width — fromLittleEndian_fits_width
├ encodeHead_one_byte_form, _two_byte_form, _four_byte_form, _eight_byte_form
└ decodeHead_extended_facts — readArgument_accepted_facts
decodeHead_consumes_input
└ decodeHead_extended_facts
```

WHO USES WHOM: CTAPHID, AUTHENTICATOR, CREDENTIALS, PIN

```
receivePackets_ignores_other_channels — receivePacket_ignores_other_channels
receivePackets_preserves_well_formed
└ receivePacket_preserves_well_formed — deliverIfComplete_is_well_formed
fragmented_message_is_reassembled
├ continuations_complete_message (and itself, on a shorter remainder)
└ trimming_keeps_host_payload, continuationPackets_of_empty

one_touch_signs_at_most_once
├ signature_requires_confirmed_touch — processRequest_never_signs_with_presence
├ completePresence_signs_with_presence
└ completePresence_clears_pending
trace_signature_counters_increase
├ trace_signature_counters_bounded
│  └ runTrace_never_lowers_counter — handleEvent_never_lowers_counter
└ signature_carries_next_counter
epoch_change_requires_reset_in_window
└ epoch_change_requires_confirmed_touch, parked_reset_was_requested_in_window,
   completePresence_clears_pending
faulted_stays_faulted_and_never_signs   (direct)

unwrap_recovers_nonce                   (direct)
credential_bound_to_relying_party — unwrap_accepts_only_wrapped_ids

wrong_pins_between_successes_le_eight
└ runTrace_keeps_budget — handleEvent_keeps_budget — attempt_keeps_budget
wrong_pins_in_a_row_le_three
└ runTrace_keeps_streak — handleEvent_keeps_streak — attempt_keeps_streak
blocked_until_reset — blocked_step
comparison_needs_a_counted_retry        (direct)
```

WHO USES WHOM: PRESENCE GATE, RECORD LOG

```
press_held_from_the_start_never_confirms
└ confirmed_needs_release_then_debounced_press — gateAfter_accounts
timeout_at_deadline — gateAfter_accounts
timeout_is_final — gateAfter_accounts

confirmed_strictly_increases
├ trace_never_loses_confirmed
│  ├ mount_fits — scanEnd_le_length, erased_from_scanEnd
│  ├ append_ok — le_latestOf, maxSequence_le, le_maxSequence, maxSequence_mem
│  ├ append_preserves_latest — latest_located, le_latestOf, get_set_other
│  └ cut_lengths
└ append_ok
```

WHO USES WHOM: THE OPTIGA SESSION AND COUNTER

```
live_needs_check — accept_moves_forward — accept_needs_everything
used_needs_live — accept_needs_everything
used_strictly_increase
├ used_bounded — accept_moves_forward, accept_needs_everything
└ accept_moves_forward, accept_needs_everything
released_strictly_increase — released_le_mark
```

The reading order follows the files: numbers and bytes first (§10.2), then CBOR heads (§10.3) and the validator built on them (§10.4), CTAPHID (§10.5), the authenticator state machine (§10.6), credential IDs (§10.7), the

PIN lockout (§10.8), the presence gate (§10.9), the record log (§10.10) and the OPTIGA session (§10.11). §10.12 lists what the proofs leave out, and §10.13 maps every Rust name to its Lean counterpart. The Lean syntax is introduced in the same order in the comments of the source files, and `formal/Jotakey.lean` repeats the order.

10.1 BEFORE YOU START

The best way to read a Lean proof is in an editor. With the Lean 4 extension for VS Code, open the `formal/` folder, place the cursor on any line of a proof, and the **infoview** panel shows the hypotheses available at that point and the goal still to be proved. A proof that seems cryptic on paper becomes a sequence of small, visible steps. The tactics used are summarised in §9.3; `omega` (linear arithmetic) and `simp` (rewriting) do most of the routine work.

Four conventions run through all the files:

- **Names say what things are.** Functions are named after what they do (`receivePacket`, `completePresence`), theorems after what they state (`decodeHead_accepts_only_canonical`), and variables after what they hold (`width`, `relyingParty`, `nextSequence`). The one deliberate exception is `ih`, the conventional name for an induction hypothesis. The Rust code follows the same rule in its own conventions; §10.13 translates between the two.
- **Hypotheses are arguments.** `(hFits : value < 256 ^ width)` in a theorem's signature means "assuming the value fits in `width` bytes". Hypothesis names start with `h` and say what they assume. Calling the theorem requires a proof of each, so every assumption is visible where the theorem is used.
- **Bytes are natural numbers.** The models use `List Nat` for byte strings. Where a theorem needs real bytes, it says so with `(hBytes : ∀ byte ∈ bytes, byte < 256)`. In Rust the type `u8` guarantees this, so the hypothesis always holds for the real code.
- **Inversion lemmas.** Several lemmas start from "the function returned `some …`" and conclude what the input must have looked like. The proof follows the function's branches with `split at h`, throws away the branches that return `none`, and reads the facts off the branch that remains. `readArgument_accepted_facts`, `decodeHead_extended_facts`, `parked_reset_was_requested_in_window` and `unwrap_accepts_only_wrapped_ids` all work this way.

10.2 BYTES AND NUMBERS

File: `formal/Jotakey/Cbor/Heads.lean`, first half. CBOR stores multi-byte arguments big-endian. Before we can say anything about heads, we need four conversion functions and the facts relating them.

HEADS.LEAN: THE CONVERSION FUNCTIONS

```
def toLittleEndian : Nat → Nat → List Nat    -- the low `width` bytes of `value`
  | 0,         _     => []
  | width + 1, value => value % 256 :: toLittleEndian width (value / 256)

def fromLittleEndian : List Nat → Nat        -- little-endian bytes to a number
  | [] => 0
  | byte :: tail => byte + 256 * fromLittleEndian tail

def toBigEndian (width value : Nat) : List Nat := (toLittleEndian width value).reverse
def fromBigEndian (bytes : List Nat) : Nat := fromLittleEndian bytes.reverse
```

The big-endian functions are defined through the little-endian ones and `reverse`. That is a deliberate modelling choice. Little-endian functions peel one byte off the front of a list, which is exactly the shape of a list induction. Every big-endian fact then follows from its little-endian twin plus the library facts that `reverse` keeps length and membership and undoes itself. Eight theorems come in four pairs:

THEOREMS	STATEMENT
`toLittleEndian_length`, `toBigEndian_length`	The conversion always produces exactly `width` bytes.

THEOREMS	STATEMENT
`littleEndian_number_roundtrip`, `bigEndian_number_roundtrip`	If `value < 256 ^ width`, converting it to `width` bytes and back gives `value`: a number that fits survives the round trip.
`fromLittleEndian_fits_width`, `fromBigEndian_fits_width`	For a list of bytes, the number it holds is `< 256 ^ bytes.length`: `k` bytes always hold a number that fits in `k` bytes.
`littleEndian_bytes_roundtrip`, `bigEndian_bytes_roundtrip`	For a list of bytes, converting to a number and back to the same width gives the same list: bytes survive the round trip.

`toLittleEndian_length`. Induction on `width`, for every `value` (`generalizing value`, because the recursive call is at `value / 256`, not `value`). For `0` the list is empty. For `width + 1` the list is one byte followed by `toLittleEndian width (value / 256)`, whose length the induction hypothesis gives as `width`. **`toBigEndian_length`** is one `simp` call: `toBigEndian` reverses, reversing keeps length, done. Used by `readArgument_reads_encoded`.

`littleEndian_number_roundtrip`. Its hypothesis, that `value` fits in `width` bytes, is essential. For example, one byte of 1000 is `toLittleEndian 1 1000 = [232]`, which reads back as 232, not 1000: without the hypothesis the high bytes are cut off. The proof is induction on `width`:

HEADS.LEAN

```
theorem littleEndian_number_roundtrip (width value : Nat) (hFits : value < 256 ^ width) :
    fromLittleEndian (toLittleEndian width value) = value := by
  induction width generalizing value with
  | zero => simp [toLittleEndian, fromLittleEndian]; omega      -- value < 1, so value = 0
  | succ width ih =>
    have hQuotientFits : value / 256 < 256 ^ width := by       -- the rest fits in width bytes
      rw [Nat.pow_succ] at hFits
      exact (Nat.div_lt_iff_lt_mul (by decide)).mpr hFits
    simp only [toLittleEndian, fromLittleEndian, ih _ hQuotientFits]
    omega                                  -- value % 256 + 256 * (value / 256) = value
```

In the `succ` case the induction hypothesis can only be used for numbers that fit in `width` bytes, so the proof first shows that `value / 256` does (`hQuotientFits`). Unfolding one step of each function, and replacing the inner round trip by `value / 256`, leaves `value % 256 + 256 * (value / 256) = value`, which is division with remainder, and `omega` knows it. **`bigEndian_number_roundtrip`** reduces to it because the two `reverse`s cancel. Used by `readArgument_reads_encoded`.

`fromLittleEndian_fits_width`. Induction on the list. The empty list gives `0 < 1`. For `byte :: tail`, the induction hypothesis says the tail's number `T` is below `256 ^ tail.length`, which for natural numbers is `T + 1 ≤ 256 ^ tail.length`. Multiplying by 256, and using `byte < 256`: `byte + 256 · T < 256 · (T + 1) ≤ 256 · 256 ^ tail.length`. The proof writes these steps as `have`s and lets `omega` combine them. One detail shows how `omega` works: it treats `256 ^ tail.length` as an unknown, opaque number. `256 * x` and `x * 256` are then different terms to it, so the proof first rewrites one into the other with `Nat.mul_comm`. **`fromBigEndian_fits_width`** applies it to the reversed list. Used, through `prefix_value_fits_width`, in the canonical-uniqueness proof: an argument read from `k` bytes fits back into `k` bytes.

`littleEndian_bytes_roundtrip`. Induction on the list again. For `byte :: tail` the number is `byte + 256 · T`. Because `byte < 256`, its remainder modulo 256 is `byte` and its quotient is `T` (two `omega` facts, `hRemainder` and `hQuotient`). So `toLittleEndian` emits `byte`, then converts `T` back into `tail.length` bytes, which is `tail` by the induction hypothesis. **`bigEndian_bytes_roundtrip`** is its big-endian twin. Used, through `reencoded_prefix_restores_bytes`, in the canonical-uniqueness proof.

10.3 CBOR HEADS

File: `formal/Jotakey/Cbor/Heads.lean`, second half. A **head** starts every CBOR item: an initial byte `majorType · 32 + additionalInfo` and, for additional info 24 to 27, an argument of 1, 2, 4 or 8 big-endian bytes (§5.1). The model has three functions:

HEADS.LEAN: ENCODER AND DECODER

```
def encodeHead (majorType argument : Nat) : List Nat :=      -- always the shortest form
  if argument < 24 then [majorType * 32 + argument]
  else if argument < 2 ^ 8 then (majorType * 32 + 24) :: toBigEndian 1 argument
  else if argument < 2 ^ 16 then (majorType * 32 + 25) :: toBigEndian 2 argument
  else if argument < 2 ^ 32 then (majorType * 32 + 26) :: toBigEndian 4 argument
  else (majorType * 32 + 27) :: toBigEndian 8 argument

def readArgument (width minimum : Nat) (bytes : List Nat) : Option (Nat × List Nat) :=
  if bytes.length < width then none                              -- truncated
  else if fromBigEndian (bytes.take width) < minimum then none   -- not minimal
  else some (fromBigEndian (bytes.take width), bytes.drop width)

def decodeHead : List Nat → Option (Nat × Nat × List Nat)
  | [] => none
  | initialByte :: rest =>
    let majorType := initialByte / 32
    let additionalInfo := initialByte % 32
    if majorType = 7 ∧ 24 ≤ additionalInfo ∧ additionalInfo ≤ 27 then none   -- floats
    else if additionalInfo < 24 then some (majorType, additionalInfo, rest)
    else if additionalInfo = 24 then
      (readArgument 1 24 rest).map fun (value, after) => (majorType, value, after)
    -- … the same for 25, 26, 27 with widths 2, 4, 8 and minimums 2^8, 2^16, 2^32
    else none                                        -- reserved, indefinite
```

The `minimum` argument of `readArgument` is the minimality rule: a value read from the 2-byte form must be at least 2^8, because anything smaller has a shorter encoding. That single comparison is what the canonical-uniqueness theorem depends on.

The round trip

`readArgument_reads_encoded`. Suppose the value is at least `minimum` and fits in `width` bytes. Then reading its encoding followed by `rest` returns the value and leaves exactly `rest`. The encoding has length `width` (`toBigEndian_length`), so `take width` returns it and `drop width` returns `rest` (two `have`s using library lemmas about `take` / `drop` of an append). Its value is `value` (`bigEndian_number_roundtrip`). Both rejection tests then fail: the input is long enough, and `value ≥ minimum`.

`decodeHead_inverts_encodeHead` (key theorem). For `majorType < 7` and `argument < 2^64`:

HEADS.LEAN

```
theorem decodeHead_inverts_encodeHead (majorType argument : Nat) (rest : List Nat)
    (hDataType : majorType < 7) (hFits64 : argument < argumentLimit) :
    decodeHead (encodeHead majorType argument ++ rest) = some (majorType, argument, rest)
```

The proof has five cases, chosen with `by_cases` to match the five branches of `encodeHead`: `argument < 24`, `< 2^8`, `< 2^16`, `< 2^32`, and the rest. Each case has the same three steps:

1. The initial byte `majorType · 32 + info` splits back into `majorType` (division by 32) and `info` (remainder), proved by `omega` because `info < 32` (`hMajor`, `hInfo`).
2. For the extended forms, `readArgument_reads_encoded` reads the argument back. Its hypothesis `minimum ≤ argument` holds because the case excludes the smaller values. For example, in the 2-byte case we know `¬ argument < 2^8` (the negation of `hOneByte`).
3. A final `simp; omega` clears the remaining tests in `decodeHead`. The float test `majorType = 7 ∧ …` is false because of `hDataType`.

The hypothesis `hDataType` excludes major type 7 because the decoder rejects info 24 to 27 there (floats). Jotakey only uses major-type-7 simple values below 24 (`false`, `true`, `null`), which the decoder does accept, but the theorem does not cover them. `hBytes` is not needed here: `encodeHead` always produces bytes, since `toBigEndian` takes every byte modulo 256.

Canonical uniqueness

The converse direction, from accepted bytes to the encoder, needs more scaffolding. Its lemmas each answer one question the main proof will ask:

- **`readArgument_accepted_facts`**: if `readArgument` returned `some (value, after)`, then the input had at least `width` bytes, `minimum ≤ value`, `value` is the number in the first `width` bytes, and `after` is what follows them. An inversion lemma. `split at h` follows the two `if`s. In the rejecting branches `h` claims `none = some (value, after)`, which `simp` recognises as impossible. In the accepting branch `obtain ⟨rfl, rfl⟩` substitutes `value` and `after` by the expressions they equal, and what is left is already known.
- **`decodeHead_extended_facts`**: the same for the four extended branches of `decodeHead`. If one of them accepted, giving `(majorType, argument, rest)`, then `majorType = initialByte / 32` and the four facts above hold. The proof looks at what `readArgument` returned (`cases hRead : …`); `none` cannot map to `some`.
- **`prefix_value_fits_width`**: for a byte list with at least `width` elements, the number in its first `width` bytes is `< 256 ^ width`. This is `fromBigEndian_fits_width` applied to that prefix.
- **`reencoded_prefix_restores_bytes`**: for the same list, re-encoding the first `width` bytes and appending the rest gives the list back (`bigEndian_bytes_roundtrip`, then `take ++ drop` is the whole list).
- **`encodeHead_one_byte_form`, `_two_byte_form`, `_four_byte_form`, `_eight_byte_form`**: given the range of `argument`, which branch `encodeHead` takes. For example, if `2⁸ ≤ argument < 2¹⁶`, then the encoding is `(majorType · 32 + 25)` followed by `toBigEndian 2 argument`. Each proof unfolds `encodeHead`, splits every `if` (`repeat' split`), and closes each branch with `rfl` (the matching branch) or `omega` (the branch conditions contradict the range).

`decodeHead_accepts_only_canonical` (key theorem):

HEADS.LEAN

```
theorem decodeHead_accepts_only_canonical (bytes : List Nat) (majorType argument : Nat)
    (rest : List Nat) (hBytes : ∀ byte ∈ bytes, byte < 256)
    (h : decodeHead bytes = some (majorType, argument, rest)) :
    bytes = encodeHead majorType argument ++ rest
```

The proof follows `decodeHead`'s chain of `if`s with `split at h`, one branch at a time:

- **Rejected branches** (floats, info 28 to 31): `h` says `none = some …`. Impossible.
- **Immediate argument** (info < 24): `majorType` and `argument` are the quotient and remainder of the initial byte by 32, and `rest` is the tail. `encodeHead` takes its first branch because `argument < 24`, and quotient · 32 + remainder is the initial byte again.
- **Extended argument** (info 24 to 27, so `width` is 1, 2, 4 or 8): by `decodeHead_extended_facts`, the argument is the number in the next `width` bytes and is at least `minimum`; by `prefix_value_fits_width`, it is below `256 ^ width`. That is exactly the range where the matching `encodeHead_…_form` lemma applies, so the goal becomes: the input is the initial byte, then `toBigEndian width argument`, then the rest. By `reencoded_prefix_restores_bytes`, re-encoding the argument gives back the bytes it was read from. `congr 1` leaves only the initial bytes to compare, and `omega` checks them.

The proof does not say "the decoder is strict" anywhere. Strictness is **forced** by the statement. Take the non-minimal head `19 00 05`: 5 written in two bytes. A decoder without the minimality check would accept it as `(0, 5)`, but `encodeHead 0 5 = [05]`, so the theorem would be false and no proof would exist. In the info-25 case, the proof uses `hMinimal : 2⁸ ≤ argument` to apply `encodeHead_two_byte_form`, and that fact comes only from the minimality check. §9.8 shows the differential test catching exactly this bug in Rust.

The hypothesis `hBytes` is needed as well. Without it, `[0x18, 300]` (a "byte" of 300) decodes as `(0, 300)`, but `encodeHead 0 300` is the three bytes `[0x19, 1, 44]`. In Rust the type `u8` makes `hBytes` hold automatically.

`decodeHead_consumes_input` (key theorem) says an accepted head always leaves less input than it found: if `decodeHead` returns `rest`, then `rest.length < bytes.length`. The proof is the same case analysis, simpler: an immediate head leaves the tail after one byte, and an extended one leaves `tail.drop width`, no longer than the tail. The proof ends with `all_goals first | (simp at h; done) | (…)`: on every remaining branch, first try to show the branch is impossible, and if that does not close it, use `decodeHead_extended_facts`

and arithmetic. Every head consumes input, so a loop over heads always moves forward. In Rust this is the reason an array claiming 2^{64} elements runs out of input after at most as many iterations as there are bytes. The model does not yet state that work bound for the whole validator; this lemma is the step it would be built from.

10.4 THE STRICT VALIDATOR

File: `formal/Jotakey/Cbor/Cbor.lean`. This file defines the whole validator (`skipItem`, `skipArray`, `skipMap`, `validate`, with helpers such as `readMapKey`, `canonicalKeyLess` and `isValidUtf8`) on top of the heads, and contains **no theorems**. Two guarantees come from it anyway.

Termination. The three `skip` functions call each other (an array contains items, an item may be an array), so they are defined together in a `mutual` block. Lean accepts them only after checking that every recursive call decreases a measure. Here the measure is a pair `(fuel, count)`, compared lexicographically. Entering a container lowers `fuel`; moving to the next element of an array or map keeps `fuel` and lowers the count; and an item (count 0) is always below the array that contains it (count `count + 1`). The definition compiling is therefore a proof that `validate` terminates on every input.

An executable specification. `validate` and `decodeHead` are what `jotakey-spec` runs in the differential test (§9.8). Agreement on 101,536 queries ties the Rust decoder to the same definitions the head theorems are about. The nine `#guard` lines at the end of the file are build-time checks on hand-picked inputs: correct and misordered maps, duplicate keys, depth 4 and 5, a non-minimal head, an indefinite length, a float, and `true` followed by a trailing byte.

Which properties of the validator are **not** proved? Map-key order, rejection of duplicate keys, the depth limit, and UTF-8 validity are checked by the `#guard`s, the differential test, and the Rust tests and fuzzers. No theorem about them exists. They would be natural next theorems: for instance, "if `validate` accepts, the keys of every map are strictly increasing in canonical order".

10.5 CTAPHID REASSEMBLY

File: `formal/Jotakey/CtapHid.lean`. A `ReceiveState` is `idle`, `receiving` (owner channel, command, announced total, buffer so far, next expected sequence number) or `busy` (a complete message waiting for the authenticator). `receivePacket` handles one `ParsedPacket` (a packet already split into its fields), and `receivePackets` folds it over a list of packets.

Isolation

`receivePacket_ignores_other_channels`: if channel `owner` owns the transaction (`hOwner : state.owner = some owner`) and the packet is on another channel (`hOtherChannel`), then `receivePacket state packet = state`. The proof is a case analysis on the state. `idle` has no owner, so `hOwner` is false. In `receiving`, every branch of `receivePacket` first compares the packet's channel with the owner, and `hOtherChannel` says they differ, so `simp` picks the branch that returns the state unchanged. In `busy`, `receivePacket` ignores every packet, and `cases packet <;> rfl` checks both packet kinds.

`receivePackets_ignores_other_channels` (key theorem): if `owner` owns the transaction and every packet in the list is on another channel, then receiving them all leaves the state unchanged. Induction on the list: the first packet changes nothing (`receivePacket_ignores_other_channels`), so the rest runs from the same state. Any number of foreign packets, of any kind, in any order, are invisible to the owner. The model has no outputs or timers. The "channel busy" errors the Rust code sends back to the other channels are outside it.

Bounded memory

`WellFormed` is a predicate on receive states: in `receiving`, the buffer is shorter than the announced total and the total is at most 1200; in `busy`, the message is at most 1200 bytes.

- **`deliverIfComplete_is_well_formed`**: `deliverIfComplete`, which delivers a message once all its bytes are in, produces a well-formed state from a buffer no longer than its total. Either the buffer is still short (still receiving), or it is delivered and `buffer.length ≤ total ≤ 1200`.
- **`receivePacket_preserves_well_formed`**: one packet preserves `WellFormed`. Case analysis on state and packet. The two cases where data is stored need an argument. An init packet is refused if it announces

more than 1200 bytes; otherwise it stores at most `announcedLength` bytes of its payload. A continuation packet stores at most `total - buffer.length` more bytes. In both, `deliverIfComplete_is_well_formed` applies.

- **`receivePackets_preserves_well_formed`** (key theorem): any packet sequence preserves `WellFormed`. Induction, with `receivePacket_preserves_well_formed` at each packet.

Note what makes the proof work: the device cuts every payload to what it still expects, whatever the packet claims. A model that appended the full 59 bytes of every continuation packet would make `receivePacket_preserves_well_formed` false at the last packet of a message.

Exact reassembly

The host side is modelled too. `fragmentMessage channel command message` builds the packets a host must send: an init packet with the first 57 bytes, then `continuationPackets` with 59 bytes each and sequence numbers 0, 1, 2 and so on.

- **`trimming_keeps_host_payload`**: `(bytes.take n).take (min bytes.length n) = bytes.take n`. The device cuts each payload to the bytes it still expects; this lemma says that cut removes nothing from a packet the host built.
- **`continuationPackets_of_empty`**: no bytes left means no continuation packets.
- **`continuations_complete_message`**: the core lemma. If the device is receiving `message` and holds a prefix `buffer`, with `buffer ++ rest = message` and `buffer` shorter than `message`, then the host's continuation packets for `rest` take it to `busy channel message`.

`continuations_complete_message` is proved by **calling itself**. That is how Lean expresses an induction that is not over a plain list or number, here the length of `rest`. `termination_by rest.length` names the measure, and `decreasing_by` proves it drops: the recursive call uses `rest.drop 59`, shorter because `rest` is not empty (`hRestNonEmpty`). The body handles one packet. The device appends `rest.take 59` (`trimming_keeps_host_payload` shows the cut is harmless). If the buffer is still short, the remaining packets are exactly those for `rest.drop 59` with the next sequence number, and the recursive call finishes. Otherwise `rest` fitted in this one packet, the buffer is `buffer ++ rest = message`, and no packets remain.

`fragmented_message_is_reassembled` (key theorem) says that any message of at most 1200 bytes, fragmented the way a host must fragment it, arrives intact:

CTAPHID.LEAN

```
theorem fragmented_message_is_reassembled (channel command : Nat) (message : List Nat)
    (hMaxSize : message.length ≤ maxMessageSize) :
    receivePackets .idle (fragmentMessage channel command message) = .busy channel message
```

The init packet is accepted and stores `message.take 57`. If that is the whole message, it is delivered at once. Otherwise `continuations_complete_message` applies, with `buffer = message.take 57` and `rest = message.drop 57`. This includes the empty message: an early version of the theorem required `0 < message.length`, and Lean showed that hypothesis was never used (§9.6).

10.6 THE AUTHENTICATOR STATE MACHINE

File: `formal/Jotakey/Authenticator.lean`. Parsing and cryptography are abstracted away. A request arrives as a `Command` already classified by the parser, and a signature is the output `signature relyingParty counter`. Relying parties and credentials are plain numbers: the model only needs to tell them apart. `processRequest` handles a request and may park a command that needs a touch; `completePresence` handles the outcome of the wait for a touch; `handleEvent` dispatches one event to either, and `runTrace` runs any list of events. The `State` holds the `pending` command, the persisted `signCounter`, the `resetEpoch` and the `faulted` flag.

Most single-event proofs have the same shape: split into every combination of state and input (`cases … <;> …`), let `simp` compute what `processRequest` or `completePresence` returns, and see that the

claim holds in each case. There are dozens of cases, and Lean checks all of them. If a command is ever added to `Command`, `cases` includes it automatically, and the proof fails if the new command breaks the property.

User presence (invariant 1)

- **`processRequest_never_signs_with_presence`**: whatever the state, command and uptime, `processRequest` never outputs a signature carrying the UP flag. The proof tries faulted or not × every command, plus the uptime `if` for reset; every output is an error, `info`, `needsPresence`, or (for a silent assertion) a signature with the flag `false`.
- **`request_signs_only_silently`**: the only request that signs at all is a silent assertion on a healthy device, for its own relying party, and its signature has the UP flag clear. This is the model of the client pre-flight (§5.2).
- **`completePresence_signs_with_presence`**: every signature a completed touch produces carries the UP flag.
- **`completePresence_clears_pending`**: after `completePresence`, nothing is parked, whatever the outcome. Every branch sets `pending := .idle`.
- **`signature_requires_confirmed_touch`**: if an event outputs a signature carrying the UP flag for `relyingParty`, then the event was `presence .confirmed`, the device was not faulted, and the parked command was a makeCredential or getAssertion **for that same relying party**. A request cannot sign with the flag (`processRequest_never_signs_with_presence`). For a presence event, the proof tries every parked command × every result (18 cases, `simp_all` computes each). Only the two confirmed signing cases produce a signature, and there the relying party is the parked one.
- **`one_touch_signs_at_most_once`** (key theorem): `completePresence` applied twice never signs the second time, with or without the flag. Suppose it did; the signature would carry the flag (`completePresence_signs_with_presence`). `signature_requires_confirmed_touch` says a signing command was parked before the second completion, but `completePresence_clears_pending` says nothing was. `rcases` takes the two possibilities apart (makeCredential, or getAssertion with some credential), and in each `cases` sees that `.idle` cannot equal a different constructor.

The signature counter (invariant 2)

- **`handleEvent_never_lowers_counter`**: one event never lowers `signCounter`. Every branch keeps it or adds 1.
- **`signature_carries_next_counter`**: if an event signs with `counter`, then `counter = state.signCounter + 1` and the new state's `signCounter` is `counter`. In the Rust code this is the write-ahead rule: `N + 1` is persisted before the signature that carries it is released.
- **`runTrace_never_lowers_counter`**: over a whole trace, the final counter is at least the start. Induction, chaining single events with `Nat.le_trans`.
- **`trace_signature_counters_bounded`**: every signature `counter` in a trace satisfies `start < counter ≤ final`.
- **`trace_signature_counters_increase`** (key theorem): the signature counters of any trace are `Pairwise (· < ·)`, so each is smaller than every counter that comes after it.

AUTHENTICATOR.LEAN

```
theorem trace_signature_counters_increase (state : State) (events : List Event) :
    (signatureCounters (runTrace state events).2).Pairwise (· < ·)
```

`trace_signature_counters_bounded` exists only to make this proof go through, and it shows a technique worth knowing: **strengthening the induction hypothesis**. Try to prove `trace_signature_counters_increase` directly by induction on the events. The tail of the trace is pairwise increasing by the induction hypothesis. But if the first event signs with counter `first`, we must also show that `first` is below every **later** counter, and "pairwise increasing" says nothing about where the later counters lie. So we first prove the stronger `trace_signature_counters_bounded`, "every counter lies strictly above the start and at most at the end", and that is enough. The first signature's `first` is the counter right after the first event

(`signature_carries_next_counter`). Every later signature lies strictly above that counter, because the bounded lemma applies to the rest of the trace, which starts there. Proving something stronger to make an induction work is very common.

The trace is **any** list of events: requests of every kind, touches, timeouts, cancellations and resets, in any order. A reset changes the epoch but not the counter, so counters keep increasing across resets too, as relying parties require.

Reset (invariant 6) and faults (invariant 7)

- **`parked_reset_was_requested_in_window`**: if processing a request leaves a reset parked, the request was `reset` with `uptimeMs ≤ 10000`. Inversion over every command and the uptime `if`.
- **`epoch_change_requires_confirmed_touch`**: if an event changes the reset epoch, the event was a confirmed touch and a reset was parked. Requests never change the epoch. The proof shows that case by case, after `exfalso; apply hChanged` turns "find the contradiction" into "show the epochs are equal". For presence events, only reset/confirmed changes it.
- **`epoch_change_requires_reset_in_window`** (key theorem): start from a state with no reset parked (the hypothesis `hNoParkedReset`; power-up has none). If the epoch ever changes, the trace contains a reset request whose uptime was at most 10,000 ms. Induction on the events. If the first event changed the epoch, `epoch_change_requires_confirmed_touch` says a reset was parked at the start, which contradicts `hNoParkedReset`. Otherwise the change happens later, and to use the induction hypothesis we need "no reset parked" after the first event. A touch leaves nothing parked (`completePresence_clears_pending`). A request that parked a reset **is** the witness we are looking for (`parked_reset_was_requested_in_window` supplies the bound). Any other request leaves no reset parked, and the induction hypothesis finds the witness further on.
- **`faulted_stays_faulted_and_never_signs`** (key theorem): if `faulted` is set, then after any event it is still set and the output is not a signature. Both `processRequest` and `completePresence` take their first branch; `simp` sees it directly. Applying it at each event in turn shows that a faulted device never signs again in any trace. That induction is not written out as a separate theorem.

10.7 CREDENTIAL IDS

File: `formal/Jotakey/Credential.lean`. A credential ID is `[1] ++ nonce ++ mac key relyingParty nonce`. The MAC is a **parameter**, declared once with `variable (mac : …)`: every theorem holds for any function of that type, HMAC-SHA256 included, and states as a hypothesis whatever it needs from it.

- **`unwrap_recovers_nonce`** (key theorem): assume the MAC always returns 16 bytes (the hypothesis `hTagLength`) and the nonce has 32. Then unwrapping a freshly wrapped ID at the same relying party returns the nonce. Direct computation: the length is 1 + 32 + 16, the version byte matches, splitting after 32 bytes gives back the nonce and the tag, and the recomputed tag equals the stored one.
- **`unwrap_accepts_only_wrapped_ids`**: if `unwrap` accepts `credentialId` and returns `nonce`, then `credentialId = wrap mac key relyingParty nonce` and the nonce has 32 bytes. No assumption about the MAC. An inversion proof: the accepting branch says the version is right, the length is 49, and the recomputed MAC of `rest.take 32` equals `rest.drop 32`. Putting the pieces back together (`List.take_append_drop`) gives exactly `wrap`'s output. `unwrap` accepts nothing else: not a different version byte, not a longer ID with trailing bytes, not a near miss.
- **`credential_bound_to_relying_party`** (key theorem):

CREDENTIAL.LEAN

```
theorem credential_bound_to_relying_party
    (hNoCrossSiteCollision : ∀ key party party' nonce,
      party ≠ party' → mac key party nonce ≠ mac key party' nonce)
    (key relyingParty otherParty nonce : List Nat) (hNonceLength : nonce.length = nonceLength)
    (hDifferentParty : relyingParty ≠ otherParty) :
    unwrap mac key otherParty (wrap mac key relyingParty nonce) = none
```

The proof is by contradiction. Suppose `unwrap` at `otherParty` returned some `recovered` nonce. By `unwrap_accepts_only_wrapped_ids` the ID also equals `wrap` at `otherParty` for `recovered`: the nonce followed by its tag at `relyingParty` equals `recovered` followed by its tag at `otherParty`. Both nonces are 32 bytes, so `List.append_inj` splits the equation into `nonce = recovered` and equal tags for the two relying parties, which `hNoCrossSiteCollision` rules out because they differ.

> **THE ASSUMPTION IS AN IDEALISATION**
> Stated for **all** inputs, `hNoCrossSiteCollision` is false for any real 16-byte MAC. There are more relying parties than tags, so some pair must collide. What cryptography provides is that nobody can **find** such a collision, except with probability about 2^{-128} per attempt. Read the theorem as: a MAC collision is the only way a credential ID can be accepted at a site it was not minted for. The ID format, the parsing and the comparison add no other way. Proving the probabilistic statement itself would need a framework for cryptographic proofs, such as EasyCrypt or SSProve, and is outside the scope of this project.

10.8 PIN LOCKOUT

File: `formal/Jotakey/ClientPin.lean`. A PIN is only as strong as the limit on guessing it: a 4-digit PIN with unlimited tries falls in 10 000 attempts. The model keeps the persisted state (the PIN and the retry counter, starting at 8) and the RAM state (wrong PINs in this power cycle). An **attempt** counts itself first, storing `retries - 1`, and then compares. A correct PIN refills the counter and clears the mismatches; a wrong one adds a mismatch. At 0 retries the PIN is blocked; at 3 mismatches PIN entry stops until the next power cycle. The events are attempts, changes of PIN, setting it, power cycles, resets, and `interruptedAttempt`: power lost after the attempt was counted.

- **`comparison_needs_a_counted_retry`**: a PIN is compared, rightly or wrongly, only with a retry left and fewer than 3 mismatches, and a wrong one leaves the counter exactly one lower. Case analysis over `attempt`.
- **`wrong_pins_between_successes_le_eight`** (key theorem): along **any** trace from a state with at most 8 retries, at most 8 wrong PINs are compared between one correct entry (or setting the PIN, or a reset) and the next. The induction carries the budget `wrong + retries ≤ 8`: a wrong PIN adds one to `wrong` and removes one retry, and every event that clears `wrong` refills the counter. Since `retries` cannot go below 0, `wrong` stays at most 8. An interrupted attempt removes a retry without comparing anything, which only helps.
- **`wrong_pins_in_a_row_le_three`**: from power-up, at most 3 wrong PINs are compared in a row without a correct entry, a power cycle or a reset between them. Same shape, with the invariant `streak ≤ mismatches ≤ 3`.
- **`blocked_until_reset`** (key theorem): once the counter is 0 with a PIN set, no trace without a reset accepts a PIN. Every other event either refuses or, for `setPin`, sees a PIN already set, and none of them raises the counter.

What makes “counted before compared” matter is the power cut: if the device compared first and stored afterwards, unplugging it at the right moment would give an attacker a free guess. The model has no event in which a comparison happens without its cost, because `attempt` lowers the counter in the same step. On the Rust side the order is checked directly: the mock platform records the stored counter at the moment the PIN is first processed, and both a unit test and the `client_pin` fuzz target require it to be one lower already. A planted bug that compared first was caught by both.

10.9 WHEN A TOUCH COUNTS

`Presence.lean` models `PresenceGate` (`presence.rs`), the rule both firmwares feed their sensor readings to while a request waits for the user: the C6's BOOT button and the key's touch electrode. `Authenticator.lean` takes a confirmed touch as an input; this model says where one can come from. A gate starts when the request arrives (`start nowMs` sets the deadline 30 s later) and `poll gate nowMs pressed` handles one reading: past the deadline, or once expired, it times out; a release resets the press count and records that a release was seen; a press after a release counts, and the second in a row confirms.

The history of readings is a list, **newest first**, so the reading just taken is the head (`::`) and induction starts at the oldest one. `gateAfter startMs history` is the gate after that history.

- **`gateAfter_accounts`**: the gate after any history satisfies `Accounts`, five facts about how its state relates to the history behind it: the deadline is `startMs + 30000`; if not expired, every reading so far came before it; a reading at or past it expires the gate; if a release was seen, the history contains one; and, until it expires, the press count is at most the run of presses at the head of the history (`leadingPresses`). Induction on the history, splitting `poll` into its branches. That last field needs the "until it expires": an expired gate keeps its count while later readings change, which is harmless because it only ever answers `timeout`. The first version of the invariant missed this and `omega` produced the counterexample.
- **`confirmed_needs_release_then_debounced_press`**: if the poll of a new reading confirms, that reading is a press, the last two readings are presses, an older reading since the request is a release, and every reading came before the deadline. A confirmation comes from one branch of `poll`; `Accounts` of the older history turns its conditions into statements about the readings.
- **`press_held_from_the_start_never_confirms`** (key theorem): a sensor pressed at every reading never confirms. The previous theorem would need a release, and there is none.
- **`timeout_at_deadline`** and **`timeout_is_final`** (key theorems): a reading at or past the deadline times out, and so does every poll after it, whatever time it reports. The Rust gate keeps an `expired` flag for exactly this.

PRESENCE.LEAN

```
theorem confirmed_needs_release_then_debounced_press (startMs nowMs : Nat) (pressed : Bool)
    (older : List (Nat × Bool))
    (hConfirmed : (poll (gateAfter startMs older) nowMs pressed).2 = .confirmed) :
    pressed = true ∧
      debouncePolls ≤ leadingPresses ((nowMs, pressed) :: older) ∧
      (∃ reading ∈ older, reading.2 = false) ∧
      ∀ reading ∈ (nowMs, pressed) :: older, reading.1 < startMs + upTimeoutMs
```

The readings' times may come in any order: the theorems do not assume a monotonic clock. The differential test (§9.8) feeds both implementations sequences with jumps forward and back, and they agree step by step.

10.10 THE RECORD LOG UNDER POWER LOSS

`RecordLog.lean` models `RecordLog` (`storage.rs`), which persists the signature counter on the C6 (and in the key's `dev-key` builds), the reset epoch, the PIN record and the key's pairing secret. `Authenticator.lean` assumes a persisted counter; this model proves the log is one, whatever power cuts interrupt it.

The model works at the level of **slots**: a sector holds `capacity` slots, each `erased`, `torn` (anything that fails the CRC) or `record sequence`. The byte layout below that is the Rust tests' job: records sit at stride-aligned offsets and cover whole programming units, each programmed once, so a cut while writing one record damages its slot alone (`mock_flash_refuses_partial_and_repeated_programming`). `mount` computes the latest sequence number, the active sector and the next free slot exactly as Rust does, and `target` where the next append goes.

A power cut is **nondeterministic**. `AppendStep` is a relation, not a function: `ok`, or a `cut` that may leave each slot of the target sector as `CutSlot` allows. During an erase, every slot may end up as it was, erased or torn; during a write, the slot being written may end up erased, torn or holding the new record, and every other slot keeps its value. Each theorem holds for every outcome the relation allows.

- **`mount_fits`**: a freshly mounted log fits the flash it came from (`Fits`): its latest number is the flash's, the active sector holds it, everything from `next` on in the active sector is erased, and both sectors have `capacity` slots.
- **`append_preserves_latest`**: no outcome of an append, completed or cut, lowers the latest record on the flash. If the append erases, it erases the **other** sector, since a log with a record never erases its active one; if it writes, it writes past the latest record's slot. Either way that record survives.
- **`append_ok`**: a confirmed append returns `latest + 1`, which becomes the latest record, and the log as Rust updates it still fits.

- **`trace_never_loses_confirmed`**: a `Run` is any sequence of appends, cuts and remounts from an erased flash, where a failed append is followed by a remount (the documented contract of `RecordLog::append`, which every platform keeps). Along any run, the log fits the flash and the latest record is at least the last confirmed number. Induction on the run.
- **`confirmed_strictly_increases`** (key theorem): every confirmed number exceeds the one confirmed before it.

RECORDLOG.LEAN

```
theorem confirmed_strictly_increases (capacity : Nat) (hCapacity : 0 < capacity)
    {events flash log confirmed flash' sequence}
    (hRun : Run capacity events flash log confirmed)
    (hStep : AppendStep capacity log flash flash' (some sequence)) : confirmed < sequence
```

The differential test checks `mount` and a completed append against the Rust code on generated flash contents (realistic runs, torn records, and the debris a cut erase leaves), at both programming units. The cut outcomes are checked by the `record_log` fuzz target and the power-cut property tests instead, because a relation has no single answer to compare.

10.11 THE OPTIGA SESSION

`Shielded.lean` models how the jotakey key decides what to believe from its secure element (`optiga/shielded.rs`, `optiga/device.rs`; §6.3 explains the protocol). The cryptography is not modelled: a response either carries a tag that verifies under the session keys (`authentic`) or does not. What is modelled is the **rule**, and the rule is where a replay or a reordering would slip through.

`accept` is `Session::accept`: refuse a response for any use but the live-session check while the session is not live; refuse anything but the record header; refuse a sequence number outside `(last, last + 3]`; refuse a tag that does not verify; and only then move `last`. `step` is how the driver uses it, event by event: a handshake opens a session that is not live; the live-session check's answer makes it live only if accepted **and** equal to the MCU's own value; any refusal or other failure drops the session. Histories are lists of events, newest first.

- **`accept_needs_everything`** and **`accept_moves_forward`**: an accepted response met every condition, and accepting moves the window strictly forward, by at most three.
- **`live_needs_check`** (key theorem): if the session after a history is live, then since the last handshake a live-session check came back right. Induction on the history: a handshake makes a session that is not live, only a correct check sets `fresh`, and everything else keeps the flag (`accept_moves_forward`) or drops the session.
- **`used_needs_live`** (key theorem): a response is used only in a live session, authentic, in the window, and the number reported is its own.
- **`used_strictly_increase`** (key theorem): the sequence numbers used since the last handshake strictly increase. Its invariant `used_bounded` says they all lie at or below the window's position while the session exists, and nothing more is used once it is dropped.
- **`released_strictly_increase`** (key theorem): `release` is the counter rule of `Optiga::increment_counter`; whatever values are read back, the values released strictly increase.

SHIELDED.LEAN

```
theorem live_needs_check :
    ∀ (history : List Event) (s : Session), stateAfter history = some s → s.fresh = true →
      checkSinceHandshake history
theorem used_strictly_increase : ∀ history : List Event, (used history).Pairwise (· > ·)
theorem released_strictly_increase : ∀ values : List Nat, (released values).Pairwise (· > ·)
```

What these theorems give is conditional on the cryptography, as always: an old recording fails the check because it cannot contain a PRF value for a nonce chosen after it was made, and a forged response fails because its tag does not verify. The differential test drives the real `Session`, with real CCM tags (some

damaged), through generated event histories and compares every state with `step`; the `optiga_bus` fuzz target puts an attacker between the driver and a simulated OPTIGA and checks the same properties end to end.

10.12 WHAT THE PROOFS LEAVE OUT

Each model makes choices about what to leave out (§9.4), and those choices are as important as the theorems. In one place:

MODEL	NOT COVERED BY A THEOREM
CBOR	The validator's map-key order, duplicate-key rejection, depth limit and UTF-8 checks. They are checked by `#guard`s, the differential test and the Rust tests and fuzzers, not proved. Major type 7 is outside the head round trip.
CTAPHID	`INIT`, `CANCEL`, timeouts and the response path. A combined theorem — owner packets interleaved with foreign ones give the same result as the owner packets alone — would follow from the existing lemmas but is not stated.
Authenticator	The parser's classification of requests into `Command`, the clock that provides `uptimeMs`, flash write failures, and keepalives. Fault absorption is proved per event, not over traces.
Credentials	The cryptography: the MAC is a parameter, and `hNoCrossSiteCollision` idealises collision resistance. Key derivation (HKDF, P-256 scalars) is not modelled.
PIN lockout	The PIN protocol's cryptography (key agreement, encryption, MACs) and the tokens: which requests count as attempts is taken from the code, not derived. Storage write failures are not modelled (in Rust they stop the attempt before the comparison). The reset here is unconditional; its window and touch are proved in the authenticator model.
Presence gate	Cancellation, which the firmware checks before each poll, and the sensor: whether one reading is a press (the key's `TouchDetector` thresholds) is outside the model. Rust saturates the deadline at `u64::MAX` and the press count at 255; the model has no such limits.
Record log	Payloads (checked by the fuzz target), and the byte layout under the slots (checked by the Rust tests). A transient flash error with the power still on is modelled only through the remount contract. Sequence numbers past `u32::MAX` (Rust refuses to append).
OPTIGA session	The cryptography (CCM, the PRF; a tag is a flag), the OPTIGA itself (that it picks `RND` at random, and that its counter only goes up, which holds once the unit is locked), the I2C data link and APDU parsers (total by construction and fuzzed, not proved), and that each response answers the request just sent (true because the driver sends one request at a time and drops the session on any failure). Sequence numbers are naturals; Rust's stay below `SEQ_LIMIT`.
Link to Rust	The CBOR, presence, record-log and OPTIGA-session models are tied to the code by differential testing (§9.8). The others are tied by careful transcription, review, and the tests and fuzz oracles of chapter 8 that check the same properties on the real code (§9.7). The planned Aeneas experiment would replace transcription with translation.

None of these gaps is hidden: each is either a hypothesis in a theorem's signature or a part of the system that no theorem mentions. That is the standard to keep as the models grow. When a new feature is added, its invariant goes into the model first, the proof goes into `AxiomAudit.lean`, and anything the proof assumes stays visible in the signature.

10.13 RUST AND LEAN NAMES

Each side follows its own language's conventions. Rust writes functions in `snake_case` and constants in `SCREAMING_SNAKE_CASE`; Lean writes definitions in `lowerCamelCase` and names theorems in `snake_case` after what they state. Constants that quote the CTAP specification (`BROADCAST_CID`, `cmd::CBOR`) keep the spec's spelling in Rust. Everything else uses descriptive words on both sides, so most names differ only in casing.

The tables below list every modelled item (Rust paths are under `crates/jotakey-core/src`, Lean paths under `formal/Jotakey`); `formal/NAMES.md` holds the same table next to the code, and `AGENTS.md` requires both to change together with any rename.

RUST	LEAN	NOTES
CBOR		
`Decoder::head`, `Encoder::head`	`decodeHead`, `encodeHead`	Rust advances a cursor; Lean returns the rest of the input.
`Decoder::read_be` + minimality check	`readArgument`	
`Decoder::skip(depth)`	`skipItem`, `skipArray`, `skipMap`	One function with loops; three mutually recursive ones.
`skip(0)` + `position()`	`validate`	Answers `validate <hex>` in `jotakey-spec`.
`read_slice`, `next_key`, `canonical_lt`	`takeExactly`, `readMapKey`, `canonicalKeyLess`	
`core::str::from_utf8`, `MAX_DEPTH`	`isValidUtf8`, `maxNestingDepth`	
CTAPHID		
`ReceiveState` (`Idle`, `Receiving`, `Busy`)	`ReceiveState` (`idle`, `receiving`, `busy`)	Same names.
`Receiving { channel, command, total, received, next_sequence, last_packet_ms }`	`receiving channel command total buffer nextSequence`	Rust counts the bytes received; Lean holds them. Lean has no clock.
`Busy { channel }`	`busy channel message`	Rust keeps the message in `receive_buffer`.
`CtapHid::handle_packet`, `maybe_dispatch`	`receivePacket`, `deliverIfComplete`	Lean leaves out INIT, CANCEL and timeouts.
`Packet` (raw `[u8; 64]`)	`ParsedPacket` (`init`, `continuation`)	Different on purpose: the model starts after parsing.
`MAX_MSG_SIZE`, `INIT_DATA`, `CONT_DATA`	`maxMessageSize`, `initPayloadSize`, `continuationPayloadSize`	
—	`receivePackets`, `WellFormed`, `fragmentMessage`, `continuationPackets`	Model only: packet sequences, the invariant, the host side.
Authenticator		
`Authenticator::process`, `complete`	`processRequest`, `completePresence`	Rust parses CBOR; Lean receives a classified `Command`.
`PresenceResult`	`PresenceResult`	Same name.
`Pending`	`PendingCommand`	Same variants. Their `user_verified` (UV) is not modelled here.
`PendingOrSilent::Silent`	`Command.silentAssertion`	getAssertion with `up: false`: signed in `process`, never parked.
`sign(…, user_present, …)`	`Output.signature … userPresent`	The UP flag; `true` only from `complete` under `Confirmed`.
`Outcome` + response bytes	`Output`	
`Platform::increment_counter`, `rotate_epoch`, `uptime_ms`	`State.signCounter`, `State.resetEpoch`, `uptimeMs`	Rust keeps them behind the platform trait.
`RESET_WINDOW_MS`	`resetWindowMs`	
—	`Command`, `Event`, `handleEvent`, `runTrace`, `signatureCounters`	Model only.

RUST	LEAN	NOTES
Credential IDs		
`wrap`, `unwrap` (`tagger`, `rp_id_hash`, `id`)	`wrap`, `unwrap` (`mac key`, `relyingParty`, `credentialId`)	Lean takes the MAC as a parameter `mac`; Rust's `Tagger` plays `mac key`. Rust's `unwrap` can also fail when the hardware does, which the model leaves out.
`VERSION`, `NONCE_LEN`, `TAG_LEN`	`formatVersion`, `nonceLength`, `tagLength`	
return type `[u8; TAG_LEN]`	hypothesis `MacOutputsTagLength mac`	The Rust type guarantees what Lean must assume.
PIN lockout		
`PinRecord`, `PinSession::mismatches`	`State` (`pin`, `retries`, `mismatches`)	The verifier becomes the PIN; no cryptography.
`check_pin`, `change_pin`, `set_pin`	`attempt`, `Event.changePin`, `Event.setPin`	`attempt` counts, then compares.
`PIN_RETRIES_MAX`, `MISMATCHES_PER_POWER_CYCLE`	`maxRetries`, `mismatchesPerPowerCycle`	
power lost after `store_pin`	`Event.interruptedAttempt`	
PIN statuses after a comparison	`Output.wrongPin`	Whatever the status code.
Presence gate		
`PresenceGate::new`, `poll`	`start`, `poll`	Same names.
`PresenceGate { deadline_ms, expired, released_seen, pressed_polls }`	`Gate { deadlineMs, expired, releasedSeen, pressedPolls }`	
`GateStep` (`Waiting`, `Confirmed`, `Timeout`)	`Step` (`waiting`, `confirmed`, `timeout`)	
`UP_TIMEOUT_MS`, `DEBOUNCE_POLLS`	`upTimeoutMs`, `debouncePolls`	
—	`gateAfter`, `leadingPresses`, `Accounts`	Model only: histories, newest first.
Record log		
`RecordLog::mount`, `append`	`mount`, `AppendStep` (`ok`, `cut`)	Lean's append is a relation: a cut has many outcomes.
`RecordLog { active, next, latest }`	`Log { active, next, latest }`	`latest` is a number, `0` for `None`; payloads are left out.
`scan_end`	`scanEnd`	
the sector switch in `append`	`target`	
the two sectors of a log (`Flash` trait, `MockFlash`)	`Flash { zero, one }` of `Slots`	Slots are record-sized; `program_unit` sets the stride.
—	`Fits`, `CutSlot`, `Run`, `latestOf`, `maxSequence`	Model only.
OPTIGA session		
`Session::accept`	`accept`	The tag check is the flag `Response.authentic`.
`Session { last_sseq, fresh }`	`Session { lastSseq, fresh }`	The keys are left out.
`Purpose`, `in_window`	`Purpose`, `inWindow`	
`SEQ_WINDOW`, `SEQ_LIMIT`, `SCTR_RECORD`	`seqWindow`, `seqLimit`, `recordSctr`	
`Optiga::establish`, `command` (drop on failure)	`step` over `Event`	`handshake`, `check`, `use`, `fail`.
`release_counter`	`release`	

RUST	LEAN	NOTES
—	stateAfter, used, checkSinceHandshake, Bounded, released	Model only: histories, newest first.

The properties line up the same way: the Rust tests and fuzz oracles check on the real code what the Lean theorems prove about the model.

RUST TEST OR FUZZ ORACLE	LEAN THEOREM
head_roundtrip	decodeHead_inverts_encodeHead
accepted_heads_are_canonical, cbor_decode oracle	decodeHead_accepts_only_canonical
other_channel_gets_busy…, ctaphid_stack	receivePackets_ignores_other_channels
ctaphid_stack buffer assertions	receivePackets_preserves_well_formed
no_signature_without_presence, ctap_dispatch oracle	signature_requires_confirmed_touch, one_touch_signs_at_most_once
monotonic_across_power_cuts	trace_signature_counters_increase
reset_window_and_effect	epoch_change_requires_confirmed_touch, epoch_change_requires_reset_in_window
fails_closed	faulted_stays_faulted_and_never_signs
roundtrip, bound_to_rp (credential.rs)	unwrap_recovers_nonce, credential_bound_to_relying_party
wrong_pins_are_counted_and_block, client_pin model	wrong_pins_between_successes_le_eight, wrong_pins_in_a_row_le_three, blocked_until_reset
an_attempt_is_stored_before_the_pin_is_compared, retries_at_pin_check oracle	comparison_needs_a_counted_retry
confirmation_needs_release_then_debounced_press, a_press_held_from_the_start_never_confirms	confirmed_needs_release_then_debounced_press, press_held_from_the_start_never_confirms
deadline_is_thirty_seconds_after_the_request	timeout_at_deadline, timeout_is_final
monotonic_across_power_cuts_any_unit, record_log fuzz oracle	trace_never_loses_confirmed, confirmed_strictly_increases
accepted_sequence_numbers_increase, replays_forgeries_and_alerts_are_refused	accept_needs_everything, accept_moves_forward, used_strictly_increase
a_replayed_session_is_not_live, nothing_is_used_before_the_session_is_live, optiga_bus oracles	live_needs_check, used_needs_live
counter_release_rule, a_counter_that_goes_back_is_refused, optiga_bus counter oracle	released_strictly_increase

11 ROADMAP

The MVP is deliberately small: every line of it is tested, fuzzed, mutation-tested, and, for the security-critical state machines, proved. The next steps, in order, each follow the same discipline: model, prove, implement, test, fuzz, mutate.

11.1 FULL CTAP 2.1 PASSKEYS

Discoverable credentials ("username-less passkeys") need the authenticator to **store** something per credential, and need a PIN, because a discoverable credential with only presence would let anyone holding the key list your accounts. The steps:

1. **Resident-key store.** A fixed-capacity table in the `jotakey` partition (for example 64 entries). Each entry holds `rpIdHash`, the user handle (≤ 64 bytes), user name and display name (truncated), a creation counter, and the credential nonce. The private key is still derived, not stored. Entries live in a record log

like the counter's, so writes stay power-safe. Lean: model the store as a finite map, and prove capacity bounds and that deletion really deletes.

2. **makeCredential with `rk: true`.** Store the entry **before** returning the response. Replace an existing entry for the same (`rpIdHash`, user handle). Return `CTAP2_ERR_KEY_STORE_FULL` when full. Advertise `options.rk = true`.
3. **getAssertion without allow list.** Find all entries for the RP, newest first. Return the first with `numberOfCredentials`, then serve `authenticatorGetNextAssertion` (0x08) from a short-lived iterator that a new command or a 30 s timeout invalidates. Include `user` in the response (only `id` unless UV was performed).
4. **clientPIN, protocol 2.** Done (§6.5). getPINRetries, getKeyAgreement, setPIN, changePIN, getPINToken and getPinUvAuthTokenUsingPinWithPermissions with the `mc` and `ga` permissions; tokens in makeCredential and getAssertion set the UV flag. The lockout rules are invariant 10, proved in Lean (§10.8) and checked by a model-based fuzz target. What remains:
   - **On the key, enforce the PIN in the OPTIGA.** Today the microcontroller compares the PIN and keeps the counter, so an attacker who runs code on it can skip both. The OPTIGA's monotonic counters and access conditions may let the secure element refuse to derive a credential's seed unless the PIN was presented, which would make the PIN protect against a laboratory thief too. Whether the Trust M V1 can do this is open.
   - **`FIDO_2_1`.** Advertising it needs the rest of CTAP 2.1: `authenticatorSelection`, credential management for resident keys, and the getInfo members that go with them.
   - **Built-in verification** (a fingerprint sensor) would add `uv`, getUVRetries and getPinUvAuthTokenUsingUvWithPermissions; the PIN stays as the fallback CTAP requires.
5. **credentialManagement (0x0A).** Enumerate RPs and credentials, delete credentials, update user info. Requires a `pinUvAuthToken` with the `cm` permission.
6. **Extensions.** `credProtect` (levels 1–3: hide credentials from assertion without UV), `hmac-secret` (symmetric secrets for disk encryption and password managers, derived per credential with a salt from the platform), and later `largeBlob`.
7. **U2F / CTAP1 compatibility.** `U2F_REGISTER` and `U2F_AUTHENTICATE` over `CTAPHID_MSG`, for older relying parties. Clear the `NMSG` capability bit.
8. **Versions and conformance.** Advertise `FIDO_2_1` and pass the FIDO Alliance conformance tools for the implemented feature set.

11.2 HARDWARE

The jotakey (§7.5) delivered the two largest hardware steps of the original plan: a secure element holding the root, generated on the device, and native USB without a bridge. What follows:

- **Bring-up of the jotakey key.** Its firmware is written (§6.3): USB HID, the touch sensor, the LED, the OPTIGA driver with its shielded connection and live-session check, and the provisioning builds, all tested against a simulated OPTIGA. Next is running it on a board: the wire-level details only real chips can confirm, the touch thresholds, the torn-write path, and an on-device test firmware for the key.
- **Signed firmware updates (exploration).** Production keys are locked and never updated (§7.5). An alternative worth studying is a small, immutable bootloader that installs only firmware signed with an offline key. It would let fixes reach deployed keys, at the price of a bootloader that is itself security-critical code to design, test and prove.
- **OPTIGA Trust M V3**, once it is in stock: the same package and pinout, with HMAC, HKDF and AES. `F` would become HMAC-SHA256 on both platforms.
- **Signing inside the secure element**, which would stop a thief who breaks the microcontroller from using the key at all. It needs a secure element that can sign with derived keys, or a fixed-size store of per-credential keys.
- **Persistent BLE bonds** on the C6, in the encrypted partition, so phones and laptops do not have to repair after a power cycle.

11.3 ASSURANCE

- **Aeneas experiment** (§9.7): translate `ctaphid.rs` and `cbor.rs` to Lean with Charon/Aeneas, and prove that the generated functions refine the hand-written models. The core is already written in the supported Rust subset.
- **Kani harnesses**: prove absence of panics in the decoders and state machines for all inputs up to a bound, directly on the Rust code.
- **Lean models for the record log** (power-loss safety as a theorem over interleavings of writes and cuts) and for the BLE framer.
- **Reproducible firmware builds** and published hashes, so a user can check that the binary they flash is the one that was reviewed.
- **Side-channel evaluation** of the signing path with a ChipWhisperer-class setup, to put numbers on chapter 7.

01 INVARIANT TRACEABILITY

Every invariant of `AGENTS.md` §2, with where it is enforced, tested and proved.

#	ENFORCED IN	TESTED / FUZZED	PROVED (FORMAL/JOTAKEY/…)
1	`ctap/mod.rs` `complete` (only UP=1 signing path); silent `up:false` assertions signed with UP clear; `presence.rs` `PresenceGate` (fresh debounced press), fed by the BOOT button (C6) or the touch electrode (key)	`no_signature_without_presence`, `processing_parks_and_complete_consumes`, `silent_assertion_signs_at_once_without_the_up_flag`; `ctap_dispatch` oracle; `presence.rs` proptests, presence differential test	`Authenticator.signature_requires_confirmed_touch`, `request_signs_only_silently`, `one_touch_signs_at_most_once`; `Presence.press_held_from_the_start_never_confirms`, `confirmed_needs_release_then_debounced_press`
2	`increment_counter` before signing; `storage.rs` append + read-back (C6; key `dev-key` builds); OPTIGA up-counter `0xE120`, read back through a live session and released only above the last (`optiga/device.rs`, key)	`register_then_authenticate…`, `monotonic_across_power_cuts_any_unit`, `record_log` fuzz target, record-log differential test, on-device torn write; `a_counter_that_goes_back_is_refused`, `optiga_bus` fuzz target, counter differential test	`Authenticator.trace_signature_counters_increase`; `RecordLog.confirmed_strictly_increases`, `trace_never_loses_confirmed`; `Shielded.released_strictly_increase`, `used_strictly_increase`
3	`credential.rs` tag over rpIdHash, `ct_eq`	`bound_to_rp`, `any_bit_flip_is_rejected`, `credential_is_bound_to_rp`; `credential_unwrap`	`Credential.unwrap_accepts_only_wrapped_ids`, `credential_bound_to_relying_party`
4	`cbor.rs` strict decoder; `MAX_MSG_SIZE` everywhere; no-panic lints	`decoder_never_panics`, size boundaries; all fuzz targets; differential test	`Cbor.decodeHead_accepts_only_canonical`, `decodeHead_consumes_input`; `CtapHid.receivePackets_preserves_well_formed`
5	`ctaphid.rs` single transaction, owner checks	`other_channel_gets_busy…`, `hid_init_resync_only_touches…`; `ctaphid_stack`	`CtapHid.receivePackets_ignores_other_channels`, `fragmented_message_is_reassembled`
6	`ctap/reset.rs` window + touch; epoch rotation	`reset_window_and_effect`, `reset_window_boundary_is_inclusive`	`Authenticator.epoch_change_requires_confirmed_touch`, `epoch_change_requires_reset_in_window`
7	`main.rs` boot sequence; `Authenticator::fault`; `RngHealth` on every byte; key: live OPTIGA session or no root (`optiga/shielded.`	`fails_closed`, `every_injected_fault_is_detected`, on-device KATs and TRNG; `a_replayed_session_is_`	`Authenticator.faulted_stays_faulted_and_never_signs`; `Shielded.live_needs_check`, `used_needs_live`

#	ENFORCED IN	TESTED / FUZZED	PROVED (FORMAL/ JOTAKEY/…)
	`rs` `Session::accept`, live-session check)	`not_live`, `optiga_bus` fuzz target, session differential test	
8	`Zeroizing` secrets; HMAC peripheral (C6) or OPTIGA (key); no `Debug` of secrets	Review; `cargo deny`	—
9	`subtle::ConstantTimeEq`; RustCrypto `p256` and bitsliced `aes`; branch-free PIN policy scan	Review	—
10	`ctap/client_pin.rs` `check_pin` (store `retries − 1`, then compare), `usable_pin`, `PinSession::mismatches`; PIN log (C6)	`wrong_pins_are_counted_and_block`, `an_attempt_is_stored_before_the_pin_is_compared`, `a_failed_restore_after_a_correct_pin_issues_no_token`; `client_pin` model and `retries_at_pin_check` oracle	`ClientPin.wrong_pins_between_successes_le_eight`, `wrong_pins_in_a_row_le_three`, `blocked_until_reset`, `comparison_needs_a_counted_retry`

02 REPOSITORY MAP

PATH	CONTENTS
`AGENTS.md`	Normative requirements and security rules for anyone (human or AI) changing the code.
`crates/jotakey-core`	Protocol core; `tests/` (CTAP, transports, differential).
`crates/jotakey-fw`	Firmware; `partitions.csv`; `deny.toml` with documented exceptions.
`crates/jotakey-testfw`	On-device tests (`cargo test` with the board attached).
`crates/jotakey-bridge`	Linux serial ⇄ uhid bridge.
`crates/jotakey-host-tests`	Independent client, simulator, RP checks, hardware tests.
`crates/jotakey-explorer`	`just explore`: terminal browser for attached FIDO keys (read-only).
`fuzz/`	Eight cargo-fuzz targets; `seeds/` written by `make_seeds.py`.
`formal/`	Lean 4: `Cbor`, `CtapHid`, `Authenticator`, `Credential`; `Main.lean` (executable spec); `AxiomAudit.lean`.
`scripts/`	`provision.sh` (irreversible, human-only), udev rules, `fido2_check.py`, `fido2_pin_check.py`.
`docs/`	This report (`typst compile docs/jotakey.typ`).

03 GETTING STARTED

FROM CLONE TO A WORKING KEY (DEVELOPMENT BUILD)

```
rustup target add riscv32imac-unknown-none-elf
cargo install espflash probe-rs-tools cargo-fuzz cargo-mutants cargo-deny just
curl -sSf https://raw.githubusercontent.com/leanprover/elan/master/elan-init.sh | sh

just test && just lean && just diff          # host tests, proofs, Rust-vs-Lean
cd crates/jotakey-fw
cargo run --release --features dev-key       # INSECURE dev key; logs on the UART port
cd ../.. && just bridge /dev/ttyACM0         # needs /dev/uhid access (scripts/99-jotakey.rules)
python3 scripts/fido2_check.py               # or register at https://webauthn.io
```

04 GLOSSARY

TERM	MEANING
AAGUID	Authenticator Attestation GUID: 16 bytes identifying the authenticator model.
Assertion	The signed response of an authentication ceremony.
authData	authenticatorData: rpIdHash, flags, counter, optional credential data.
CBOR	Concise Binary Object Representation (RFC 8949).
COSE_Key	CBOR encoding of a public key (RFC 9052/9053).
CTAP	Client-to-Authenticator Protocol (FIDO Alliance).
CTAPHID	CTAP over USB HID: 64-byte reports, channels.
Discoverable credential	Resident key: stored on the authenticator with the user handle; a “passkey”.
KAT	Known-answer test: compute on fixed input, compare with a published result.
Relying party (RP)	The website or service that registers and verifies credentials.
RP ID	The domain a credential is scoped to.
UP / UV	User presence (a touch) / user verification (PIN or biometric).
WebAuthn	W3C Web Authentication API, the browser side of FIDO2.

05 REFERENCES

- FIDO Alliance. **Client to Authenticator Protocol (CTAP)**, versions 2.0 (2019), 2.1 (2021), 2.2.
- W3C. **Web Authentication: An API for accessing Public Key Credentials**, Levels 2 and 3.
- C. Bormann, P. Hoffman. **RFC 8949: Concise Binary Object Representation**, 2020.
- T. Pornin. **RFC 6979: Deterministic Usage of DSA and ECDSA**, 2013.
- H. Krawczyk, P. Eronen. **RFC 5869: HKDF**, 2010.
- NIST. **SP 800-90B: Recommendation for the Entropy Sources Used for Random Bit Generation**, 2018.
- Espressif. **ESP32-C6 Technical Reference Manual**; **Security Advisory AR2023-007** (2024).
- W. M. McKeeman. **Differential Testing for Software**, Digital Technical Journal 10(1), 1998.
- X. Yang, Y. Chen, E. Eide, J. Regehr. **Finding and Understanding Bugs in C Compilers (Csmith)**, PLDI 2011.
- G. Klein et al. **seL4: Formal Verification of an OS Kernel**, SOSP 2009.
- X. Leroy. **Formal verification of a realistic compiler**, CACM 2009.
- J.-K. Zinzindohoué et al. **HACL*: A Verified Modern Cryptographic Library**, CCS 2017.
- A. Erbsen et al. **Simple High-Level Code for Cryptographic Arithmetic (Fiat-Crypto)**, S&P 2019.
- S. Ho, J. Protzenko. **Aeneas: Rust Verification by Functional Translation**, ICFP 2022.
- L. de Moura, S. Ullrich. **The Lean 4 Theorem Prover and Programming Language**, CADE 2021.
- E. W. Dijkstra. **Notes on Structured Programming**, 1970.