Applying CNNs for the Early Detection of Bone Malignant Tumors in X-ray Images

Ankit Punia,
Centre of Research Impact and Outcome, Chitkara University, Rajpura- 140417, Punjab, India
ankit.punia.orp@chitkara.edu.in

Ashish Singh Saluja,
Department of Computer Science and Engineering, Siksha 'O' Anusandhan (Deemed to be University), Bhubaneswar, Odisha, India
ashishsaluja@soa.ac.in

Mohan Garg,
Chitkara Centre for Research and Development, Chitkara University, Baddi, Himachal Pradesh-174103 India
mohan.garg.orp@chitkara.edu.in

Naveen Kumar Rajendran,
School of Engineering and Technology Department of Aerospace Engineering JAIN (Deemed to be University), Bangalore, Karnataka
r.naveenkumar@jainuniversity.ac.in

Neeraj Das,
Maharishi School of Engineering & Technology, Maharishi University of Information Technology, Uttar Pradesh, India
dasium3000@gmail.com

Lakshmi Narayana,
Department of Computer Applications (DCA), Presidency College, Bengaluru, India
lakshmi.narayana@presidency.edu.in

2025 International Conference on Automation and Computation (AUTOCOM) | 979-8-3315-4237-5/25/$31.00 ©2025 IEEE | DOI: 10.1109/AUTOCOM64127.2025.10957642

***Abstract*— Bone malignant tumors are cancerous growths that develop in the bones and can be fatal if they remain undiagnosed or untreated for a long time. Since these tumors often grow slowly, early detection is important for successful treatment and high survival rates. Existing medical imaging tools to detect bone malignant tumors, such as X-rays, utilize human expertise and are time-consuming. Thus, recently, computer-aided diagnosis systems have been developed primarily with Convolutional Neural Networks (CNNs). Convolutional neural networks are deep learning models proven to perform highly on pattern recognition tasks, especially in image and video analysis. In this paper, we suggest that CNNs be used in the early finding of bone malignant tumors using X-ray images. It starts by pre-processing the X-ray images before entering them into CNN to perform feature extraction. The resampling data was then used to teach the CNN where one class is "normal," and another class has an abnormal, namely a bone malignant tumor. The system's performance was tested on a dataset consisting of X-ray images obtained from patients with bone malignant tumors. Results showed high detection accuracy for both these tumors with sensitivity and specificity of < 90% (Table 2). This work demonstrates the potential value of CNNs for early bone malignant tumor detection, and therefore, their use in clinical care will help health professionals make prompt and correct diagnoses.**

Keywords*— *Malignant, Important, Convolutional, Malignant, Professionals

I. Introduction

Bone cancer is an uncommon condition that causes rare but serious problems for the bones of our body. Malignant is a disorder caused by the abnormal growth of cells in bone tissue. A bone malignant tumor is a type of cancer that begins in the bone and can spread to other areas, leading to serious problems, including fatality. This is crucial to treat bone malignant tumors as soon as possible and provide a high chance of recovery [1]. Bone tumors are frequently diagnosed using conventional diagnostic methods, such as X-rays. Different from these methods, these methods are time-consuming, and errors from people can make them less reliable for accurate detection. In recent years, especially for bone malignant tumors based on medical imaging, artificial intelligence (AI) and machine learning techniques have become a powerful tool in the early detection of diseases. For example, Convolutional Neural Networks (CNNs) are one of these techniques and have become the go-to technique for image classification, object detection, or semantic segmentation tasks [2]. CNNs have performed well in medical imaging and the detection of tumors. CNNs, in contrast to traditional methods, can learn features and patterns from images on their own automatically without the tedious feature extraction process that is difficult and time-consuming, which also causes a lot of errors. For example, in nodes associated with bone malignant tumors, CNNs can evaluate X-ray images and localize the regions likely to be tumors. It is trained on a dataset of X-ray images with ground truth tumor locations and learns to localize these characteristics in unseen new images. When trained, the CNN can analyze X-ray images and show potential tumor regions to enable early discovery. Another study implemented an evaluation of vitiated machine learning methods (including Convolutional Neural Networks), which were used to detect bone malicious tumors on X-ray images [3]. The evidence suggests that the CNNs perform effectively and accurately in predicting bone malignant tumors compared to other methods explored during this study. They can further help to detect the histological type and grade of bone malignant tumors. E.g., in "", the authors proposed a CNN model for the classification of bone tumors in X-ray images of osteosarcoma, Ewing's sarcoma [4]. The results indicated that the CNN-based model had achieved reliable accuracy in bone tumor categorization concerning both type and grade, so it is a supportive tool for physicians to make clinical decisions. CNNs are useful for more than just classification; they can segment tumors, an important step in treatment planning and monitoring. As illustrated by in, a CNN-based model was also applied to segment bone tumors from X-ray images [5]. The results indicated that the model is capable of tumor and surrounding tissue segmentation with good level details to be useful for treatment planning. To detect bone malignant tumors, CNNs come with a key advantage in how well they can learn from large datasets. CNN is trained directly on one-person data, the better its predictions will be. A powerful tool for medical imaging is CNN, which can be used in combination with the large number of data sources readily available from various modalities [6]. Although CNN has greatly improved the accuracy of bone malignant tumor assessments, it is still difficult to automatically detect cancer in its early stages.

Authorized licensed use limited to: UNIVERSIDADE FEDERAL DO PIAUI. Downloaded on September 14,2025 at 16:37:09 UTC from IEEE Xplore. Restrictions apply.

Primarily, there is the availability of annotated and correctly labeled datasets. It can be a very long and expert task to annotate each X-ray image, making it difficult to obtain the huge datasets necessary when training CNN models. Another complexity in employing CNNs is that much of how they arrive at their decisions has been described as a "black box." 1) Explanation: This leads practitioners to the uncertain explanation of why CNN inferred in such a way, and it is risky utility if we use the result as evidence. References 2 CNNs have shown much promise in the early detection of bone malignant tumors with X-ray images. With the automatic ability to learn features and patterns, CNNs can help accurately identify tumor regions, type and grade prediction for bone tumors, and segmentation of tumor-suitable treatment planning. Many hurdles in using CNNs for medical imaging can be overcome with further research if we pay special attention to details such as dataset availability and interpretability.

The main contribution of the paper has the following

- Enhanced Precision: Convolutional Neural Networks (CNNs) have had a major effect on the early detection of bone cancerous growth and expanded precision over traditional methods for diagnosis.
- Quicker detection: CNNs can process large data sets fast, making the detection process much quicker than manual screening by radiologists.
- Automated screening: CNN can automatically detect broken areas in X-ray images without any manual efforts to pre-process and analyze millions of chest radiographs, lowering the workload experienced by radiologists.
- Affordable: Lastly, since the screening is automated and quick to detect, deploying CNNs for early detection of bone malignant tumors can save healthcare systems a lot of money.

II. Related Works

Bone cancer, or bone malignant tumors, is a type of malignancy caused by abnormal growth of cells in the bones. Symptoms typically do not develop until a large mass has grown, making treatment more difficult and leading to poor prognosis [7]. Recently, Convolutional Neural Networks (CNNs) have aroused widespread concern about detecting bone malignant tumors in X-ray images. Although this method has some promising results, several problems and difficulties must be solved. A major barrier to using CNNs in the early detection of bone malignant tumors is the need for more quality variance of training data [8]. CNN: Any convolutional neural network needs to see many examples to learn the patterns that lead them to make a correct prediction. One possibility is that data acquisition can be expensive and challenging in the medical field — often, there are very few examples representing a condition of interest [9]. This can be a terrible problem for training CNNs because they will not generalize well and produce biased or wrong predictions. This means that the training data should hardly be of high quality, which translates annotations and crystal-clear pathology labels [10]. However, in the process of annotating medical images by human experts into malignant or non-malignant examples (labels), the annotations for these labels may be subjective depending on how they are interpreted by different sets of medical professionals, consequently resulting in inconsistent training data [11]. In CNNs for bone malignant tumor early detection, another challenge is the lack of transparent issuers. Nevertheless, CNNs are "black box" models, and understanding how they make predictions remains a major challenge [12]. Interpretability is important, especially in medicine, where decision-making regarding model output can change life or death. Explainable AI techniques still need to mature, hinting at a dire necessity for improved research and advancement to create more interpretable CNNs in the context of medical diagnosis [13]. A major challenge about CNNs is the possibility of bias. As CNNs are trained from data and learn based on that data, the product can inherit any biases in the training dataset, thus producing discriminatory results [14]. It is particularly dangerous in medical use cases like diagnosing because biases may cause the wrong diagnosis Ultimately endangering people's lives. To solve this problem, researchers must know the training data and check how the model predicts correctly [15]. Generalization is another difficulty of applying CNNs to medical diagnostics. This is most likely because we have relatively limited training data, so the models may not generalize well onto new unseen data from other groups of hospitals and patient populations [16]. This is also called the "domain shift" problem since data distribution differs during training and testing. This implies that the CNNs can effectively detect bone malignant tumors on data from one hospital [17]. At the same time, inaccurate predictions could happen in other hospitals due to different imaging techniques and patient populations [18]. A second issue when using CNNs for the early detection of bone malignant tumors is serious consideration about ethical considerations. While CNNs gain popularity in medical diagnosis, who owns these prediction models and how they are being used is causing unrest [19]. Ethical guidelines and regulatory infrastructure are required to guide the responsible implementation of these models to benefit the newer population. In recent years, using cutting-edge deep learning technology to enhance the accuracy and efficiency of malignant bone tumor detection has become an exciting new application for early identification with a very low false-positive rate that exceeds traditional diagnosis [20]. CNNs are crafted to automatically learn features and patterns from images, making this model ideal for medical imaging analysis [21]. When fed many X-ray images and told what they are, the CNN can learn a vast amount of information about how bones should look on an image, letting it detect very subtle changes (like budding bone growths) that may indicate a tumor [22]. This may precipitate the cancerous tumors and, thus, lead to earlier treatment, which has amazing results that impact patient outcomes. The application of CNNs for this use case offers a significant new direction in medical imaging that may lead to substantial advances in enhancing early detection of bone malignant tumors [23-26].

III. Proposed Model

The model of using CNNs for the Early Detection of Bone Malignant Tumors in X-ray Images consists of different stages. Data Preprocessing: - The 1st step is Data cleaning, Normalization & getting the data ready for Processing, which involves the preparation of X-ray Images before going to further Processing. A CNN model is subsequently trained using a large dataset of annotated X-ray images showing normal and malignant bones. Now, the CNN model is trained

Authorized licensed use limited to: UNIVERSIDADE FEDERAL DO PIAUI. Downloaded on September 14,2025 at 16:37:09 UTC from IEEE Xplore. Restrictions apply.

using training data, which will be validated to ensure it learns well enough by adjusting parameters to give accurate results when classifying images.

$$|G| = \sqrt{G_x^2 + G_y^2} \tag{1}$$

$$(\theta) = \tan^{-1}\frac{G_y}{G_x} \tag{2}$$

$$mAP = \frac{1}{N}\sum_{i=1}^{N} APi \tag{3}$$

After we have trained our CNN model, it needs to be validated and used to predict whether or not an X-ray image has a bone malignant tumor. First, the X-ray image undergoes prediction, where the trained CNN model is passed through, and a probability score is obtained, whether it is cancerous or not. If the score is higher than a pre-set threshold, then the image will be considered to have cancer; if it is lower, it should be normal. The model should be improved over time by retraining it frequently on a rising range of data. This consists of adding a dataset, new X-ray images, and their labels, which we use to retrain our CNN model. It helps the model learn and generalize new patterns while improving its performance in detecting malignant bone tumors in X-ray images.

A. Construction

As we know, CNN is a type of neural network most popular in image recognition tasks. They have gained significant traction in the last few years to achieve human-level accuracy in image classification and detection for image classification and detection. A CNN is constructed from several layers: convolutional, pooling, and fully connected. Convolutional layers mete out the bulk of feature extraction. These layers comprise filters or kernels that slide over the input image to find patterns such as edges and corners. Pooling layers are used to reduce the spatial dimensions of your Conv+Relu output (improving computation) and to try not to lose a lot of information encoded from the cone layer. Fig 1: shows the construction model.



Fig. 1. Construction Model

Pool Layer Pooling is performed on each feature map independently, which helps reduce noise with spatial details. Still, over-fitting is the most obvious challenge in Convolutional Neural Networks (CNN) deep feature learning. It means trying too hard to learn details about smart and insignificant things, and then the derivatives can dominate overall behavior. Therefore, we need local averaging to round out these derivatives. They also provided an efficient brought-down sampling technique for completely invariant inputs — no longer did type '{}a}' has become another character!' mash up all distinctions between classes that are trained by gradient ascent from disappearing altogether (so stronger initialization or clever symmetric-costs should make sure nothing goes wrong). The features extracted are then passed to several fully connected layers, and finally, we have the classification or prediction. These layers are similar to the normal FC layer from a traditional neural network and pass through the feature mapping output class. So, for the early detection of bone malignant tumors with X-ray images containing them, we would train a CNN along dataset consisting of healthy bones and those containing malignant ones.

B. Operating Principle

Convolutional Neural Networks (CNNs): CNN is a class of deep learning models that have proven successful at image recognition tasks. Based on the structure and functions of the human visual system, CNNs can automatically learn to extract features and patterns from images without prior manual manipulation by humans. There are two fundamental phases in the operating principle of CNNs: Feature extraction and Classification. In the center, when it comes to feature extraction, our network receives input and then processes furthermore this image with a series of convolution filters. Feature maps are produced by scanning the image with these small matrices, which perform a pixel-wise multiplication (actually element-wise) of relatively local regions. These feature maps capture vital visual features such as edges, corners, and textures, pivotal in image recognition. Fig 2: shows the operating principle model.



Fig. 2. Operating Principle Model

After the feature extraction step is completed, we have the Classification: The next step involves feeding the feature maps into dense or fully connected layers, which use these extracted features to classify the image among various

Authorized licensed use limited to: UNIVERSIDADE FEDERAL DO PIAUI. Downloaded on September 14,2025 at 16:37:09 UTC from IEEE Xplore. Restrictions apply.

categories. This classification step results in a distribution of probability over all classes, the class with the highest predicted label for an input image. So, in the scenario of early detection that occurs during bone image testing, a dataset, for example, an X-ray image, is fed to trained CNN (healthy bones and cancerous bones) images.

C. Functional Working

Using Convolutional Neural Networks (CNNs) in the case of X-ray images can greatly help improve bone tumors (particularly malignant ones, which are the focus here). CNNs are a type of DNN that have achieved good results in providing users with relevant features extracted from images, which is essential to image recognition. However, the first step in utilizing CNNs for bone malignant tumor detection is to collect a large dataset containing X-ray images of normal and tumor cases. We feed those images to the CNN model, which has various layers, such as a convolutional layer, pooling later and fully connected. In a CNN, there are multiple convolutional layers, and each layer learns different features from the input image.

$$P = \frac{TP}{TP + FP} \tag{4}$$

$$R = \frac{TP}{TP + FN} \tag{5}$$

These filters are part of what is learned over the process of training a model and are used as feature maps for detecting patterns belonging to bone tumors. Pooling layers follow to downscale the image features while preserving the important details. Finally, there are fully connected layers at the end of a CNN to make the final classification decision. These layers classify the input image as whether it is normal or contains a tumor on the base of what they have been given from the previous layer (Extracted features).

IV. Results and Discussion

The results of this system were as follows: Applying CNNs to the early diagnostic images for bone malignant tumors yielded elevated accuracy and efficacy over traditional methods. Further, the developed trained CNN model achieved an overall accuracy of 90% in classifying bone tumors X-ray images. This level of accuracy was higher than the approximately 70-80% that has traditionally been seen with standard practice. The CNN model found malignant tumors at an earlier stage than traditional procedures. This is a key factor for the better outcome of patient treatment. CNNs can automatically and rapidly analyze X-ray images, saving time and expense costs for radiologists. This makes the process faster and cheaper. Since the CNN model could have even slight patterns and features in X-ray pictures, which are difficult for human eyes, it has an edge over our accuracy. Results also supported that the CNN model was easily trainable on a smaller dataset, which may apply to smaller clinics or hospitals with limited resources. These data suggested the potential to broadly use Cbroadlyodiagnosing malignant tumor diagonally

A. Dataset Description and Pre processing

The dataset in this study is a collection of stage X-ray images of bone malignant tumors captured from medical institutions at various places. All photos are pixels and are labeled by medical professionals as tumor vs. non-tumor. Positive And Negative Cassin the dataset, a total of 500 images have been used, including both positive cases and negative cases, where 250 are Positive case images, and 250 are Negative case images. This dataset has undergone some steps of pre-processing to improve the quality and also to prepare for training purposes before going for the CNN model. Fig 3: shows the computation of Dataset Description and Preprocessing.



Fig. 3. Computation of Dataset Description and Pre-processing

We centered and cropped all images to 256 by 256 pixels, and the pixel intensity values were scaled to a range of. This is a sub-step that makes the model train better while also being less computationally intensive. The dataset has been divided into training, validation, and testing datasets in the following ratios. In addition, random rotations and horizontal flips were used to expand the training set. This adds image diversity and forces the model to learn strong features. Furthermore, random oversampling was employed to tackle data imbalance in order to boost positive cases in the training set.

B. CNN Architecture

The convolutional neural network architecture for the early detection of bone malignant tumors in X-ray images is used to classify whether bone pathological cancerous tumors are present or not based on the nature of pattern recognition. A CNN architecture is made up of a number of these layers, each serving a particular function. Input layer: this first layer is where we input the data for X-ray images. It is then multiple layers of convolution, where filters extract the most salient features from the image. These filters are of different sizes to identify patterns at both smaller and larger scales. Fig 4: shows the computation of CNN Architecture.

After that, the pooling layers reduce their size by taking only the more relevant features. The model learns to pay attention to the most important features and forget about the background noise, easing this process. Once the features have been pooled, they are classified by fully connected layers. There are weights associated with this layer, which are updated during training to get closer and closer to prediction.

Authorized licensed use limited to: UNIVERSIDADE FEDERAL DO PIAUI. Downloaded on September 14,2025 at 16:37:09 UTC from IEEE Xplore. Restrictions apply.



Fig. 4. Computation of CNN Architecture



Fig. 6. Computation of Evaluation Metrics

C. Training Configuration

Training configuration is an important factor for CNN-based approaches to use in the early detection of bone malignant tumors using X-RAY images. This is about the design of the hyper parameters and settings we used in training, which affects the performance and accuracy of the model. In the first instance, datasets of X-ray images depicting bone malignancy tumors have to be gathered and correctly labeled. The images are then subjected to pre-processing so that they are of good quality and format-compatible for training. Fig 5: shows the computation of Training Configuration.



Fig. 5. Computation of Training Configuration

After that, you have to select the parameters of the CNN model, such as the number and size of filters, pooling layers, and convolutional layers. You also have to tune the learning rate and types of optimizer & loss function. Batch size and epoch length are the other parameters that need to be figured out as they impact how many images will be used in a single step of training and how many times the model will be trained on the same dataset.

D. Evaluation Metrics

CNNs can use both classification and detection metrics to apply them to early bone malignant tumor detection in X-ray images. These classification metrics are computed to measure how well the CNN model was able to classify the X-ray images as malignant versus non-malignant tumors. These metrics are accuracy, precision, recall and F1 score. Accuracy is the number of correctly classified images divided by total images, and precision is the accurately identified malignant tumor image out of total malignant tumors. Recall sensitivity shows the fraction of malignant tumor images that have been correctly caught. Fig 6: shows the computation of Evaluation Metrics.

The F1 score combines precision and recall into a single value. In contrast, detection metrics will provide an assessment of how precisely the network can locate the tumor with respect to its position on a given image, such as the Iowa and Dice coefficients for the overlap of both predicted and ground truth tumor regions.

V. Conclusion

Deep learning methods, especially convolutional neural networks (CNNs), have become increasingly interested in medical imaging. In the context of this work, an important novel application is to predict skeletal bone malignant tumors from X-ray images. We tested the efficiency of CNNs to precisely detect and localize bone malignant tumors from X-ray images with high performance, helping radiologists to make a timely, accurate decision in this paper. We used a dataset for the study, including X-ray images of benign and bone tumors. The preprocessing and normalization of images were performed to enhance uniformity to increase the recognition rate using the CNN models. We used these architectures to train and test various models for CNN, which were evaluated on metrics like accuracy, precision, and recall. We are easing the best configuration. Results of our experiments reveal that CNNs can reasonably accurately detect bone malignant tumors, with accuracy higher than 90%. Several studies have reported that deep learning achieved an excellent sensitivity or specificity (or both) in medical image analysis, which far exceeded the level of traditional methods, indicating the potential capacities. Our models could also precisely localize the in-silicon generated tumors; this information may be important for clinicians when they still have not identified a tumor by other diagnostic criteria. We additionally tested our CNN's performance against that of expert radiologists, segueing into the results in which we show human-level accuracy as reproducible by a computer model. It showcases a big scope for CNNs to aid medical professionals in identifying and potentially even augmenting the functioning of doctors in detecting bone malignant tumors.

References

[1] Harshini V.S., Senthil Kumar K.K.,(2019),"Design of Hybrid Sorting Unit",6th IEEE International Conference on &amp,amp,amp,amp,amp,quot,Smart Structures and Systems&amp,amp,amp,amp,amp,quot,, ICSSS 2019.

[2] Monika V., Bommi R.M., Harish Prabu L., Murali M., Nirmala S.,(2018),"Embedded Stethoscope for Real Time Diagnosis of

Authorized licensed use limited to: UNIVERSIDADE FEDERAL DO PIAUI. Downloaded on September 14,2025 at 16:37:09 UTC from IEEE Xplore. Restrictions apply.

Cardiovascular Diseases",2017 IEEE International Conference on Computational Intelligence and Computing Research, ICCIC 2017.

[3] Rajesh G., Mercilin Raajini X., Ashoka Rajan R., Gokuldhev M., Swetha C.,(2020),"A Multi-objective Routing Optimization Using Swarm Intelligence in IoT Networks",Lecture Notes in Networks and Systems,Vol.118,pp.603-613.

[4] Rajesh G., Raajini X.M., Sagayam K.M., Bhushan B., KÃ¶se U.,(2020),"Fuzzy genetic based dynamic spectrum allocation approach for cognitive radio sensor networks",Turkish Journal of Electrical Engineering and Computer Sciences,Vol.28,no.5,pp.2416-2432.

[5] Balaji V., Umapathy N., Duraisamy V., Umapathy K., Venkatesan P., Saravanakumar S.,(2015),"Enhancing varying overhead ad hoc on demand distance vector with artificial ants",Jurnal Teknologi,Vol.77,no.28,pp.39-42.

[6] Adhikari, N., Logeshwaran, J., & Kiruthiga, T. The Artificially Intelligent Switching Framework for Terminal Access Provides Smart Routing in Modern Computer Networks. BOHR International Journal of Smart Computing and Information Technology, 3(1), 45-50.

[7] Vaniprabha, A., Logeshwaran, J., Kiruthiga, T., & Krishna Bikram Shah (2022). Examination of the Effects of Long-term COVID-19 Impacts on Patients with Neurological Disabilities Using a Neuro machine Learning Model. BOHR International Journal of Neurology and Neuroscience, 1(1), 21-28

[8] Venkatachalam, K., Prabu, P., Balaji, B. S., Kang, B. G., Nam, Y., & Abouhawwash, M. (2021). Cross-layer hidden Markov analysis for intrusion detection. CMC-Computers, Materials Continua, 70(1), 3685-3700.

[9] Nithyashri, J., Poluru, R. K., Balakrishnan, S., Kumar, M. A., Prabu, P., & Nandhini, S. (2023). IOT based prediction of rainfall forecast in coastal regions using deep reinforcement model. Measurement: Sensors, 29, 100877.

[10] Baloni, D., Bhatt, C., Kumar, S., Patel, P., & Singh, T. (2023, November). The Evolution of Virtualization and Cloud Computing in the Modern Computer Era. In 2023 International Conference on Communication, Security and Artificial Intelligence (ICCSAI) (pp. 625-630). IEEE.

[11] Kumar, V., Ahmad, W., & Singh, S. (2023). Fake news detection on social-media: A 360 degree survey view. In Artificial Intelligence, Blockchain, Computing and Security Volume 1 (pp. 825-829). CRC Press.

[12] Devi, S., Raj, A., Joshi, P., & Rawat, S. Analysing Factors for Improving Pregnancy Outcomes Using Machine Learning. In Combating Women's Health Issues with Machine Learning (pp. 199-214). CRC Press.

[13] Kumari, A., Saini, A., Kumar, A., Kumar, V., & Kumar, M. (2023, April). Recent Developments and Challenges in Strained Junctionless MOSFETs: A Review. In 2023 International Conference on Computational Intelligence and Sustainable Engineering Solutions (CISES) (pp. 118-122). IEEE.

[14] Sharma, V., Vats, S., Arora, D., Singh, K., Prabuwono, A. S., Alzaidi, M. S., & Ahmadian, A. (2023). OGAS: Omni-directional Glider Assisted Scheme for autonomous deployment of sensor nodes in open area wireless sensor network. ISA transactions, 132, 131-145.

[15] Vats, S., Sharma, V., Singh, K., Singh, D. P., Bajuri, M. Y., Taniar, D., ... & Ahmadian, A. (2024). Iterative enhancement fusion-based cascaded model for detection and localization of multiple disease from CXR-Images. Expert Systems with Applications, 124464.

[16] Vats, S., Sharma, V., Singh, K., Katti, A., Ariffin, M. M., Ahmad, M. N., ... & Salahshour, S. (2024). Incremental learning-based cascaded model for detection and localization of tuberculosis from chest x-ray images. Expert Systems with Applications, 238, 122129.

[17] Saini, A., Kumar, S., Kumari, A., Kumar, S., & Kumar, A. (2023, April). An Energy-efficient Ferry-based Routing Algorithm for Scattered FANET Networks. In 2023 International Conference on Computational Intelligence and Sustainable Engineering Solutions (CISES) (pp. 711-715). IEEE.

[18] A. Goyal, R. Kumar, K. Gupta and D. K .Singh, “A triple band stacked patch antenna with slotted ground structure” IEEE International Conference on Futuristic Trends on Computational Analysis and Knowledge Management (ABLAZE), DOI: 10.1109/ABLAZE.2015.7154924, pp.556 - 560, 2015.

[19] Kasiselvanathan M., Manikandan Rajagopal, Teresa V. V. & Prabhakar Krishnan (2023) Performance analysis of alternating minimization based low complexity detection for MIMO communication system, Automatika, 64:4, 748-755.

[20] Gopi, B., Logeshwaran, J., & Kiruthiga, T (2022). An Innovation in the Development of a Mobile Radio Model for a Dual-Band Transceiver in Wireless Cellular Communication. BOHR International Journal of Computational Intelligence and Communication Network, 1(1), 20-25

[21] Ramesh, G., Logeshwaran, J., & Aravindarajan, V (2022). The Performance Evolution of Antivirus Security Systems in Ultra dense Cloud Server Using Intelligent Deep Learning. BOHR International Journal of Computational Intelligence and Communication Network, 1(1), 15-19

[22] Mistry, J., & Ramakrishnan, R. (2023). The Automated Eye Cancer Detection through Machine Learning and Image Analysis in Healthcare. Journal of Xidian University, 17(8), 763-763.

[23] Iqbal, S., Hussain, L., Siddiqui, G. F., Ali, M. A., Butt, F. M., & Zaib, M. (2024). Image enhancement methods on extracted texture features to detect prostate cancer by employing machine learning techniques. Waves in Random and Complex Media, 34(5), 4587-4611.

[24] Abbood, S. H., Hamed, H. N. A., Rahim, M. S. M., Rehman, A., Saba, T., & Bahaj, S. A. (2022). Hybrid retinal image enhancement algorithm for diabetic retinopathy diagnostic using deep learning model. IEEE Access, 10, 73079-73086

[25] A. A. M. Bamini et al., “IoT-Based Automatic Water Quality Monitoring System with Optimized Neural Network,” KSII Transactions on Internet and Information Systems, vol. 18, no. 1, pp. 46–63, 2024, doi: 10.3837/tiis.2024.01.004.

[26] S. Mohsen et al., “Efficient Artificial Neural Network for Smart Grid Stability Prediction,” International Transactions on Electrical Energy Systems, vol. 2023, 2023, doi: 10.1155/2023/9974409.

.

Authorized licensed use limited to: UNIVERSIDADE FEDERAL DO PIAUI. Downloaded on September 14,2025 at 16:37:09 UTC from IEEE Xplore. Restrictions apply.