

MARE-Madeira 2025

Movement speed estimation

Using the 'ctmm' R package



Inês Silva

✉ i.simoes-silva@hzdr.de

Vectors


Specified by both **magnitude** (value + unit)
and **direction**

Displacement

Velocity

Acceleration

N/A



magnitude of **velocity** vector

Scalars


Specified by only **magnitude** (value + unit)

Distance

Speed

Acceleration/deceleration

Time






Average **velocity**

Displacement divided by *time*

Instantaneous **velocity**

The instantaneous rate of change of the **position vector** with respect to **time**
(i.e., examined for a **very small time interval**)

$$\mathbf{v}_t = \lim_{\Delta t \rightarrow 0} \frac{\Delta \mathbf{r}}{\Delta t}$$




↪ For **speed**, take the magnitude only.

Average **velocity**
Displacement divided by *time*

Instantaneous **velocity**


The instantaneous rate of change of the **position vector** with respect to **time**
(i.e., examined for a **very small time interval**)

$$\mathbf{V}_t = \lim_{\Delta t \rightarrow 0} \frac{\Delta \mathbf{r}}{\Delta t}$$






Speed- and distance-related metrics provide quantifiable links between **behavior** and **energetics**, can inform on risk/reward tradeoffs or as signals of **anthropogenic disturbance**.



Adapted from Nathan *et al.* (2008)




Speed and distance traveled are among the most routinely estimated metrics from animal tracking data.

Usually estimated by summing the **straight-line distance (SLD)** between location estimates...

$$\hat{d} = |\Delta \mathbf{r}| = \sqrt{\Delta x^2 + \Delta y^2}$$

... and divide that by Δt if speed is the desired metric.




Speed and distance traveled are among the most routinely estimated metrics from animal tracking data.

Usually estimated by summing the **straight-line distance (SLD)** between location estimates...

$$\hat{d} = |\Delta \mathbf{r}| = \sqrt{\Delta x^2 + \Delta y^2}$$

... and divide that by Δt if speed is the desired metric.



Speed and distance traveled are among the most routinely estimated metrics from animal tracking data.


Usually estimated by summing the **straight-line distance (SLD)** between location estimates...

$$\hat{d} = |\Delta \mathbf{r}| = \sqrt{\Delta x^2 + \Delta y^2}$$


... and divide that by Δt if speed is the desired metric.




Although SLD is easy to quantify,
it is also **heavily biased**.




Unless the animal moved in a perfectly straight line, this will always **underestimate** distance traveled.




Solution: Increase the sampling frequency until the straight lines provide a better *approximation* of a curve?






Solution: Increase the sampling frequency until the straight lines provide a better *approximation* of a curve?



Solution: Increase the sampling frequency until the straight lines provide a better **approximation** of a curve?




Solution: Increase the sampling frequency until the straight lines provide a better **approximation** of a curve?

However,

If error is uncorrelated in time, estimates converge to **infinity** with infinite sampling frequency ($\Delta t \rightarrow 0$).

Why? The actual distance traveled by the animal goes to **0** in the limit where $\Delta t \rightarrow 0$, but the magnitude of uncorrelated measurement error is **independent of t** .



Continuous-time speed and distance (CTSD)

Noonan *et al.* (2020)

| Model | Autocorrelation | | | Parameters: |
|-------|-----------------|----------|------------|-----------------------------|
| | Position | Velocity | Restricted | |
| IID | No | No | Yes | $\tau = \text{NULL}$ |
| BM | Yes | No | No | $\tau = \infty$ |
| OU | Yes | No | Yes | $\tau = \tau_p$ |
| IOU | Yes | Yes | No | $\tau = \{\infty, \tau_v\}$ |
| OUF | Yes | Yes | Yes | $\tau = \{\tau_p, \tau_v\}$ |




Requires a *correlated velocity model*.

Continuous-time speed and distance (CTSD)

 Noonan *et al.* (2020)


Select best-fit movement model,
so we can repeat over **multiple
rounds of simulations**.



Continuous-time speed and distance (CTSD)

 Noonan *et al.* (2020)


Select best-fit movement model,
so we can repeat over **multiple
rounds of simulations**...




Continuous-time speed and distance (CTSD)


 Noonan *et al.* (2020)


Select best-fit movement model,
so we can repeat over **multiple
rounds of simulations**...




...Until we get a **point estimate**, and
variance around the estimate (for the
confidence intervals).













Sampling frequency (max)

1 fix every 15 minutes



Chuck Homler





White-nosed coati
(*Nasua narica*)



Sampling frequency (max)

1 fix every 15 minutes



Chuck Homler







White-nosed coati
(*Nasua narica*)



Wood turble

(*Glyptemys insculpta*)





To keep in mind...

