

Web Languages and Technologies

Faculdade de Engenharia da Universidade do Porto
30th January 2015

Duration: 2h / No Consultation

Name: _____

Number: _____

- 1 val. 1. In as news site, what is the most semantically correct way to present the title of a news item?

- ☐ `<article><h1 class="header">Título</h1>...</article>`
- ☒ `<article><header><h1>Título</h1></header>...</article>`
- ☐ `<article><h1>Título</h1>...</article>`
- ☐ `<article><div class="header"><h1>Título</h1></div>...</article>`

- 1 val. 2. An user receives an email with the following link:

```
<a href="http://www.example.com/user/profile/action_delete.php">Funny Cats</a>
```

What kind of vulnerability was being exploited?

- ☐ SQL Injection
- ☐ Cross-Site Scripting
- ☐ Javascript Vulnerability
- ☒ Cross-Site Request Forgery

- 1 val. 3. Which one of these strategies, is a good strategy to prevent *brute force* attacks on passwords?

- ☒ Use slow *hashing* functions
- ☐ Use two *salts* for each password
- ☐ Do not allow repeated passwords
- ☐ *Hash* the passwords several times

- 1 val. 4. In PHP, the *strpos* function returns the position, starting in 0, of the first occurrence of a *string* inside another *string*; or *false* if the *string* is not found. After the following code, which is the correct way to test if the *string* has not been found?

```
$pos = strpos($search, $test);
```

- ☐ `if (!$pos) echo "Not found";`
- ☐ `if ($pos != true) echo "Not found";`
- ☒ `if ($pos === false) echo "Not found";`
- ☐ `if ($pos == false) echo "Not found";`

1 val. 5. In PHP, what elements will be present in the array $\$a$ after running the following code?

```
1 <?php
2     $a = array(0, 1, 2, 3);
3     foreach ($a as $k => $v)
4         $a[$k]++;
5 ?>
```

(1,2,3,4)

1 val. 6. Explain, briefly, what is the $\$$ symbol in jQuery.

1 val. 7. In the *HTTP* protocol, methods *GET* and *HEAD* are considered *idempotent*. Explain, briefly, what does that mean.

São métodos que independentemente da instância a que estão a ser chamados, o resultado obtido será sempre o mesmo.

1 val. 8. In XSD, how do we define an element that can contain both other elements and text?

- ☐ With a *mixed simpleType*
- ☐ With a *complex type*
- ☐ With a *mixed complexType*
- ☐ With a *simpleType*