

1 The MultiNest Algorithm

The MultiNest algorithm is a Bayesian inference tool for parameter space exploration and model selection that has come to widespread use in Astrophysics and Cosmology over the past years.

It builds upon the nested sampling technique producing the Bayesian evidence by integrating the likelihood associated with a given set of parameters over the multidimensional parameter space, and creates samples of the posterior distribution as a by-product.

The novel way in which MultiNest represents the sampled volume by an optimized set of ellipsoids makes it especially powerful for exploring multi-modal posteriors or posteriors with curving degeneracies in high dimensions.

Our implementation follows the full description of the algorithm in Feroz et al. [2009].

2 Performance

put comparison tables and colorful pictures here

3 User Instructions

Compile the code using **make**. This program relies on the GNU Scientific Library (GSL) to do linear algebra, so be sure you have GSL installed and that the compiler knows where to find its source files. Before running the program, run time parameters must be set in a file in the **RunTimeFiles** directory. The format of run time files must be as follows.

problem/data file	: problem or data file name
N_{columns}	: #
Dimension	: #
N_{points}	: #
efficiency factor	: 1.0 (default vaule)
repartition factor	: 1.2 (default value)
θ_1	: prior $\theta_{1,\min}$ $\theta_{1,\max}$
θ_2	: prior $\theta_{2,\min}$ $\theta_{2,\max}$

Here, θ_i is the i^{th} parameter, **prior** is the prior probability distribution for a given parameter, and the efficiency and repartition factors are optimization settings that are related to ellipsoidal partitioning and sampling. We have supplied three run time files for the test problems described above. The lighthouse problem is the only test case that requires data for likelihood evaluations, and

its data file can be found in the `DataFiles` directory. The current version of the code can only run these three problems, but we plan to adapt it for much more general use.

The program takes the name of the run time file as a command-line argument. From the `MultiNest` directory, run the three test cases using the commands below.

```
./multinest eggbox.txt
./multinest gauss.shells.txt
./multinest lighthouse.txt
```

If you would like to run make quick test runs with the code, lower the number of active points (`Npoints`) in the run time files. Although our code can run the egg-box and Gaussian shells problems in an arbitrary number of dimensions, we have focused on 2 dimensions (2D), which allows for easy visualization and requires practical computation times.

If the program runs successfully, it will output `posterior.pdfs.dat`, which has columns θ_1 , θ_2 , $\log(\mathcal{L})$, and \mathcal{L}/\mathcal{Z} . As the name implies, this file contains the necessary data to visualize the desired 2D posterior probability distributions. In addition, the program will output text similar to the following to the command-line.

```
getting runtime parameters
creating 2000 active points in 2 dimensions
running MultiNest algorithm... this may take a few minutes
job complete!
**** results ****
number iterations = 34001
number reclusters = 2534
information: H = 8.9353 bits
global evidence: logZ = 235.683 +/- 0.0556484
*****
```

As promised, the code tells us the evidence \mathcal{Z} , plus some additional information about how the algorithm is progressing.

References

- F. Feroz, M. P. Hobson, and M. Bridges. MULTINEST: an efficient and robust Bayesian inference tool for cosmology and particle physics. *MNRAS*, 398: 1601–1614, October 2009. doi: 10.1111/j.1365-2966.2009.14548.x.
- D. S. Sivia and J. Skilling. *Data Analysis: A Bayesian Tutorial*. Oxford University Press, 2 edition, 2006.