



Lecture 6: Search II





Question

Suppose we want to travel from city 1 to city n (going only forward) and back to city 1 (only going backward). It costs $c_{ij} \geq 0$ to go from i to j . Which of the following algorithms will find the minimum cost path (select all that apply)?

depth-first search


breadth-first search

dynamic programming

uniform cost search

- Let's first start by figuring out what the search problem actually is. Any action sequence needs to satisfy the constraint that we move forward to n and then move backwards to 1. So we need to keep track of the current city i as well as the direction in the state.
- We can write down the details, but all that matters for this question is that the graph is acyclic (note that the graph implied by c_{ij} over cities is not acyclic, but keeping track of directionality makes it acyclic). Also, all edge costs are non-negative.
- Now, let's think about which algorithms will work. Recall the various assumptions of the algorithms. DFS won't work because it assumes all edge costs are zero. BFS also won't work because it assumes all edge costs are the same. Dynamic programming will work because the graph is acyclic. Uniform cost search will also work because all the edge costs are non-negative.

Review



Definition: search problem

- s_{start} : starting state
- $\text{Actions}(s)$: possible actions
- $\text{Cost}(s, a)$: action cost
- $\text{Succ}(s, a)$: successors
- $\text{IsGoal}(s)$: found solution?

Objective: find the minimum cost path from s_{start} to an s satisfying $\text{IsGoal}(s)$.



Key idea: state

A **state** is a summary of all the past actions sufficient to choose future actions **optimally**.



Roadmap

Learning costs

A* search

Relaxation



Search

Problem:

Transportation example

Start state: 1

Walk action: from s to $s + 1$ (cost: 1)

Tram action: from s to $2s$ (cost: 2)

Goal state: n



search algorithm

Solution:

walk walk tram tram tram walk tram tram

- Recall the magic tram example from the last lecture. Given a search problem (specification of the start state, goal test, actions, successors, and costs), we can use a search algorithm (DP or UCS) to yield a solution, which is a sequence of actions of minimum cost reaching a goal state from the start state.



Learning

Problem:

Transportation example

Start state: 1

Walk action: from s to $s + 1$ (cost: ?)

Tram action: from s to $2s$ (cost: ?)

Goal state: n

Solution:

walk walk tram tram tram walk tram tram



learning algorithm

walk cost: **1**, tram cost: **2**

- Now suppose we don't know what the costs are, but we observe someone getting from 1 to n via some sequence of walking and tram-taking. Can we figure out what the costs are? This is the goal of learning.

Learning as an inverse problem

Forward problem (search):

$$\text{Cost}(s, a) \longrightarrow (a_1, \dots, a_k)$$


Inverse problem (learning):

$$(a_1, \dots, a_k) \longrightarrow \text{Cost}(s, a)$$

- More generally, so far we have thought about search as a "forward" problem: given costs, finding the optimal sequence of actions.
- Learning concerns the "inverse" problem: given the desired sequence of actions, reverse engineer the costs.

Predicting the path

Input x : search problem without costs




Output y : solution path

walk walk walk

- Let's cast the problem as predicting an output y given an input x . Here, the input x is the search problem (visualized as a search tree) without the costs provided. The output y is the desired solution path. The question is what the costs should be set to so that y is actually the minimum cost path of the resulting search problem.

Transportation example




- Here we have depicted two search trees. On the left, we have the cost of walking and taking the tram to both be 1. The minimum cost path is shown in red (walk, tram).
- But this is not our desired output, because we actually saw the person walk all the way from 1 to 4. How can we update the action costs so that the minimum cost path is walking? One way is to crank up the tram cost to 3.
- In a more complex example, there might be thousands of actions and their associated costs. How do we tune these costs automatically?

Costs

Costs depend only on the action:

$$\text{Cost}(s, a) = \mathbf{w}(a)$$

Output:



Path cost:

$$\text{Cost}(y) = \mathbf{w}(a_1) + \mathbf{w}(a_2) + \mathbf{w}(a_3)$$

- For each action a , we define a weight $w(a)$ representing the cost of action a . Without loss of generality, let us assume that the cost of the action does not depend on the state s .
- Then the cost of a path y is simply the sum of the weights of the actions on the path.
- Not important: If we wanted the cost to depend on the state, then we could call (s, a) the action.

Learning algorithm



Algorithm: Structured Perceptron [Collins, 2002]

- For each action: $\mathbf{w}(a) \leftarrow 0$
 - For each iteration $t = 1, \dots, T$:
 - For each training example $(x, y) \in \mathcal{D}_{\text{train}}$:
 - Compute the minimum cost path y' given w
 - For each action $a \in y$: $\mathbf{w}(a) \leftarrow \mathbf{w}(a) - 1$
 - For each action $a \in y'$: $\mathbf{w}(a) \leftarrow \mathbf{w}(a) + 1$
 - Try to decrease cost of true y (from training data)
 - Try to increase cost of predicted y' (from search)
- [live solution]

- We are now in position to state the (simplified version of) **structured Perceptron** algorithm.
- Advanced: the Perceptron algorithm performs stochastic gradient descent (SGD) on a modified hinge loss with a constant step size of $\eta = 1$. The modified hinge loss is $\text{Loss}(x, y, \mathbf{w}) = \max\{-\mathbf{w} \cdot \phi(x), 0\}$, where the margin of 1 has been replaced with a zero. The structured Perceptron is a generalization of the Perceptron algorithm, which is stochastic gradient descent on $\text{Loss}(x, y, \mathbf{w}) = \max_{y'} \{\sum_{a \in y} \mathbf{w}(a) - \sum_{a \in y'} \mathbf{w}(a)\}$ (note the relationship to the multiclass hinge loss). Even if you don't really understand the loss function, you can still understand the algorithm, since it is very intuitive.
- We iterate over the training examples. Given the current weights w (action costs), we run a search algorithm to find the minimum cost path according to those weights y' . Then we update the weights to favor actions that appear in the correct output y (by reducing their costs) and disfavor actions that appear in the predicted output y' (by increasing their costs).
- The structured Perceptron was first used for natural language processing tasks. Given its simplicity, the Perceptron works reasonably well. With a few minor tweaks, you get state-of-the-art algorithms for structured prediction, which can be applied to many tasks such as machine translation, gene prediction, information extraction, etc.
- On a historical note, the structured Perceptron merges two relatively classic communities. The first is search algorithms (uniform cost search was developed by Dijkstra in 1956). The second is machine learning (Perceptron was developed by Rosenblatt in 1957). It was only over 40 years later that the two met.



Roadmap


Learning costs

A* search


Relaxation

A* algorithm


UCS in action:



A* in action:



Can uniform cost search be improved?




Problem: UCS orders states by cost from s_{start} to s

Desiderata: take into account cost from s to s_{goal}

- Now our goal is to make UCS faster. If we look at the UCS algorithm, we see that it explores states based on how far they are away from the start state. As a result, it will explore many states which are close to the start state, but actually moving farther away from the goal.
- Intuitively, we'd like to bias UCS towards exploring states which are closer to the goal, and that's exactly what A^* does.

Exploring states

UCS: explore states in order of $\text{PastCost}(s)$



A*: explore states in order of $\text{PastCost}(s) + h(s)$



Definition: Heuristic function

A heuristic $h(s)$ is any estimate of $\text{FutureCost}(s)$.

- First, some terminology: $\text{PastCost}(s)$ is the minimum cost from the start state to s , and $\text{FutureCost}(s)$ is the minimum cost from s to a goal state. Without loss of generality, we can just assume we have one goal state. (If we have multiple ones, create a new official goal state which is the successor of all the original goal states.)
- Recall that UCS explores states in order of $\text{PastCost}(s)$. It'd be nice if we could explore states in order of $\text{PastCost}(s) + \text{FutureCost}(s)$, which would definitely take the goal into account, but computing $\text{FutureCost}(s)$ would be as expensive as solving the original problem.
- A* relies on a heuristic $h(s)$, which is an estimate of $\text{FutureCost}(s)$. For A* to work, $h(s)$ must satisfy some conditions, but for now, just think of $h(s)$ is an approximation. We will soon show that A* will explore states in order of $\text{PastCost}(s) + h(s)$. This is nice, because now states which are estimated (by $h(s)$) to be really far away from the goal will be explored later, even if their $\text{PastCost}(s)$ is small.

A* search




Algorithm: A* search [Hart/Nilsson/Raphael, 1968]

Run uniform cost search with **modified edge costs**:

$$\text{Cost}'(s, a) = \text{Cost}(s, a) + h(\text{Succ}(s, a)) - h(s)$$

Intuition: add a penalty for how much action a takes us away from the goal

Example:




- Here is the A* algorithm: just run UCS with modified edge costs. You might feel tricked because we said we'd give you a shiny new algorithm, but actually, you just got a refurbished version of UCS. (This is a slightly unorthodox presentation of A*. The normal presentation is modifying UCS to prioritize by $\text{PastCost}(s) + h(s)$ rather than $\text{PastCost}(s)$.) But I think the modified edge costs view shows a deeper connection to UCS, and we don't even have to modify the UCS code at all.
- How should we think of these modified edge costs? It's the same edge cost $\text{Cost}(s, a)$ plus an additional term. This term is difference between the estimated future cost of the new state $\text{Succ}(s, a)$ and that of the current state s . In other words, we're measuring how much farther from the goal taking action a is taking us. If this difference is positive, then we're penalizing the action a more. If this difference is negative, then we're favoring this action a .
- Let's look at small example. All edge costs are 1. Let's suppose we define $h(s)$ to be the actual $\text{FutureCost}(s)$, the minimum cost to the goal. In general, this is not the case, but let's see what happens in the best case. The modified edge costs are 2 for actions moving away from the goal and 0 for actions moving towards the goal.
- In this case, UCS with original edge costs 1 will explore all the nodes. However, A* (UCS with modified edge costs) will explore only the three nodes on the path to the goal.

An example heuristic

Will any heuristic work?

No.

Counterexample:



- So far, we've just said that $h(s)$ is just an approximation of $\text{FutureCost}(s)$. But can it be any approximation?
- The answer is no, as the counterexample clearly shows. The modified edge costs would be 1001 to B and 2 to C. UCS would go to C first and then to D, finding a cost 3 path rather than the optimal cost 2 path through B.
- If our heuristic is lying to us (bad approximation of future costs), then running A* (UCS on modified costs) could lead to a suboptimal solution.

Consistent heuristics



Definition: consistency

A heuristic h is **consistent** if


- $\text{Cost}'(s, a) = \text{Cost}(s, a) + h(\text{Succ}(s, a)) - h(s) \geq 0$
- $h(s_{\text{goal}}) = 0$.

Condition 1 (triangle inequality): needed for UCS to work.

Condition 2: $\text{FutureCost}(s_{\text{goal}}) = 0$ so match it.

- We need $h(s)$ to be **consistent**, which means two things. First, the modified edge costs are non-negative (this is the main property). This is important for UCS to find the minimum cost path (remember that UCS only works when all the edge costs are non-negative).
- Second, $h(s_{\text{goal}}) = 0$, which is just saying: be reasonable. The minimum cost from the goal to the goal is trivially 0, so just use 0.

Correctness of A^*




Proposition: correctness

If h is consistent, A^* returns the minimum cost path.

- The main theoretical result for A^* is that if we use any consistent heuristic, then we will be guaranteed to find the minimum cost path.

Proof of A* correctness

- Consider any path $[s_0, a_1, s_1, \dots, a_L, s_L]$:



- Key identity:

$$\underbrace{\sum_{i=1}^L \text{Cost}'(s_{i-1}, a_i)}_{\text{modified path cost}} = \underbrace{\sum_{i=1}^L \text{Cost}(s_{i-1}, a_i)}_{\text{original path cost}} + \underbrace{h(s_L) - h(s_0)}_{\text{constant}}$$

- Therefore, A* (finding the minimum cost path using modified costs) solves the original problem (even though edge costs are all different!)


- To show the correctness of A^* , let's take any path of length L from $s_0 = s_{\text{start}}$ to $s_L = s_{\text{goal}}$. Let us compute the modified path cost by just adding up the modified edge costs. Just to simplify notation, let $c_i = \text{Cost}(s_{i-1}, a_i)$ and $h_i = h(s_i)$. The modified path cost is $(c_1 + h_1 - h_0) + (c_2 + h_2 - h_1) + \dots + (c_L + h_L - h_{L-1})$. Notice that most of the h_i 's actually cancel out (this is known as **telescoping sums**).
- We end up with $\sum_{i=1}^L c_i$, which is the original path cost plus $h_L - h_0$. First, notice that $h_L = 0$ because s_L is a goal state and by the second condition of consistency, $h(s_L) = 0$. Second, h_0 is just a constant (in that it doesn't depend on the path at all), since all paths must start with the start state.
- Therefore, the modified path cost is equal to the original path cost plus a constant. A^* , which is running UCS on the modified edge costs, is equivalent to running UCS on the original edge costs, which minimizes the original path cost.
- This is kind of remarkable: all the edge costs are modified in A^* , but yet the final path cost is the same (up to a constant)!

A* search




Key idea: distortion

A* distorts costs to favor goal states.



- We've proven that A^* is correct (finds the minimum cost path) for any consistent heuristic h . But for A^* to be interesting, we need to show that it's more efficient than UCS (on the original edge costs). We will measure speed in terms of the number of states which are explored prior to exploring a goal state.
- What exactly is A^* doing to the edge costs? Intuitively, it's biasing us towards the goal state.


Extremes



- If $h(s) = 0$, then A^* is same as UCS.
- If $h(s) = \text{FutureCost}(s)$, then A^* only explores nodes on a minimum cost path.
- Usually $h(s)$ is somewhere in between.

- In this diagram, each ellipse corresponds to the set of states which are explored by A^* with various heuristics. In general, any heuristic we come up with will be between the trivial heuristic $h(s) = 0$ which corresponds to UCS and the oracle heuristic $h(s) = \text{FutureCost}(s)$ which is unattainable.

Efficiency of A*



Theorem: efficiency of A*

A* explores all states s satisfying
 $\text{PastCost}(s) \leq \text{PastCost}(s_{\text{goal}}) - h(s)$

Interpretation: the larger $h(s)$, the better


Proof: A* explores all s such that

$$\begin{aligned} & \text{PastCost}(s) + h(s) - h(s_{\text{start}}) \\ & \leq \\ & \text{PastCost}(s_{\text{goal}}) + h(s_{\text{goal}}) - h(s_{\text{start}}) \end{aligned}$$

- Our second theorem is about the efficiency of A*: recall that UCS explores states in order of past cost, so that it will explore every state whose past cost is less than the past cost of the goal state.
- A* explores all states for which $\text{PastCost}'(s) = \text{PastCost}(s) + h(s) - h(s_{\text{start}})$ is less than $\text{PastCost}'(s_{\text{goal}}) = \text{PastCost}(s_{\text{goal}}) + h(s_{\text{goal}}) - h(s_{\text{start}})$, or equivalently $\text{PastCost}(s) + h(s) \leq \text{PastCost}(s_{\text{goal}})$ since $h(s_{\text{goal}}) = 0$.
- From here, it's clear that we want $h(s)$ to be as large as possible so we can push as many states over the $\text{PastCost}(s_{\text{goal}})$ threshold, so that we don't have to explore them. Of course, we still need h to be consistent to maintain correctness.
- For example, suppose $\text{PastCost}(s_1) = 1$ and $h(s_1) = 1$ and $\text{PastCost}(s_{\text{goal}}) = 2$. Then we would have to explore s_1 ($1 + 1 \leq 2$). But if we were able to come up with a better heuristic where $h(s_1) = 2$, then we wouldn't have to explore s_1 ($1 + 2 > 2$).

Admissibility

Intuition: FutureCost(s) should be the best, so $h(s)$ can't be larger than it



Definition: admissibility

A heuristic $h(s)$ is admissible if
$$h(s) \leq \text{FutureCost}(s)$$



Theorem: consistency implies admissibility

If a heuristic $h(s)$ is **consistent**, then $h(s)$ is **admissible**.

Proof: use induction on FutureCost(s)

- So far, we've just assumed that $\text{FutureCost}(s)$ is the best possible heuristic (ignoring for the moment that it's impractical to compute). Let's actually prove this now.
- To do this, we just have to show that any consistent heuristic $h(s)$ satisfies $h(s) \leq \text{FutureCost}(s)$ (since by the previous theorem, the larger the heuristic, the better). In fact, this property has a special name: $h(s)$ is **admissible** if this property holds. In other words, an admissible heuristic $h(s)$ **underestimates** the future cost: it is being an optimist.
- The proof proceeds by induction on $\text{FutureCost}(s)$. In the base case, we have $0 = h(s_{\text{goal}}) \leq \text{FutureCost}(s_{\text{goal}}) = 0$ by the second condition of consistency.
- In the inductive case, let s be a state and let a be an optimal action leading to $s' = \text{Succ}(s, a)$ that achieves the minimum cost path to the goal; in other words, $\text{FutureCost}(s) = \text{Cost}(s, a) + \text{FutureCost}(s')$. Note that $\text{FutureCost}(s) \leq \text{FutureCost}(s')$, so by the inductive hypothesis, we have $h(s') \leq \text{FutureCost}(s')$. Next, we have a chain of inequalities: $h(s) \leq \text{Cost}(s, a) + h(s') \leq \text{Cost}(s, a) + \text{FutureCost}(s') = \text{FutureCost}(s)$, where the first inequality follows by consistency of $h(s)$, the second inequality follows by the inductive hypothesis, and the third equality follows because a was chosen to be the optimal action. Therefore, we conclude that $h(s) \leq \text{FutureCost}(s)$.
- Aside: People often talk about admissible heuristics. Using A* with an admissible heuristic is only guaranteed to find the minimum cost path for tree search algorithms, where we don't use an explored list. However, the UCS and A* algorithms we are consider in this class are graph search algorithms, which require consistent heuristics, not just admissible heuristics, to find the minimum cost path. There are some admissible heuristics which are not consistent, but most natural ones are consistent.



Roadmap

Learning costs

A* search

Relaxation

How do we get good heuristics? Just relax...



Relaxation

Intuition: ideally, use $h(s) = \text{FutureCost}(s)$, but that's as hard as solving the original problem.



Key idea: relaxation


Constraints make life hard. Get rid of them.



- So far, given a heuristic $h(s)$, we can run A* using it and get a savings which depends on how large $h(s)$ is. However, we've only seen two heuristics: $h(s) = 0$ and $h(s) = \text{FutureCost}(s)$. The first does nothing (gives you back UCS), and the second is hard to compute.
- What we'd like to do is to come up with a general principle for coming up with heuristics. The idea is that of a **relaxation**: instead of computing $\text{FutureCost}(s)$ on the original problem, let us compute $\text{FutureCost}(s)$ on an easier problem, where the notion of easy will be made more formal shortly.
- Note that coming up with good heuristics is about **modeling**, not algorithms. We have to think carefully about our problem domain and see what kind of structure we can exploit in it.



Relaxation summary




Closed form solution




Example: knock down walls

Goal: move from triangle to circle



Hard



Easy

Heuristic:

$$h(s) = \text{ManhattanDistance}(s, (2, 5))$$

$$\text{e.g., } h((1, 1)) = 5$$

- Here's a simple example. Suppose states are positions (r, c) on the grid. Possible actions are moving up, down, left, or right, provided they don't move you into a wall or off the grid; and all edge costs are 1. The start state is at the triangle at $(1, 1)$, and the goal state is the circle at position $(2, 5)$.
- With an arbitrary configuration of walls, we can't compute $\text{FutureCost}(s)$ except by doing search. However, if we just **relaxed** the original problem by removing the walls, then we can compute $\text{FutureCost}(s)$ in **closed form**: it's just the Manhattan distance between s and s_{goal} . Specifically, $\text{ManhattanDistance}((r_1, c_1), (r_2, c_2)) = |r_1 - r_2| + |c_1 - c_2|$.



An annoying example



Example: original problem

Start state: 1

Walk action: from s to $s + 1$ (cost: 1)

Tram action: from s to $2s$ (cost: 2)

Goal state: n


Constraint: can't have more tram actions than walk actions.

State: (location, **#walk** - **#tram**)

Number of states goes from $O(n)$ to $O(n^2)$!

[live solution]

- Let's revisit our magic tram example. Suppose now that a decree comes from above that says you can't have take the tram more times than you walk. This makes our lives considerably worse, since if we wanted to respect this constraint, we have to keep track of additional information (augment the state).
- In particular, we need to keep track of the number of walk actions that we've taken so far minus the number of tram actions we've taken so far, and enforce that this number does not go negative. Now the number of states we have is much larger and thus, search becomes a lot slower.



Easier search



Example: relaxed problem

Start state: 1

Walk action: from s to $s + 1$ (cost: 1)

Tram action: from s to $2s$ (cost: 2)

Goal state: n

~~Constraint: can't have more tram actions than walk actions.~~

Original state: (location, **#walk - #tram**)

Relaxed state: location

- What if we just ignore that constraint and solve the original problem? That would be much easier/faster. But how do we construct a consistent heuristic from the solution from the relaxed problem?

Easier search

- Compute relaxed $\text{FutureCost}'(\text{location})$ for **each** location $(1, \dots, n)$ using dynamic programming or UCS



Example: reversed relaxed problem

Start state: n

Walk action: from s to $s - 1$ (cost: 1)

Tram action: from s to $s/2$ (cost: 2)

Goal state: 1

Modify UCS to compute all past costs in reversed relaxed problem (equivalent to future costs in relaxed problem!)

- Define heuristic for original problem:


$$h((\text{location}, \# \text{walk} - \# \text{tram})) = \text{FutureCost}'(\text{location})$$

[live solution]

- We want to now construct a heuristic $h(s)$ based on the future costs under the relaxed problem.
- For this, we need the future costs for all the relaxed states. One straightforward way to do this is using dynamic programming. However, if we have cycles, then we need to use uniform cost search.
- But recall that UCS only computes the past costs of all states up until the goal. So we need to make two changes. First, we simply don't stop at the goal, but keep on going until we've explored all the states. Second, we define a **reversed relaxed problem** (where all the edges are just reversed), and call UCS on that. UCS will return past costs in the reversed relaxed problem which correspond exactly to future costs in the relaxed problem.
- Finally, we need to construct the actual heuristic. We have to be a bit careful because the state spaces of the relaxed and original problems are different. For this, we set the heuristic $h(s)$ to the future cost of the relaxed version of s .
- Note that the minimum cost returned by A* (UCS on the modified problem) is the true minimum cost minus the value of the heuristic at the start state.

Independent subproblems

[8 puzzle]



Original problem: tiles **cannot** overlap (constraint)

Relaxed problem: tiles **can** overlap (no constraint)

Relaxed solution: 8 indep. problems, each in closed form



Key idea: independence

Relax original problem into independent subproblems.

- So far, we've seen that some heuristics $h(s)$ can be computed in closed form and others can be computed by doing a cheaper search. But there's another way to define heuristics $h(s)$ which are efficient to compute.
- In the 8-puzzle, the goal is to slide the tiles around to produce the desired configuration, but with the constraint that no two tiles can occupy the same position. However, we can throw that constraint out the window to get a relaxed problem. Now, the new problem is really easy, because the tiles can now move **independently**. So we've taken one giant problem and turned it into 8 smaller problems. Each of the smaller problems can now be solved separately (in this case, in closed form, but in other cases, we can also just do search).
- It's worth remembering that all of these relaxed problems are simply used to get the value of the heuristic $h(s)$ to guide the full search. The actual solutions to these relaxed problems are not used.

General framework

Removing constraints


(knock down walls, walk/tram freely, overlap pieces)



Reducing edge costs

(from ∞ to some finite cost)

Example:




Original: $\text{Cost}((1, 1), \text{East}) = \infty$

Relaxed: $\text{Cost}'((2, 2), \text{East}) = 1$

- We have seen three instances where removing constraints yields simpler solutions, either via closed form, easier search, or independent subproblems. But we haven't formally proved that the heuristics you get are consistent!
- Now we will analyze all three cases in a unified framework. Removing constraints can be thought of as adding edges (you can go between pairs of states that you weren't able to before). Adding edges is equivalent to reducing the edge cost from infinity to something finite (the resulting edge cost).


General framework



Definition: relaxed search problem

A **relaxation** P' of a search problem P has costs that satisfy:

$$\text{Cost}'(s, a) \leq \text{Cost}(s, a).$$



Definition: relaxed heuristic

Given a relaxed search problem P' , define the **relaxed heuristic** $h(s) = \text{FutureCost}'(s)$, the minimum cost from s to a goal state using $\text{Cost}'(s, a)$.

- More formally, we define a relaxed search problem as one where the relaxed edge costs are no larger than the original edge costs.
- The relaxed heuristic is simply the future cost of the relaxed search problem, which by design should be efficiently computable.

General framework



Theorem: consistency of relaxed heuristics

Suppose $h(s) = \text{FutureCost}'(s)$ for some relaxed problem P' .
Then $h(s)$ is a consistent heuristic.

Proof:

$$\begin{aligned} h(s) &\leq \text{Cost}'(s, a) + h(\text{Succ}(s, a)) \text{ [triangle inequality]} \\ &\leq \text{Cost}(s, a) + h(\text{Succ}(s, a)) \text{ [relaxation]} \end{aligned}$$

- We now need to check that our defined heuristic $h(s)$ is actually consistent, so that using it actually will yield the minimum cost path of our original problem (not the relaxed problem, which is just a means towards an end).
- Checking consistency is actually quite easy. The first inequality follows because $h(s) = \text{FutureCost}(s)$, and all future costs correspond to the minimum cost paths. So taking action a from state s better be no better than taking the best action from state s .
- The second inequality follows just by the definition of a relaxed search problem.
- The significance of this theorem is that we only need to think about coming up with relaxations rather than worrying directly about checking consistency.

Tradeoff

Correctness:

edge costs are lower \Rightarrow consistent heuristic

Example: removing constraints

Efficiency:


$h(s) = \text{FutureCost}'(s)$ must be easy to compute

Example: closed form, easier search

- There are two important properties that a heuristic should have.
- First, from the search problem's perspective, reducing the edge costs makes going to the goal easier. This is important for getting a consistent heuristic and guaranteeing that A* will return the correct answer.
- Second, from the search algorithm's perspective, just because we reduced all the edge costs doesn't mean that the search problem is actually easier to solve. We also need to make sure that when we reduce edge costs, it's done in a way such that we can compute $h(s)$ efficiently.
- So far, we have come up with many ways of creating consistent heuristics based on relaxation. There is a tension here: if we relax too much, then we don't get much gain over UCS (which uses the weakest heuristic $h(s) = 0$). On the other hand, if we don't relax enough, then we probably won't be able to compute it efficiently. So the art of designing heuristics is to balance informativeness with computational efficiency.

Max of two heuristics

How do we combine two heuristics?



Proposition: max heuristic

Suppose $h_1(s)$ and $h_2(s)$ are consistent.

Then $h(s) = \max\{h_1(s), h_2(s)\}$ is consistent.

Proof: exercise

- In many situations, you'll be able to come up with two heuristics which are both reasonable, but no one dominates the other. Which one should you choose? Fortunately, you don't have to choose because you can use both of them!
- The key point is the max of two consistent heuristics is consistent. Why max? Remember that we want heuristic values to be larger. And furthermore, we can prove that taking the max leads to a consistent heuristic.
- Stepping back a bit, there is a deeper takeaway with A* and relaxation here. The idea is that when you are confronted with a difficult problem, it is wise to start by solving easier versions of the problem (being an optimist). The result of solving these easier problems can then be a useful guide in solving the original problem.
- For example, if the relaxed problem turns out to have no solution, then you don't even have to bother solving the original problem, because a solution can't possibly exist (you've been optimistic by using the relaxation).



Summary

- **Structured Perceptron (reverse engineering)**: learn cost functions (search + learning)
- **A***: add in heuristic estimate of future costs
- **Relaxation (breaking the rules)**: framework for producing consistent heuristics
- **Next time**: when actions have unknown consequences...



cs221.stanford.edu/q

Question

What was the most useful part of this class?