

Layer-skipping connections facilitate training of layered networks using equilibrium propagation.

Jimmy Gammell Sae Woo Nam Adam N. McCaughan

July 28, 2020

Motivation

- ▶ Seek to implement deep learning in neuromorphic analog hardware

Motivation


- ▶ Seek to implement deep learning in neuromorphic analog hardware
- ▶ Want learning framework requiring simple hardware

Motivation

- ▶ Seek to implement deep learning in neuromorphic analog hardware
- ▶ Want learning framework requiring simple hardware
 - ▶ Neurons and connections perform few distinct tasks


Background: equilibrium propagation

- Equilibrium propagation: a biologically motivated learning framework




Background: equilibrium propagation

- ▶ Equilibrium propagation: a biologically motivated learning framework
 - ▶ Gradient descent on cost function (alternative to backpropagation)




Background: equilibrium propagation




- ▶ Equilibrium propagation: a biologically motivated learning framework
 - ▶ Gradient descent on cost function (alternative to backpropagation)
 - ▶ Energy-based networks, e.g. continuous Hopfield network

Background: equilibrium propagation




- ▶ Equilibrium propagation: a biologically motivated learning framework
 - ▶ Gradient descent on cost function (alternative to backpropagation)
 - ▶ Energy-based networks, e.g. continuous Hopfield network
- ▶ First phase of training: free phase

Background: equilibrium propagation




- ▶ Equilibrium propagation: a biologically motivated learning framework
 - ▶ Gradient descent on cost function (alternative to backpropagation)
 - ▶ Energy-based networks, e.g. continuous Hopfield network
- ▶ First phase of training: free phase
 - ▶ Evolve to equilibrium for input

Background: equilibrium propagation




- ▶ Equilibrium propagation: a biologically motivated learning framework
 - ▶ Gradient descent on cost function (alternative to backpropagation)
 - ▶ Energy-based networks, e.g. continuous Hopfield network
- ▶ First phase of training: free phase
 - ▶ Evolve to equilibrium for input
 - ▶ Prediction: output activations at equilibrium

Background: equilibrium propagation




- Second phase of training: weakly-clamped phase

Background: equilibrium propagation




- ▶ Second phase of training: weakly-clamped phase
 - ▶ Perturb output activations towards target output

Background: equilibrium propagation



- ▶ Second phase of training: weakly-clamped phase
 - ▶ Perturb output activations towards target output
 - ▶ Evolve to equilibrium

Background: equilibrium propagation



- ▶ Second phase of training: weakly-clamped phase
 - ▶ Perturb output activations towards target output
 - ▶ Evolve to equilibrium
- ▶ Differences between equilibrium states can be used to compute gradient

Background: equilibrium propagation

- ▶ Advantageous due to simplicity of neurons and connections

Background: equilibrium propagation

- ▶ Advantageous due to simplicity of neurons and connections
 - ▶ One computation in both phases of training

Background: equilibrium propagation

- ▶ Advantageous due to simplicity of neurons and connections
 - ▶ One computation in both phases of training
 - ▶ One type of information to transmit in both phases of training


Background: equilibrium propagation

- ▶ Advantageous due to simplicity of neurons and connections
 - ▶ One computation in both phases of training
 - ▶ One type of information to transmit in both phases of training
 - ▶ Biologically-plausible (relative to backpropagation)

Background: equilibrium propagation


- ▶ Advantageous due to simplicity of neurons and connections
 - ▶ One computation in both phases of training
 - ▶ One type of information to transmit in both phases of training
 - ▶ Biologically-plausible (relative to backpropagation)
 - ▶ Implementable in neuromorphic analog hardware

Background: vanishing gradient problem




- Problem: vanishing gradients in layered networks

Background: vanishing gradient problem




- Problem: vanishing gradients in layered networks
 - Slow training

Background: vanishing gradient problem




- ▶ Problem: vanishing gradients in layered networks
 - ▶ Slow training
 - ▶ Bit-depth issues

Background: vanishing gradient problem



- ▶ Problem: vanishing gradients in layered networks
 - ▶ Slow training
 - ▶ Bit-depth issues
- ▶ Need to solve - deep networks better than shallow networks


Background: vanishing gradient problem



- ▶ Problem: vanishing gradients in layered networks
 - ▶ Slow training
 - ▶ Bit-depth issues
- ▶ Need to solve - deep networks better than shallow networks
- ▶ Not yet solved in simple, biologically-plausible manner


Background: vanishing gradient problem

- Original paper: independent learning rates for each layer




Background: vanishing gradient problem

- ▶ Original paper: independent learning rates for each layer
 - ▶ Increase with depth to compensate




Background: vanishing gradient problem

- ▶ Original paper: independent learning rates for each layer
 - ▶ Increase with depth to compensate
- ▶ Unappealing for following reasons:




Background: vanishing gradient problem

- ▶ Original paper: independent learning rates for each layer
 - ▶ Increase with depth to compensate
- ▶ Unappealing for following reasons:
 1. More hyperparameters to tune




Background: vanishing gradient problem




- ▶ Original paper: independent learning rates for each layer
 - ▶ Increase with depth to compensate
- ▶ Unappealing for following reasons:
 1. More hyperparameters to tune
 2. Inconvenient in neuromorphic hardware

Background: vanishing gradient problem



- ▶ Original paper: independent learning rates for each layer
 - ▶ Increase with depth to compensate
- ▶ Unappealing for following reasons:
 1. More hyperparameters to tune
 2. Inconvenient in neuromorphic hardware
 3. Seems unlikely in biological systems

Background: vanishing gradient problem



- ▶ Original paper: independent learning rates for each layer
 - ▶ Increase with depth to compensate
- ▶ Unappealing for following reasons:
 1. More hyperparameters to tune
 2. Inconvenient in neuromorphic hardware
 3. Seems unlikely in biological systems
- ▶ Problem can be mitigated by instead using topological modification based on layer-skipping connections


Our solution: layer-skipping connections

- ▶ Vanishing gradient problem can be mitigated with layer-skipping connections

Our solution: layer-skipping connections


- ▶ Vanishing gradient problem can be mitigated with layer-skipping connections
- ▶ Topology inspired by small-world networks

Original layered topology




► From original paper

Original layered topology




- ▶ From original paper
- ▶ Per-layer learning rates

Our topological modifications




► Starting point:
original topology

Our topological modifications




- ▶ Starting point: original topology
- ▶ One learning rate for all layers

Our topological modifications




- Hidden layers fully connected

Our topological modifications




► Consider each connection

Our topological modifications




- ▶ Consider each connection
- ▶ Remove with probability p

Our topological modifications




- For each removed connection, randomly connect a different pair

Our topological modifications




- For each removed connection, randomly connect a different pair
- No connections within input or output layers

Results: training error of layered network with per-layer learning rates




- Baseline performance: network from original paper

Results: training error of layered network with per-layer learning rates




- Baseline performance: network from original paper
- Per-layer learning rates

Results: training error of layered network with single global learning rate




- Network with one global learning rate

Results: training error of layered network with single global learning rate




- Network with one global learning rate
- Training slows down

Results: training error of network with our topology




- Network with our topology (still one global learning rate)

Results: training error of network with our topology




- ▶ Network with our topology (still one global learning rate)
- ▶ Trains significantly faster than layered network

Results: training error of network with our topology




- ▶ Network with our topology (still one global learning rate)
- ▶ Trains significantly faster than layered network
- ▶ Performance similar to original network

Results: vanishing gradient in layered network with single global learning rate




- Vanishing gradient problem when one learning rate is used

Results: vanishing gradient in layered network with our topology



- Our topology mitigates vanishing gradient problem

Results: vanishing gradient in layered network with our topology



- ▶ Our topology mitigates vanishing gradient problem
- ▶ Shallowest weights train faster due to lack of layer-skipping connections to target

Conclusions

- ▶ Our topology mitigates vanishing gradient problem

Conclusions

- ▶ Our topology mitigates vanishing gradient problem
- ▶ Avoids issues with per-layer rates

Conclusions

- ▶ Our topology mitigates vanishing gradient problem
- ▶ Avoids issues with per-layer rates
 1. Only two new hyperparameters; constant with depth

Conclusions

- ▶ Our topology mitigates vanishing gradient problem
- ▶ Avoids issues with per-layer rates
 1. Only two new hyperparameters; constant with depth
 2. Small-world networks have been observed in biological brains

Conclusions

- ▶ Our topology mitigates vanishing gradient problem
- ▶ Avoids issues with per-layer rates
 1. Only two new hyperparameters; constant with depth
 2. Small-world networks have been observed in biological brains
 3. Easy to implement in networks with configurable connectivity

Conclusions

- ▶ Our topology mitigates vanishing gradient problem
- ▶ Avoids issues with per-layer rates
 1. Only two new hyperparameters; constant with depth
 2. Small-world networks have been observed in biological brains
 3. Easy to implement in networks with configurable connectivity
- ▶ Good solution where simplicity, biological plausibility important

Directions for future research

- ▶ Try on harder datasets (e.g. CIFAR, ImageNet) where depth is very important

Directions for future research

- ▶ Try on harder datasets (e.g. CIFAR, ImageNet) where depth is very important
- ▶ Effect of p on test error

Directions for future research

- ▶ Try on harder datasets (e.g. CIFAR, ImageNet) where depth is very important
- ▶ Effect of p on test error
- ▶ Effectiveness on deeper networks

Directions for future research

- ▶ Try on harder datasets (e.g. CIFAR, ImageNet) where depth is very important
- ▶ Effect of p on test error
- ▶ Effectiveness on deeper networks
- ▶ Try training a network with added layer-skipping connections, then removing them afterwards

Acknowledgments

- ▶ Sonia Buckley
- ▶ Zach Grey
- ▶ Adam N. McCaughan
- ▶ Sae Woo Nam
- ▶ Alex Tait

NIST



Boulder