

# COATi: statistical pairwise alignment of protein coding sequences

Juan J. Garcia Mesa<sup>1,2</sup>, Ziqi Zhu<sup>1,3</sup>, Reed A. Cartwright<sup>1,3,\*</sup>

1 Biodesign Institute, Arizona State University

2 Ira A. Schools of Engineering, Arizona State University

3 School of Life Sciences, Arizona State University

\* cartwright@asu.edu

## Abstract

Sequence alignment is an essential method in bioinformatics and the basis of many analyses, including phylogenetic inference, ancestral sequence reconstruction, and gene annotation. Sequence artifacts and errors made in alignment reconstruction can impact downstream analyses leading to erroneous conclusions in comparative and functional genomic studies. For example, abiological frameshifts and early stop codons are common artifacts found in protein coding sequences annotated in reference genomes. While this is eventually fixed in the reference genomes of model organisms, many genomes contain these artifacts, and researchers often discard large amounts of data in comparative genomic studies to prevent artifacts from impacting results. To address this need, we present COATi, a statistical, codon-aware pairwise aligner that supports complex insertion-deletion models and can handle artifacts present in genomic data. COATi will allow users to reduce the amount of discarded data while generating more accurate sequence alignments.

## 1 Introduction

Sequence alignment is a fundamental task in bioinformatics and a cornerstone step in comparative and functional genomic analysis (Rosenberg 2009). While sophisticated advances have been made, the challenge of alignment inference has not been fully solved (Morrison 2015). The alignment of protein coding DNA sequences is one such challenge, and a common approach to this problem is to perform alignment inference in amino-acid space (e.g. Bininda-Emonds, Olaf 2005; Abascal et al. 2010). While this approach is an improvement over DNA models, it discards information, underperforms compared to alignment at the codon level, and fails in the presence of artifacts such as frameshifts and early stop codons. Although some aligners incorporate codon substitution models, they do not support frameshifts or lack a statistical model. In addition, while modeling indels to appear within codons is rare, this is often the case (Zhu 2022; Taylor et al. 2004). Considering gaps to only appear between codons can result in missing the optimal alignment and inflate estimates of sequence divergence (Fig. 1).

Uncorrected errors in the alignment stage can lead to erroneous results in comparative and functional genomic studies (Schneider et al. 2009). Current methods are ill-equipped to handle common artifacts in genomic data, requiring costly curation practices that discard significant amounts of information. To address this problem, we present COATi, short for COdon-aware Alignment Transducer, a pairwise statistical aligner that incorporates codon substitution models and is robust to artifacts present in modern genomic data.

**a) Biology**

	Ser	His	Lys	Gly	Arg	Ser	Asp	Ala	
A:	TCC	CAT	AAG	GGG	CGG	T-- -CG	GAC	GCC	---
D:	TCC	CA-	--G	GGG	CGG	TCC CAG	GAC	GCC	ACG
	Ser		Gln	Gly	Arg	Ser	Gln	Asp	Ala
									Thr

**b) Prank (codon)**

	Ser	His	Lys	Gly	Arg	Ser		Asp	Ala
A:	TCC	CAT	AAG	GGG	CGG	TCG	---	GAC	GCC
D:	TCC	CAG	---	GGG	CGG	TCC	CAG	GAC	GCC
	Ser	Gln		Gly	Arg	Ser	Gln	Asp	Ala
									Thr

**c) MAFFT, ClustalΩ, and MACSE**

	Ser	His	Lys	Gly	Arg	Ser	Asp	Ala	
A:	TCC	CAT	AAG	GGG	CGG	TCG	GAC	GCC	---
D:	TCC	CAG	GGG	CGG	TCC	CAG	GAC	GCC	ACG
	Ser	Gln	Gly	Arg	Ser	Gln	Asp	Ala	Thr

**d) COATi**

	Ser	His	Lys	Gly	Arg	Ser	Asp	Ala	
A:	TCC	CAT	AAG	GGG	CGG	T-- -CG	GAC	GCC	---
D:	TCC	CA-	--G	GGG	CGG	TCC CAG	GAC	GCC	ACG
	Ser		Gln	Gly	Arg	Ser	Gln	Asp	Ala
									Thr

**Figure 1:** Standard algorithms produce suboptimal alignments. (a) shows a possible alignment of an ancestor sequence (A) and a descendant sequence (D). (b), (c), and (d) are the results of different aligners. Nucleotide mismatches are highlighted in red. Phase 0, phase 1, and phase 2 indels are shown in gray, purple, and orange, respectively. Additionally, the orange indel is type II (an amino-acid indel plus an amino-acid change) while the purple indel is type I (an amino-acid indel only). COATi is the only aligner able to retrieve the biological alignment in this example.

## Materials and Methods

Statistical alignment is typically performed using pairwise hidden Markov models (pair-HMMs), which have the ability to rigorously model molecular sequence evolution (Bradley and Holmes 2007). Pair-HMMs are computational machines with two output tapes that contain a finite number of states typically labeled match, insert, and delete that emit symbols (nucleotides or amino acids) to one or both tapes. Each tape represents a sequence and a path through a pair-HMM is a possible pairwise alignment. Conceptually, these machines generate two sequences ( $X$  and  $Y$ ) from an unknown ancestor and can calculate the probability that two sequences are related, represented by  $P(X, Y)$  (Yoon 2009).

A limitation of pair-HMMs is the ability to only model the evolution of two related sequences from an unknown ancestor. Finite-state transducers (FSTs) have similar benefits to pair-HMMs with the additional feature to generate a descendant sequence given an ancestral one. FSTs con-

sume symbols from an input tape and emit symbols to an output tape. Properly weighted, an FST can calculate the probability that a descendant sequence  $Y$  evolved from an ancestor sequence  $X$ , represented by  $P(Y|X)$ . Furthermore, well-established algorithms for combining FSTs in different ways allow the design of complex models by combining simpler FSTs (Bradley and Holmes 2007). A powerful and versatile algorithm for comparative sequence analysis is composition, which consists of sending the output of one FST into the input of a second FST. The model implemented in COATi is designed by composing smaller FSTs, each representing a specific process.

Genome quality impacts conclusions drawn from comparative genomic studies. **TODO: Juan, add citations.** Genomes for model organisms often get refined over many iterations and achieve high quality with meticulously curated protein coding sequences. In contrast, genomes for non-model organisms might only receive partial curation and typically have lower quality sequences and annotations. These genomes often lack the amount of sequencing data needed to fix artifacts, including missing exons, erroneous mutations, and indels (Jackman et al. 2018). FSTs and their powerful methods provide a well-suited framework to statistically align a sequence from a non-model organism against a sequence from a model organism.

COATi implements the pairwise alignment of a potentially lower-quality sequence against a high-quality sequence as a path through the Evolution FST (Fig. 2), based on existing transducers (e.g. Holmes and Bruno 2001). Here, COATi treats the high-quality (reference) sequence as the “ancestor” and the potentially lower-quality sequence as the “descendant”. This FST is the result of composing a substitution FST that encodes a codon model (Fig. 2-a) and an indel FST that models insertions and deletions, including frameshifts (Fig. 2-b). A key innovation of this FST with respect to others is the combination of a codon substitution model with a nucleotide-based geometric indel model that allows gaps to occur at any position.

Composing both sequences with the Evolution FST results in the transducer of all possible alignments. Any path through this FST represents a pairwise alignment, while the shortest path corresponds to the best alignment. All FST operations in COATi, including model development, composition, search for the shortest path, and other optimization algorithms, are performed using the C++ openFST library (Allauzen et al. 2007). However, the Evolution FST has a large state space to keep track of codon substitution rates when codons might be interspersed with indel events. This additional state space increase the computational complexity of the alignment algorithm.

Codon substitution models are uncommon in sequence aligners, despite their extensive use in phylogenetics. COATi implements the Muse and Gaut (1994) codon model (codon-triplet-mg) and the Empirical Codon Model (Kosiol et al. 2007) (codon-triplet-ecm). It also lets the user provide a codon substitution matrix. The default FST model (codon-triplet-mg) does not allow substitutions from stop codons **TODO: Juan is this still correct? Do we need to mention the extra error rate.**, although it supports mutations to (early) stop codons under the assumption that these are artifacts common in low-quality data.

To reduce the runtime complexity of COATi, we have also developed an approximation of the Evolution FST that can be implemented with standard dynamic programming techniques. This approximation uses a marginal substitution model where the output nucleotides are independent of one another and only depend on the input codon and position. This produces a  $(61 \times 3) \times 4$  substitution model and eliminates the need to track dependencies between output nucleotides.



sequence pairs that contained gaps identified by at least one aligner, and 5399 ungapped sequence pairs. We then randomly introduced gap patterns extracted from all five methods into the ungapped sequence pairs to generate the benchmark alignments. Alignment accuracy was measured using the distance metric  $d_{seq}$  (Blackburne and Whelan 2011) between simulated and inferred alignments. In addition, accuracy of positive and negative selection was calculated using the  $F_1$  score by estimating  $k_s$  and  $k_a$  statistics (Li 1993).

	COATi	PRANK	MAFFT	ClustalΩ	MACSE
Avg alignment error ( $d_{seq}$ )	0.00101	0.01010	0.00982	0.01582	0.00932
Perfect alignments	2452	22	2175	1150	1580
Best alignments	3624	155	2763	1609	2081
Imperfect alignments	1136	3566	1413	2438	2008
F1 score of positive selection	90.8%	80.5%	73.5%	61.3%	70.6%
F1 score of negative selection	99.1%	98.0%	97.2%	96.0%	97.4%

**Table 1:** COATi generates better alignments than other alignment algorithms. Results of COATi, PRANK, MAFFT, ClustalΩ, and MACSE aligning 5399 empirically simulated sequence pairs. Perfect alignments have  $d_{seq} = 0$ , best alignments have the lowest  $d_{seq}$ , and imperfect alignments have  $d_{seq} > 0$  when at least one aligner found a perfect alignment.

COATi was significantly more accurate (lower  $d_{seq}$ ) at inferring simulated alignments compared to other methods; all p-values were less than  $2.2 \cdot 10^{-16}$  according to the one-tailed Wilcoxon signed rank test. In addition, COATi produced more perfect alignments, less imperfect alignments, and more accurately retrieved events of positive selection (Table 1). It obtained better results compared to a wide variety of alignment strategies. ClustalΩ, performing a common approach of aligning via amino acid translations, obtained the highest average alignment error and had difficulties retrieving positive selection. MACSE, which allows frameshifts, is also based on an amino acid model and obtained similar results to the DNA-based MAFFT. PRANK, using a codon model, had a similar average alignment error to MACSE and MAFFT but had issues recovering the simulated alignments.

Despite human and gorilla sequences having a relatively short evolutionary distance, COATi showed a biologically significant improvement over other methods, with an average alignment error nine-fold smaller than the next best method. COATi is an FST-based application that can calculate the optimal alignment between a pair of sequences in the presence of artifacts using a statistical model. It will allow researchers to analyze more data with higher accuracy and facilitate the study of important biological processes that shape genomic data.

## Availability

The source code for COATi, along with documentation, is freely available on GitHub: <https://github.com/CartwrightLab/coati> and is implemented in C++. Code to replicate the analysis can be found on GitHub: <https://github.com/jgarciamesa/coati-testing>.

## Acknowledgments

This research was funded by NSF award DBI-1929850.

*Conflict of interest:* none declared.

## References

- Abascal F, Zardoya R, and Telford MJ. 2010. Translatorex: multiple alignment of nucleotide sequences guided by amino acid translations. *Nucleic acids research* 38:W7–W13.
- Allauzen C, Riley M, Schalkwyk J, Skut W, and Mohri M. 2007. Openfst: A general and efficient weighted finite-state transducer library. In *International Conference on Implementation and Application of Automata*, pages 11–23. Springer.
- Bininda-Emonds, Olaf. 2005. transalign: using amino acids to facilitate the multiple alignment of protein-coding dna sequences. *BMC bioinformatics* 6:1–6.
- Blackburne BP and Whelan S. 2011. Measuring the distance between multiple sequence alignments. *Bioinformatics* 28:495–502. ISSN 1367-4803.
- Bradley RK and Holmes I. 2007. Transducers: an emerging probabilistic framework for modeling indels on trees. *Bioinformatics* 23.
- Holmes I and Bruno WJ. 2001. Evolutionary hmms: a bayesian approach to multiple alignment. *Bioinformatics* 17:803–820.
- Hubbard T, Barker D, Birney E, Cameron G, Chen Y, Clark L, Cox T, Cuff J, Curwen V, Down T, et al. 2002. The ensembl genome database project. *Nucleic acids research* 30:38–41.
- Jackman SD, Coombe L, Chu J, Warren RL, Vandervalk BP, Yeo S, Xue Z, Mohamadi H, Bohlmann J, Jones SJ, et al. 2018. Tigmint: correcting assembly errors using linked reads from large molecules. *BMC bioinformatics* 19:1–10.
- Katoh K, Misawa K, Kuma Ki, and Miyata T. 2002. Mafft: a novel method for rapid multiple sequence alignment based on fast fourier transform. *Nucleic acids research* 30:3059–3066.
- Kosiol C, Holmes I, and Goldman N. 2007. An empirical codon model for protein sequence evolution. *Molecular biology and evolution* 24:1464–1479.
- Li WH. 1993. Unbiased estimation of the rates of synonymous and nonsynonymous substitution. *Journal of molecular evolution* 36:96–99.
- Löytynoja A. 2014. Phylogeny-aware alignment with prank. In *Multiple sequence alignment methods*, pages 155–170. Springer.
- Morrison DA. 2015. Is sequence alignment an art or a science? *Systematic Botany* 40:14–26.
- Muse SV and Gaut BS. 1994. A likelihood approach for comparing synonymous and nonsynonymous nucleotide substitution rates, with application to the chloroplast genome. *Molecular biology and evolution* 11:715–724.
- Ranwez V, Harispe S, Delsuc F, and Douzery EJ. 2011. Macse: Multiple alignment of coding sequences accounting for frameshifts and stop codons. *PloS one* 6:e22,594.

- 156 Rosenberg MS. 2009. *Sequence alignment: methods, models, concepts, and strategies*. Univ of  
157 California Press.
- 158 Schneider A, Souvorov A, Sabath N, Landan G, Gonnet GH, and Graur D. 2009. Estimates of pos-  
159 itive darwinian selection are inflated by errors in sequencing, annotation, and alignment. *Genome*  
160 *biology and evolution* 1:114–118.
- 161 Sievers F, Wilm A, Dineen D, Gibson TJ, Karplus K, Li W, Lopez R, McWilliam H, Remmert M,  
162 Söding J, et al. 2011. Fast, scalable generation of high-quality protein multiple sequence align-  
163 ments using clustal omega. *Molecular systems biology* 7:539.
- 164 Taylor MS, Ponting CP, and Copley RR. 2004. Occurrence and consequences of coding sequence  
165 insertions and deletions in mammalian genomes. *Genome research* 14:555–566.
- 166 Yoon BJ. 2009. Hidden markov models and their applications in biological sequence analysis.  
167 *Current genomics* 10:402–415.
- 168 Zhu Z. 2022. Profiling of indel phases in coding regions. Ph.D. thesis, Arizona State University.