CITABRIA 7ECA GROUND PROCEDURES		
DISPATCH	StarterPUSH	Tail Wh
Weather BRIEF	Throttle 1000 RPM	Ties
NOTAMsCHECK	Oil Pressure CHECK Ammeter CHECK	Doors FI
W&B CHECK Perf. Regs CHECK	Mixture LEAN	F1I
SquawksCHECK	Lights ON	Run
Illness CHECK	Radios SET	Mixture
Medication CHECK Stress CHECK	ATIS GET Barometer SET	Evacua
Alcohol CHECK	XPDRSET	1
Fatigue CHECK	Taxi Diag OPEN	Crank
Eating CHECK	TAXI	Mixture Throttle
INSPECTION	Brakes TEST	Fuel S
Fuel DRAIN, CHECK	Controls WIND	Evacua
AV1ATE CHECK AROW CHECK	RUNUP	
Mags OFF	Brakes SET Controls CORRECT	
Fuel Gauges TRUE	TrimTAKEOFF	
Fuel ShutoffIN MasterON	Flight Inst CHECK	
Lights CHECK	Fuel ShutoffIN	
Stall Horn CHECK	Mixture BEST POWER Throttle 1800 RPM	
Master OFF	Mags CHECK	
ELT ARMED Oil 6 qts	Carb. Heat CHECK	
Exterior CHECK	Engine Inst CHECK Throttle 1000 RPM	
Ties/ChocksREMOVE	Doors CLOSED	
Walkaround EXECUTE	Seatbelts CHECK	
START Passangers RPIEE	SWITCH TO FLIGHT	
Passengers BRIEF Seatbelts CHECK	SHUTDOWN	
Stick FULL AFT	XPDR SET, OFF	
Breakers CHECK	Brakes SET Lights OFF	
Fuel Shutoff IN Brakes SET	GPS OFF	
Electrical OFF	Mixture IDLE C/O	
Door CLOSED	Mags OFF	
Carb. Heat OFF	Master OFF Flight Plan CLOSE	
MixtureRICH HOT: SKIP PRIME	SECURING	
Prime4x	Front Lap Belt . AROUND	
Primer LOCKED	STICK	
Master Switch ON	Back Lap Belt . BUCKLE	
Mags ON Throttle SLIGHT	Hobbs/Tach NOTE Squawks NOTE	
Brakes SET	Sun ShadesREPLACE	
Clear Prop . ANNOUNCE	WheelsCHOCK	

Tail Wheel ... REORIENT
TiesTIE
DoorsLOCK

FIRE ON START

IF START

Run 5 sec
Mixture IDLE C/O
Evacuage GO

IF NO START

Crank CONTINUE
Mixture IDLE C/O
Throttle FULL
Fuel Shutoff OUT
Evacuage GO

CITABRIA 7ECA FLIGHT PROCEDURES			
TAKEOFF BRIEF	APPROACH CFGS	NOTES	
Runway CHECK Crosswind CHECK Abort Speed NOTE Technique NOTE Min. Ret. Alt NOTE Best Glide NOTE Time NOTE Mixture BEST POWER	NORMAL Speed 60-65 Landing FULL STALL WHEEL Speed 65-70 Landing MAINS Stick FORWARD	 All airspeeds in MPH Carb. heat always on if icing suspected, indicated by gradual loss of RPM Only use rudder on 	
CLIMB	LOW VOLTAGE Master	takeoff and landing (no brakes)	
Throttle OPEN	Nonessentials OFF Flight TERMINATE	Mixture should be leaned	
IF BELOW 5000	at any aititude when		
Mixture BEST POWER Engine Inst CHECK Speed 75-80 Best Rate 69 Best Angle 58	Master CYCLE Flight TERMINATE ENGINE FAILURE Best Glide65	der 75% power. Lean until engine roughness, then enrichen to smoothness.	
PRE-DESCENT	Fuel Shutoff ON	IMPORTANT NUM. V _{rotate} 60	
Engine InstCHECK ATISGET BarometerSET TowerCONTACT MixtureENRICH LightsON	Throttle	Vx 58 Vy 75 Va 120 Vno 120 Vne 162 Best Glide 65 Max Gross 1800	
AFTER LANDING	Squawk	Max Crosswind15	
Trim TAKEOFF Mixture LEAN Taxi Diag OPEN Carb. Heat OFF SWITCH TO GROUND TAKEOFF CFGS	Emergency DECLARE Fuel ShutoffOUT MixtureIDLE C/O MagsOFF LandingEXECUTE ENGINE FIRE	Fuel35	
NORMAL	Mixture IDLE C/O Fuel ShutoffOUT		
Rotate	Switches ALL OFF Cabin Heat OFF Extinguisher USE Flight TERMINATE		
Rotate	ELECTRICAL FIRE ElectricalOFF VentsOPEN		
Attitude TAIL LOW After Liftoff LEVEL	ExtinguisherUSE IF FIRE CONTINUES		

Flight **TERMINATE**