| PART NUMBER | AMPERAGE | UL AC VOLTAGE | AC I.R. | UL DC VOLTAGE | DC I.R. | IEC VOLTAGE | IEC I.R. | LABEL STYLE |
|--------------|----------|---------------|---------|---------------|---------|-------------|----------|-------------|
| PSR030FL0125 | 125A | 700VAC | 200kA | 600VDC | 150kA | 690VAC | 200kA | 914-981 |
| PSR030FL0160 | 160A | 700VAC | 200kA | 600VDC | 150kA | 690VAC | 200kA | 914-981 |
| PSR030FL0200 | 200A | 700VAC | 200kA | 600VDC | 150kA | 690VAC | 200kA | 914-981 |
| PSR030FL0250 | 250A | 700VAC | 200kA | 600VDC | 150kA | 690VAC | 200kA | 914-981 |
| PSR030FL0315 | 315A | 700VAC | 200kA | 600VDC | 150kA | 690VAC | 200kA | 914-981 |
| PSR030FL0350 | 350A | 700VAC | 200kA | 600VDC | 150kA | 690VAC | 200kA | 914-981 |
| PSR030FL0400 | 400A | 700VAC | 200kA | 600VDC | 150kA | 690VAC | 200kA | 914-981 |
| PSR030FL0450 | 450A | 700VAC | 200kA | 600VDC | 150kA | 690VAC | 200kA | 914-981 |
| PSR030FL0500 | 500A | 700VAC | 200kA | 600VDC | 150kA | 690VAC | 200kA | 914-981 |
| PSR030FL0550 | 550A | 700VAC | 200kA | 600VDC | 150kA | 690VAC | 200kA | 914-981 |
| PSR032FL0630 | 630A | 700VAC | 200kA | 600VDC | 150kA | 690VAC | 200kA | 914-981 |
| PSR032FL0700 | 700A | 700VAC | 200kA | 600VDC | 150kA | 690VAC | 200kA | 914-981 |
| PSR032FL0800 | 800A | 700VAC | 200kA | 600VDC | 150kA | 690VAC | 200kA | 914-981 |
| PSR032FL0900 | 900A | 700VAC | 200kA | 600VDC | 150kA | 690VAC | 200kA | 914-981 |
| PSR032FL1000 | 1000A | 700VAC | 200kA | 600VDC | 150kA | 690VAC | 200kA | 914-981 |
| PSR032FL1100 | 1100A | 700VAC | 200kA | 600VDC | 150kA | 690VAC | 200kA | 914-981 |
| PSR033FL1100 | 1100A | 700VAC | 200kA | 600VDC | 150kA | 690VAC | 200kA | 914-981 |
| PSR033FL1250 | 1250A | 700VAC | 200kA | 600VDC | 150kA | 690VAC | 200kA | 914-981 |
| PSR033FL1400 | 1400A | 700VAC | 200kA | 500VDC | 150kA | 690VAC | 200kA | 914-981 |
| PSR033FL1500 | 1500A | 650VAC | 200kA | 500VDC | 150kA | 600VAC | 200kA | 914-981 |
| PSR033FL1600 | 1600A | 650VAC | 200kA | 500VDC | 150kA | 600VAC | 200kA | 914-981 |
| PSR033FL1800 | 1800A | 650VAC | 200kA | 500VDC | 150kA | 600VAC | 200kA | 914-981 |
| PSR033FL2000 | 2000A | 600VAC | 200kA | 500VDC | 150kA | 550VAC | 200kA | 914-981 |
| PSR071FL0160 | 160A | 1300VAC | 100kA | 1000VDC | 150kA | 1250VAC | 100kA | 914-981 |
| PSR071FL0200 | 200A | 1300VAC | 100kA | 1000VDC | 150kA | 1250VAC | 100kA | 914-981 |
| PSR071FL0250 | 250A | 1300VAC | 100kA | 1000VDC | 150kA | 1250VAC | 100kA | 914-981 |
| PSR071FL0315 | 315A | 1300VAC | 100kA | 1000VDC | 150kA | 1250VAC | 100kA | 914-981 |
| PSR071FL0350 | 350A | 1300VAC | 100kA | 1000VDC | 150kA | 1250VAC | 100kA | 914-981 |
| PSR071FL0400 | 400A | 1300VAC | 100kA | 1000VDC | 150kA | 1250VAC | 100kA | 914-981 |
| PSR071FL0450 | 450A | 1300VAC | 100kA | 1000VDC | 150kA | 1250VAC | 100kA | 914-981 |
| PSR072FL0500 | 500A | 1300VAC | 100kA | 900VDC | 150kA | 1250VAC | 100kA | 914-981 |
| PSR072FL0550 | 550A | 1300VAC | 100kA | 900VDC | 150kA | 1250VAC | 100kA | 914-981 |
| PSR072FL0630 | 630A | 1300VAC | 100kA | 900VDC | 150kA | 1250VAC | 100kA | 914-981 |
| | • | | | | | | | |

| | Littelfuse® |
|---|------------------------------------|
| | POWR-SPEED™ |
| PART NUMBER ———————————————————————————————————— | → PSRxxxFLxxxx → xxxxA |
| UL AC VOLTAGE, I.R.———— UL DC VOLTAGE, I.R.————— | → xxxVAC, xxxkA → xxxVDC, xxxkA |
| IEC VOLTAGE, I.R.———— | xxxVAC, xxxkA |
| DATE CODE————— | ⊞▶ IEC60269-4, aR |
| | RoHS LXXXXF CE |
| MEASURED RESISTANCE (SEE NOTE 6) | ✓ X.XXX mΩ MADE IN MEXICO |

| REVISION | | | | | |
|----------|--------|-------------------------|--|--|--|
| REV | DATE | DESCRIPTION | | | |
| Α | 3/1/17 | 517205GCP - RELEASE MRY | | | |

NOTES

- 1. LABEL MATERIAL TO BE SEMI GLOSS PHARMACEUTICAL LITHO MATERIAL, A 40# LINER WITH PERMANENT ADHESIVE.
- 2. LOGO INFORMATION TO CONFORM TO LITTELFUSE PRINT 095115.
- 3. REFER TO CHART FOR LABEL INFORMATION BY PART NUMBER.
- 4. RoHS, CCC, CE AND UL LOGOS TO CONFORM TO LITTELFUSE PRINT LS-000003.5. PRINTING TO BE CLEAR, LEGIBLE AND NOT SMEARED; CANNOT OVERLAP.
- •6. EACH FUSE MUST BE LABELED WITH THE MEASURED RESISTANCE.

| • | DENOTES CRITICAL CHARACTERISTICS. | | | | | |
|---|--|--|--------------|-------------------------------|--|--|
| СРК | DENOTES CPK DIMENSIONS, -MINIMUM CPK VALUE | | | | | |
| <u>(ST)</u> | DENOTES A CHARACTERISTIC THAT PROVIDES AN INDICATION OF PROCESS PERFORMANCE. PROCEDURE FOR MEASUREMENT AND TRACKING TO BE DEFINED IN LITTELFUSE INSPECTION INSTRUCTIONS. | | | | | |
| СР | DENOTES CP DIMENSIONS, -MINIMUM CP VALUE MUST BE WITHIN THE DIMENSIONAL LIMITATIONS SHOWN ON DRAWING AND INITIALLY LOCATED TO ALLOW FOR MAXIMUM TOOL LIFE. | | | | | |
| MATL SPEC SEE NOTE 1 | | | FINISH | | | |
| DRW DATE 2/3/2017 | | | SCALE NTS | FINISH GOOD WT GRAMS/PIECE | | |
| UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN MILLIMETERS, DIMENSIONS IN BRACKETS [] ARE INCHES DIMENSIONING AND DO NOT INCLUDE PLATING. TOLERANCING TO BE INTERPRETED IN ACCORDANCE WITH ANSI Y14.5M-1994 | | | | | | |
| 3RD ANGLE PROJECTION ONE PLACE DEC ± .25 [.01] FRACTION ± | | | | | | |

TITLE

FUSE LABEL SPEC FOR PSR SERIES METRIC FLUSH MOUNT

TWO PLACE DEC ± .100 [.004]



REVISION DRWG NO.

LS-000218

ANGULAR ±1°

SHEET 1 OF 1

