

Improving Webcam Eye-Tracking: Impact of Hardware and Head Stabilization on Data Quality

Jason Geller^{1*} , João Veríssimo²  & Julia Droulin³ 

¹Boston College, Department of Psychology and Neuroscience

²University of Lisbon, School of Arts and Humanities

³University of North Carolina - Chapel Hill, Speech and Hearing Division

Webcam-based eye-tracking offers a scalable and accessible alternative to traditional lab-based systems. While recent studies demonstrate that webcam eye-tracking can replicate canonical effects across domains such as language, memory, and decision-making, questions remain about its precision and reliability. In particular, spatial accuracy, temporal resolution, and attrition rates are often poorer than those observed with research-grade systems, raising the possibility that environmental and hardware factors introduce substantial noise. The present registered report directly tests two factors that may introduce noise into webcam data: camera quality and head stabilization. In Experiment 1, we examine the effect of external webcam quality (high vs. standard) in a single word Visual World Paradigm (VWP) task, testing whether using a better webcam can yield stronger competition effects, earlier effect onsets, and reduced attrition. In Experiment 2, we assess the impact of head stabilization (chinrest vs. no chinrest) under identical environmental conditions. Together, these studies identify the impact of hardware and movement on webcam eye-tracking data quality. Results will inform a more methodological understanding of webcam-based eye-tracking, clarifying whether its current limitations are intrinsic to the technology or can be mitigated through improved hardware and experimental control. These set of studies have implications for both online and in-lab utilization of webcam eye-tracking.

Keywords: webcam eye-tracking, webcams, VWP, Lab-based experimentation, competition, spoken word recognition

Words: 4742

Online experimentation in the behavioral sciences has advanced considerably since its introduction at the 1996 Society for Computers in Psychology (SCiP) conference in Chicago, IL (Reips, 2021). One methodological domain that has shown particular promise in moving online is eye tracking. Traditionally, eye-tracking studies required controlled laboratory settings equipped with specialized and costly hardware—a process that is both resource- and time-intensive. More recently, however, a growing body of research has shown that eye tracking can be successfully adapted to online environments (Bogdan et al., 2024; Bramlett & Wiener, 2024; Cruysen et al., 2023; James et al., 2025; Prystauka et al., 2024; Slim et al., 2024; Slim & Hartsuiker, 2023; Vos et al., 2022; Yang & Krajbich, 2021; Özsoy et al., 2023). By leveraging computers with webcams, researchers can now record eye movements remotely, making it possible to collect data from virtually any location at any time. This shift not only enhances scalability, but also broadens access to more diverse and representative participant samples.

Webcam-based eye tracking has become an increasingly viable and accessible method for behavioral research. Implementation typically requires only a standard computing device (e.g., laptop, desktop, tablet, or smartphone) equipped with a built-in or external webcam. Data are collected through a web browser running dedicated software capable of recording and estimating gaze position in real time. This accessibility has been further enhanced by the integration of webcam-based eye tracking into several established experimental platforms, including Gorilla (Anwyl-Irvine et al., 2019), PsychoPy/PsychoJS (Peirce et al., 2019), jsPsych (Leeuw, 2014), PCIBex (Zehr & Schwarz, 2022), and Labvanced (Kaduk et al., 2023).

*Send correspondence to: Jason Geller, drjasongeller@gmail.com.

To reliably estimate where users are looking, webcam-based eye tracking typically relies on appearance-based methods, which infer gaze direction directly from visual features of the eye region (e.g., pupil and iris appearance) (Cheng et al., 2024; Saxena et al., 2024). Recent work has extended these methods using deep learning to learn gaze–appearance mappings directly from data (Kaduk et al., 2023; Saxena et al., 2024). This contrasts with research-grade eye trackers, which use model-based algorithms combining infrared illumination with geometric modeling of the pupil and corneal reflections (Cheng et al., 2024).

The most widely used library for webcam eye tracking is WebGazer.js (Papoutsaki et al., 2016; Patterson et al., 2025). WebGazer.js is an open-source JavaScript library that performs real-time gaze estimation using standard webcams. It is an appearance-based method that leverages computer vision techniques to detect the face and eyes, extract image features, and map these features onto known screen coordinates during a brief calibration procedure. Once trained, gaze locations on the screen are estimated via ridge regression (Papoutsaki et al., 2016).

Although webcam eye-tracking is still relatively new, validation efforts are steadily accumulating and the results are encouraging. Researchers have successfully applied webcam-based methods to domains such as language (Bramlett & Wiener, 2025; Geller et al., 2025; Prystauka et al., 2024), judgment and decision-making (Yang & Krajovich, 2021), and memory (James et al., 2025). Overall, these studies replicate canonical effects and show strong convergence with findings from traditional lab-based eye-tracking systems.

However, there are several limitations associated with web-based eye tracking. First, experimental effects are typically smaller than those observed in lab-based studies (Bogdan et al., 2024; Cruysen et al., 2023; Degen et al., 2021; Kandel & Snedeker, 2024; Slim et al., 2024; Slim & Hartsuiker, 2023). Second, relative to research-grade eye trackers, both spatial accuracy/precision and temporal resolution tend to be lower with webcam eye-tracking. Spatial accuracy refers to the extent to which measured gaze positions deviate from the true gaze point, whereas precision reflects the consistency of those measurements over time (Carter & Luke, 2020). In webcam-based eye tracking, spatial accuracy and precision often exceed 1° of visual angle (Semmelmann & Weigelt, 2018). Regarding temporal resolution, sampling rates are typically more variable, with most webcams rarely exceeding 30Hz. Consequently, detectable effects tend to span a relatively broad temporal range, with some users reporting a 1000 ms onset difference (Geller et al., 2025; Semmelmann & Weigelt, 2018; Slim et al., 2024; Slim & Hartsuiker, 2023). This variability makes webcam eye tracking less suitable for studies that require fine-grained spatial or temporal fidelity—for example, paradigms involving many or small areas of interest (AOIs) (James et al., 2025) or tasks requiring millisecond-level temporal precision (Slim et al., 2024). Lastly, webcam-based studies tend to exhibit higher attrition rates. For instance, Patterson et al. (2025) reported an average attrition rate of approximately 13% across studies, with substantial variability across individual experiments (Geller et al., 2025; Prystauka et al., 2024). Together, increased noise and variation often necessitates the need for larger sample sizes for comparable power and to combat high attrition.

An open question is whether the limitations of web-based eye-tracking primarily stem from the WebGazer.js algorithm itself or from environmental and hardware constraints—and, crucially, whether future improvements in the set up of webcam eye-tracking can mitigate these issues. On the algorithmic side, recent work (James et al., 2025; Yang & Krajovich, 2021) demonstrated that modifying WebGazer.js so that the sampling rate is polled consistently and timestamps are aligned to data acquisition (rather than completion) markedly improves temporal resolution. Implementing these changes within online experiment platforms such as Gorilla and jsPsych has brought webcam-based eye-tracking closer to the timing fidelity achieved in laboratory settings. For example, using the Gorilla platform, Prystauka et al. (2024) reported a 50 ms timing difference, while Geller et al. (2025) observed a 100 ms difference between lab-based and online effects.

To our knowledge, no study has directly tested how environmental and hardware constraints impact webcam-based eye-tracking data. Slim & Hartsuiker (2023) provided some evidence suggesting that hardware quality may underlie some of these limitations, reporting a positive correlation between sampling rate and calibration accuracy. Similarly, Geller et al. (2025) found that participants who failed calibration more often reported using standard-quality built-in webcams and working in suboptimal environments (e.g., natural lighting). Together, these findings suggest

that both hardware and environmental factors may contribute to the increased noise commonly observed in online eye-tracking data. In the proposed research we plan to manipulate two factors, hardware selection (webcams) and participant stability, across two experiments.

Proposed Research

To address environmental and technical sources of noise in webcam eye-tracking, we plan to bring participants into the lab to complete a Gorilla-hosted webcam task under standardized conditions. We manipulate two key factors (between subjects) across two experiments. Experiment 1 varies external webcam quality (high- vs. standard-quality external cameras). Experiment 2 varies head stabilization (with vs. without a chinrest). All sessions will use identical ambient lighting, fixed viewing distance, the same display/computer model, and controlled network settings. These manipulations specifically target sources of measurement noise induced by the quality of the webcam and the amount of movement by the participant. If noise is reduced, the measured gaze signal should become more stable and less variable across time and trials. In turn, this can make existing effects easier to detect, potentially manifesting as (a) larger effects (i.e., clearer differences in looking proportions), (b) earlier and more reliable detection of effect onsets when using time-course methods, and (c) lower calibration failure and attrition rates.

To examine these factors, we employed a paradigm widely used in psycholinguistics—the Visual World Paradigm (VWP) (Cooper, 1974; Tanenhaus et al., 1995). The VWP has been successfully adapted for webcam-based eye tracking (Bramlett & Wiener, 2024; 2025; Geller et al., 2025; Prystauka et al., 2024). Although implementations vary across studies (Huettig et al., 2011), the version used here investigates phonemic competition, wherein item sets are typically constructed so that the display contains a target (e.g., *carrot*), a cohort competitor (e.g., *carriage*), a rhyme competitor (e.g., *parrot*), and an unrelated distractor (e.g., *tadpole*). This configuration allows researchers to examine the dynamics of lexical competition—for instance, how phonologically similar words such as *carriage* (cohort effect) or *parrot* (rhyme effect) influence online spoken-word processing. Typically, fixations to cohort or rhyme competitors persist longer or emerge earlier than fixations to unrelated distractors, reflecting transient lexical activation. In the present study, we focus specifically on cohort competition effects, which have been robustly demonstrated in online VWP research (Geller et al., 2025; Slim et al., 2024), making this paradigm an ideal test case for our investigation.

The current research aims to inform best practices for webcam-based eye tracking, with particular attention to hardware and physical setup considerations (e.g., head-movement). While these guidelines will be useful for researchers conducting webcam eye tracking in the wild, they will also be valuable for studies conducted in a laboratory-setting. In particular, this work can inform researchers who may wish to use webcam eye tracking in place of more expensive infrared eye-tracking systems.

Experiment 1: High-Quality Webcam vs. Standard-Quality Webcam

Both Slim & Hartsuiker (2023) and Geller et al. (2025) observed a clear relationship between webcam quality and calibration accuracy in webcam-based eye-tracking. Building on these findings, Experiment 1 tests how webcam quality influences competition effects in a single-word VWP. Specifically, we ask whether a higher-quality webcam yields (a) a greater proportion of looks to relevant interest areas (i.e., greater looks to cohorts vs. unrelated items) (b) an earlier emergence of these effects over time, and (c) lower data attrition rates relative to a lower-quality webcam.

To address this, participants will complete the same VWP task using one of two webcam types: a high-quality external webcam (e.g., Logitech Brio) and a standard external webcam designed to emulate a typical built-in laptop camera (e.g., Logitech C270). The high-quality webcam offers higher resolution, a higher sampling rate (60Hz), and greater frame-rate stability, and more consistent illumination handling—factors expected to enhance gaze precision and tracking reliability. In contrast, more standard webcams, while representative of most participants' home setups, typically provide lower frame rates and exhibit greater variability under different lighting conditions. Comparing these two setups enables a direct assessment of how hardware quality constrains the strength, timing, and reliability of linguistic competition effects in webcam-based eye-tracking.

Hypotheses

We hypothesize several effects related to competition, onset, and attrition.

Competition Effects

(H1a) Participants will show an overall greater proportion of looks to competitors. (H1b) Webcam quality (high vs. standard) will influence the overall proportion of looks, with higher-quality webcams detecting a greater proportion of looks.

Timing/Onset Effects

(H2a) Each webcam condition will show a change in the proportion of looks across time. More specifically we hypothesize the proportion change will be non-linear across time and that there will be a difference between the two conditions across time. (H2b) For standard-quality webcams vs. high-quality webcam, onsets will be detected later due to increased noise.

Attrition

(H3) Attrition rates will be lower in the high-quality webcam condition than in the standard-quality webcam condition.

Method

All stimuli (audio and images), code, and data (raw and summary) will be placed on OSF at this link: <https://osf.io/cf6xr/overview>. The entire experiment will be stored on Gorilla's open materials with a link to preview the tasks. In addition, the code and manuscript will be fully reproducible using Quarto and the package manager nix (Dolstra & contributors, 2023) in combination with the R package {rix} (Rodrigues & Baumann, 2025). Together, nix and {rix} enable reproducible computational environments at both the system and package levels. This manuscript and all of the necessary files to reproduce it can be found on GitHub: <https://github.com/jgeller112/Webcam2Lab-VWP>.

Sampling Goal

We conducted an a priori power analysis via Monte Carlo simulation in R. Data from 21 participants, collected online using the Gorilla experimental platform during the development of the webgazerR package and employing the same stimuli and VVWP design, were used to seed the simulations. In these data, we observed a cohort effect of approximately 3%. Using this value as our seed, we collapsed the data across time bins to compute binomial counts per trial and fit a binomial generalized linear mixed model (GLMM) to obtain fixed-effect estimates. We then augmented the dataset by adding a between-subjects factor for webcam quality, with participants evenly assigned to high- and standard-quality groups. In the high-quality webcam group, we modeled both a higher overall fixation rate and a larger cohort effect, whereas in the standard-quality group the cohort effect was halved relative to the high-quality group. Simulated datasets were generated under this model, and the planned GLMM—including a condition $\times$ webcam interaction—was refit to each simulated dataset ($N = 5000$). Power was estimated as the proportion of simulations in which the interaction term exceeded $|z| = 1.96$. The analysis script to run this power analysis is located here: <https://osf.io/4trmn/files/a46g8>. Results indicated that a total of 35 participants per group ($N = 70$) would provide approximately 90% power to detect the hypothesized reduction in the cohort effect and overall fixation rate under standard-quality webcam conditions. Because this analysis only examines overall proportions and we plan to also examine effects across time, we will plan to recruit 50 participants in each group ($N = 100$ total). We will run our study until we have 100 usable participants (50 in each group). For the calibration analysis (see below), all participants who enter the study will be included.

Materials

VWP

Picture Stimuli. Stimuli were adapted from Colby & McMurray (2023). Each set comprised four images: a target, an onset (cohort) competitor, a rhyme competitor, and an unrelated item (e.g., rocket, rocker, pocket, bubble). For the webcam study, we used 30 sets (15 monosyllabic, 15 bisyllabic).

Within each set, only the target and its onset competitor served as auditory targets once each, yielding two trial types: TCRU (target-cohort-rhyme-unrelated) and TCUU (target-cohort-unrelated-unrelated). This resulted in 60 trials total (30 sets $\times$ 2 targets per set). A MATLAB script generated a unique randomized list per participant, pseudo-randomizing display positions so that each image type was approximately equally likely to appear in any quadrant across subjects.

All 120 images were from a commercial clipart database that were selected by a small focus group of students and edited to have a cohesive style using a standard lab protocol (McMurray et al., 2010). Images were all scaled to 300×300 pixels.

Auditory Stimuli. Auditory stimuli were recorded by a female monolingual speaker of English in a sound-attenuated room sampled at 44.1 kHz. Auditory tokens were edited to reduce noise and remove clicks. They were then amplitude normalized to 70 dB SPL. All .wav files were converted to .mp3 for online data collection.

Webcams

To manipulate recording quality, two webcams will be used. In the high-quality condition, we will use a Logitech Brio webcam, which records in 4K resolution (up to 4096×2160 px) with a 90° field of view and samples at 60 Hz. This setup provides high-fidelity video with greater spatial and temporal precision. In the standard-quality condition, we will use a Logitech C270 HD webcam, which records in 720p resolution and samples at 30 Hz, producing video quality comparable to that of a typical built-in laptop webcam and therefore simulating lower-quality online recordings.

Both webcams will be mounted in a fixed position above the monitor to maintain consistent framing across participants. Lighting will be standardized to ensure uniform image quality across all sessions.

Experimental Setup and Procedure

All tasks will be completed in a single session lasting approximately 30 minutes. The experiment will be programmed and administered in Gorilla (Anwyl-Irvine et al., 2019). Participants will be brought into a room in the Human Neuroscience Lab at Boston College and seated in front of a 23-inch Dell U2312HM monitor (1920×1080 px) approximately 65 cm from the screen. Auditory information will be presented over Sony ZX110 headphones to ensure consistent audio presentation and minimize background noise. The experimental tasks will be fixed and presented in this order: informed consent, single word VWP, and a demographic questionnaire. The entire experiment can be viewed on Gorilla at this link:

Before the main task, an instructional video will demonstrate the calibration procedure. Calibration will occur twice—once at the start and again after 30 trials—with up to three attempts allowed each time. In each calibration phase, participants will view nine calibration targets and five validation points, looking directly at each target as instructed. Participants will then complete four practice trials to familiarize themselves with the task. Each trial begins with a 500 ms central fixation cross, followed by a preview display of four images located in the screen's corners. After 1500 ms, a start button appears at the center; participants click it to confirm fixation before hearing the spoken word. The images remain visible throughout the trial, and participants indicate their response by clicking the image corresponding to the spoken target. A response deadline of 5 seconds will be used. Eye movements are recorded continuously during each. Following the main VWP task, participants will complete a brief demographic questionnaire, after which they will be thanked for their participation.

Data Preprocessing and Exclusions

We will follow guidelines outlined in Geller et al. (2025). At the participant level, individuals with overall task accuracy below 80% and fewer than 40 trials will be removed from the analysis. At the trial level, only correct-response trials (accuracy = 1) will be retained. Reaction times (RTs) outside ± 2.5 SD of the participant-level distribution (computed within condition) will be discarded.

For eye-tracking preprocessing we will use the {webgazeR} package in R that contains helper functions to preprocess webcam eye-tracking data. All webcam eye-tracking files and behavioral data will be merged. Data quality will be screened via sampling-rate checks with very low-frequency recordings (e.g., < 15 Hz) by-participant and by-trial excluded (Bramlett & Wiener,

2025; Vos et al., 2022). We will quantify out-of-bounds (OOB) samples—gaze points outside the normalized screen (1,1)—and remove participants and trials with excessive OOB data ($> 30\%$). OOB samples will be discarded prior to analysis. In addition, Gorilla provides calibration/quality metrics (“convergence” and “confidence,” both 0–1); trials with convergence < 0.5 or confidence > 0.5 will be excluded.

Areas of Interest (AOIs) will be defined in normalized coordinates as the four screen quadrants, and gaze samples will be assigned to AOIs. To create a uniform time base, data will be downsampled into 50-ms bins. Trial time will be aligned to the actual stimulus onset by taking the audio onset metric provided by Gorilla. We then subtract 100 ms due to silence prefixed to the audio recording.

For the analysis portion we will count the number of looks to cohort (vs. unrelated) items. We will first count the number of looks to cohorts and unrelated items by participant $\times$ trial $\times$ time bin. Then we will take the count over trial to give us a dataset with participant $\times$ time bin for each webcam. These look counts will serve as inputs to the statistical models and summaries.

The display contained two types of critical trials: TCRU (target–cohort–rhyme–unrelated) and TCUU (target–cohort–unrelated–unrelated). Because some items served as a rhyme competitor (R) in TCRU trials and as an unrelated item (U) in TCUU trials, we adopted a principled scheme to define the “unrelated” baseline in our cohort analyses. For the primary analysis of cohort competition, we used a single, unrelated competitor as the baseline. Concretely, For each trial, we identified one critical unrelated item that was never used as a rhyme competitor (R) anywhere in the experiment. In TCRU trials, this was the standard unrelated item. In TCUU trials, when one of the two unrelated objects also served as a rhyme competitor in other trials, we excluded that item from the C–U contrast and treated only the remaining object as the unrelated baseline.

Analysis Plan

Competition and Onset Effects

To analyze overall competition effects and onset latency, we will use generalized additive mixed models (GAMMs; (Wood, 2017)). GAMMs extends the generalized linear modeling framework by modeling effects that are expected to vary nonlinearly over time—a common feature in the VWP (Brown-Schmidt et al., 2025; Ito & Knoeferle, 2022; Mitterer, 2025; Verissimo & Lago, 2025). These models capture non-linear effects by fitting smoothing splines to the data using data-driven, machine-learning-based methods, with the amount of non-linearity captured by how “wiggly” the time course. This approach reduces the risk of over-fitting and eliminates the need to use polynomial terms, as required in traditional growth curve models (Mirman, 2014). Importantly, GAMMs also allow researchers to account for autocorrelation in time-series data, which is especially critical in gaze analyses where successive samples are not independent. By modeling the autocorrelation structure, GAMMs provide more accurate estimates of temporal effects and prevent inflation of Type I error rates (Rij et al., 2019). In addition to this, fitting GAMMs allow us to estimate the onset of the competition effect in each condition (Verissimo & Lago, 2025).

Gaze samples will be analyzed with a binomial (logistic) GAMM using the `bam()` function from the `{mgcv}` package (Wood, 2017). For visualization, we will employ functions from the `{tidygam}` package (Coretta, 2024), the `{onsets}` package (Verissimo & Lago, 2025) to examine onset latencies, and the `{itsadug}` (van Rij et al., 2022) package for AR functions and to test differences in smooth splines across the time (`get_differences()`). The dependent variable will consist of gaze counts to cohorts compared to unrelated items, for each participant and in each 50ms time bin. All analyses were conducted on a window ranging from -100 ms from target onset to 1200 ms.

The right model in the context of GAMMs is a difficult one. The results can vary depending on whether one uses an ordered factor scheme or unordered factor scheme. Because of this we plan to fit the model multiple ways to test for robustness. In one model (Listing 1) we will fit a model that includes a parametric term for webcam type that is unordered where the reference level will be the standard quality webcam (treatment-coded such that high-quality = 1 and standard-quality = 0). To examine whether webcam type moderates the cohort effect over time, we will include smooth terms for time-by-condition interactions with camera. To account for individual differences, we will include participant-specific random smooths for time, and participant-specific random smooths for time within each level of the camera factor.

This specification allows the model to capture:

1. The overall (parametric) effect of webcam type on the proportion of looks to cohorts verse unrelated items. Here, the intercept reflects the expected proportion of looks in the standard-quality condition, and the webcam coefficient reflects the difference in looks between high- and standard-quality webcams (H1a and H1b).
2. Condition-specific, time-varying trajectories in cohort competition (via the smooth terms), which support inferences about the timing (onsets) and dynamics of cohort effects across conditions. By fitting the model with an unordered factor we can examine the time smooths for each condition separately and then compare offset differences between them (H2a and H2b).
3. Deviations from these group-level trajectories at the individual participant level (via random smooths)

In another instantiation of the model (see Listing 2) we will include a parametric term for webcam type that is ordered. To examine whether webcam type moderates the cohort effect over time, we will include smooth terms for time and time-by-condition interactions (which is needed when fitting ordered factor). To account for individual differences, we will include participant-specific random smooths for time, and participant-specific random smooths for time within each level of the camera factor.

This specification allows the model to capture:**This specification allows the model to capture two components:**

1. The overall (parametric) effect of webcam type. With webcam type coded as an ordered factor with standard-quality as the reference level, the model intercept represents the expected proportion of looks in the standard-quality condition, and the webcam coefficient represents the difference between high-quality and standard-quality webcams (H1a, H1b).
2. Condition-specific, time-varying trajectories in cohort competition. By including factor-smooths for time and the time x webcam type, the model estimates a baseline smooth for the standard-quality webcam and a *difference* smooth for the high-quality webcam. Because the webcam factor is ordered, the difference smooth directly represents how the trajectory for high-quality deviates from the standard-quality trajectory. This structure enables inferences about the timing and dynamics of cohort effects across webcam conditions, including onset differences (H2a, H2b). We will also look at
3. Deviations from these group-level trajectories at the individual participant level (via random smooths).

Although “maximal” random-effects structures are often recommended in linear mixed-effects models (Barr et al., 2013), such specifications can be computationally prohibitive in GAMMs. The present specification follows the recommendations of Veríssimo & Lago (2025). Statistical significance will be assessed at $\alpha = .05$. When fitting difference curves with simultaneous CIs, we will correct for multiple comparisons using a Bnefornni correction[(Krause et al., 2024)].

To account for autocorrelation in the residuals, we will first fit the model without an autoregressive term in order to estimate the autocorrelation parameter (ρ). We will then re-fit the model including a first-order autoregressive process (AR(1)) to properly model temporal dependencies. Although using larger time bins can reduce autocorrelation, it does not eliminate it entirely, so explicitly modeling residual autocorrelation ensures valid statistical inference. Template code to fit the models is included below.

327 Listing 1. GAMM model set-up unordered camera factor

```

328 library(mgcv) # perform gam
329 library(tidygam) # visualization of gams
330 library(itsadug) # get_differences
331 library(onsets) # onset differences
332 # combine levels of both factors into one factor
333 dat$camera <- as.factor(dat$camera)
334
335 # get start event for AR
336 start_event = start_event(., column = "Time", # for ar
337                             event = c("subj", "Trial"),
338                             label = "start.event",
339                             label.event = NULL,
340                             order = FALSE)$start.event)
341 # quick rho estimate (fit once without AR to get residual ACF ~ lag1)
342
343 m0 <-
344 bam(cbind(fix_cohort, fix_unrelated) ~ 1 +
345      camera + s(time, by = camera, k = 10) +
346      s(participant, by=camera, bs = "re") +
347      s(time, participant, by=camera, bs = "re"),
348      family = binomial(), method = "fREML",
349      discrete = TRUE, data = dat, na.action = na.omit,
350
351 rho <- acf(residuals(m0, type = "pearson"), plot = FALSE)$acf[2]
352
353 # final model with AR(1) to handle within-series autocorrelation
354
355 m1 <-
356 bam(cbind(fix_cohort, fix_unrelated) ~ 1 +
357      camera + s(time, by = camera, k = 10) +
358      s(participant, by=camera, bs = "re") +
359      s(time, participant, by=camera, bs = "re") +
360      rho=rho, AR.start = start_event

```


361 Listing 2. GAMM model set-up ordered camera factor

```

362 library(mgcv) # perform gam
363 library(tidygam) # visualization of gams
364 library(itsadug) # get_differences
365 library(onsets) # onset differences
366 # combine levels of both factors into one factor
367
368 dat$camera_ord <- as.factor(dat$camera)
369 dat$camera_ord <- as.ordered(dat$camera) # get ordered
370
371
372 # get start event for AR
373 start_event = start_event(., column = "Time", # for ar
374                             event = c("subject", "Trial"),
375                             label = "start.event",
376                             label.event = NULL,
377                             order = FALSE)$start.event)
378 # quick rho estimate (fit once without AR to get residual ACF ~ lag1)
379
380 m0 <-
381 bam(cbind(fix_cohort, fix_unrelated) ~ 1 +
382     1 + Condition_ord + s(Time) +
383     s(Time, by=Condition_ord) +
384     (Participant, bs="re") +
385     s(Participant, by=Condition_ord, bs="re") +
386     s(Participant, Time, bs="re") +
387     s(Participant, Time, by=Condition_ord, bs="re"),
388     family = binomial(), method = "fREML",
389     discrete = TRUE, data = dat, na.action = na.omit,
390
391 rho <- acf(residuals(m0, type = "pearson"), plot = FALSE)$acf[2]
392
393 # final model with AR(1) to handle within-series autocorrelation
394
395 m1 <-
396 bam(cbind(fix_cohort, fix_unrelated) ~ 1 +
397     1 + Condition_ord + s(Time) +
398     s(Time, by=Condition_ord) +
399     (Participant, bs="re") +
400     s(Participant, by=Condition_ord, bs="re") +
401     s(Participant, Time, bs="re") +
402     s(Participant, Time, by=Condition_ord, bs="re"),
403     family = binomial(), method = "fREML",
404     discrete = TRUE, data = dat, na.action = na.omit,
405     rho=rho, AR.start = start_event

```

406 Listing 3. Getting onset differences using the {onsets} package for unordered model

```

407 # Obtain onsets in each condition (and their differences)
408
409 onsets_comp <- get_onsets(model = m1, # Fitted GAMM
410                           time_var = "time", # Name of time variable
411                           by_var = "camera", # Name of condition/group variable
412                           compare = T, # Obtain differences
413 between onsets
414                           n_samples = 10000, # Large number of
415 samples (less variable results)
416                           seed = 1, # Random seed for
417 reproducibility

```

418 *Listing 4. Getting onset differences using the {onsets} package for ordered model*

```

419 # Obtain onsets in each condition (and their differences)
420
421 onsets_comp <- get_onsets(model = m1,           # Fitted GAMM
422                          time_var = "time",    # Name of time variable
423                          by_var = "camera",     # Name of condition/group variable
424                          cov_vars = "",        # every fixed effect must be
425                          included
426                          compare = T,         # Obtain differences
427                          between onsets
428                          n_samples = 10000,   # Large number of
429                          samples (less variable results)
430                          seed = 1,           # Random seed for
431                          reproducibility

```

432 Calibration

433 To examine whether webcam type affects calibration rejection, we will fit a logistic regression
 434 model using the `glm()` function (see Listing 5. Calibration outcome will be coded as a binary
 435 variable, where *0* indicates that a participant failed to calibrate at either of the calibration phases,
 436 and *1* indicates that the participant successfully passed both calibration phases. This model will
 437 allow us to estimate whether the webcam condition reliably predicts the probability of successful
 438 calibration.

439 *Listing 5. Logistic model to examine the effect of webcams on calibration*

```

440 # fit glm model
441 glm(calibration ~ camera, family = binomial(link = "logit"))

```

442 Experiment 2: Head stabilization (chin rest) vs. no head stabilization

443 In Experiment 2, we will use the same standard-quality external webcam as in Experiment 1, but
 444 will manipulate head stability by comparing a chin-rest condition to a no-chin-rest condition.
 445 [Hessels et al. \(2014\)](#) offered evidence that head movement can impact the accuracy and reliability
 446 of eye-tracking estimates, showing that even moderate deviations in head position can produce
 447 systematic calibration drift, increased data loss, and slower recovery when gaze is reacquired.
 448 Importantly, their study demonstrates that these effects are not limited to extreme movements,
 449 and can arise during typical participant behavior when head position is not constrained. Some
 450 online platforms (e.g., LabVanced; [\(Finger et al., 2017\)](#)) attempt to mitigate head motion by warning
 451 participants when they move outside a predefined region; however, it remains unclear how such
 452 motion control interacts with WebGazer.js estimates of event detection and onset latency. In
 453 laboratory-based eye-tracking, chin rests are routinely used to stabilize the head in a fixed position
 454 so that only the eyes move during the experiment. By introducing a chin-rest manipulation, we
 455 can directly assess the extent to which head stability contributes to competition effects, the timing
 456 of event detection, and participant attrition in webcam-based eye-tracking. We therefore test the
 457 following hypotheses regarding competition, onset, and attrition.

458 Hypotheses

459 We hypothesize several effects related to competition, onset, and attrition. These are generally the
 460 same as Experiment 1.

461 Competition Effects

462 (H1a) Participants will show an overall greater proportion of looks to competitors. (H1b) Head
 463 stabilization (chin rest vs. no chin rest) will influence the overall proportion of looks, with chin
 464 rest condition detecting a greater proportion of looks.

Timing/Onset Effects

(H2a) Chin-rest and no chin rest conditions will show effects on time. (H2b) For no chin-rest condition vs. chin rest comparison onsets will be detected later due to increased noise.

Attrition

(H3) Attrition rates will be lower in the high-quality webcam condition than in the standard-quality webcam condition.

Sampling Goal, Materials, Procedure, and Analysis Plan

The sampling goal, materials, procedure, and analysis plan are the same as Experiment 1. The main difference is whether participants use a chin rest or not.

References

- Anwyl-Irvine, A. L., Massonnié, J., Flitton, A., Kirkham, N., & Evershed, J. K. (2019). Gorilla in our midst: An online behavioral experiment builder. *Behavior Research Methods*, 52(1), 388–407. <https://doi.org/10.3758/s13428-019-01237-x>
- Barr, D. J., Levy, R., Scheepers, C., & Tily, H. J. (2013). Random effects structure for confirmatory hypothesis testing: Keep it maximal. *Journal of Memory and Language*, 68(3), 255–278. <https://doi.org/10.1016/j.jml.2012.11.001>
- Bogdan, P. C., Dolcos, S., Buetti, S., Lleras, A., & Dolcos, F. (2024). Investigating the suitability of online eye tracking for psychological research: Evidence from comparisons with in-person data using emotion–attention interaction tasks. *Behavior Research Methods*, 56(3), 2213–2226. <https://doi.org/10.3758/s13428-023-02143-z>
- Bramlett, A. A., & Wiener, S. (2024). The art of wrangling. *Linguistic Approaches to Bilingualism*. <https://doi.org/https://doi.org/10.1075/lab.23071.bra>
- Bramlett, A. A., & Wiener, S. (2025). The Art of Wrangling: Working with Web-Based Visual World Paradigm Eye-Tracking Data in Language Research. *Linguistic Approaches to Bilingualism*, 15(4), 538–570. <https://doi.org/10.1075/lab.23071.bra>
- Brown-Schmidt, S., Cho, S.-J., Fenn, K. M., & Trude, A. M. (2025). Modeling spatio-temporal patterns in intensive binary time series eye-tracking data using Generalized Additive Mixed Models. *Brain Research*, 1854, 149511. <https://doi.org/10.1016/j.brainres.2025.149511>
- Carter, B. T., & Luke, S. G. (2020). Best practices in eye tracking research. *International Journal of Psychophysiology*, 155, 49–62. <https://doi.org/10.1016/j.ijpsycho.2020.05.010>
- Cheng, Y., Wang, H., Bao, Y., & Lu, F. (2024). *Appearance-Based Gaze Estimation With Deep Learning: A Review and Benchmark* (Issue arXiv:2104.12668). <https://doi.org/10.48550/arXiv.2104.12668>
- Colby, S. E., & McMurray, B. (2023). Efficiency of spoken word recognition slows across the adult lifespan. *Cognition*, 240, 105588. <https://doi.org/10.1016/j.cognition.2023.105588>
- Cooper, R. M. (1974). The control of eye fixation by the meaning of spoken language: A new methodology for the real-time investigation of speech perception, memory, and language processing. *Cognitive Psychology*, 6(1), 84–107. [https://doi.org/10.1016/0010-0285\(74\)90005-X](https://doi.org/10.1016/0010-0285(74)90005-X)
- Coretta, S. (2024). *tidygam: Tidy Prediction and Plotting of Generalised Additive Models*. <https://github.com/stefanocoretta/tidygam>
- Cruyssen, I. Van der, Ben-Shakhar, G., Pertzov, Y., Guy, N., Cabooter, Q., Gunschera, L. J., & Verschuere, B. (2023). The validation of online webcam-based eye-tracking: The replication of the cascade effect, the novelty preference, and the visual world paradigm. *Behavior Research Methods*. <https://doi.org/10.3758/s13428-023-02221-2>
- Degen, J., Kursat, L., & Leigh, D. D. (2021). Seeing is believing: Testing an explicit linking assumption for visual world eye-tracking in psycholinguistics. *Proceedings of the Annual Meeting of the Cognitive Science Society*, 43(43).
- Dolstra, E., & contributors, T. N. (2023,). *Nix*. <https://nixos.org/>
- Finger, H., Goeke, C., Diekamp, D., Standvoß, K., & König, P. (2017,). LabVanced: A Unified JavaScript Framework for Online Studies. *International Conference on Computational Social Science (Ic2s2)*.

- Geller, J., Prystauka, Y., Colby, S. E., & Drouin, J. R. (2025). Language without Borders: A Step-by-Step Guide to Analyzing Webcam Eye-Tracking Data for L2 Research. *Research Methods in Applied Linguistics*, 4(3), 100226. <https://doi.org/10.1016/j.rmal.2025.100226>
- Hessels, R. S., Cornelissen, T. H. W., Kemner, C., & Hooge, I. T. C. (2014). Qualitative tests of remote eyetracker recovery and performance during head rotation. *Behavior Research Methods*, 47(3), 848–859. <https://doi.org/10.3758/s13428-014-0507-6>
- Huetting, F., Rommers, J., & Meyer, A. S. (2011). Using the visual world paradigm to study language processing: a review and critical evaluation. *Acta Psychologica*, 137(2), 151–171. <https://doi.org/10.1016/j.actpsy.2010.11.003>
- Ito, A., & Knoeferle, P. (2022). Analysing data from the psycholinguistic visual-world paradigm: Comparison of different analysis methods. *Behavior Research Methods*, 55(7), 3461–3493. <https://doi.org/10.3758/s13428-022-01969-3>
- James, A. N., Ryskin, R., Hartshorne, J. K., Backs, H., Bala, N., Barcenas-Meade, L., Bhattarai, S., Charles, T., Copoulos, G., Coss, C., Eisert, A., Furuhashi, E., Ginell, K., Guttman-McCabe, A., Harrison, E. (., Hoban, L., Hwang, W. A., Iannetta, C., Koenig, K. M., ... de Leeuw, J. R. (2025). What Paradigms Can Webcam Eye-Tracking Be Used For? Attempted Replications of Five Cognitive Science Experiments. *Collabra: Psychology*, 11(1), 140755. <https://doi.org/10.1525/collabra.140755>
- Kaduk, T., Goeke, C., Finger, H., & König, P. (2023). Webcam eye tracking close to laboratory standards: Comparing a new webcam-based system and the EyeLink 1000. *Behavior Research Methods*, 56(5), 5002–5022. <https://doi.org/10.3758/s13428-023-02237-8>
- Kandel, M., & Snedeker, J. (2024). Assessing two methods of webcam-based eye-tracking for child language research. *Journal of Child Language*, 52(3), 675–708. <https://doi.org/10.1017/s0305000924000175>
- Krause, J., Rij, J. van, & Borst, J. P. (2024). Word Type and Frequency Effects on Lexical Decisions Are Process-dependent and Start Early. *Journal of Cognitive Neuroscience*, 36(10), 2227–2250. https://doi.org/10.1162/jocn_a_02214
- Leeuw, J. R. de. (2014). jsPsych: A JavaScript library for creating behavioral experiments in a Web browser. *Behavior Research Methods*, 47(1), 1–12. <https://doi.org/10.3758/s13428-014-0458-y>
- McMurray, B., Samelson, V. M., Lee, S. H., & Tomblin, J. B. (2010). Individual differences in online spoken word recognition: Implications for SLI. *Cognitive Psychology*, 60(1), 1–39. <https://doi.org/10.1016/j.cogpsych.2009.06.003>
- Mirman, D. (2014). *Growth Curve Analysis and Visualization Using R*. Chapman, Hall/CRC.
- Mitterer, H. (2025). A web-based mouse-tracking task for early perceptual language processing. *Behavior Research Methods*, 57(11). <https://doi.org/10.3758/s13428-025-02827-8>
- Papoutsaki, A., Sangkloy, P., Laskey, J., Daskalova, N., Huang, J., & Hays, J. (2016, July). WebGazer: Scalable Webcam Eye Tracking Using User Interactions. *International Joint Conference on Artificial Intelligence*.
- Patterson, A. S., Nicklin, C., & Vitta, J. P. (2025). Methodological recommendations for webcam-based eye tracking: A scoping review. *Research Methods in Applied Linguistics*, 4(3), 100244. <https://doi.org/10.1016/j.rmal.2025.100244>
- Peirce, J., Gray, J. R., Simpson, S., MacAskill, M., Höchenberger, R., Sogo, H., Kastman, E., & Lindeløv, J. K. (2019). PsychoPy2: Experiments in behavior made easy. *Behavior Research Methods*, 51(1), 195–203. <https://doi.org/10.3758/s13428-018-01193-y>
- Prystauka, Y., Altmann, G. T. M., & Rothman, J. (2024). Online eye tracking and real-time sentence processing: On opportunities and efficacy for capturing psycholinguistic effects of different magnitudes and diversity. *Behavior Research Methods*, 56(4), 3504–3522. <https://doi.org/10.3758/s13428-023-02176-4>
- Reips, U.-D. (2021). Web-based research in psychology: A review. *Zeitschrift Für Psychologie*, 229(4), 198–213. <https://doi.org/10.1027/2151-2604/a000475>
- Rij, J. van, Hendriks, P., Rijn, H. van, Baayen, R. H., & Wood, S. N. (2019). Analyzing the Time Course of Pupillometric Data. *Trends in Hearing*, 23. <https://doi.org/10.1177/2331216519832483>

- Rodrigues, B., & Baumann, P. (2025). *rix: Reproducible Data Science Environments with 'Nix'*. <https://docs.ropensci.org/rix/>
- Saxena, S., Fink, L. K., & Lange, E. B. (2024). Deep Learning Models for Webcam Eye Tracking in Online Experiments. *Behavior Research Methods*, 56(4), 3487–3503. <https://doi.org/10.3758/s13428-023-02190-6>
- Semmelmann, K., & Weigelt, S. (2018). Online webcam-based eye tracking in cognitive science: A first look. *Behavior Research Methods*, 50(2), 451–465. <https://doi.org/10.3758/s13428-017-0913-7>
- Slim, M. S., & Hartsuiker, R. J. (2023). Moving visual world experiments online? A web-based replication of Dijkgraaf, Hartsuiker, and Duyck (2017) using PCIBex and WebGazer.js. *Behavior Research Methods*, 55(7), 3786–3804. <https://doi.org/10.3758/s13428-022-01989-z>
- Slim, M. S., Kandel, M., Yacovone, A., & Snedeker, J. (2024). Webcams as Windows to the Mind? A Direct Comparison Between In-Lab and Web-Based Eye-Tracking Methods. *Open Mind*, 8, 1369–1424. https://doi.org/10.1162/opmi_a_00171
- Tanenhaus, M. K., Spivey-Knowlton, M. J., Eberhard, K. M., & Sedivy, J. C. (1995). Integration of visual and linguistic information in spoken language comprehension. *Science (New York, N.Y.)*, 268(5217), 1632–1634. <http://www.ncbi.nlm.nih.gov/pubmed/7777863>
- van Rij, J., Wieling, M., Baayen, R. H., & van Rijn, H. (2022). *itsadug: Interpreting Time Series and Autocorrelated Data Using GAMMs*.
- Veríssimo, J., & Lago, S. (2025, April 29). *A novel method for detecting the onset of experimental effects in visual world eye-tracking*. PsyArXiv. https://doi.org/10.31234/osf.io/yk4xb_v3
- Vos, M., Minor, S., & Ramchand, G. C. (2022). Comparing infrared and webcam eye tracking in the Visual World Paradigm. *Glossa Psycholinguistics*, 1(1). <https://doi.org/10.5070/G6011131>
- Wood, S. N. (2017). *Generalized Additive Models: An Introduction with R* (2nd ed.). Chapman, Hall/CRC.
- Yang, X., & Krajovich, I. (2021). Webcam-Based Online Eye-Tracking for Behavioral Research. *Judgment and Decision Making*, 16(6), 1485–1505. <https://doi.org/10.1017/S1930297500008512>
- Zehr, J., & Schwarz, F. (2022). PennController for Internet Based Experiments (IBEX). *Open Science Framework*. <https://doi.org/10.17605/OSF.IO/MD832>
- Özsoy, O., Çiçek, B., Özal, Z., Gagarina, N., & Sekerina, I. A. (2023). Turkish-German heritage speakers' predictive use of case: webcam-based vs. in-lab eye-tracking. *Frontiers in Psychology*, 14, 1155585. <https://doi.org/10.3389/fpsyg.2023.1155585>