

Supplemental Material for An Exploration of  
Exploration: Measuring the ability of lexicase  
selection to find obscure pathways

Jose Guadalupe Hernandez, Alexander Lalejini, and Charles Ofria

2021-06-21



# Contents

<b>1</b>	<b>Introduction</b>	<b>5</b>
1.1	About our supplemental material . . . . .	5
1.2	Contributing authors . . . . .	5
1.3	Research overview . . . . .	5
<b>2</b>	<b>Data Availability</b>	<b>7</b>
2.1	Source code . . . . .	7
2.2	Experimental results . . . . .	7
<b>3</b>	<b>Compile and run experiments</b>	<b>9</b>
3.1	Docker . . . . .	9
<b>4</b>	<b>Tournament selection vs Lexicase selection</b>	<b>11</b>
4.1	Overview . . . . .	11
4.2	Analysis dependencies . . . . .	11
4.3	Setup . . . . .	12
4.4	Exploration diagnostic performance . . . . .	13
4.5	Final Performance . . . . .	14
4.6	Unique starting positions . . . . .	17
4.7	Manuscript figures . . . . .	22
<b>5</b>	<b>Diagnostic cardinality</b>	<b>25</b>
5.1	Overview . . . . .	25
5.2	Analysis dependencies . . . . .	25
5.3	Setup . . . . .	26
5.4	Exploration diagnostic performance . . . . .	27
5.5	Unique starting positions . . . . .	29
5.6	Manuscript figures . . . . .	34
<b>6</b>	<b>Increasing population size versus increasing generations</b>	<b>37</b>
6.1	Overview . . . . .	37
6.2	Analysis dependencies . . . . .	37
6.3	Setup . . . . .	38
6.4	Exploration diagnostic performance . . . . .	39

6.5	Unique starting positions . . . . .	42
6.6	Manuscript figures . . . . .	46
<b>7</b>	<b>Epsilon lexicase</b>	<b>49</b>
7.1	Overview . . . . .	49
7.2	Analysis dependencies . . . . .	49
7.3	Setup . . . . .	50
7.4	Exploration diagnostic performance . . . . .	51
7.5	Unique starting positions . . . . .	53
7.6	Manuscript figures . . . . .	57
<b>8</b>	<b>Down-sampled lexicase</b>	<b>59</b>
8.1	Overview . . . . .	59
8.2	Analysis dependencies . . . . .	59
8.3	Setup . . . . .	60
8.4	Exploration diagnostic performance . . . . .	61
8.5	Unique starting positions . . . . .	64
8.6	Manuscript figures . . . . .	67
<b>9</b>	<b>Cohort lexicase</b>	<b>69</b>
9.1	Overview . . . . .	69
9.2	Analysis dependencies . . . . .	69
9.3	Setup . . . . .	70
9.4	Exploration diagnostic performance . . . . .	71
9.5	Unique starting positions . . . . .	73
9.6	Manuscript figures . . . . .	77
<b>10</b>	<b>Down-sampled lexicase versus cohort lexicase</b>	<b>79</b>
10.1	Overview . . . . .	79
10.2	Analysis dependencies . . . . .	79
10.3	Setup . . . . .	80
10.4	Exploration diagnostic performance . . . . .	81
10.5	Unique starting positions . . . . .	84
10.6	Manuscript figures . . . . .	87
<b>11</b>	<b>Novelty lexicase</b>	<b>91</b>
11.1	Overview . . . . .	91
11.2	Analysis dependencies . . . . .	91
11.3	Setup . . . . .	92
11.4	Exploration diagnostic performance . . . . .	93
11.5	Unique starting positions . . . . .	95
11.6	Manuscript figures . . . . .	98

# Chapter 1

## Introduction

This is the supplemental material associated with our 2021 GPTP contribution entitled, *An Exploration of Exploration: Measuring the ability of lexibase selection to find obscure pathways*. Preprint forthcoming.

### 1.1 About our supplemental material

This supplemental material is hosted on GitHub using GitHub pages. The source code and configuration files used to generate this supplemental material can be found in this GitHub repository. We compiled our data analyses and supplemental documentation into this nifty web-accessible book using bookdown.

Our supplemental material includes the following:

- TODO

### 1.2 Contributing authors

- Jose Guadalupe Hernandez
- Alexander Lalejini
- Charles Ofria

### 1.3 Research overview

Abstract:

TODO



## Chapter 2

# Data Availability

### 2.1 Source code

The source code for this work is available on GitHub at <https://github.com/jgh9094/GPTP-2021-Exploration-Of-Exploration>.

### 2.2 Experimental results

The data from our experiments are available online in an OSF repository (Lalejini and Hernandez, 2021) at <https://osf.io/xpjft/>.





## Chapter 3

# Compile and run experiments

Here, we provide a guide to compiling and running our experiments using our Docker image.

Please file an issue on GitHub if something is unclear or does not work.

### 3.1 Docker

TODO

#### 3.1.1 Getting the right image

##### 3.1.1.1 DockerHub

##### 3.1.1.2 Local build

#### 3.1.2 Spinning up a container

#### 3.1.3 Running inside the container

#### 3.1.4 Copying content from the container



## Chapter 4

# Tournament selection vs Lexicase selection

### 4.1 Overview

```
# Relative location of data.
working_directory <- "experiments/2021-05-27-tournament/analysis/"
# working_directory <- "./"

# Settings for visualization
cb_palette <- "Set2"

# Create directory to dump plots
dir.create(paste0(working_directory, "imgs"), showWarnings=FALSE)
```

### 4.2 Analysis dependencies

```
library(ggplot2)
library(tidyverse)
library(knitr)
library(cowplot)
library(viridis)
library(RColorBrewer)
library(rstatix)
library(ggsignif)
library(Hmisc)
source("https://gist.githubusercontent.com/benmarwick/2a1bb0133ff568cbe28d/raw/fb53bd97121f7f9ce9")
```

These analyses were conducted in the following computing environment:

```
print(version)

##
## platform      x86_64-pc-linux-gnu
## arch          x86_64
## os            linux-gnu
## system        x86_64, linux-gnu
## status
## major         4
## minor         1.0
## year          2021
## month         05
## day           18
## svn rev       80317
## language      R
## version.string R version 4.1.0 (2021-05-18)
## nickname      Camp Pontanezen
```

### 4.3 Setup

```
data_loc <- paste0(
  working_directory,
  "data/timeseries-res-1000g.csv"
)

data <- read.csv(data_loc, na.strings="NONE")

data$selection_name <- factor(
  data$selection_name,
  levels=c("EpsilonLexicase", "Tournament"),
  labels=c("Lexicase", "Tournament")
)

data$elite_trait_avg <-
  data$ele_agg_per / data$OBJECTIVE_CNT
data$unique_start_positions_coverage <-
  data$uni_str_pos / data$OBJECTIVE_CNT

final_data <- filter(data, evaluations==max(data$evaluations))

# Labeler for stats annotations
p_label <- function(p_value) {
  threshold = 0.0001
```

```

    if (p_value < threshold) {
      return(paste0("p < ", threshold))
    } else {
      return(paste0("p = ", p_value))
    }
  }

# Significance threshold
alpha <- 0.05

# Common graph variables
performance_ylim <- 105
coverage_ylim <- 1.0

##### misc #####
# Configure our default graphing theme
theme_set(theme_cowplot())

```

## 4.4 Exploration diagnostic performance

```


elite_ave_performance_fig <- ggplot(
  data,
  aes(
    x=gen,
    y=elite_trait_avg,
    color=selection_name,
    fill=selection_name
  )
) +
stat_summary(geom="line", fun=mean) +
stat_summary(
  geom="ribbon",
  fun.data="mean_cl_boot",
  fun.args=list(conf.int=0.95),
  alpha=0.2,
  linetype=0
) +
scale_y_continuous(
  name="Average trait performance",
  limits=c(0, performance_ylim)
) +
scale_x_continuous(
  name="Generation"
) +

```

```

scale_fill_brewer(
  name="Selection",
  limits=c("Lexicase", "Tournament"),
  labels=c("Lexicase", "Tournament"),
  palette=cb_palette
) +
scale_color_brewer(
  name="Selection",
  limits=c("Lexicase", "Tournament"),
  labels=c("Lexicase", "Tournament"),
  palette=cb_palette
)
elite_ave_performance_fig

```



## 4.5 Final Performance

```

# Compute manual labels for geom_signif
stat.test <- final_data %>%
  wilcox_test(elite_trait_avg ~ selection_name) %>%
  adjust_pvalue(method = "bonferroni") %>%
  add_significance() %>%
  add_xy_position(x="selection_name", step.increase=1)
stat.test$manual_position <- stat.test$y.position * 1.05

```

```
stat.test$label <- mapapply(p_label, stat.test$p.adj)
```

```
elite_final_performance_fig <- ggplot(  
  final_data,  
  aes(  
    x=selection_name,  
    y=elite_trait_avg,  
    fill=selection_name  
  )  
)+  
  geom_flat_violin(  
    position = position_nudge(x = .2, y = 0),  
    alpha = .8,  
    scale="width"  
  )+  
  geom_point(  
    mapping=aes(color=selection_name),  
    position = position_jitter(width = .15),  
    size = .5,  
    alpha = 0.8  
  )+  
  geom_boxplot(  
    width = .1,  
    outlier.shape = NA,  
    alpha = 0.5  
  )+  
  scale_y_continuous(  
    name="Average trait performance",  
    limits=c(0, performance_ylim)  
  )+  
  scale_x_discrete(  
    name="Selection",  
    limits=c("Lexicase", "Tournament"),  
    labels=c("Lexicase", "Tournament"),  
  )+  
  scale_fill_brewer(  
    name="Selection",  
    palette=cb_palette,  
    limits=c("Lexicase", "Tournament"),  
    labels=c("Lexicase", "Tournament"),  
  )+  
  scale_color_brewer(  
    name="Selection",  
    palette=cb_palette,  
    limits=c("Lexicase", "Tournament"),
```

```

    labels=c("Lexicase", "Tournament"),
  ) +
  labs(
    subtitle=paste0(
      "Kruskal-Wallis, ",
      p_label(
        signif(
          kruskal.test(
            formula=elite_trait_avg~selection_name,
            data=final_data)$p.value,digits=4
          )
        )
      )
    )
  ) +
  ggsignif::geom_signif(
    data=filter(stat.test, p.adj <= alpha),
    aes(
      xmin=group1,
      xmax=group2,
      annotations=label,
      y_position=manual_position
    ),
    manual=TRUE,
    inherit.aes=FALSE
  ) +
  theme(
    legend.position="none"
  )


```

```

## Warning: Ignoring unknown aesthetics: xmin, xmax, annotations, y_position
elite_final_performance_fig

```






.y.	group1	group2	n1	n2	statistic	p	p.adj	p.adj.signif	y.position	groups
elite_trait_avg	Lexicase	Tournament	50	50	2357	0	0	****	97.477	Lexicase , T

## 4.6 Unique starting positions

```
ggplot(data, aes(x=gen, y=uni_str_pos, color=selection_name)) +
  stat_summary(geom="line", fun=mean) +
  stat_summary(
    geom="ribbon",
    fun.data="mean_cl_boot",
    fun.args=list(conf.int=0.95),
    alpha=0.2,
    linetype=0
  ) +
  scale_y_continuous(
    name="Unique activation positions (population)",
    limits=c(0, 100)
  ) +
  scale_x_continuous(
    name="Generation"
  )
```




Different cardinalities have numbers of possible starting positions, so next, we look at the proportion of starting positions (out of all possible) maintained by populations.

```
unique_start_position_coverage_fig <- ggplot(
  data,
  aes(
    x=gen,
    y=unique_start_positions_coverage,
    color=selection_name,
    fill=selection_name
  )
) +
stat_summary(geom="line", fun=mean) +
stat_summary(
  geom="ribbon",
  fun.data="mean_cl_boot",
  fun.args=list(conf.int=0.95),
  alpha=0.2,
  linetype=0
) +
scale_y_continuous(
  name="Activation position coverage",
  limit=c(0, coverage_ylim)
) +
```

```

scale_x_continuous(
  name="Generation"
) +
scale_fill_brewer(
  name="Selection",
  limits=c("Lexicase", "Tournament"),
  labels=c("Lexicase", "Tournament"),
  palette=cb_palette
) +
scale_color_brewer(
  name="Selection",
  limits=c("Lexicase", "Tournament"),
  labels=c("Lexicase", "Tournament"),
  palette=cb_palette
)
unique_start_position_coverage_fig

```



#### 4.6.1 Final starting position Coverage

```

# Compute manual labels for geom_signif
stat.test <- final_data %>%
  wilcox_test(unique_start_positions_coverage ~ selection_name) %>%
  adjust_pvalue(method = "bonferroni") %>%
  add_significance() %>%

```

```

    add_xy_position(x="selection_name",step.increase=1)
stat.test$manual_position <- stat.test$y.position * 1.05
stat.test$label <- mapapply(p_label,stat.test$p.adj)

```

```

unique_start_positions_coverage_final_fig <- ggplot(
  final_data,
  aes(
    x=selection_name,
    y=unique_start_positions_coverage,
    fill=selection_name
  )
) +
geom_flat_violin(
  position = position_nudge(x = .2, y = 0),
  alpha = .8,
  scale="width"
) +
geom_point(
  mapping=aes(color=selection_name),
  position = position_jitter(width = .15),
  size = .5,
  alpha = 0.8
) +
geom_boxplot(
  width = .1,
  outlier.shape = NA,
  alpha = 0.5
) +
scale_y_continuous(
  name="Activation position coverage",
  limits=c(0, coverage_ylim)
) +
scale_x_discrete(
  name="Selection",
  limits=c("Lexicase", "Tournament"),
  labels=c("Lexicase", "Tournament"),
) +
scale_fill_brewer(
  name="Selection",
  palette=cb_palette,
  limits=c("Lexicase", "Tournament"),
  labels=c("Lexicase", "Tournament"),
) +
scale_color_brewer(
  name="Selection",

```

```


palette=cb_palette,
limits=c("Lexicase", "Tournament"),
labels=c("Lexicase", "Tournament"),
) +
labs(
  subtitle=paste0(
    "Kruskal-Wallis, ",
    p_label(
      signif(
        kruskal.test(
          formula=unique_start_positions_coverage~selection_name,
          data=final_data)$p.value,digits=4
        )
      )
    )
  ) +
  ggsignif::geom_signif(
    data=filter(stat.test, p.adj <= alpha),
    aes(
      xmin=group1,
      xmax=group2,
      annotations=label,
      y_position=manual_position
    ),
    manual=TRUE,
    inherit.aes=FALSE
  ) +
  theme(
    legend.position="none"
  )
)

```

```

## Warning: Ignoring unknown aesthetics: xmin, xmax, annotations, y_position
unique_start_positions_coverage_final_fig

```



.y.	group1	group2	n1	n2	statistic	p	p.adj	p.adj.s
unique_start_positions_coverage	Lexicase	Tournament	50	50	2500	0	0	****

## 4.7 Manuscript figures

```

legend <- cowplot::get_legend(
  elite_ave_performance_fig +
  guides(
    color=guide_legend(nrow=1),
    fill=guide_legend(nrow=1)
  ) +
  theme(
    legend.position = "bottom",
    legend.box="horizontal",
    legend.justification="center"
  )
)

grid <- plot_grid(
  elite_ave_performance_fig +
  ggtitle("Performance over time") +
  labs(subtitle="") +
  theme(legend.position="none"),
  elite_final_performance_fig +


```

```
  ggtitle("Final performance") +
  theme(),
unique_start_position_coverage_fig +
  ggtitle("Activation position coverage over time") +
  labs(subtitle="") +
  theme(legend.position="none"),
unique_start_positions_coverage_final_fig +
  ggtitle("Final activation position coverage") +
  theme(),
nrow=2,
ncol=2,
rel_widths=c(3,2),
labels="auto"
)

grid <- plot_grid(
  grid,
  legend,
  nrow=2,
  ncol=1,
  rel_heights=c(1, 0.1)
)

save_plot(
  paste(
    working_directory,
    "imgs/tournament-vs-lexicase-panel.pdf",
    sep=""
  ),
  grid,
  base_width=12,
  base_height=8
)

grid
```





## Chapter 5

# Diagnostic cardinality

### 5.1 Overview

```
# Relative location of data.
working_directory <-
  "experiments/2021-05-27-cardinality/analysis/"
# working_directory <- "./"

# Settings for visualization
cb_palette <- "Set2"
# Create directory to dump plots
dir.create(paste0(working_directory, "imgs"), showWarnings=FALSE)
```

### 5.2 Analysis dependencies

```
library(ggplot2)
library(tidyverse)
library(cowplot)
library(viridis)
library(RColorBrewer)
source("https://gist.githubusercontent.com/benmarwick/2a1bb0133ff568cbe28d/raw/fb53bd97121f7f9ce9")
```

These analyses were conducted in the following computing environment:

```
print(version)

##
## platform      x86_64-pc-linux-gnu
## arch          x86_64
```

```
## os          linux-gnu
## system      x86_64, linux-gnu
## status
## major       4
## minor       1.0
## year        2021
## month       05
## day         18
## svn rev     80317
## language    R
## version.string R version 4.1.0 (2021-05-18)
## nickname    Camp Pontanezen
```

```
data_loc <- paste0(
  working_directory,
  "data/timeseries-res-1000g.csv"
)
data <- read.csv(
  data_loc,
  na.strings="NONE"
)

data$cardinality <- as.factor(
  data$OBJECTIVE_CNT
)
data$selection_name <- as.factor(
  data$selection_name
)

data$elite_trait_avg <-
  data$ele_agg_per / data$OBJECTIVE_CNT


data$unique_start_positions_coverage <-
  data$uni_str_pos / data$OBJECTIVE_CNT

##### misc #####
# Configure our default graphing theme
theme_set(theme_cowplot())
```

## 5.4 Exploration diagnostic performance

First, we look at performance over time. Specifically, we look at the normalized aggregate score of the most performant individuals over time. To control for different cardinalities having different maximum scores, we normalized performances (by dividing by cardinality) to values between 0 and 100.

```
elite_trait_ave_fit <- ggplot(  
  data,  
  aes(  
    x=gen,  
    y=elite_trait_avg,  
    color=cardinality,  
    fill=cardinality  
  )  
) +  
stat_summary(geom="line", fun=mean) +  
stat_summary(  
  geom="ribbon",  
  fun.data="mean_cl_boot",  
  fun.args=list(conf.int=0.95),  
  alpha=0.2,  
  linetype=0  
) +  
scale_y_continuous(  
  name="Average trait performance",  
  limits=c(0, 100)  
) +  
scale_x_continuous(  
  name="Generation"  
) +  
scale_fill_brewer(  
  name="Cardinality",  
  palette=cb_palette  
) +  
scale_color_brewer(  
  name="Cardinality",  
  palette=cb_palette  
)  
elite_trait_ave_fit
```



#### 5.4.1 Final performance


Next, we look only at the final performances of each treatment

```
final_data <- filter(data, gen==max(data$gen))
elite_trait_ave_fit_final <- ggplot(
  final_data,
  aes(x=cardinality, y=elite_trait_avg, fill=cardinality)
) +
  geom_flat_violin(
    position = position_nudge(x = .2, y = 0),
    alpha = .8,
    scale="width"
  ) +
  geom_point(
    mapping=aes(color=cardinality),
    position = position_jitter(width = .15),
    size = .5,
    alpha = 0.8
  ) +
  geom_boxplot(
    width = .1,
    outlier.shape = NA,
    alpha = 0.5
  ) +
```

```

scale_y_continuous(
  name="Average trait performance",
  limits=c(0, 100)
) +
scale_x_discrete(
  name="Cardinality"
) +
scale_fill_brewer(
  name="Cardinality",
  palette=cb_palette
) +
scale_color_brewer(
  name="Cardinality",
  palette=cb_palette
) +
theme(
  legend.position="none"
)
elite_trait_ave_fit_final


```



## 5.5 Unique starting positions

Next, we analyze the number of unique starting position maintained by populations.


```
ggplot(data, aes(x=gen, y=uni_str_pos, color=cardinality)) +
  stat_summary(geom="line", fun=mean) +
  stat_summary(
    geom="ribbon",
    fun.data="mean_cl_boot",
    fun.args=list(conf.int=0.95),
    alpha=0.2,
    linetype=0
  ) +
  scale_y_continuous(
    name="Unique activation positions (population)",
  ) +
  scale_x_continuous(
    name="Generation"
  )
)
```



Different cardinalities have numbers of possible starting positions, so next, we look at the proportion of starting positions (out of all possible) maintained by populations.

```
unique_start_positions_coverage_fig <- ggplot(
  data,
  aes(
    x=gen,
    y=unique_start_positions_coverage,
  )
)
```

```
    color=cardinality,
    fill=cardinality
  )
) +
stat_summary(geom="line", fun=mean) +
stat_summary(
  geom="ribbon",
  fun.data="mean_cl_boot",
  fun.args=list(conf.int=0.95),
  alpha=0.2,
  linetype=0
) +
scale_y_continuous(
  name="Activation position coverage",
  limits=c(0.0, 1.05)
) +
scale_x_continuous(
  name="Generation"
) +
scale_fill_brewer(
  name="Cardinality",
  palette=cb_palette
) +
scale_color_brewer(
  name="Cardinality",
  palette=cb_palette
)
unique_start_positions_coverage_fig
```



### 5.5.1 Final starting position coverage


```
final_unique_start_positions_coverage_fig <- ggplot(
  final_data,
  aes(
    x=cardinality,
    y=unique_start_positions_coverage,
    fill=cardinality
  )
) +
  geom_flat_violin(
    position = position_nudge(x = .2, y = 0),
    alpha = .8,
    scale="width"
  ) +
  geom_point(
    mapping=aes(color=cardinality),
    position = position_jitter(width = .15),
    size = .5,
    alpha = 0.8
  ) +
  geom_boxplot(
    width = .1,
    outlier.shape = NA,
```



```

    alpha = 0.5
  ) +
  scale_y_continuous(
    name="Activation position coverage",
    limits=c(0, 1.05)
  ) +
  scale_x_discrete(
    name="Cardinality"
  ) +
  scale_fill_brewer(
    name="Cardinality",
    palette=cb_palette
  ) +
  scale_color_brewer(
    name="Cardinality",
    palette=cb_palette
  ) +
  theme(
    legend.position="none"
  )
final_unique_start_positions_coverage_fig

```



## 5.6 Manuscript figures

Combine figures for the manuscript.

```


legend <- cowplot::get_legend(
  elite_trait_ave_fit +
    guides(
      color=guide_legend(nrow=1),
      fill=guide_legend(nrow=1)
    ) +
    theme(
      legend.position = "bottom",
      legend.box="horizontal",
      legend.justification="center"
    )
)

grid <- plot_grid(
  elite_trait_ave_fit +
    ggtitle("Performance over time") +
    theme(legend.position="none"),
  elite_trait_ave_fit_final +
    ggtitle("Final performance") +
    theme(),
  unique_start_positions_coverage_fig +
    ggtitle("Activation position coverage over time") +
    theme(legend.position="none"),
  final_unique_start_positions_coverage_fig +
    ggtitle("Final activation position coverage") +
    theme(),
  nrow=2,
  ncol=2,
  rel_widths=c(3,2),
  labels="auto"
)

grid <- plot_grid(
  grid,
  legend,
  nrow=2,
  ncol=1,
  rel_heights=c(1, 0.1)
)

save_plot(
  paste(working_directory, "imgs/cardinality-panel.pdf", sep=""),

```





## Chapter 6

# Increasing population size versus increasing generations

### 6.1 Overview

```
# Relative location of data.
working_directory <-
  "experiments/2021-06-03-cardinality-pop-size/analysis/"
# working_directory <- "./"

# Settings for visualization
cb_palette <- "Set2"

# Create directory to dump plots
dir.create(paste0(working_directory, "imgs"), showWarnings=FALSE)
```

### 6.2 Analysis dependencies

```
library(ggplot2)
library(tidyverse)
library(cowplot)
library(viridis)
library(RColorBrewer)
source("https://gist.githubusercontent.com/benmarwick/2a1bb0133ff568cbe28d/raw/fb53bd97121f7f9ce9")
```

These analyses were conducted in the following computing environment:

```
print(version)

##
## platform      x86_64-pc-linux-gnu
## arch          x86_64
## os            linux-gnu
## system        x86_64, linux-gnu
## status
## major         4
## minor        1.0
## year         2021
## month        05
## day          18
## svn rev       80317
## language      R
## version.string R version 4.1.0 (2021-05-18)
## nickname      Camp Pontanezen
```

### 6.3 Setup

```
data_loc <- paste0(working_directory, "data/timeseries.csv")
data <- read.csv(data_loc, na.strings="NONE")

data$cardinality <- as.factor(
  data$OBJECTIVE_CNT
)
data$selection_name <- as.factor(
  data$selection_name
)

data$epsilon <- as.factor(
  data$LEX_EPS
)

data$POP_SIZE <- as.factor(
  data$POP_SIZE
)


data <- filter(data, cardinality=="100") # These runs finished.
data$elite_trait_avg <-
  data$ele_agg_per / data$OBJECTIVE_CNT
data$unique_start_positions_coverage <-
  data$uni_str_pos / data$OBJECTIVE_CNT
```

```
final_data <- filter(data, evaluations==max(data$evaluations))

##### misc #####
# Configure our default graphing theme
theme_set(theme_cowplot())
```

## 6.4 Exploration diagnostic performance


```
elite_ave_performance_fig <-
  ggplot(
    data,
    aes(
      x=evaluations,
      y=elite_trait_avg,
      color=POP_SIZE,
      fill=POP_SIZE
    )
  ) +
  stat_summary(geom="line", fun=mean) +
  stat_summary(
    geom="ribbon",
    fun.data="mean_cl_boot",
    fun.args=list(conf.int=0.95),
    alpha=0.2,
    linetype=0
  ) +
  scale_y_continuous(
    name="Average trait performance"
  ) +
  scale_x_continuous(
    name="Evaluations"
  ) +
  scale_fill_brewer(
    name="Population Size",
    palette=cb_palette
  ) +
  scale_color_brewer(
    name="Population Size",
    palette=cb_palette
  )
elite_ave_performance_fig
```



Same as above, but by generations instead of evaluations.

```
ggplot(data, aes(x=gen, y=elite_trait_avg, color=POP_SIZE)) +
  stat_summary(geom="line", fun=mean) +
  stat_summary(
    geom="ribbon",
    fun.data="mean_cl_boot",
    fun.args=list(conf.int=0.95),
    alpha=0.2,
    linetype=0
  ) +
  scale_y_continuous(
    name="Elite trait average"
  ) +
  scale_x_continuous(
    name="Generations"
  )
```





### 6.4.1 Final performance


```
elite_final_performance_fig <- ggplot(
  final_data,
  aes(x=POP_SIZE, y=elite_trait_avg, fill=POP_SIZE)
) +
  geom_flat_violin(
    position = position_nudge(x = .2, y = 0),
    alpha = .8,
    scale="width"
  ) +
  geom_point(
    mapping=aes(color=POP_SIZE),
    position = position_jitter(width = .15),
    size = .5,
    alpha = 0.8
  ) +
  geom_boxplot(
    width = .1,
    outlier.shape = NA,
    alpha = 0.5
  ) +
  scale_y_continuous(
    name="Average trait performance",

```

```

    limits=c(0, 100)
  ) +
  scale_x_discrete(
    name="Population Size"
  ) +
  scale_fill_brewer(
    name="Population Size",
    palette=cb_palette
  ) +
  scale_color_brewer(
    name="Population Size",
    palette=cb_palette
  ) +
  theme(
    legend.position="none"
  )
elite_final_performance_fig

```




## 6.5 Unique starting positions

```

unique_start_position_coverage_fig <- ggplot(
  data,
  aes(

```


```
x=evaluations,
y=unique_start_positions_coverage,
color=POP_SIZE,
fill=POP_SIZE
)
) +
stat_summary(geom="line", fun=mean) +
stat_summary(
  geom="ribbon",
  fun.data="mean_cl_boot",
  fun.args=list(conf.int=0.95),
  alpha=0.2,
  linetype=0
) +
scale_y_continuous(
  name="Activation position coverage",
  limits=c(0.0, 1.0)
) +
scale_x_continuous(
  name="Evaluations"
) +
scale_fill_brewer(
  name="Population Size",
  palette=cb_palette
) +
scale_color_brewer(
  name="Population Size",
  palette=cb_palette
)
unique_start_position_coverage_fig
```



### 6.5.1 Final starting position coverage

```
unique_start_positions_coverage_final_fig <- ggplot(
  final_data,
  aes(
    x=POP_SIZE,
    y=unique_start_positions_coverage,
    fill=POP_SIZE
  )
) +
  geom_flat_violin(
    position = position_nudge(x = .2, y = 0),
    alpha = .8,
    scale="width"
  ) +
  geom_point(
    mapping=aes(color=POP_SIZE),
    position = position_jitter(width = .15),
    size = .5,
    alpha = 0.8
  ) +
  geom_boxplot(
    width = .1,
    outlier.shape = NA,
```

```
alpha = 0.5
) +
scale_y_continuous(
  name="Activation position coverage",
  limits=c(0, 1.0)
) +
scale_x_discrete(
  name="Population size"
) +
scale_fill_brewer(
  name="Population size",
  palette=cb_palette
) +
scale_color_brewer(
  name="Population size",
  palette=cb_palette
) +
theme(
  legend.position="none"
)
unique_start_positions_coverage_final_fig
```



## 6.6 Manuscript figures

```


legend <- cowplot::get_legend(
  elite_ave_performance_fig +
    guides(
      color=guide_legend(nrow=1),
      fill=guide_legend(nrow=1)
    ) +
    theme(
      legend.position = "bottom",
      legend.box="horizontal",
      legend.justification="center"
    )
)

grid <- plot_grid(
  elite_ave_performance_fig +
    ggtitle("Performance over time") +
    theme(legend.position="none"),
  elite_final_performance_fig +
    ggtitle("Final performance") +
    theme(),
  unique_start_position_coverage_fig +
    ggtitle("Activation position coverage over time") +
    theme(legend.position="none"),
  unique_start_positions_coverage_final_fig +
    ggtitle("Final activation position coverage") +
    theme(),
  nrow=2,
  ncol=2,
  rel_widths=c(3,2),
  labels="auto"
)

grid <- plot_grid(
  grid,
  legend,
  nrow=2,
  ncol=1,
  rel_heights=c(1, 0.1)
)

save_plot(
  paste(working_directory, "imgs/pop-size-panel.pdf", sep=""),

```







## Chapter 7

# Epsilon lexicase

### 7.1 Overview

```
# Relative location of data.
working_directory <- "experiments/2021-05-28-epsilon/analysis/"
# working_directory <- "./"

# Settings for visualization
cb_palette <- "Set2"
# Create directory to dump plots
dir.create(paste0(working_directory, "imgs"), showWarnings=FALSE)
```

### 7.2 Analysis dependencies

```
library(ggplot2)
library(tidyverse)
library(cowplot)
library(viridis)
library(RColorBrewer)
source("https://gist.githubusercontent.com/benmarwick/2a1bb0133ff568cbe28d/raw/fb53bd97121f7f9ce9")
```

These analyses were conducted in the following computing environment:

```
print(version)

##
## platform      x86_64-pc-linux-gnu
## arch          x86_64
## os            linux-gnu
```

```
## system      x86_64, linux-gnu
## status
## major       4
## minor       1.0
## year        2021
## month       05
## day         18
## svn rev     80317
## language    R
## version.string R version 4.1.0 (2021-05-18)
## nickname    Camp Pontanezen
```

## 7.2 Setup

```
data_loc <- paste0(
  working_directory,
  "data/timeseries-res-1000g.csv"
)
data <- read.csv(data_loc, na.strings="NONE")

data$cardinality <- as.factor(
  data$OBJECTIVE_CNT
)
data$selection_name <- as.factor(
  data$selection_name
)

data$epsilon <- as.factor(
  data$LEX_EPS
)


data$elite_trait_avg <-
  data$ele_agg_per / data$OBJECTIVE_CNT
data$unique_start_positions_coverage <-
  data$uni_str_pos / data$OBJECTIVE_CNT

final_data <- filter(data, evaluations==max(data$evaluations))

##### misc #####
# Configure our default graphing theme
theme_set(theme_cowplot())
```

## 7.4 Exploration diagnostic performance

```
elite_ave_performance_fig <-  
  ggplot(  
    data,  
    aes(x=gen, y=elite_trait_avg, color=epsilon, fill=epsilon)  
  ) +  
  stat_summary(geom="line", fun=mean) +  
  stat_summary(  
    geom="ribbon",  
    fun.data="mean_cl_boot",  
    fun.args=list(conf.int=0.95),  
    alpha=0.2,  
    linetype=0  
  ) +  
  scale_y_continuous(  
    name="Average trait performance"  
  ) +  
  scale_x_continuous(  
    name="Generations"  
  ) +  
  scale_fill_brewer(  
    name="Epsilon",  
    palette=cb_palette  
  ) +  
  scale_color_brewer(  
    name="Epsilon",  
    palette=cb_palette  
  )  
elite_ave_performance_fig
```




#### 7.4.1 Final performance

```
elite_final_performance_fig <- ggplot(
  final_data,
  aes(x=epsilon, y=elite_trait_avg, fill=epsilon)
) +
  geom_flat_violin(
    position = position_nudge(x = .2, y = 0),
    alpha = .8,
    scale="width"
  ) +
  geom_point(
    mapping=aes(color=epsilon),
    position = position_jitter(width = .15),
    size = .5,
    alpha = 0.8
  ) +
  geom_boxplot(
    width = .1,
    outlier.shape = NA,
    alpha = 0.5
  ) +
  scale_y_continuous(
    name="Average trait performance",
```

```

    limits=c(0, 100)
  ) +
  scale_x_discrete(
    name="Epsilon"
  ) +
  scale_fill_brewer(
    name="Epsilon",
    palette=cb_palette
  ) +
  scale_color_brewer(
    name="Epsilon",
    palette=cb_palette
  ) +
  theme(
    legend.position="none"
  )
elite_final_performance_fig

```




## 7.5 Unique starting positions

```

unique_start_position_coverage_fig <- ggplot(
  data,
  aes(

```

```
    x=gen,
    y=unique_start_positions_coverage,
    color=epsilon,
    fill=epsilon
  )
) +
stat_summary(geom="line", fun=mean) +
stat_summary(
  geom="ribbon",
  fun.data="mean_cl_boot",
  fun.args=list(conf.int=0.95),
  alpha=0.2,
  linetype=0
) +
scale_y_continuous(
  name="Activation position coverage",
  limits=c(0.0, 1.0)
) +
scale_x_continuous(
  name="Generations"
) +
scale_fill_brewer(
  name="Epsilon",
  palette=cb_palette
) +
scale_color_brewer(
  name="Epsilon",
  palette=cb_palette
)
unique_start_position_coverage_fig
```




### 7.5.1 Final coverage

```
unique_start_positions_coverage_final_fig <- ggplot(
  final_data,
  aes(
    x=epsilon,
    y=unique_start_positions_coverage,
    fill=epsilon
  )
) +
geom_flat_violin(
  position = position_nudge(x = .2, y = 0),
  alpha = .8,
  scale="width"
) +
geom_point(
  mapping=aes(color=epsilon),
  position = position_jitter(width = .15),
  size = .5,
  alpha = 0.8
) +
geom_boxplot(
  width = .1,
  outlier.shape = NA,
```

```

alpha = 0.5
) +
scale_y_continuous(
  name="Activation position coverage",
  limits=c(0, 1.0)
) +
scale_x_discrete(
  name="Epsilon"
) +
scale_fill_brewer(
  name="Epsilon",
  palette=cb_palette
) +
scale_color_brewer(
  name="Epsilon",
  palette=cb_palette
) +
theme(
  legend.position="none"
)
unique_start_positions_coverage_final_fig

```





## 7.6 Manuscript figures

```

legend <- cowplot::get_legend(
  elite_ave_performance_fig +
    guides(
      color=guide_legend(nrow=1),
      fill=guide_legend(nrow=1)
    ) +
    theme(
      legend.position = "bottom",
      legend.box="horizontal",
      legend.justification="center"
    )
)

grid <- plot_grid(
  elite_ave_performance_fig +
    ggtitle("Performance over time") +
    theme(legend.position="none"),
  elite_final_performance_fig +
    ggtitle("Final performance") +
    theme(),
  unique_start_position_coverage_fig +
    ggtitle("Activation position coverage over time") +
    theme(legend.position="none"),
  unique_start_positions_coverage_final_fig +
    ggtitle("Final activation position coverage") +
    theme(),
  nrow=2,
  ncol=2,
  rel_widths=c(3,2),
  labels="auto"
)

grid <- plot_grid(
  grid,
  legend,
  nrow=2,
  ncol=1,
  rel_heights=c(1, 0.1)
)


save_plot(
  paste(working_directory, "imgs/epsilon-panel.pdf", sep=""),
  grid,

```

```

base_width=12,
base_height=8
)
grid

```



## Chapter 8

# Down-sampled lexicase

### 8.1 Overview

```
# Relative location of data.
working_directory <- "experiments/2021-05-28-downsampled/analysis/"
# working_directory <- "./"

# Settings for visualization
cb_palette <- "Set2"
# Create directory to dump plots
dir.create(paste0(working_directory, "imgs"), showWarnings=FALSE)
```

### 8.2 Analysis dependencies

```
library(ggplot2)
library(tidyverse)
library(cowplot)
library(viridis)
library(RColorBrewer)
source("https://gist.githubusercontent.com/benmarwick/2a1bb0133ff568cbe28d/raw/fb53bd97121f7f9ce9")
```

These analyses were conducted in the following computing environment:

```
print(version)

##
## platform      _
## arch          x86_64-pc-linux-gnu
## os            linux-gnu
```

```
## system      x86_64, linux-gnu
## status
## major       4
## minor       1.0
## year        2021
## month       05
## day         18
## svn rev     80317
## language    R
## version.string R version 4.1.0 (2021-05-18)
## nickname    Camp Pontanezen
```

```
data_loc <- paste0(working_directory, "data/timeseries.csv")
data <- read.csv(data_loc, na.strings="NONE")

data$cardinality <- as.factor(
  data$OBJECTIVE_CNT
)
data$selection_name <- as.factor(
  data$selection_name
)

data$epsilon <- as.factor(
  data$LEX_EPS
)

data$proportion <- factor(
  data$DSLEX_PROP,
  levels=c(1, 0.5, 0.2, 0.1, 0.05, 0.02, 0.01)
)


data$elite_trait_avg <- data$ele_agg_per / data$OBJECTIVE_CNT
data$unique_start_positions_coverage <- data$uni_str_pos / data$OBJECTIVE_CNT

final_data <- filter(data, evaluations==max(data$evaluations))

##### misc #####
# Configure our default graphing theme
theme_set(theme_cowplot())
```

## 8.4 Exploration diagnostic performance

```
elite_ave_performance_fig <-  
  ggplot(  
    data,  
    aes(  
      x=evaluations,  
      y=elite_trait_avg,  
      color=proportion,  
      fill=proportion  
    )  
  ) +  
  stat_summary(geom="line", fun=mean) +  
  stat_summary(  
    geom="ribbon",  
    fun.data="mean_cl_boot",  
    fun.args=list(conf.int=0.95),  
    alpha=0.2,  
    linetype=0  
  ) +  
  scale_y_continuous(  
    name="Average trait performance",  
    limits=c(0, 100)  
  ) +  
  scale_x_continuous(  
    name="Evaluations"  
  ) +  
  scale_fill_brewer(  
    name="Sampling rate",  
    palette=cb_palette  
  ) +  
  scale_color_brewer(  
    name="Sampling rate",  
    palette=cb_palette  
  )  
elite_ave_performance_fig
```




#### 8.4.1 Final performance

```
elite_final_performance_fig <- ggplot(
  final_data,
  aes(
    x=proportion,
    y=elite_trait_avg,
    fill=proportion
  )
) +
  geom_flat_violin(
    position = position_nudge(x = .2, y = 0),
    alpha = .8,
    scale="width"
  ) +
  geom_point(
    mapping=aes(color=proportion),
    position = position_jitter(width = .15),
    size = .5,
    alpha = 0.8
  ) +
  geom_boxplot(
    width = .1,
    outlier.shape = NA,
```

```

alpha = 0.5
) +
scale_y_continuous(
  name="Average trait performance",
  limits=c(0, 100)
) +
scale_x_discrete(
  name="Sampling rate"
) +
scale_fill_brewer(
  name="Sampling rate",
  palette=cb_palette
) +
scale_color_brewer(
  name="Sampling rate",
  palette=cb_palette
) +
theme(
  legend.position="none"
)
elite_final_performance_fig


```



## 8.5 Unique starting positions

```
unique_start_position_coverage_fig <- ggplot(  
  data,  
  aes(  
    x=evaluations,  
    y=unique_start_positions_coverage,  
    color=proportion,  
    fill=proportion  
  )  
) +  
stat_summary(geom="line", fun=mean) +  
stat_summary(  
  geom="ribbon",  
  fun.data="mean_cl_boot",  
  fun.args=list(conf.int=0.95),  
  alpha=0.2,  
  linetype=0  
) +  
scale_y_continuous(  
  name="Activation position coverage",  
  limits=c(0.0, 1.0)  
) +  
scale_x_continuous(  
  name="Evaluations"  
) +  
scale_fill_brewer(  
  name="Sampling rate",  
  palette=cb_palette  
) +  
scale_color_brewer(  
  name="Sampling rate",  
  palette=cb_palette  
)  
unique_start_position_coverage_fig
```






### 8.5.1 Final starting position coverage

```
unique_start_positions_coverage_final_fig <- ggplot(
  final_data,
  aes(
    x=proportion,
    y=unique_start_positions_coverage,
    fill=proportion
  )
) +
geom_flat_violin(
  position = position_nudge(x = .2, y = 0),
  alpha = .8,
  scale="width"
) +
geom_point(
  mapping=aes(color=proportion),
  position = position_jitter(width = .15),
  size = .5,
  alpha = 0.8
) +
geom_boxplot(
  width = .1,
  outlier.shape = NA,
```

```

alpha = 0.5
) +
scale_y_continuous(
  name="Activation position coverage",
  limits=c(0, 1.0)
) +
scale_x_discrete(
  name="Sampling rate"
) +
scale_fill_brewer(
  name="Sampling rate",
  palette=cb_palette
) +
scale_color_brewer(
  name="Sampling rate",
  palette=cb_palette
) +
theme(
  legend.position="none"
)
unique_start_positions_coverage_final_fig

```



## 8.6 Manuscript figures

```

legend <- cowplot::get_legend(
  elite_ave_performance_fig +
    guides(
      color=guide_legend(nrow=1),
      fill=guide_legend(nrow=1)
    ) +
    theme(
      legend.position = "bottom",
      legend.box="horizontal",
      legend.justification="center"
    )
)

grid <- plot_grid(
  elite_ave_performance_fig +
    ggtitle("Performance over time") +
    theme(legend.position="none"),
  elite_final_performance_fig +
    ggtitle("Final performance") +
    theme(),
  unique_start_position_coverage_fig +
    ggtitle("Activation position coverage over time") +
    theme(legend.position="none"),
  unique_start_positions_coverage_final_fig +
    ggtitle("Final activation position coverage") +
    theme(),
  nrow=2,
  ncol=2,
  rel_widths=c(3,2),
  labels="auto"
)

grid <- plot_grid(
  grid,
  legend,
  nrow=2,
  ncol=1,
  rel_heights=c(1, 0.1)
)


save_plot(
  paste(working_directory, "imgs/down-sampled-panel.pdf", sep=""),
  grid,

```

```

base_width=12,
base_height=8
)
grid

```



## Chapter 9

# Cohort lexicase

### 9.1 Overview

```
# Relative location of data.
working_directory <- "experiments/2021-06-01-cohort/analysis/"
# working_directory <- "./"

# Settings for visualization
cb_palette <- "Set2"
# Create directory to dump plots
dir.create(paste0(working_directory, "imgs"), showWarnings=FALSE)
```

### 9.2 Analysis dependencies

```
library(ggplot2)
library(tidyverse)
library(cowplot)
library(viridis)
library(RColorBrewer)
source("https://gist.githubusercontent.com/benmarwick/2a1bb0133ff568cbe28d/raw/fb53bd97121f7f9ce9")
```

These analyses were conducted in the following computing environment:

```
print(version)

##
## platform      x86_64-pc-linux-gnu
## arch          x86_64
## os            linux-gnu
```

```
## system      x86_64, linux-gnu
## status
## major       4
## minor       1.0
## year        2021
## month       05
## day         18
## svn rev     80317
## language    R
## version.string R version 4.1.0 (2021-05-18)
## nickname    Camp Pontanezen
```

### 9.3 Setup

```
data_loc <- paste0(working_directory, "data/timeseries.csv")
data <- read.csv(data_loc, na.strings="NONE")

data$cardinality <- as.factor(
  data$OBJECTIVE_CNT
)
data$selection_name <- as.factor(
  data$selection_name
)

data$epsilon <- as.factor(
  data$LEX_EPS
)

data$proportion <- factor(
  data$COH_LEX_PROP,
  levels=c(1, 0.5, 0.2, 0.1, 0.05, 0.02, 0.01)
)


data$elite_trait_avg <-
  data$ele_agg_per / data$OBJECTIVE_CNT
data$unique_start_positions_coverage <-
  data$uni_str_pos / data$OBJECTIVE_CNT

final_data <- filter(data, evaluations==max(data$evaluations))

##### misc #####
# Configure our default graphing theme
theme_set(theme_cowplot())
```

## 9.4 Exploration diagnostic performance

```
elite_ave_performance_fig <-  
  ggplot(  
    data,  
    aes(  
      x=evaluations,  
      y=elite_trait_avg,  
      color=proportion,  
      fill=proportion  
    )  
  ) +  
  stat_summary(geom="line", fun=mean) +  
  stat_summary(  
    geom="ribbon",  
    fun.data="mean_cl_boot",  
    fun.args=list(conf.int=0.95),  
    alpha=0.2,  
    linetype=0  
  ) +  
  scale_y_continuous(  
    name="Average trait performance",  
    limits=c(0, 100)  
  ) +  
  scale_x_continuous(  
    name="Evaluations"  
  ) +  
  scale_fill_brewer(  
    name="Cohort size",  
    palette=cb_palette  
  ) +  
  scale_color_brewer(  
    name="Cohort size",  
    palette=cb_palette  
  )  
elite_ave_performance_fig
```



#### 9.4.1 Final performance

```

elite_final_performance_fig <- ggplot(
  final_data,
  aes(x=proportion, y=elite_trait_avg, fill=proportion)
) +
  geom_flat_violin(
    position = position_nudge(x = .2, y = 0),
    alpha = .8,
    scale="width"
  ) +
  geom_point(
    mapping=aes(color=proportion),
    position = position_jitter(width = .15),
    size = .5,
    alpha = 0.8
  ) +
  geom_boxplot(
    width = .1,
    outlier.shape = NA,
    alpha = 0.5
  ) +
  scale_y_continuous(
    name="Average trait performance",


```



```

    limits=c(0, 100)
  ) +
  scale_x_discrete(
    name="Cohort size"
  ) +
  scale_fill_brewer(
    name="Cohort size",
    palette=cb_palette
  ) +
  scale_color_brewer(
    name="Cohort size",
    palette=cb_palette
  ) +
  theme(
    legend.position="none"
  )
elite_final_performance_fig

```




## 9.5 Unique starting positions

```

unique_start_position_coverage_fig <- ggplot(
  data,
  aes(

```

```
x=evaluations,
y=unique_start_positions_coverage,
color=proportion,
fill=proportion
)
) +
stat_summary(geom="line", fun=mean) +
stat_summary(
  geom="ribbon",
  fun.data="mean_cl_boot",
  fun.args=list(conf.int=0.95),
  alpha=0.2,
  linetype=0
) +
scale_y_continuous(
  name="Activation position coverage",
  limits=c(0.0, 1.0)
) +
scale_x_continuous(
  name="Evaluations"
) +
scale_fill_brewer(
  name="Cohort size",
  palette=cb_palette
) +
scale_color_brewer(
  name="Cohort size",
  palette=cb_palette
)
unique_start_position_coverage_fig
```




### 9.5.1 Final starting position coverage

```
unique_start_positions_coverage_final_fig <- ggplot(
  final_data,
  aes(
    x=proportion,
    y=unique_start_positions_coverage,
    fill=proportion
  )
) +
geom_flat_violin(
  position = position_nudge(x = .2, y = 0),
  alpha = .8,
  scale="width"
) +
geom_point(
  mapping=aes(color=proportion),
  position = position_jitter(width = .15),
  size = .5,
  alpha = 0.8
) +
geom_boxplot(
  width = .1,
  outlier.shape = NA,
```

```

alpha = 0.5
) +
scale_y_continuous(
  name="Activation position coverage",
  limits=c(0, 1.0)
) +
scale_x_discrete(
  name="Cohort size"
) +
scale_fill_brewer(
  name="Cohort size",
  palette=cb_palette
) +
scale_color_brewer(
  name="Cohort size",
  palette=cb_palette
) +
theme(
  legend.position="none"
)
unique_start_positions_coverage_final_fig

```



## 9.6 Manuscript figures

```

legend <- cowplot::get_legend(
  elite_ave_performance_fig +
    guides(
      color=guide_legend(nrow=1),
      fill=guide_legend(nrow=1)
    ) +
    theme(
      legend.position = "bottom",
      legend.box="horizontal",
      legend.justification="center"
    )
)

grid <- plot_grid(
  elite_ave_performance_fig +
    ggtitle("Performance over time") +
    theme(legend.position="none"),
  elite_final_performance_fig +
    ggtitle("Final performance") +
    theme(),
  unique_start_position_coverage_fig +
    ggtitle("Activation position coverage over time") +
    theme(legend.position="none"),
  unique_start_positions_coverage_final_fig +
    ggtitle("Final activation position coverage") +
    theme(),
  nrow=2,
  ncol=2,
  rel_widths=c(3,2),
  labels="auto"
)

grid <- plot_grid(
  grid,
  legend,
  nrow=2,
  ncol=1,
  rel_heights=c(1, 0.1)
)

save_plot(
  paste(working_directory, "imgs/cohort-panel.pdf", sep=""),
  grid,

```

```


base_width=12,
base_height=8
)

```

```

grid

```



## Chapter 10

# Down-sampled lexicase versus cohort lexicase

### 10.1 Overview

```
# Relative location of data.
working_directory <-
  "experiments/2021-06-05-downsample-vs-cohort/analysis/"
# working_directory <- "./"

# Settings for visualization
cb_palette <- "Dark2"
# Create directory to dump plots
dir.create(paste0(working_directory, "imgs"), showWarnings=FALSE)
```

### 10.2 Analysis dependencies

```
library(ggplot2)
library(tidyverse)
library(cowplot)
library(viridis)
library(RColorBrewer)
source("https://gist.githubusercontent.com/benmarwick/2a1bb0133ff568cbe28d/raw/fb53bd97121f7f9ce9")
```

These analyses were conducted in the following computing environment:

```
print(version)
```

```
##
```

-

```
## platform      x86_64-pc-linux-gnu
## arch          x86_64
## os            linux-gnu
## system        x86_64, linux-gnu
## status
## major         4
## minor         1.0
## year          2021
## month         05
## day           18
## svn rev       80317
## language      R
## version.string R version 4.1.0 (2021-05-18)
## nickname      Camp Pontanezen
```

### 10.3 Setup

```
data_loc <- paste0(working_directory, "data/timeseries.csv")
data <- read.csv(data_loc, na.strings="NONE")

data$cardinality <- as.factor(
  data$OBJECTIVE_CNT
)
data$selection_name <- as.factor(
  data$selection_name
)

data$epsilon <- as.factor(
  data$LEX_EPS
)

# I always set cohort and downsampled lexicase sampling rates to
# be the same on a given run (regardless of selection scheme)
data$proportion <- factor(
  data$COH_LEX_PROP,
  levels=c(1, 0.5, 0.2, 0.1, 0.05, 0.02, 0.01)
)

data$elite_trait_avg <-
  data$ele_agg_per / data$OBJECTIVE_CNT
data$unique_start_positions_coverage <-
  data$uni_str_pos / data$OBJECTIVE_CNT

final_data <- filter(data, evaluations==max(data$evaluations))
```




```
##### misc #####
# Configure our default graphing theme
theme_set(theme_cowplot())
```

## 10.4 Exploration diagnostic performance

```
elite_ave_performance_fig <-
  ggplot(
    data,
    aes(
      x=gen,
      y=elite_trait_avg,
      color=selection_name,
      fill=selection_name
    )
  ) +
  stat_summary(geom="line", fun=mean) +
  stat_summary(
    geom="ribbon",
    fun.data="mean_cl_boot",
    fun.args=list(conf.int=0.95),
    alpha=0.2,
    linetype=0
  ) +
  scale_y_continuous(
    name="Average trait performance",
    limits=c(0, 100)
  ) +
  scale_x_continuous(
    name="Generations"
  ) +
  scale_fill_brewer(
    name="Selection",
    palette=cb_palette,
    limits=c("CohortLexicase", "DownSampledLexicase"),
    labels=c("Cohort lexicase", "Down-sampled lexicase")
  ) +
  scale_color_brewer(
    name="Selection",
    palette=cb_palette,
    limits=c("CohortLexicase", "DownSampledLexicase"),
    labels=c("Cohort lexicase", "Down-sampled lexicase")
  )
```


```
elite_ave_performance_fig
```



#### 10.4.1 Final performance

```
elite_final_performance_fig <- ggplot(
  final_data,
  aes(x=selection_name, y=elite_trait_avg, fill=selection_name)
) +
  geom_flat_violin(
    position = position_nudge(x = .2, y = 0),
    alpha = .8,
    scale="width"
  ) +
  geom_point(
    mapping=aes(color=selection_name),
    position = position_jitter(width = .15),
    size = .5,
    alpha = 0.8
  ) +
  geom_boxplot(
    width = .1,
    outlier.shape = NA,
    alpha = 0.5
  ) +
```

```
scale_y_continuous(  
  name="Average trait performance",  
  limits=c(0, 100)  
) +  
scale_x_discrete(  
  name="Selection",  
  limits=c("CohortLexicase", "DownSampledLexicase"),  
  labels=c("Cohort lexicase", "Down-sampled lexicase")  
) +  
scale_fill_brewer(  
  name="Selection",  
  palette=cb_palette,  
  limits=c("CohortLexicase", "DownSampledLexicase"),  
  labels=c("Cohort lexicase", "Down-sampled lexicase")  
) +  
scale_color_brewer(  
  name="Selection",  
  palette=cb_palette,  
  limits=c("CohortLexicase", "DownSampledLexicase"),  
  labels=c("Cohort lexicase", "Down-sampled lexicase")  
) +  
theme(  
  legend.position="none"  
)  
elite_final_performance_fig
```




## 10.5 Unique starting positions

```
unique_start_position_coverage_fig <- ggplot(
  data,
  aes(
    x=gen,
    y=unique_start_positions_coverage,
    color=selection_name,
    fill=selection_name
  )
) +
stat_summary(geom="line", fun=mean) +
stat_summary(
  geom="ribbon",
  fun.data="mean_cl_boot",
  fun.args=list(conf.int=0.95),
  alpha=0.2,
  linetype=0
) +
scale_y_continuous(
  name="Activation position coverage",
  limits=c(0.0, 1.0)
) +
```

```

scale_x_continuous(
  name="Generations"
) +
scale_fill_brewer(
  name="Selection",
  palette=cb_palette,
  limits=c("CohortLexicase", "DownSampledLexicase"),
  labels=c("Cohort lexicase", "Down-sampled lexicase")
) +
scale_color_brewer(
  name="Selection",
  palette=cb_palette,
  limits=c("CohortLexicase", "DownSampledLexicase"),
  labels=c("Cohort lexicase", "Down-sampled lexicase")
)
unique_start_position_coverage_fig

```



### 10.5.1 Final starting position coverage

```


unique_start_positions_coverage_final_fig <- ggplot(
  final_data,
  aes(
    x=selection_name,

```

```

        y=unique_start_positions_coverage,
        fill=selection_name
    )
) +
geom_flat_violin(
    position = position_nudge(x = .2, y = 0),
    alpha = .8,
    scale="width"
) +
geom_point(
    mapping=aes(color=selection_name),
    position = position_jitter(width = .15),
    size = .5,
    alpha = 0.8
) +
geom_boxplot(
    width = .1,
    outlier.shape = NA,
    alpha = 0.5
) +
scale_y_continuous(
    name="Activation position coverage",
    limits=c(0, 1.0)
) +
scale_x_discrete(
    name="Selection",
    limits=c("CohortLexicase", "DownSampledLexicase"),
    labels=c("Cohort lexicase", "Down-sampled lexicase")
) +
scale_fill_brewer(
    name="Selection",
    palette=cb_palette,
    limits=c("CohortLexicase", "DownSampledLexicase"),
    labels=c("Cohort lexicase", "Down-sampled lexicase")
) +
scale_color_brewer(
    name="Selection",
    palette=cb_palette,
    limits=c("CohortLexicase", "DownSampledLexicase"),
    labels=c("Cohort lexicase", "Down-sampled lexicase")
) +
theme(
    legend.position="none"
)
unique_start_positions_coverage_final_fig

```



## 10.6 Manuscript figures

```

legend <- cowplot::get_legend(
  elite_ave_performance_fig +
    guides(
      color=guide_legend(nrow=1),
      fill=guide_legend(nrow=1)
    ) +
    theme(
      legend.position = "bottom",
      legend.box="horizontal",
      legend.justification="center"
    )
)

grid <- plot_grid(
  elite_ave_performance_fig +
    ggtitle("Performance over time") +
    theme(legend.position="none"),
  elite_final_performance_fig +
    ggtitle("Final performance") +
    theme(),
  unique_start_position_coverage_fig +

```

```

    ggtitle("Activation position coverage over time") +
    theme(legend.position="none"),
  unique_start_positions_coverage_final_fig +
    ggtitle("Final activation position coverage") +
    theme(),
  nrow=2,
  ncol=2,
  rel_widths=c(3,2),
  labels="auto"
)


grid <- plot_grid(
  grid,
  legend,
  nrow=2,
  ncol=1,
  rel_heights=c(1, 0.1)
)

save_plot(
  paste(
    working_directory,
    "imgs/down-sampled-vs-cohort-panel.pdf",
    sep=""
  ),
  grid,
  base_width=12,
  base_height=8
)

grid

```







# Chapter 11

## Novelty lexibase

### 11.1 Overview

```
# Relative location of data.
working_directory <- "experiments/2021-06-01-novelty/analysis/"
# working_directory <- "./"

# Settings for visualization
cb_palette <- "Set2"
# Create directory to dump plots
dir.create(paste0(working_directory, "imgs"), showWarnings=FALSE)
```

### 11.2 Analysis dependencies

```
library(ggplot2)
library(tidyverse)
library(cowplot)
library(viridis)
library(RColorBrewer)
source("https://gist.githubusercontent.com/benmarwick/2a1bb0133ff568cbe28d/raw/fb53bd97121f7f9ce9")
```

These analyses were conducted in the following computing environment:

```
print(version)

##
## platform      x86_64-pc-linux-gnu
## arch          x86_64
## os            linux-gnu
```

```
## system      x86_64, linux-gnu
## status
## major       4
## minor       1.0
## year        2021
## month       05
## day         18
## svn rev     80317
## language    R
## version.string R version 4.1.0 (2021-05-18)
## nickname    Camp Pontanezen
```

### 11.3 Setup

```
data_loc <- paste0(
  working_directory,
  "data/timeseries-res-1000g.csv"
)

data <- read.csv(data_loc, na.strings="NONE")

data$cardinality <- as.factor(
  data$OBJECTIVE_CNT
)
data$selection_name <- as.factor(
  data$selection_name
)

data$epsilon <- as.factor(
  data$LEX_EPS
)

data$k <- as.factor(
  data$NOVEL_K
)


data$elite_trait_avg <-
  data$ele_agg_per / data$OBJECTIVE_CNT
data$unique_start_positions_coverage <-
  data$uni_str_pos / data$OBJECTIVE_CNT

final_data <- filter(data, evaluations==max(data$evaluations))

##### misc #####
```

```
# Configure our default graphing theme
theme_set(theme_cowplot())
```

```
elite_ave_performance_fig <-
  ggplot(
    data,
    aes(x=gen, y=elite_trait_avg, color=k, fill=k)
  ) +
  stat_summary(geom="line", fun=mean) +
  stat_summary(
    geom="ribbon",
    fun.data="mean_cl_boot",
    fun.args=list(conf.int=0.95),
    alpha=0.2,
    linetype=0
  ) +
  scale_y_continuous(
    name="Average trait performance",
    limits=c(0, 100)
  ) +
  scale_x_continuous(
    name="Generations"
  ) +
  scale_fill_brewer(
    name="k",
    palette=cb_palette
  ) +
  scale_color_brewer(
    name="k",
    palette=cb_palette
  )
elite_ave_performance_fig
```




### 11.4.1 Final performance

```
elite_final_performance_fig <- ggplot(
  final_data,
  aes(x=k, y=elite_trait_avg, fill=k)
) +
  geom_flat_violin(
    position = position_nudge(x = .2, y = 0),
    alpha = .8,
    scale="width"
  ) +
  geom_point(
    mapping=aes(color=k),
    position = position_jitter(width = .15),
    size = .5,
    alpha = 0.8
  ) +
  geom_boxplot(
    width = .1,
    outlier.shape = NA,
    alpha = 0.5
  ) +
  scale_y_continuous(
    name="Average trait performance",
```

```

    limits=c(0, 100)
  ) +
  scale_x_discrete(
    name="k"
  ) +
  scale_fill_brewer(
    name="k",
    palette=cb_palette
  ) +
  scale_color_brewer(
    name="k",
    palette=cb_palette
  ) +
  theme(
    legend.position="none"
  )
elite_final_performance_fig

```



## 11.5 Unique starting positions


```

unique_start_position_coverage_fig <- ggplot(
  data,
  aes(x=gen, y=unique_start_positions_coverage, color=k, fill=k)
)

```

```
) +
stat_summary(geom="line", fun=mean) +
stat_summary(
  geom="ribbon",
  fun.data="mean_cl_boot",
  fun.args=list(conf.int=0.95),
  alpha=0.2,
  linetype=0
) +
scale_y_continuous(
  name="Activation position coverage",
  limits=c(0.0, 1.0)
) +
scale_x_continuous(
  name="Generations"
) +
scale_fill_brewer(
  name="k",
  palette=cb_palette
) +
scale_color_brewer(
  name="k",
  palette=cb_palette
)
unique_start_position_coverage_fig
```






### 11.5.1 Final starting position coverage

```
unique_start_positions_coverage_final_fig <- ggplot(
  final_data,
  aes(x=k, y=unique_start_positions_coverage, fill=k)
) +
  geom_flat_violin(
    position = position_nudge(x = .2, y = 0),
    alpha = .8,
    scale="width"
  ) +
  geom_point(
    mapping=aes(color=k),
    position = position_jitter(width = .15),
    size = .5,
    alpha = 0.8
  ) +
  geom_boxplot(
    width = .1,
    outlier.shape = NA,
    alpha = 0.5
  ) +
  scale_y_continuous(
    name="Activation position coverage",
```

```

    limits=c(0, 1.0)
  ) +
  scale_x_discrete(
    name="k"
  ) +
  scale_fill_brewer(
    name="k",
    palette=cb_palette
  ) +
  scale_color_brewer(
    name="k",
    palette=cb_palette
  ) +
  theme(
    legend.position="none"
  )
unique_start_positions_coverage_final_fig

```



## 11.6 Manuscript figures

```

legend <- cowplot::get_legend(
  elite_ave_performance_fig +
  guides(

```

```

        color=guide_legend(nrow=1),
        fill=guide_legend(nrow=1)
    ) +
    theme(
        legend.position = "bottom",
        legend.box="horizontal",
        legend.justification="center"
    )
)


grid <- plot_grid(
  elite_ave_performance_fig +
    ggtitle("Performance over time") +
    theme(legend.position="none"),
  elite_final_performance_fig +
    ggtitle("Final performance") +
    theme(),
  unique_start_position_coverage_fig +
    ggtitle("Activation position coverage over time") +
    theme(legend.position="none"),
  unique_start_positions_coverage_final_fig +
    ggtitle("Final activation position coverage") +
    theme(),
  nrow=2,
  ncol=2,
  rel_widths=c(3,2),
  labels="auto"
)

grid <- plot_grid(
  grid,
  legend,
  nrow=2,
  ncol=1,
  rel_heights=c(1, 0.1)
)

save_plot(
  paste(working_directory, "imgs/novelty-panel.pdf", sep=""),
  grid,
  base_width=12,
  base_height=8
)

grid

```



# Bibliography

Lalejini, A. M. and Hernandez, J. G. (2021). Data for measuring the ability of lexicase selection to find obscure pathways to optimality.