

Flurry Advertising

Android Release Notes

SDK version 3.0.5
Updated: 10/26/2012

Version 3.0.5- 10/26/2012

- added fix to prevent crashing of bad phone ids in AndroidSDK 2.2

Version 3.0.4- 10/15/2012

- added additional delegate methods for spaceDidReceiveAd and spaceDidFailToReceiveAd when ads are/aren't received
- deleted unused delegate listener onReward
- renamed IListener to FlurryAdListener
- fixed offerwall bug where after app is installed and opened from the playstore, returning to app causes crash
- fixed bug where banners are loaded faster than expected when device is rotated
- fixed bug where onStartSession/initializeAds crashed due to race condition and phoneId.
- added method for sending ad event logs for mediated networks to server on endSession
- prevent mediated takeovers from auto-refreshing

Version 3.0.3- 09/26/2012

- fixed rotation of network ads
- allow users to opt out of viewing clips ads if they have not loaded
- verified support for clips in AdUnity
- verified support for re-engagement in AdUnity
- fixed concurrent modification exception race condition when trying to send logs
- fixed offerwall bug where min, max offers not being honored
- added support for network mediation of millenial 4.5.1
- fixed auto-rotation of offerwall templates
- fixed bug where non-supported clips video would attempt to be played

Version 3.0.2- 07/30/2012

- Added a public method "enableTestAds" to fetch all ads in test mode
- fixed impression tracking bug that resulted in impressions=clicks in reporting
- fixed offerwall bug where closing one fullscreen offerwall opened another
- fixed offerwall bug where low number of offers shown
- fixed templating bug caused by ads with an apostrophe in title or description
- fixed a bug that prevented install_referrer from working with the google play store

Version 3.0.1- 07/12/2012

- Fixes potential race conditions on startSession and initializeAds
- Fixes clearing of user cookies.
- Fixes visibility of user logs and warnings in case of incorrect integration
- Fixes potential clashes of libraries if developers are using the same.

Version 3.0.rc.128 - 06/14/2012

- Adds method to check if an ad is available
- Adds method initialize to allow precaching of ads at startup.
- Adds methods setKeywordsForTargeting:(NSDictionary *)keywords to allow campaign targeting based on developer supplied key-value pairs.
- Updates `FlurryAgent.getAd` to include a default ad size parameter.
- Updates `FlurryAgent.getAd` to display ad completely asynchronously (without blocking) when timeout is set to 0. This is useful for the display of banners where interaction with the app can continue unimpeded by the ad display (in contrast to an interstital view).
- Implementation of Rewarded Catalogs
- Updates ad tracking to specify unique key for every distinct frame.
- Added method to enable setting up individual ad spaces to receive test ads.

Version 3.0.a.124 - 05/09/2012

- Allows finer control of ad display with new method `FlurryAgent.removeAd(Context context, String myAdSpaceName, ViewGroup viewSpace);`. This method allows a publisher to decide exactly when to remove an ad from a view.
- Adds checks for failed requests to receive ads from third party networks.
- Prevents code paths that can result in infinte loops
- Updates location to send ad logs

Version 3.0.a.123 - 05/02/2012

- Initial Release of Alpha SDK
