

Notes 8

awk

- **Definition**
 - Used for processing and displaying text.
- **Formula**
 - `awk + options + {awk command} + file + file to save (optional)`
- **Examples**
 - Print the first column of every line of a file.
 - `awk '{print $1}' ~/Documents/Csv/cars.csv`
 - Print first field of /etc/passwd file.
 - `awk -F: '{print $1}' /etc/passwd`
 - Print the first and last field of the /etc/passwd file.
 - `awk -F: '{print $1," = ",$NF}' /etc/passwd`

sed

- **Definition**
 - Performs operations on files and standard output.
- **Formula**
 - `sed + options + sed script + file`
- **Examples**
 - Replacing a string in given file (replace pizza for rice).
 - `sed 's/pizza/rice/' shopping-list.lst`
 - Replacing the number of occurrences of a pattern in a file.
 - `sed 's/pizza/rice/4' shopping-list.lst`
 - Replacing from the given number occurrence to the rest occurrences in a file. Start at the second time the word appears and continue to till the end of the file.
 - `sed 's/pizza/rice/3g' shopping-list.lst`

less

- **Definition**
 - Used to display the contents of a file or a command output one page at a time.
- **Formula**
 - `less + options + filename`
- **Examples**
 - Viewing a small file.
 - `less -F ~/Documents/godzilla/godzilla2014.erl`
 - Viewing a file using absolute path.
 - `less ~/Documents/dbz.txt`
 - Viewing a file using relative path.
 - `less ../dbz/goku.txt`

- **Definition**

- Used to save standard output.

- **Formula**

- `output +> + file`

- **Examples**

- Save the output of a command to a file.
 - `ls -lA ~ > all-files-in-home.txt`
- Save the error generated by a command to a file.
 - `ls -lA downloads/ 2> error-of-ls`
- Save the error to a file and the success to another.
 - `ls -lA downloads/ Pictures > success.txt 2> error.txt`

>>

- **Definition**

- Used to add more to a file instead of overwriting its content.

- **Formula**

- `command +>> + file`

- **Examples**

- Add the output of `ls -la` to the end of the file `allmyfiles.lst`
 - `ls -la >> allmyfiles.lst`
- Add text to the end of a file.
 - `echo "I like dinosaurs" >> jurassic_park.txt`
- Add content of one file to another.
 - `cat file1.txt >> file2.txt`

|

- **Definition**

- Used to redirect the standard output of a command to the standard input of another.

- **Formula**

- `command_1 + | + command_2 + | + command_3 + | + ... + | + command_N`

- **Examples**

- Use `grep` to look for a string in a particular man page.
 - `man ls | grep "human-readable"`
- Display only the options of any command from its man page.
 - `man ls | grep "^[[:space:]]*[[[:punct:]]]"`
- Display only the ip addresses from the output of the `ip` command.
 - `ip addr | grep -Eo '[[[:digit:]]{1,3}\. [[[:digit:]]{1,3}\. [[[:digit:]]{1,3}\. [[[:digit:]]{1,3}]'`