

Zero-calibration BMIs for sequential tasks using error-related potentials

Jonathan Grizou*, Iñaki Iturrate†, Luis Montesano†, Manuel Lopes*, Pierre-Yves Oudeyer*

* INRIA Bordeaux Sud-Ouest, France {jonathan.grizou, manuel.lopes, pierre-yves.oudeyer}@inria.fr

† Departamento de Informática e Ingeniería de Sistemas (DIIS), Universidad de Zaragoza, Spain
{iturrate, montesano}@unizar.es



JONATHAN GRIZOU

Learning from EEG error-related potentials






Fig. 1. Experimental protocol. *Green square*, moving cursor. *Red square*, target location. *Dotted square*, cursor location at the previous time step. Correct and erroneous movements are shown at times $t + 1$ and $t + 2$, respectively.

Chavarriaga, Ricardo, and J. del R Millán. "Learning from EEG error-related potentials in noninvasive brain-computer interfaces." *Neural Systems and Rehabilitation Engineering, IEEE Transactions on* 18.4 (2010): 381-388.

Experimental setup




Iturrate, I., L. Montesano, and J. Minguez. "Task-dependent signal variations in EEG error-related potentials for brain–computer interfaces." *Journal of neural engineering* 10.2 (2013): 026024.



Calibration

Restricted interaction protocol,
e.g. assessing agent's actions


Known target, i.e. known signal to
meaning relation




Calibration

Restricted interaction protocol,
e.g. assessing agent's actions

Known target, i.e. known signal to
meaning relation



Infer signal to meaning model,
e.g. train a classifier





Calibration

Restricted interaction protocol,
e.g. assessing agent's actions

Known target, i.e. known signal to
meaning relation



Infer signal to meaning model,
e.g. train a classifier





Learning

Restricted interaction protocol,
e.g. assessing agent's actions

Unknown target, but target must be
one of the squares

Known signal to meaning classifier




Calibration

Restricted interaction protocol,
e.g. assessing agent's actions

Known target, i.e. known signal to
meaning relation



Infer signal to meaning model,
e.g. train a classifier



Learning



Restricted interaction protocol,
e.g. assessing agent's actions

Unknown target, but target must be
one of the squares

Known signal to meaning classifier



Identify the intended target



Calibration and Learning

Restricted interaction protocol,
e.g. assessing agent's actions

Known target, i.e. known signal to
meaning relation



Infer signal to meaning model,
e.g. train a classifier


Restricted interaction protocol,
e.g. assessing agent's actions

Unknown target, but target must be
one of the squares

Known signal to meaning classifier



Identify the intended target



Calibration and Learning

Restricted interaction protocol,
e.g. assessing agent's actions

Known target, i.e. known signal to meaning relation





Infer signal to meaning model,
e.g. train a classifier

Unknown target, but target must be one of the squares

Known signal to meaning classifier



Identify the intended target



Calibration and Learning

Restricted interaction protocol,
e.g. assessing agent's actions

Known target, i.e. known signal to
meaning relation




Infer signal to meaning model,
e.g. train a classifier

Unknown target, but target must be
one of the squares

Known signal to meaning classifier




Identify the intended target



Calibration and Learning

Restricted interaction protocol,
e.g. assessing agent's actions

Known signal to meaning relation for
each hypothetic target




Calibration and Learning

Restricted interaction protocol,
e.g. assessing agent's actions

Known signal to meaning relation for
each hypothetic target

The intended hypothesis should label correctly the signals



Calibration and Learning


Restricted interaction protocol,
e.g. assessing agent's actions

Known signal to meaning relation for
each hypothetic target

The intended hypothesis should label **correctly** the signals
???


What does it means ? we do not know the ground truth!

Toy example




Sequential task
{state, action, instruction} interaction loop
Instructions are feedback on the robot' actions

Toy example



Sequential task
{state, action, instruction} interaction loop
Instructions are feedback on the robot' actions

Finding the hypothesis that best explains the underlying structure of the data





- 1- Assigning hypothetic labels for each possible target
- 2- Computing the likelihoods of the resulting datasets (signal + label)



Correct



Wrong







Correct



Wrong







Correct



Wrong








Correct



Wrong






Correct



Wrong









Correct





Wrong







Experimental setup




- 34 features, high amount of noise
- 25 possible targets (5x5 grid world)

Online experiments



Standard calibration procedure : ~ 400 steps

Planning



Requirements

Hypothesis (a finite and reasonable number for now).

Pre-defined interaction frame to interpret the signals wrt. an objective, e.g. feedback, guidance, object naming...

Useful feature space to project signals.

A unifying framework ?

Calibration procedure: Reducing the number of hypothesis to one.

Language games: Several objects, one is named.

...

A unifying framework ?

Calibration procedure: Reducing the number of hypothesis to one.


Language games: Several objects, one is named.

...

Which open new perspectives

Perspectives

Different people, with their own preferences, skills, and limitations.



Requires to build a personalized database for each user and modality

Perspectives

Different people, with their own preferences, skills, and limitations.

Different Languages



Adaptive Classifier

Adaptive Classifier

Adaptive Classifier

Brain signals



Adaptive Classifier




Adaptive Classifier

Adaptive Classifier

Adaptive Classifier

Facial expressions



Hand signs



Gestures



Adapt automatically and online
to each user's own preferred teaching signals.

Of interest

- Learn a task from unlabeled signals
- Reuse acquired knowledge.
- Use standard classification technics.
- Signal expressed as feature vector in \mathbb{R}^N (can encode facial expression, gesture, speech, EEG ...).

Of interest

- Learn a task from unlabeled signals
- Reuse acquired knowledge.
- Use standard classification technics.
- Signal expressed as feature vector in R^N (can encode facial expression, gesture, speech, EEG ...).

Limitations

- Non differentiable signals: as other technics but we can't test it
- Computationally expensive, but highly parallelisable
- Symmetric hypothesis

Of interest

- Learn a task from unlabeled signals
- Reuse acquired knowledge.
- Use standard classification technics.
- Signal expressed as feature vector in R^N (can encode facial expression, gesture, speech, EEG ...).

Limitations

- Non differentiable signals: as other technics but we can't test it
- Computationally expensive, but highly parallelisable
- Symmetric hypothesis

Short-term applications

- Cases requiring an expert to calibrate and re-calibrate devices due to frequent signal variations.
- Example of suitable scenario: grasping an object on a table.

Thank you for your attention

jonathan.grizou@inria.fr

<https://flowers.inria.fr/jgrizou>

Jonathan Grizou, Manuel Lopes, and Pierre-Yves Oudeyer. "Robot learning simultaneously a task and how to interpret human instructions." *Joint IEEE International Conference on Development and Learning and on Epigenetic Robotics (ICDL-EpiRob)*. 2013.



JONATHAN GRIZOU