

1. Table of contents

- 1. Table of contents
 - 1.1. Introduction
- 2. Markdown Notes
 - 2.1. VsCode extensions
- 3. Git notes
 - 3.1. Notes on creating a git repository on github
 - 3.1.1. Some notes on the above commands
 - 3.2. Check previous commit
 - 3.3. Git stash and log
 - 3.4. Create local git repository
 - 3.5. Change the author name
 - 3.6. Remove tracked file that is now in .gitignore
 - 3.7. Check last commit changes
 - 3.8. Installing git in live ISO arch
 - 3.9. Change remote URL
 - 3.10. Add remote URL
 - 3.11. Different Pushes
 - 3.12. Download a file from github
 - 3.13. Merge branches
 - 3.14. Check merge conflicts
 - 3.15. Merge mistake (You committed changes to (local) master)
 - 3.16. Git merge "Deleted by us"
 - 3.17. Commit ID and SHA
 - 3.18. Git over ssh using ssh config
- 4. Bash Notes
 - 4.1. Bash Note 1
 - 4.2. Bash Note 2
 - 4.3. Bash Note 3
 - 4.4. Bash Note 4 - Compare Files
 - 4.5. Bash Note 5 - Use of curly braces
 - 4.6. Bash Note 6 - Search recursively in directory
- 5. Lyx
 - 5.1. Configure lyx
 - 5.2. Kpathsea
 - 5.3. Configure minted
 - 5.4. Install custom cls
- 6. Qemu
 - 6.1. Commands
 - 6.2. Variables
- 7. Inkscape
- 8. VsCode
- 9. Zathura
- 10. Zsh

- [11. Jupyter](#)
 - [11.1. Jupyter-Lab](#)
 - [11.2. Opening browser](#)
- [12. Tmux](#)
- [13. Pacman](#)
 - [13.1. Pacman cache](#)
 - [13.2. Install from live usb](#)
 - [13.3. Pacman infos](#)
 - [13.4. pacman mirrors](#)
- [14. Grub](#)
 - [14.1. Install grub manually when manjaro fails](#)
- [15. Vim](#)
 - [15.1. Install Vim in cluster](#)
 - [15.2. Vim snippets](#)
 - [15.3. Manage Tabs](#)
 - [15.4. Vim surroundings](#)
 - [15.5. Some commands](#)
- [16. Lighdm](#)
- [17. i3Blocks](#)
- [18. PcmamFM](#)
 - [18.1. Basic Configuration](#)
- [19. MPV](#)
 - [19.1. Annoying bar at the top](#)
 - [19.2. Watch stream](#)
- [20. Mime-Types](#)
 - [20.1. Alternative to xdg:](#)
- [21. Color-Scheme](#)
- [22. LibreOffice](#)
- [23. Misc](#)

1.1. Introduction

In this document I include some notes about general stuff I learn and do during my work/free time.

2. Markdown Notes

2.1. VsCode extensions

- Markdown all in One
 - `Ctrl + Shift + P`: Markdown All in One: section numbers, create table of contents, etc
- Markdown lint
- vscode-pandoc
 - `Ctrl + Shift + P` -> Pandoc Render
 - Add `"pandoc.pdfOptString": "-t html --css style.css"` to `settings.json` in `.vscode/settings.json` in the work directory containing the markdown project. This `settings.json` overrides the global variables specified in that file. This can also be edited by doing `Ctrl+Shift+P: Preferences: Workspace Settings`. The `style.css` is put in the same folder of the `.md` file
 - ``pacman -S pandoc pandoc-crossref wkhtmltopdf``
- Markdown PDF

We can add to the `setting.json` for vscode workspace to use a specific style to generate the pdf:

```
"markdown-pdf.styles": [  
    "style.css",  
],
```

3. Git notes

3.1. Notes on creating a git repository on github

On folder do:

```
git init
git commit
git branch -M main
git remote add origin https://github.com/jgroboredo/test.git
git push -u origin main
```

3.1.1. Some notes on the above commands

- `git branch -m master main`

renames the master branch in local git repository

- In the second step, we'll have to create a new branch on the remote named "main" - because Git does not allow to simply "rename" a remote branch. Instead, we'll have to create a new "main" branch and then delete the old "master" branch: `git push -u origin main` We now have a new branch on the remote named "main".
- When you clone a repository with `git clone`, it automatically creates a remote connection called origin pointing back to the cloned repository.
- When you do a `git push origin master`, you are saying to git: "Look git, I want to push the current branch I am on to the remote repository named origin, and I want to push to the master branch in that remote.". By default, the remote repository is named origin. I only need to specify where I want to push if there are more than 1 repositories.
- When you execute the command: `git remote add origin "github repo link"` you are saying that for the current project, there is a remote repository with the name origin, with the address of "github repo link"

3.2. Check previous commit

```
git log
git checkout <commit_hash> (example:
18e0b6a044a715b04bcacd599061b6b8bd586a7a)
git checkout <branch_to_return_to_present_state>
```

3.3. Git stash and log

```
git log --stat -> see which files were altered in each commit
git stash; git stash list; git stash drop
```

3.4. Create local git repository

- Create a folder which is going to be the "server" -> For example, Notes.git
- Inside the repository do: `git init --bare`
- On the same computer do: `git clone /path/to/server` -> the repository created this way will be linked to the "server" by an absolute path which only works on this same pc
- On the other computer do: `git clone goncalo@ip:/path/to/server`

3.5. Change the author name

```
git config --global user.name "John Doe"
```

3.6. Remove tracked file that is now in .gitignore

```
git rm --cached <file>
```

3.7. Check last commit changes

`git show --name-only` -> Lists just the files in the last commit and doesn't give you the entire guts
`git diff HEAD^ HEAD` -> HEAD^ identifies last commit

3.8. Installing git in live ISO arch

If error in keys: `pacman -Sy archlinux-keyring; pacman-key --populate archlinux`

3.9. Change remote URL

- `git remote -v`

To check the present remote url

- `git remote set-url origin git@github.com:jgrobored0/Linux_Infos.git`

3.10. Add remote URL

- `git remote add name_of_remote git@github.com:jgrobored0/Linux_Infos.git`
- `git push -u name_of_remote --all`

Note: this changes the default repository! It also pushes all branches!

- `git config --edit`

Can use this command to change the default git push

- `git branch --set-upstream-to <remote-name>`

Set preferred remote for current branch

- `git branch branch_name --set-upstream-to <remote-name>/branch`

set preferred remote for branch_name

- `git branch -vv`

shows the default remote for the current branch

3.11. Different Pushes

- To push all branches to all remotes: `git remote | xargs -L1 git push --all`
- Push a specific branch to all remotes: `git remote | xargs -L1 -I R git push R branch_name`
- To make a git alias for the command: `git config --global alias.pushall '!git remote | xargs -L1 git push --all'`

Or

- Create an all remote with several repo URLs to its name:

```
git remote add all origin-host:path/proj.git
git remote set-url --add all nodester-host:path/proj.git
git remote set-url --add all duostack-host:path/proj.git
git push all --all
```

Or

- If you want to always push to repo1, repo2, and repo3 but always pull only from repo1, set up the remote 'origin' as:

```
git remote add origin https://exampleuser@example.com/path/to/repo1
git remote set-url --push --add origin
https://exampleuser@example.com/path/to/repo1
git remote set-url --push --add origin
https://exampleuser@example.com/path/to/repo2
git remote set-url --push --add origin
https://exampleuser@example.com/path/to/repo3
```

- If you only want to pull from repo1 but push to repo1 and repo2 for a specific branch specialBranch:

```
[remote "origin"]
  url = ssh://git@aaa.xxx.com:7999/yyy/repo1.git
  fetch = +refs/heads/*:refs/remotes/origin/*
  ...
[remote "specialRemote"]
  url = ssh://git@aaa.xxx.com:7999/yyy/repo1.git
  pushurl = ssh://git@aaa.xxx.com:7999/yyy/repo1.git
  pushurl = ssh://git@aaa.xxx.com:7999/yyy/repo2.git
  fetch = +refs/heads/*:refs/remotes/origin/* (Note: Has origin here
again, only pulls from origin)
  ...
[branch "specialBranch"]
```

```
remote = origin
pushRemote = specialRemote
...
```

- My experience:
 - I can specify which remote to push or pull from:

```
git push remote_name branch
```

- A branch has a default remote: I only need to specify the remote_name and eventually the branch_name (I can't pull from a non-default remote without specifying the branch) if I don't want to do it to the default one

2.12. Use curl to download from github

```
tar xf master.tar.gz
```

3.12. Download a file from github

- Go to file, click on raw, copy link
- `curl -L "link_from_above_step" >> output`

3.13. Merge branches

- `git checkout master; git merge other_branch_name`
- Alternative: `git merge --no-ff other_branch_name`. Using `--no-ff` allows someone reviewing history to clearly see the branch you checked out to work on.
- `git branch -d branch_name`

deletes branch locally

- `git push origin --delete branch_name`

deletes a branch remotely

- `git fetch -p`

Synchronize branch listing. After fetching, branches which no longer exist on the remote will be deleted.

If I do a: `git pull origin master` on another branch, it will merge them. After creating a new branch, we need to specify tracking information for the current branch. That means we need to do something like

`git pull <remote> <branch>` for it to work. On the other hand, we can simply set tracking information for the current branch by: `git branch --set-upstream-to=origin/<branch>`
`correction_chapter1`

3.14. Check merge conflicts

`git show --name-only [commit sha]` on a commit that was a merge containing conflicts and you'll see it as part of the message.

3.15. Merge mistake (You committed changes to (local) master)

```
git branch <new-branch>
git reset HEAD~ --hard
git checkout new-branch
```

The first command creates the new branch we want to work with. The second command resets the main branch to just before the last commit, but leaves the changes you just made in the new branch. Finally, we switch to the new branch where your changes await you. If you've made multiple commits, use `git reset HEAD~<n> --hard`, where `n` is the number of commits back you want to go.

3.16. Git merge "Deleted by us"

Resolve all non deleted merge conflicts by hand, which you have to do anyway; Type `git diff --name-only --diff-filter=U` to get a list of all remaining files in conflict. These files must be the ones you want deleted. `git diff --name-only --diff-filter=U | xargs git rm`

3.17. Commit ID and SHA

```
git show -s --format=%H -> shows the last commit full id
git show -s --format=%h -> shows the last commit sha
```

3.18. Git over ssh using ssh config

`git remote set-url origin ssh://pi(here config name)/home/goncalo/HDD/Documents/git_repos/Notes.git` (here full path)

4. Bash Notes

4.1. Bash Note 1

- `$#`

number of arguments passed to the shell script

- `$1`, `$2`, etc

identify the arguments passed to the script

4.2. Bash Note 2

The code:

```
case $1 in
  -f|--from) command1; shift ;;
  *)        command2;;
esac
shift
```

will check if the first argument `$1` passed to the script matches `-f` or `--from` or any other cases; The asterisk means that it does `command2` if it doesn't match any of the cases above; The "shift" command shifts the arguments, i.e., if I have `$1`, `$2` arguments, then `$2 -> $1`.

4.3. Bash Note 3

The code:

```
SCRIPT_DIR="$( cd "$( dirname "${BASH_SOURCE[0]}" )" &> /dev/null && pwd )"
```

will give you the full directory name of the script no matter where it is being called from.

4.4. Bash Note 4 - Compare Files

```
grep -F -x -v -f fileA fileB
```

This works by using each line in `fileA` as a pattern (`-f fileA`) and treating it as a plain string to match (`-F`). You force the match to happen on the whole line `-x` and print out only the lines that don't match (`-v`). Therefore, you are printing out the lines in `fileB` that don't contain the same data as any line in `fileA`.

4.5. Bash Note 5 - Use of curly braces

1. In the example:

```
var=10          # Declare variable

echo "${var}"  # One use of the variable
echo "$var"    # Another use of the variable
```

it makes no difference to use curly braces.

2. However, the `{}` in `${}` are useful if you want to expand the variable `foo` in the string `"${foo}bar"` since `"$foobar"` would instead expand the variable identified by `foobar`.

Curly braces are also unconditionally required when:

- expanding array elements, as in `${array[42]}`
- using parameter expansion operations, as in `${filename%.*}` (remove extension)
- expanding positional parameters beyond 9: `"$8 $9 ${10} ${11}"`

4.6. Bash Note 6 - Search recursively in directory

- `grep -R "stuff"` will search recursively on all files on that directory and look for the word `stuff`
- `for i in **/.ipynb_checkpoints` will find recursively all directories with this name
- `for i in ./pattern` will search for this pattern in current directory

5. Lyx

5.1. Configure lyx

- Tools-Preferences-File Formats: PDF (pdflatex), shortname: pdf2, Viewer: Custom - zathura
- Tools-Preferences-Output-PDF command: `zathura --synctex-forward $$n:1:$$t $$o`
- Tools-Preferences-Shortcuts-New: buffer-view pdf2 and buffer-update pdf2
- For the spellchecker, might need to install hunspell-en_US and hunspell-pt_pt and enchant
- For lgrenc.def not found -> install texlive-langgreek
- To use eps figures in lyx I need ghostscript : try to epstopdf on command line to discover this.

5.2. Kpathsea

- Kpathsea is a library for path searching (e.g., for very quickly locating a given .sty file in a set of potentially large TEXMF trees, without doing a recursive directory tree traversal every time a given file is needed. (pse -> pathsea)
- kpsewhich minted.sty to search efficiently on tex library

5.3. Configure minted

```
sudo mkdir "/usr/share/texmf-texlive/tex/latex/minted/"
sudo cp minted.sty "/usr/share/texmf-texlive/tex/latex/minted/"
sudo mktexlsr
```

- Then in lyx, go to Tools/Tex Information, select latex styles and click rescan. minted.sty should appear in the list in lyx, go to "Tools>preferences>file handling>converters" and find the converter from tex to pdflatex. Edit its command line adding the option "-shell-escape" (no quotes) into the Converter field, then click the Modify button next to the list of converters. This is equivalent to going to Documents->Formats->Allow running external programs (is a better solution since it avoids writing a warning message). Then click Apply in lyx, go to Document>Settings and enter "/usepackage{minted}" (no quotes) in the latex preamble in lyx, in the part of your document where you want the highlighted code to appear, go to "Insert>TEX code" to get an Evil Red Text (ERT) box
- In Document->Settings->Listings, add following options:
 - language=C++
 - frame=single
 - mathescape=true
 - `syoeck --synctex-forward $$n:1:$$t $$o`
- Ordered bibliography: Use style unsrt and add to preamble: `\usepackage{notoccite}`

5.4. Install custom cls

- `latex my_class.ins` -> produces my_class.cls
- `kpsewhich -var-value=TEXMFHOME` -> prints path where to put cls

- Regarding the above command, it's good to put the usual path:
`$HOME/texmf/tex/latex/commonstuff/`
- `kpsewhich my_class.cls` -> to check path of the class
- Write lyx layout: In order to do this, find the basis class for our new class. For that, inspect `my_class.cls` and check the line `LoadClass`. It implies that `my_class.cls` is a descendent of that class (let's suppose it's dependent on `report` class). Then, in `/usr/share/lyx/layouts` copy `report.layout`, change its name to `my_class.layout` and edit like this:

```
\DeclareLaTeXClass[my_class]{name_of_layout}  
Input report.layout
```

- In lyx, reconfigure. Now, `name_of_layout` is the text we see in Document-Class
- Default classes: `/usr/share/texmf-dist/latex/elsarticle/elsarticle.cls`

6. Qemu

6.1. Commands

```
qemu-img create -f qcow2 qemu_image 8G
qemu-system-x86_64 -smp 6 -m 4G -enable-kvm -cdrom arch.iso -boot order=d
qemu_image
smp (number of cores)

qemu-system-x86_64 -soundhw ac97 -k en-us -vga std -enable-kvm -m 4G -
usbdevice tablet -smp 6 -enable-kvm -boot c qemu_image
#For no sound
qemu-system-x86_64 -k en-us -vga std -enable-kvm -m 4G -usbdevice tablet -
smp 6 -boot c qemu_image
```

6.2. Variables

```
-k en-us (keymap)
-usbdevice tablet

-cpu host
-smp 6 # number of cores
-machine type=pc,accel=kvm
-enable-kvm
-format=raw ??
-machine smm=off # bug?
-soundhw sb16,es1370

#telnet access
qemu-system-x86_64 -curses -monitor telnet:127.0.0.1:1234,server,nowait -
boot c qemu_image
telnet 127.0.0.1 1234 -- in another terminal

#KVM Quick Check
zgrep CONFIG_VIRTIO /proc/config.gz
lsmod | grep kvm
```

7. Inkscape

- If I have problems with eps images, in this case, also need to install ghostscript.
- Do you have ImageMagick installed? LyX relies on ImageMagick to convert among graphics formats. It also needs Ghostscript installed (IM uses GS when the conversions involve PS, EPS or PDF files).
- If **textext** package from the AUR gives problem, simply go to **textext** official website and install it from there

8. VsCode

- You can format an entire file with Format Document (Ctrl+Shift+I) or just the current selection with Format Selection (Ctrl+K Ctrl+F) in right-click context menu.
- F1 -> command pallet
- SSH : F1 -> Remote-SSH: Connect to Host...
- Install extension: TabNine

9. Zathura

- `pacman -S zathura-pdf-poppler`
- make zathura default pdf viewer: `mimeo --ad application/pdf zathura.desktop`
- to discover the real name of zathura.desktop run `locate zathura.desktop`
- to check that pdf files have the correct mimetype run `mimeo -m pdf_file.pdf`
- Clipboard: add `set selection-clipboard clipboard` to `~/.config/zathura/zathurarc` or `/etc/zathurarc`

10. Zsh

```
git clone https://github.com/zsh-users/zsh-autosuggestions ~/.zsh/zsh-  
autosuggestions  
source ~/.zsh/zsh-autosuggestions/zsh-autosuggestions.zsh in .zshrc  
mkdir .cache/zsh && touch .cache/zsh/dirs
```

11. Jupyter

11.1. Jupyter-Lab

To run over ssh, execute

```
ssh -L 8888(port on local):localhost::8889(port on remote) goncalo@ip
jupyter-lab --no-browser --port=(same as before on remote)8889
```

- To avoid authentication by token: `jupyter server password`
- To list active sessions: `jupyter lab list`
- To kill a session: `jupyter lab stop 8888` (for e.g.)

11.2. Opening browser

If jupyter doesn't open, do : `jupyter lab build` If command above gives permission error, do:

```
sudo chown -hR {user} {dir}
jupyter notebook (lab) --generate-config
```

Also, change `redirect_file` to false Na verdade, isto não funciona porque tenho de mudar o `~/.profile` para firefox LOL

-
- Can't access file (probably happens cause directory contains hidden folder `.local`):
 - set `c.ServerApp.use_redirect_file = False` in `~/.jupyter/jupyter_server_config.py`
 - Stop server:

```
lsof -n -i4TCP:[port-number]
kill -9 [PID]
```

12. Tmux

ssh host, tmux, run command, `ctr+b d`, exit. To check the tmux session, run `tmux attach`

13. Pacman

- Update pacman mirrors: `reflector --verbose --latest 5 --sort rate --save /etc/pacman.d/mirrorlist`
- Check recently installed packages: `grep -i installed /var/log/pacman.log`

13.1. Pacman cache

```
sudo ls /var/cache/pacman/pkg/ | wc -l # checks cached packages
du -sh /var/cache/pacman/pkg/ # disk space occupied by cache
sudo paccache -r # cleans all packages except most recent 3
sudo paccache -rk 1 # keep only one most recent version
sudo pacman -Sc # remove all uninstalled packages
sudo pacman -Scc # remove installed and uninstalled packages from cache
sudo paccache -ruk0 #**** remove all versions of uninstalled packages
change /etc/pacman.conf ParallelDownloads=5
```

13.2. Install from live usb

```
mount system: mount /dev/sdax /mnt
sudo pacman --root /mnt -S package
sudo pacman -Qkk | grep warning # To verify the presence of the files
installed by a package
sudo pacman --root /mnt -S $(sudo pacman --root /mnt -Qeq) --noconfirm #
reinstalls installed packages
#If need to remove aur packages:
sudo pacman --root /mnt -Qeq > packages.txt
sudo pacman --root /mnt -S $(cat packages.txt) --noconfirm
```

13.3. Pacman infos

```
pacman -Qe # lists explicitly installed packages
pacman -Rsc # uninstalls (including unneeded dependencies)
pacman -Qs "query" # search installed packages for keywords
pacman -Qdt # list unneeded packages
pacman -Rns $(pacman -Qdtq) # uninstall unneeded packages (nota: quando
adicionei isto aos aliases, sempre que abri o terminal pedia-me a pass do
sudo (estava a correr o que esta a frente de $))
```

13.4. pacman mirrors

```
sudo pacman-mirrors --fasttrack && pacman -Syyu
```

14. Grub

- If no update-grub command, do:

```
sudo nano /usr/sbin/update-grub
"
#!/bin/sh
set -e
exec grub-mkconfig -o /boot/grub/grub.cfg "$@"
"

sudo chown root:root /usr/sbin/update-grub
sudo chmod 755 /usr/sbin/update-grub
```

- If error syntax in grub-customizer:
 - View -> Show placeholders
 - select entry "script code"
 - remove
- check kernel by `uname -r`

14.1. Install grub manually when manjaro fails

- Deactivate CSM in BIOS
- Quando acaba a instalacao, ver se ele cria a particao em /boot/efi ou /boot
- `sudo fdisk --list` (para ver onde foi instalada a particao no pc)
- `sudo su`
- `mount /dev/sda2 /mnt` (em que sda2 era a particao com o linux)
- `mount /dev/sda1 /mnt/boot/efi`
- `grub-install --target=x86_64-efi --efi-directory=/mnt/boot/efi --bootloader-id=manjaro --boot-directory=/mnt/boot --recheck --debug`
- `manjaro-chroot -a`
- `update-grub`
- `umount -R /mnt`

[Link](#)

15. Vim

- `yay -S vim-plug-git`
- add `.vimrc` with the plugs I want
- add folder `~/.vim/plugged/`
- to install plugs, do `:PlugInstall`
- for fzf plugin: `:Files` command
- For the NERDTree plugin to see icon of file, install: `yay -S nerd-fonts-complete`; This font package may screw up font sizes of icons. To correct this, add to i3blocks config the following:

```
<span size='small' font_weight='light'> icon </span>
```

And change font on terminal to SauceCodePro Nerd Font Medium

- To open a file in a new tab in nerdtree, press t (or T); to open vertically click s;
- To cycle through windows: C-W-W, C-W-H, C-W-L, C-W-J, C-W-K
- To open file using fzf do:
- CTRL+T to open in new tab
- CTRL+X to open a new split
- CTRL+V to open in a new vertical split
- While in NERDTree, click on "m" to have a menu to do stuff with the file or other things
- `yay -S vim-youcompleteme-git` -> vim autocompletion (Needs to be done separately from the installation of the dotfiles)
- No need to add this plugin (vim-youcompleteme-git) to the `.vimrc` file
- add: `let g:ycm_show_diagnostics_ui = 0` to disable error checking by YouCompleteMe
- `pacman -S python-black`

15.1. Install Vim in cluster

```
git clone https://github.com/vim/vim.git
./configure --prefix=$HOME/.local && make && make install
# More flags: --disable-perlinterp --enable-rubyinterp --enable-multibyte -
--enable-pythoninterp --with-features=huge
export PATH="/home/youruser/.local/bin:$PATH"
# For plugins:
mkdir .vim/autoload
curl -fLo ~/.vim/autoload/plug.vim --create-dirs \
https://raw.githubusercontent.com/junegunn/vim-plug/master/plug.vim
```

Place in `.vimrc` before `plug#begin()`:

```
let data_dir = has('nvim') ? stdpath('data') . '/site' : '~/.vim'
if empty(glob(data_dir . '/autoload/plug.vim'))
```

```

    silent execute '!curl -fLo '.data_dir.'/autoload/plug.vim --create-dirs
https://raw.githubusercontent.com/junegunn/vim-plug/master/plug.vim'
    autocmd VimEnter * PlugInstall --sync | source $MYVIMRC
endif

```

15.2. Vim snippets

- `:UltiSnipsEdit` command opens up a custom snippets file for the current language/filytype
- Don't need the above step if I install vim-snippets plugin

15.3. Manage Tabs

- To move tabs -> `Alt + arrows`
- To merge tabs -> `Ctr + m` or `Ctrl + n`;
- To exchange position of merged tabs -> `<C-w> x`;
- To change cursor position -> `<C-w> w`;
- To rotate windows -> `<C-w> <C-r>`

15.4. Vim surroundings

- `cs(atual)(target)` -> change surround from "atual" to "target"
- `ds` -> delete surround "
- `ysiw` -> yank surround inner word [-> puts [surrounding the word the curson is in
- `ysf(smth)` -> puts [surrounding current cursor position till smth

15.5. Some commands

- procurar coisas: `/searchthing` e usa-se `n` ou `N` para avançar para as seguintes
- procurar string e substituir:

```

:s/search/replace/
:8,10 s/search/replace/g procura nas linhas 8 a 10
:%s/search/replace/g procura no documento inteiro
:%s/search/replace/gc pede confirmação para alterar

```

- copiar e colar: seleccionar o texto, y copia, p cola

16. Lighdm

```
pacman -S lightdm-gtk-greeter-settings  
change default greeter: /etc/lightdm/lightdm.conf under [Seat:*)  
pacman -S archlinux-wallpaper  
pacman -S materia-gtk-theme  
yay -S pop-icon-theme-git  
yay -S pop-gtk-theme
```


17. i3Blocks

For the scripts to work, even if it is .py, need to chmod +x

- <https://github.com/vivien/i3blocks-contrib/tree/master/>
- For calendar, install yad and xdotool; add: `for_window [class='Yad'] floating enable`

18. PcmanFM

18.1. Basic Configuration

- Go to edit -> Preferences -> Advanced :
 - Set terminal emulator (ex: xfce4-terminal) -> to open directly with vim for example
 - Set archiver integration: xarchiver
- To see thumbnails, install the following packages:
 - poppler-glib
 - ffmpegthumbnailer
 - freetype2
 - raw-thumbnailer
 - tumbler
 - libgsf
 - libgepub

19. MPV

19.1. Annoying bar at the top

- Change picom config: frame-opacity option

19.2. Watch stream

- `pacman -S yt-dlp`
- `mpv 'link'`

20. Mime-Types

20.1. Alternative to xdg:

- `yay -S mimeo`
- `yay -S xdg-utils-mimeo`

MIMEO COMMANDS

- Open files (foo, bar, etc): `mimeo foo bar baz`
- find Leafpad's desktop file: `mimeo --app2desk leafpad`
- determine "test" file's MIME-type: `mimeo -m test`
- associate "application/x-shellscript" with Leafpad: `mimeo --add application/x-shellscript leafpad.desktop`
- Associate all text files with Medit: `mimeo --add 'glob:text/*' medit.desktop`
- Association File Examples: (`mimeo --assoc-help`)

```
vlc --one-instance --playlist-enqueue %U
    ^https?:/(www.)?youtube.com/watch\?.*v=
```

Open HTTP(S) URLs with Firefox:

```
/usr/bin/firefox %U
    ^https?:/
```

Open various media files in VLC by extension:

```
/usr/bin/vlc --one-instance --playlist-enqueue %F
    \.mp3$
    \.flac$
    \.avi$
```

- CUSTOM ASSOCIATION FILES (`mimeo --help`, `mimeo --filepath-help` If `--assoc` is not passed then the following paths will be checked for custom associations, in order:

```
/home/goncalo/.config/mimeo/associations.txt
/etc/xdg/mimeo/associations.txt
```

Note: Eventually try mimi! Links:

- [repo](#)
- [aur](#)

Note: eventually take a look at package `perl-file-mimeinfo` (`mimeoopen -d`)

21. Color-Scheme

- Install: python-pywal
- Install: `yay -S fzwal-git`
- Run: `wal --theme base16-nord`
- Add to .zshrc: (`cat ~/.cache/wal/sequences &`)
- Add to .vimrc:
 - Plug 'dylanaraps/wal.vim' (install with PlugInstall)
 - `colorscheme wal`
 - `set background=dark`

NOTE:

- This pywal thing seems to screw up with other windows. Removed for now!
- It seems like it isn't pywal that messed with firefox -> Firefox stopped crashing when I disabled the popOS gtk theme!!!

22. LibreOffice

- Latex in impress: `pacman -S libreoffice-extension-texmaths`
- Check extension in Extension Manager inside libreoffice
- To install ExpandAnimations go to Tools->ExtensionManager and add there the oxt file

23. Misc

1. By disabling all F86 binds in config and installing xfce-power-management (which needs to be started in config and need to get config from Manjaro/Home/.config) and installed pa-applet-git, pavucontrol and pulseaudio (initiated in config) all the F86 binds work.
2. It is preferable to have xfce4-notify (initiated in config by running `/usr/lib/xfce4/notifyd/xfce4-notifyd`) than dunst... Better notifications. Check i3 config and uninstall dunst (in endeavour). In manjaro, do: `sudo mv /usr/share/dbus-1/services/org.knopwob.dunst.service{,.disabled}`
3. Bluetooth:
 - `pacman -S pulseaudio-bluetooth`
 - `pulseaudio -k`
 - `yay -S bluez-hciconfig`
 - `hciconfig -> lists bluetooth interfaces`
 - `sudo hciconfig hci1 down -> turn off specific interface`
4. Sticky xrandr:
 - `xrandr --output eDP --primary`
 - `pacman -S autorandr`
 - `autorandr --save laptop`
5. FSTAB

```
sshfs : jose@pi:/mnt/rebelo-pi fuse.sshfs noauto,x-
systemd.automount,_netdev,user,idmap=user,follow_symlinks,identityfile
=/root/.ssh/id_rsa,allow_other,default_permissions,uid=1995,gid=1995,n
oatime,reconnect,ServerAliveInterval=45,ServerAliveCountMax=2 0 0
```

6. SYMBOLIC LINKS

- `ln -s /complete/path/to/original/file /complete/path/to/target/file` (the target file will be a "pointer" to the original file, but it's like the file is in the new target location)
- `ln -sr /relative/path/to/original/directory /complete/path/to/target/directory` (the target directory will be a link to the first; the -r flag means relative)
- The -f flag will force the link, meaning it deletes the target file/directory if it exists

- Remember to always use complete paths and not relative paths if the -r flag is not specified

7. SSH

- I can run commands over ssh like this: `ssh user@host 'command'`
 - Example: `ssh liplisboacluster 'echo ${hostname}'` -> prints hostname
- Writing on a remote file:

```
echo 'Some Text' | ssh user@remotehost -T "cat > /remotefile.txt"
# (-T flag forwards stdin local through ssh)
cat ~/.ssh/id_rsa.pub | ssh user@remote.host 'dd
of=/.ssh/authorized_keys oflag=append conv=notrunc'
```

- In order to have several ssh keys, do:

```
ssh-keygen -t rsa -b 4096 -C "your_email@example.com"
eval $(ssh-agent)
ssh-add ~/.ssh/id_rsa2 (newly created key)
```

- In order to have ssh-agent always running, check ~/.config/systemd and .zshrc
- `systemctl --user enable ssh-agent.service` (probably don't need to do this since I have a backup of .config/systemd)
- Check services: `systemctl --user list-unit-files | grep enabled`
- Check services (all): `systemctl list-unit-files | grep enabled`
- Also, need to add to zshrc a function to load keys, since ssh-add only works for the current session
- To have a proxy:

```
Host 10.0.10.3
User goncalo
ProxyCommand ssh goncalo@jgroboredo.ddns.net -W %h:%p
```

- If ssh service fails to start with error: Start request repeated too quickly, do the following:

```
sudo systemctl stop sshd.socket and sshd.service
sudo /usr/bin/sshd -d
#If message from above command states a permission issue:
sudo chmod 400 /etc/ssh/ssh*key
```

8. Firefox crash

- Seems like it was the gtk theme from popOS that made firefox to crash
- In sway, if font problems, export `GTK_USE_PORTAL=1`

- In what concerns crashes, picom with xrender crashes! Need to use glx
- Today, 10/08/2021, firefox started crashing. Disabled picom and it did not solve the problem. Updated picom config from arch linux wiki, did not help. Firefox->Settings->Performance did not change anything
- Starting firefox from terminal does not seem to solve the problem. Does not output any errors.
- Testing launching firefox and terminal from i3 bind with the flag --no-startup-id -> doesnt work
- Testing google-chrome-stable; disabled guake
- Google-chrome also crashed; However, it recovered after a few seconds, similar to what previously happened to vscode. It seems like a X11 problem. Moved to sway.
- Testing again firefox crashes on i3. For now, uninstalled xf86-video-intel. Since then, no crashes yet.
- FIREFOX SLOW START:
 - about:config
 - set 0 to all widget.use-xdg-desktop-portal

9. ARCH NOT BOOTING IN VM

- On a recent installation of arch on a VM, it did not boot after installing the custom grub-theme. In order to solve this, either chroot or open a terminal using ctrl+alt+F2. There, delete the grub theme in /usr/share/grub/themes and after that run grub-mkconfig -o /boot/grub/grub.cfg
- The above solution doesn't work. In fact I am very dumb. This was only related with the fact that I have a intel config file in /etc/X11/xorg.d.... DUMBBBBB

10. FIND UUID OF DISK

- `sudo blkid | grep UUID=`

11. FIX YAY

- Error: yay: error while loading shared libraries: libalpm.so.11: cannot open shared object file: No such file or directory
- Fix: rebuild yay:

```
cd /tmp && git clone 'https://aur.archlinux.org/yay.git'  
&& cd /tmp/yay && makepkg -si && cd ~ && rm -rf /tmp/yay/
```

12. FIX PAMAC

- Error: libpamac-aur: /etc/pamac.conf exists in filesystem(owned by pamac-aur)
- Fix: `pacman -R pamac-aur && yay -S pamac-aur`

13. FIX TIME

- `sudo ntpd -qg`
- `install ntp`
- `sudo ntpdate pool.ntp.org`
- `timedatectl set-ntp true`

14. CHECK RAM `sudo dmidecode -t memory`

15. `lxrandr` to change monitors

16. CONFIG LINUX ACCOUNT

```
sudo useradd -m test
userdel <nome de utilizador do utilizador>
adduser username sudo
/etc/ssh/sshd_config # Allow pubkey and add authorized_keys file;
chsh -s $(which zsh)
sudo service ssh restart
# For redmine: couldn't add repos to redmine: change permissions:
chmod 775 /path/to/dir
```

17. Dmenu-extended

- For apps to open I need desktop files to associate a given mimetype to a binary
- After doing the above step, rebuild cache

18. NetworkManager/Network interface stopped working

- Solution: boot to a pen with manjaro and reboot
- See logs:

```
find /sys/class/net -follow -maxdepth 2 -name wireless
cat /proc/net/wireless
iw dev
sudo iw dev wlp0s20f3 connect "ROBOREDO"
sudo dmesg | grep firmware
sudo dmesg --level=emerg,alert,crit,err
lspci | grep net
lsmod
sudo ls /etc/netctl/interfaces
```

19. Rebuild all yay packages depending on python: `yay -S $(pacman -Qoq /usr/lib/python3.9) --answerclean All`

20. nc : install `pacman -S gnu-netcat`

21. Can add stuff to path in `.xinitrc`; a user `systemd` service needs to have `WantedBy=default.target` and not multi-user The `rcclone` command will not work in a user service since `systemd` doesn't have access to env variables. For that, just add a `env.conf` file to `.config/environment.d/` (check `printenv`)

22. Delay a systemd service:

```
[Service]
ExecStartPre=/bin/sleep 30
```

23. DMZ - portas abertas para toda a internet

24. `dhcpcd -T eth0` - check dns

25. PERMISSIONS

```
chown -R root:root /etc
find /etc -type f -exec chmod 644 {} +
find /etc -type d -exec chmod 755 {} +
chmod 755 /etc/init.d/* /etc/rc.local /etc/network/* /etc/cron.*/*
chmod 400 /etc/ssh/ssh*key
check desktop_dotfiles
```

26. Need imagemagick for blurlock

27. samba

```
smbclient '//print-server.critical.pt/Drivers/' -U critical/jgroboredo
(smbclient '//ip/Directory')
smbclient '\\files.critical.pt/Repository' -U critical/jgroboredo
get file
```

28. bluedevil; bluedevil-wizard; systemctl start bluetooth; pavucontrol: High Fidelity Playback (A2DP Sink, codec LDAC) blueberry-tray

29. `sudo lsof -i -P -n | grep LISTEN`

30. bash gum package

31. `gtk-update-icon-cache -f -t .icons` ou `(/usr/share/icons/)` Add icon field in desktop file - only the name.png