

1. Table of contents

- 1. Table of contents
 - 1.1. Introduction
- 2. Markdown Notes
 - 2.1. VsCode extensions
- 3. Git notes
 - 3.1. Notes on creating a git repository on github
 - 3.1.1. Some notes on the above commands
 - 3.2. Check previous commit
 - 3.3. Git stash and log
 - 3.4. Create local git repository
 - 3.5. Change the author name
 - 3.6. Remove tracked file that is now in .gitignore
 - 3.7. Check last commit changes
 - 3.8. Installing git in live ISO arch
 - 3.9. Change remote URL
 - 3.10. Add remote URL
 - 3.11. Different Pushes
 - 3.12. Download a file from github
 - 3.13. Merge branches
 - 3.14. Check merge conflicts
 - 3.15. Merge mistake (You committed changes to (local) master)
 - 3.16. Git merge "Deleted by us"
 - 3.17. Commit ID and SHA
 - 3.18. Git over ssh using ssh config
- 4. Bash Notes
 - 4.1. Bash Note 1
 - 4.2. Bash Note 2
 - 4.3. Bash Note 3
 - 4.4. Bash Note 4 - Compare Files
 - 4.5. Bash Note 5 - Use of curly braces
 - 4.6. Bash Note 6 - Search recursively in directory
- 5. Lyx
 - 5.1. Configure lyx
 - 5.2. Kpathsea
 - 5.3. Configure minted
 - 5.4. Install custom cls
- 6. Qemu
 - 6.1. Commands
 - 6.2. Variables
- 7. Inkscape
- 8. VsCode
- 9. Zathura
- 10. Zsh

- 11. Jupyter
 - 11.1. Jupyter-Lab
 - 11.2. Opening browser
- 12. Tmux
- 13. Pacman
 - 13.1. Pacman cache
 - 13.2. Install from live usb
 - 13.3. Pacman infos
 - 13.4. pacman mirrors
- 14. Grub
 - 14.1. Install grub manually when manjaro fails
- 15. Vim
 - 15.1. Install Vim in cluster
 - 15.2. Vim snippets
 - 15.3. Manage Tabs
 - 15.4. Vim surroundings
 - 15.5. Some commands
- 16. Lighdm
- 17. i3Blocks
- 18. PcmamFM
 - 18.1. Basic Configuration
- 19. MPV
 - 19.1. Annoying bar at the top
 - 19.2. Watch stream
- 20. Mime-Types
 - 20.1. Alternative to xdg:
- 21. Color-Scheme
- 22. LibreOffice
- 23. Reflector
- 24. AceStream
- 25. Swig
- 26. TTY Login
 - 26.1. Add Username
 - 26.2. Change startup message
- 27. HPC
 - 27.1. Modules
 - 27.2. Some Commands
- 28. Network
 - 28.1. Network not connecting at startup
 - 28.2. MAC address
- 29. Dmenu_ext
 - 29.1. Not opening paths
- 30. Nvidia
 - 30.1. NVIDIA back screen on TTY
- 31. CFP Nvidia
 - 31.1. VPN access

- 31.2. First steps to config account
- 32. Awk
- 33. Sublime-Text
- 34. Config-Printer
 - 34.1. CUPS
 - 34.2. AVAHI
 - 34.3. HP SCANNER
- 35. Sway
 - 35.1. Packages to check for base arch install
 - 35.2. Services
 - 35.3. Sway install from YT:
 - 35.4. Sway my experience
 - 35.4.1. Packages
 - 35.4.2. Configuration
 - 35.4.3. Fix cannot open display
 - 35.4.4. Mathematica
 - 35.4.5. Zoom
 - 35.4.6. Albert
- 36. Rclone
 - 36.1. Config
 - 36.2. Rclone union
 - 36.3. Problem
 - 36.4. Sync
 - 36.5. OneDrive
- 37. Pipewire
- 38. Fail2Ban
 - 38.1. Configuration
- 39. Systemd-Resolved
 - 39.1. Activate Service:
- 40. Dual Boot
 - 40.1. Windows After Linux
 - 40.2. Fix Windows bootloader Gone
- 41. RP Monitor
 - 41.1. Create db in influxdb
 - 41.2. CONFIG GRAFANA
 - 41.3. Notes
- 41. Docker
- 42. Misc

1.1. Introduction

In this document I include some notes about general stuff I learn and do during my work/free time.

2. Markdown Notes

2.1. VsCode extensions

- Markdown all in One
 - `Ctrl + Shift + P`: Markdown All in One: section numbers, create table of contents, etc
- Markdown lint
- vscode-pandoc
 - `Ctrl + Shift + P` -> Pandoc Render
 - Add `"pandoc.pdfOptString": "-t html --css style.css"` to `settings.json` in `.vscode/settings.json` in the work directory containing the markdown project. This `settings.json` overrides the global variables specified in that file. This can also be edited by doing `Ctrl+Shift+P: Preferences: Workspace Settings`. The `style.css` is put in the same folder of the `.md` file
 - ``pacman -S pandoc pandoc-crossref wkhtmltopdf`
- Markdown PDF

We can add to the `setting.json` for vscode workspace to use a specific style to generate the pdf:

```
"markdown-pdf.styles": [  
    "style.css",  
],
```

3. Git notes

3.1. Notes on creating a git repository on github

On folder do:

```
git init
git commit
git branch -M main
git remote add origin https://github.com/jgroboredo/test.git
git push -u origin main
```

3.1.1. Some notes on the above commands

- `git branch -m master main`

renames the master branch in local git repository

- In the second step, we'll have to create a new branch on the remote named "main" - because Git does not allow to simply "rename" a remote branch. Instead, we'll have to create a new "main" branch and then delete the old "master" branch: `git push -u origin main` We now have a new branch on the remote named "main".
- When you clone a repository with `git clone`, it automatically creates a remote connection called origin pointing back to the cloned repository.
- When you do a `git push origin master`, you are saying to git: "Look git, I want to push the current branch I am on to the remote repository named origin, and I want to push to the master branch in that remote.". By default, the remote repository is named origin. I only need to specify where I want to push if there are more than 1 repositories.
- When you execute the command: `git remote add origin "github repo link"` you are saying that for the current project, there is a remote repository with the name origin, with the address of "github repo link"

3.2. Check previous commit

```
git log
git checkout <commit_hash> (example:
18e0b6a044a715b04bcacd599061b6b8bd586a7a)
git checkout <branch_to_return_to_present_state>
```

3.3. Git stash and log

```
git log --stat -> see which files were altered in each commit
git stash; git stash list; git stash drop
```

3.4. Create local git repository

- Create a folder which is going to be the "server" -> For example, Notes.git
- Inside the repository do: `git init --bare`
- On the same computer do: `git clone /path/to/server` -> the repository created this way will be linked to the "server" by an absolute path which only works on this same pc
- On the other computer do: `git clone goncalo@ip:/path/to/server`

3.5. Change the author name

```
git config --global user.name "John Doe"
```

3.6. Remove tracked file that is now in .gitignore

```
git rm --cached <file>
```

3.7. Check last commit changes

`git show --name-only` -> Lists just the files in the last commit and doesn't give you the entire guts
`git diff HEAD^ HEAD` -> HEAD^ identifies last commit

3.8. Installing git in live ISO arch

If error in keys: `pacman -Sy archlinux-keyring; pacman-key --populate archlinux`

3.9. Change remote URL

- `git remote -v`

To check the present remote url

- `git remote set-url origin git@github.com:jgroboredo/Linux_Infos.git`

3.10. Add remote URL

- `git remote add name_of_remote git@github.com:jgroboredo/Linux_Infos.git`
- `git push -u name_of_remote --all`

Note: this changes the default repository! It also pushes all branches!

- `git config --edit`

Can use this command to change the default git push

- `git branch --set-upstream-to <remote-name>`

Set preferred remote for current branch

- `git branch branch_name --set-upstream-to <remote-name>/branch`

set preferred remote for branch_name

- `git branch -vv`

shows the default remote for the current branch

3.11. Different Pushes

- To push all branches to all remotes: `git remote | xargs -L1 git push --all`
- Push a specific branch to all remotes: `git remote | xargs -L1 -I R git push R branch_name`
- To make a git alias for the command: `git config --global alias.pushall '!git remote | xargs -L1 git push --all'`

Or

- Create an all remote with several repo URLs to its name:

```
git remote add all origin-host:path/proj.git
git remote set-url --add all nodester-host:path/proj.git
git remote set-url --add all duostack-host:path/proj.git
git push all --all
```

Or

- If you want to always push to repo1, repo2, and repo3 but always pull only from repo1, set up the remote 'origin' as:

```
git remote add origin https://exampleuser@example.com/path/to/repo1
git remote set-url --push --add origin
https://exampleuser@example.com/path/to/repo1
git remote set-url --push --add origin
https://exampleuser@example.com/path/to/repo2
git remote set-url --push --add origin
https://exampleuser@example.com/path/to/repo3
```

- If you only want to pull from repo1 but push to repo1 and repo2 for a specific branch specialBranch:

```
[remote "origin"]
  url = ssh://git@aaa.xxx.com:7999/yyy/repo1.git
  fetch = +refs/heads/*:refs/remotes/origin/*
  ...
[remote "specialRemote"]
  url = ssh://git@aaa.xxx.com:7999/yyy/repo1.git
  pushurl = ssh://git@aaa.xxx.com:7999/yyy/repo1.git
  pushurl = ssh://git@aaa.xxx.com:7999/yyy/repo2.git
  fetch = +refs/heads/*:refs/remotes/origin/* (Note: Has origin here
again, only pulls from origin)
  ...
[branch "specialBranch"]
```

```
remote = origin
pushRemote = specialRemote
...
```

- My experience:
 - I can specify which remote to push or pull from:

```
git push remote_name branch
```

- A branch has a default remote: I only need to specify the remote_name and eventually the branch_name (I can't pull from a non-default remote without specifying the branch) if I don't want to do it to the default one

3.12. Use curl to download from github

```
curl -LkSs https://api.github.com/repos/jgroboredo/arch_install/tarball -o
master.tar.gz
tar xf master.tar.gz
```

3.12. Download a file from github

- Go to file, click on raw, copy link
- `curl -L "link_from_above_step" >> output`

3.13. Merge branches

- `git checkout master; git merge other_branch_name`
- Alternative: `git merge --no-ff other_branch_name`. Using `--no-ff` allows someone reviewing history to clearly see the branch you checked out to work on.
- `git branch -d branch_name`

deletes branch locally

- `git push origin --delete branch_name`

deletes a branch remotely

- `git fetch -p`

Synchronize branch listing. After fetching, branches which no longer exist on the remote will be deleted.

If I do a: `git pull origin master` on another branch, it will merge them. After creating a new branch, we need to specify tracking information for the current branch. That means we need to do something like `git pull <remote> <branch>` for it to work. On the other hand, we can simply set tracking information for the current branch by: `git branch --set-upstream-to=origin/<branch>`
`correction_chapter1`

3.14. Check merge conflicts

`git show --name-only [commit sha]` on a commit that was a merge containing conflicts and you'll see it as part of the message.

3.15. Merge mistake (You committed changes to (local) master)

```
git branch <new-branch>
git reset HEAD~ --hard
git checkout new-branch
```

The first command creates the new branch we want to work with. The second command resets the main branch to just before the last commit, but leaves the changes you just made in the new branch. Finally, we switch to the new branch where your changes await you. If you've made multiple commits, use `git reset HEAD~<n> --hard`, where `n` is the number of commits back you want to go.

3.16. Git merge "Deleted by us"

Resolve all non deleted merge conflicts by hand, which you have to do anyway; Type `git diff --name-only --diff-filter=U` to get a list of all remaining files in conflict. These files must be the ones you want deleted. `git diff --name-only --diff-filter=U | xargs git rm`

3.17. Commit ID and SHA

```
git show -s --format=%H -> shows the last commit full id
git show -s --format=%h -> shows the last commit sha
```

3.18. Git over ssh using ssh config

`git remote set-url origin ssh://pi(here config name)/home/goncalo/HDD/Documents/git_repos/Notes.git` (here full path)

4. Bash Notes

4.1. Bash Note 1

- `$#`

number of arguments passed to the shell script

- `$1`, `$2`, etc

identify the arguments passed to the script

4.2. Bash Note 2

The code:

```
case $1 in
  -f|--from) command1; shift ;;
  *)        command2;;
esac
shift
```

will check if the first argument `$1` passed to the script matches `-f` or `--from` or any other cases; The asterisk means that it does `command2` if it doesn't match any of the cases above; The "shift" command shifts the arguments, i.e., if I have `$1`, `$2` arguments, then `$2 -> $1`.

4.3. Bash Note 3

The code:

```
SCRIPT_DIR="$( cd "$( dirname "${BASH_SOURCE[0]}" )" &> /dev/null && pwd )"
```

will give you the full directory name of the script no matter where it is being called from.

4.4. Bash Note 4 - Compare Files

```
grep -F -x -v -f fileA fileB
```

This works by using each line in `fileA` as a pattern (`-f fileA`) and treating it as a plain string to match (`-F`). You force the match to happen on the whole line `-x` and print out only the lines that don't match (`-v`). Therefore, you are printing out the lines in `fileB` that don't contain the same data as any line in `fileA`.

4.5. Bash Note 5 - Use of curly braces

1. In the example:

```
var=10          # Declare variable

echo "${var}"   # One use of the variable
echo "$var"     # Another use of the variable
```

it makes no difference to use curly braces.

2. However, the `{}` in `${}` are useful if you want to expand the variable `foo` in the string `"${foo}bar"` since `"$foobar"` would instead expand the variable identified by `foobar`.

Curly braces are also unconditionally required when:

- expanding array elements, as in `${array[42]}`
- using parameter expansion operations, as in `${filename%.*}` (remove extension)
- expanding positional parameters beyond 9: `"$8 $9 ${10} ${11}"`

4.6. Bash Note 6 - Search recursively in directory

- `grep -R "stuff"` will search recursively on all files on that directory and look for the word `stuff`
- `for i in **/.ipynb_checkpoints` will find recursively all directories with this name
- `for i in ./pattern` will search for this pattern in current directory

5. Lyx

5.1. Configure lyx

- Tools-Preferences-File Formats: PDF (pdflatex), shortname: pdf2, Viewer: Custom - zathura
- Tools-Preferences-Output-PDF command: `zathura --synctex-forward $$n:1:$$t $$o`
- Tools-Preferences-Shortcuts-New: buffer-view pdf2 and buffer-update pdf2
- For the spellchecker, might need to install hunspell-en_US and hunspell-pt_pt and enchant
- For lgrenc.def not found -> install texlive-langgreek
- To use eps figures in lyx I need ghostscript : try to epstopdf on command line to discover this.

5.2. Kpathsea

- Kpathsea is a library for path searching (e.g., for very quickly locating a given .sty file in a set of potentially large TEXMF trees, without doing a recursive directory tree traversal every time a given file is needed. (pse -> pathsea)
- kpsewhich minted.sty to search efficiently on tex library

5.3. Configure minted

```
sudo mkdir "/usr/share/texmf-texlive/tex/latex/minted/"
sudo cp minted.sty "/usr/share/texmf-texlive/tex/latex/minted/"
sudo mktexlsr
```

- Then in lyx, go to Tools/Tex Information, select latex styles and click rescan. minted.sty should appear in the list in lyx, go to "Tools>preferences>file handling>converters" and find the converter from tex to pdflatex. Edit its command line adding the option "-shell-escape" (no quotes) into the Converter field, then click the Modify button next to the list of converters. This is equivalent to going to Documents->Formats->Allow running external programs (is a better solution since it avoids writing a warning message). Then click Apply in lyx, go to Document>Settings and enter "/usepackage{minted}" (no quotes) in the latex preamble in lyx, in the part of your document where you want the highlighted code to appear, go to "Insert>TEX code" to get an Evil Red Text (ERT) box
- In Document->Settings->Listings, add following options:
 - language=C++
 - frame=single
 - mathescape=true
 - `syoeK --synctex-forward $$n:1:$$t $$o`
- Ordered bibliography: Use style unsrt and add to preamble: `\usepackage{notoccite}`

5.4. Install custom cls

- `latex my_class.ins` -> produces my_class.cls
- `kpsewhich -var-value=TEXMFHOME` -> prints path where to put cls

- Regarding the above command, it's good to put the usual path:
`$HOME/texmf/tex/latex/commonstuff/`
- `kpsewhich my_class.cls` -> to check path of the class
- Write lyx layout: In order to do this, find the basis class for our new class. For that, inspect `my_class.cls` and check the line `LoadClass`. It implies that `my_class.cls` is a descendent of that class (let's suppose it's dependent on `report` class). Then, in `/usr/share/lyx/layouts` copy `report.layout`, change its name to `my_class.layout` and edit like this:

```
\DeclareLaTeXClass[my_class]{name_of_layout}  
Input report.layout
```

- In lyx, reconfigure. Now, `name_of_layout` is the text we see in Document-Class
- Default classes: `/usr/share/texmf-dist/latex/elsarticle/elsarticle.cls`

6. Qemu

6.1. Commands

```
qemu-img create -f qcow2 qemu_image 8G
qemu-system-x86_64 -smp 6 -m 4G -enable-kvm -cdrom arch.iso -boot order=d
qemu_image
smp (number of cores)

qemu-system-x86_64 -soundhw ac97 -k en-us -vga std -enable-kvm -m 4G -
usbdevice tablet -smp 6 -enable-kvm -boot c qemu_image
#For no sound
qemu-system-x86_64 -k en-us -vga std -enable-kvm -m 4G -usbdevice tablet -
smp 6 -boot c qemu_image
```

6.2. Variables

```
-k en-us (keymap)
-usbdevice tablet

-cpu host
-smp 6 # number of cores
-machine type=pc,accel=kvm
-enable-kvm
-format=raw ??
-machine smm=off # bug?
-soundhw sb16,es1370

#telnet access
qemu-system-x86_64 -curses -monitor telnet:127.0.0.1:1234,server,nowait -
boot c qemu_image
telnet 127.0.0.1 1234 -- in another terminal

#KVM Quick Check
zgrep CONFIG_VIRTIO /proc/config.gz
lsmod | grep kvm
```

7. Inkscape

- If I have problems with eps images, in this case, also need to install ghostscript.
- Do you have ImageMagick installed? LyX relies on ImageMagick to convert among graphics formats. It also needs Ghostscript installed (IM uses GS when the conversions involve PS, EPS or PDF files).
- If **textext** package from the AUR gives problem, simply go to **textext** official website and install it from there

8. VsCode

- You can format an entire file with Format Document (Ctrl+Shift+I) or just the current selection with Format Selection (Ctrl+K Ctrl+F) in right-click context menu.
- F1 -> command pallet
- SSH : F1 -> Remote-SSH: Connect to Host...
- Install extension: TabNine

9. Zathura

- `pacman -S zahtura-pdf-poppler`
- make zathura default pdf viewer: `mimeo --ad application/pdf zathura.desktop`
- to discover the real name of zathura.desktop run `locate zathura.desktop`
- to check that pdf files have the correct mimetype run `mimeo -m pdf_file.pdf`
- Clipboard: add `set selection-clipboard clipboard` to `~/.config/zahtura/zathurarc` or `/etc/zathurarc`

10. Zsh

```
git clone https://github.com/zsh-users/zsh-autosuggestions ~/.zsh/zsh-  
autosuggestions  
source ~/.zsh/zsh-autosuggestions/zsh-autosuggestions.zsh in .zshrc  
mkdir .cache/zsh && touch .cache/zsh/dirs
```

11. Jupyter

11.1. Jupyter-Lab

To run over ssh, execute

```
ssh -L 8888(port on local):localhost::8889(port on remote) goncalo@ip
jupyter-lab --no-browser --port=(same as before on remote)8889
```

- To avoid authentication by token: `jupyter server password`
- To list active sessions: `jupyter lab list`
- To kill a session: `jupyter lab stop 8888` (for e.g.)

11.2. Opening browser

If jupyter doesn't open, do : `jupyter lab build` If command above gives permission error, do:

```
sudo chown -hR {user} {dir}
jupyter notebook (lab) --generate-config
```

Also, change `redirect_file` to false Na verdade, isto não funciona porque tenho de mudar o `~/.profile` para firefox LOL

-
- Can't access file (probably happens cause directory contains hidden folder `.local`):
 - set `c.ServerApp.use_redirect_file = False` in `~/.jupyter/jupyter_server_config.py`
 - Stop server:

```
lsof -n -i4TCP:[port-number]
kill -9 [PID]
```

12. Tmux

ssh host, tmux, run command, `ctr+b d`, exit. To check the tmux session, run `tmux attach`

13. Pacman

- Update pacman mirrors: `reflector --verbose --latest 5 --sort rate --save /etc/pacman.d/mirrorlist`
- Check recently installed packages: `grep -i installed /var/log/pacman.log`

13.1. Pacman cache

```
sudo ls /var/cache/pacman/pkg/ | wc -l # checks cached packages
du -sh /var/cache/pacman/pkg/ # disk space occupied by cache
sudo paccache -r # cleans all packages except most recent 3
sudo paccache -rk 1 # keep only one most recent version
sudo pacman -Sc # remove all uninstalled packages
sudo pacman -Scc # remove installed and uninstalled packages from cache
sudo paccache -ruk0 #**** remove all versions of uninstalled packages
change /etc/pacman.conf ParallelDownloads=5
```

13.2. Install from live usb

```
mount system: mount /dev/sdax /mnt
sudo pacman --root /mnt -S package
sudo pacman -Qkk | grep warning # To verify the presence of the files
installed by a package
sudo pacman --root /mnt -S $(sudo pacman --root /mnt -Qeq) --noconfirm #
reinstalls installed packages
#If need to remove aur packages:
sudo pacman --root /mnt -Qeq > packages.txt
sudo pacman --root /mnt -S $(cat packages.txt) --noconfirm
```

13.3. Pacman infos

```
pacman -Qe # lists explicitly installed packages
pacman -Rsc # uninstalls (including unneeded dependencies)
pacman -Qs "query" # search installed packages for keywords
pacman -Qdt # list unneeded packages
pacman -Rns $(pacman -Qdtq) # uninstall unneeded packages (nota: quando
adicionei isto aos aliases, sempre que abri o terminal pedia-me a pass do
sudo (estava a correr o que esta a frente de $))
```

13.4. pacman mirrors

```
sudo pacman-mirrors --fasttrack && pacman -Syyu
```

14. Grub

- If no update-grub command, do:

```
sudo nano /usr/sbin/update-grub
"
#!/bin/sh
set -e
exec grub-mkconfig -o /boot/grub/grub.cfg "$@"
"

sudo chown root:root /usr/sbin/update-grub
sudo chmod 755 /usr/sbin/update-grub
```

- If error syntax in grub-customizer:
 - View -> Show placeholders
 - select entry "script code"
 - remove
- check kernel by `uname -r`

14.1. Install grub manually when manjaro fails

- Deactivate CSM in BIOS
- Quando acaba a instalacao, ver se ele cria a particao em /boot/efi ou /boot
- `sudo fdisk --list` (para ver onde foi instalada a particao no pc)
- `sudo su`
- `mount /dev/sda2 /mnt` (em que sda2 era a particao com o linux)
- `mount /dev/sda1 /mnt/boot/efi`
- `grub-install --target=x86_64-efi --efi-directory=/mnt/boot/efi --bootloader-id=manjaro --boot-directory=/mnt/boot --recheck --debug`
- `manjaro-chroot -a`
- `update-grub`
- `umount -R /mnt`

[Link](#)

15. Vim

- `yay -S vim-plug-git`
- add `.vimrc` with the plugs I want
- add folder `~/.vim/plugged/`
- to install plugs, do `:PlugInstall`
- for fzf plugin: `:Files` command
- For the NERDTree plugin to see icon of file, install: `yay -S nerd-fonts-complete`; This font package may screw up font sizes of icons. To correct this, add to i3blocks config the following:

```
<span size='small' font_weight='light'> icon </span>
```

And change font on terminal to SauceCodePro Nerd Font Medium

- To open a file in a new tab in nerdtree, press t (or T); to open vertically click s;
- To cycle through windows: C-W-W, C-W-H, C-W-L, C-W-J, C-W-K
- To open file using fzf do:
- CTRL+T to open in new tab
- CTRL+X to open a new split
- CTRL+V to open in a new vertical split
- While in NERDTree, click on "m" to have a menu to do stuff with the file or other things
- `yay -S vim-youcompleteme-git` -> vim autocompletion (Needs to be done separately from the installation of the dotfiles)
- No need to add this plugin (vim-youcompleteme-git) to the `.vimrc` file
- add: `let g:ycm_show_diagnostics_ui = 0` to disable error checking by YouCompleteMe
- `pacman -S python-black`

15.1. Install Vim in cluster

```
git clone https://github.com/vim/vim.git
./configure --prefix=$HOME/.local && make && make install
# More flags: --disable-perlinterp --enable-rubyinterp --enable-multibyte -
--enable-pythoninterp --with-features=huge
export PATH="/home/youruser/.local/bin:$PATH"
# For plugins:
mkdir ~/.vim/autoload
curl -fLo ~/.vim/autoload/plug.vim --create-dirs \
https://raw.githubusercontent.com/junegunn/vim-plug/master/plug.vim
```

Place in `.vimrc` before `plug#begin()`:

```
let data_dir = has('nvim') ? stdpath('data') . '/site' : '~/.vim'
if empty(glob(data_dir . '/autoload/plug.vim'))
```

```
silent execute '!curl -fLo '.data_dir.'/autoload/plug.vim --create-dirs
https://raw.githubusercontent.com/junegunn/vim-plug/master/plug.vim'
autocmd VimEnter * PlugInstall --sync | source $MYVIMRC
endif
```

15.2. Vim snippets

- `:UltiSnipsEdit` command opens up a custom snippets file for the current language/filytype
- Don't need the above step if I install vim-snippets plugin

15.3. Manage Tabs

- To move tabs -> `Alt + arrows`
- To merge tabs -> `Ctr + m` or `Ctrl + n`;
- To exchange position of merged tabs -> `<C-w> x`;
- To change cursor position -> `<C-w> w`;
- To rotate windows -> `<C-w> <C-r>`

15.4. Vim surroundings

- `cs(atual)(target)` -> change surround from "atual" to "target"
- `ds` -> delete surround "
- `ysiw` -> yank surround inner word [-> puts [surrounding the word the curson is in
- `ysf(smth)` -> puts [surrounding current cursor position till smth

15.5. Some commands

- procurar coisas: `/searchthing` e usa-se `n` ou `N` para avançar para as seguintes
- procurar string e substituir:

```
:s/search/replace/
:8,10 s/search/replace/g procura nas linhas 8 a 10
:%s/search/replace/g procura no documento inteiro
:%s/search/replace/gc pede confirmação para alterar
```

- copiar e colar: seleccionar o texto, y copia, p cola

16. Lighdm

```
pacman -S lightdm-gtk-greeter-settings  
change default greeter: /etc/lightdm/lightdm.conf under [Seat:~]  
pacman -S archlinux-wallpaper  
pacman -S materia-gtk-theme  
yay -S pop-icon-theme-git  
yay -S pop-gtk-theme
```

17. i3Blocks

For the scripts to work, even if it is .py, need to chmod +x

- <https://github.com/vivien/i3blocks-contrib/tree/master/>
- For calendar, install yad and xdotool; add: `for_window [class='Yad'] floating enable`

18. PcmanFM

18.1. Basic Configuration

- Go to edit -> Preferences -> Advanced :
 - Set terminal emulator (ex: xfce4-terminal) -> to open directly with vim for example
 - Set archiver integration: xarchiver
- To see thumbnails, install the following packages:
 - poppler-glib
 - ffmpegthumbnailer
 - freetype2
 - raw-thumbnailer
 - tumbler
 - libgsf
 - libgepub

19. MPV

19.1. Annoying bar at the top

- Change picom config: frame-opacity option

19.2. Watch stream

- `pacman -S yt-dlp`
- `mpv 'link'`

20. Mime-Types

20.1. Alternative to xdg:

- `yay -S mimeo`
- `yay -S xdg-utils-mimeo`

MIMEO COMMANDS

- Open files (foo, bar, etc): `mimeo foo bar baz`
- find Leafpad's desktop file: `mimeo --app2desk leafpad`
- determine "test" file's MIME-type: `mimeo -m test`
- associate "application/x-shellscript" with Leafpad: `mimeo --add application/x-shellscript leafpad.desktop`
- Associate all text files with Medit: `mimeo --add 'glob:text/*' medit.desktop`
- Association File Examples: (`mimeo --assoc-help`)

```
vlc --one-instance --playlist-enqueue %U
    ^https?:/(www.)?youtube.com/watch\?.*v=
```

Open HTTP(S) URLs with Firefox:

```
/usr/bin/firefox %U
    ^https?:/
```

Open various media files in VLC by extension:

```
/usr/bin/vlc --one-instance --playlist-enqueue %F
    \.mp3$
    \.flac$
    \.avi$
```

- CUSTOM ASSOCIATION FILES (`mimeo --help`, `mimeo --filepath-help` If `--assoc` is not passed then the following paths will be checked for custom associations, in order:

```
/home/goncalo/.config/mimeo/associations.txt
/etc/xdg/mimeo/associations.txt
```

Note: Eventually try mimi! Links:

- [repo](#)
- [aur](#)

Note: eventually take a look at package `perl-file-mimeinfo` (`mimeoopen -d`)

21. Color-Scheme

- Install: python-pywal
- Install: `yay -S fzwal-git`
- Run: `wal --theme base16-nord`
- Add to .zshrc: (`cat ~/.cache/wal/sequences &`)
- Add to .vimrc:
 - Plug 'dylanaraps/wal.vim' (install with PlugInstall)
 - `colorscheme wal`
 - `set background=dark`

NOTE:

- This pywal thing seems to screw up with other windows. Removed for now!
- It seems like it isn't pywal that messed with firefox -> Firefox stopped crashing when I disabled the popOS gtk theme!!!

22. LibreOffice

- Latex in impress: `pacman -S libreoffice-extension-texmaths`
- Check extension in Extension Manager inside libreoffice
- To install ExpandAnimations go to Tools->ExtensionManager and add there the oxt file

23. Reflector

```
reflector --latest 200 --protocol http --protocol https --sort rate --save  
/etc/pacman.d/mirrorlist  
reflector --country 'France,Germany' --age 12 --protocol https --sort rate  
--save /etc/pacman.d/mirrorlist
```


24. AceStream

```
yay -S acestream-engine  
yay -S acestream-launcher  
acestreamid  
acestream-launcher acestream://id -p player
```

25. Swig

```
g++ -Wall -Wextra -Wpedantic -I/usr/include/python3.9 -  
I/usr/lib/python3.9/site-packages/numpy/core/include/ -fPIC -shared  
example_wrap.cxx -o _example.so -lpython3.9  
the first includes python and the second numpy/arrayobject.h
```

26. TTY Login

26.1. Add Username

```
cat /etc/systemd/system/getty@tty1.service.d/override.conf:
[Service]
ExecStart=
ExecStart=-/usr/bin/agetty -n -o <username> %I
systemctl edit getty@tty1
```

26.2. Change startup message

1. added script to bin folder that re-writes /etc/issue with the correct value of the battery. It uses a template situated in issue folder. This template has a PLACEHOLDER text that is used by sed to substitute with the value of the battery. In order for this to work, I created a systemd service (check systemd_scripts folder) which runs the script. Everything is situated in lap_dotfiles

27. HPC

27.1. Modules

- To list all currently loaded modules: `module list`
- To list all available (loadable) modules: `module avail`
- To load a module: `module load x`
- To unload a module: `module unload x`
- To swap a specific module for another: `module switch x y`

27.2. Some Commands

```
sinfo
squeue
scontrol show partition/node/....
scancel (process_id)
# Don't forget to load modules - e.g. -> module load gcc-8.1, module load
openmpi/4.0.1
module avail # to see modules
srun -n 1 -p partition bash # takes me to a shell inside the node
```

Launch Script:

```
#!/bin/bash
#SBATCH # instrucoes ao sbatch
./ficheiro.out
```

28. Network

28.1. Network not connecting at startup

- `systemctl restart NetworkManager`

28.2. MAC address

- To find the default device -> `ip route list`
- To find the mac address -> `ifconfig -a`
- Alternatives:
 - `ip addr show && ip addr show device`
 - `ip link show`

29. Dmenu_ext

29.1. Not opening paths

Add to mimeapps.list: inode/directory=pcmanfm.desktop;

30. Nvidia

30.1. NVIDIA back screen on TTY

- /etc/modprobe.d/blacklist.conf:

```
install i915 /usr/bin/false  
install intel_agp /usr/bin/false
```

31. CFP Nvidia

31.1. VPN access

- Install snx from InfoCiencias
- create .snxrc file
- connect by snx
- disconnect by snx -d

31.2. First steps to config account

- To create home directory by default: CREATE_HOME yes in /etc/login.defs
- On first login had no home:
 - mkdir /home/username
 - chown username:username /home/username
 - cp -rT /etc/skel /home/username -> to populate with default files and folders
- Generate ssh keys: ssh-keygen
- Add .pub key to ~/.ssh/authorized_keys
- The default shell was /bin/sh. So that bash works,
 - chsh /bin/bash
- Can check shells by: cat /etc/shells

32. Awk

- Print every 3 lines

```
awk 'NR%3==0' file
awk 'NR%3==0' file >> tmp && mv tmp file -> saving to file
for i in ./file_pattern ; do
    awk 'NR%3==0' $i >> tmp && mv tmp $i
done
# The above cycle iterates over the files in the current directory
```

33. Sublime-Text

- Go to sublime text webpage, linux repos and find pacman. Follow the commands
 - Go to preferences -> package control (to install the package manager)
 - To install a package: Ctrl + Shift + p (command pallet) -> Install -> Package name
 - Important packages to install: (To see packages: Preferences->Package Control->List Packages)
 - SFTP
 - C++ Starting Kit
 - C++NamespaceTool
 - ClangFormat
 - Anaconda
 - C Improved
 - C++11
 - SideBarEnhancements
- Define shortcuts for sftp: Preferences->Package Settings->SFTP->Key Bindings and write on the file on the right hand side with the directory: .config/...../Packages/User/... My first shortcuts were: alt+z(open files) e alt+x(open servers)
- Example file for server setup:

```
{
  // The tab key will cycle through the settings when first created
  // Visit https://codexns.io/products/sftp\_for\_sublime/settings for help

  // sftp, ftp or ftps
  "type": "sftp",

  "sync_down_on_open": true,
  "sync_same_age": true,

  "host": "176.79.187.130",
  "user": "goncalo",
  //"password": "",
  //"port": "22",

  "remote_path":
  "/home/goncalo/Documents/Optics/NonLinearOptics_Interpolation/",
  //"file_permissions": "664",
  //"dir_permissions": "775",

  //"extra_list_connections": 0,

  "connect_timeout": 30,
  //"keepalive": 120,
  //"ftp_passive_mode": true,
  //"ftp_obey_passive_host": false,
```

```
//"ssh_key_file": "~/.ssh/id_rsa",
//"sftp_flags": ["-F", "/path/to/ssh_config"],

//"preserve_modification_times": false,
//"remote_time_offset_in_hours": 0,
//"remote_encoding": "utf-8",
//"remote_locale": "C",
//"allow_config_upload": false,
}
```

- To use clang on save:
 - Install clang (pacman -S clang) and the clang package in sublime
 - Preferences->Package Settings->Clang Format->Setting-User:

```
{
  "binary": "/usr/bin/clang-format-3.8" (/path/to/your/clang-
format/executable/file),
  "format_on_save": true,
  "style": "Custom",
}
```

- Preferences->Package Settings->Clang Format->Custom Style-User:

```
{
  "Language": "Cpp",
  "TabWidth": 4,
  "AlignTrailingComments": "true",
  "UseTab": "Never",
}
or
Language: Cpp
BreakBeforeBraces: Attach
PointerAlignment: Right
TabWidth: 4
IndentWidth: 4
AccessModifierOffset: 0
ColumnLimit: 120
NamespaceIndentation: All
AlignTrailingComments: true
AllowAllParametersOfDeclarationOnNextLine: true
AlwaysBreakTemplateDeclarations: true
UseTab: Never
```

34. Config-Printer

34.1. CUPS

- Packages to install:
 - cups, cups-filters, liblouis, qpdf, cups-pdf, python-pycups, python-pycurl, gsfonts
 - system-config-printer
- Services to activate

```
sudo systemctl enable --now cups.service
sudo systemctl enable --now cups.socket
sudo systemctl enable --now cups.path
```

- List services: `sudo systemctl -a list-units | grep -i cups`
- Configuration:
 - Verify the following user groups are set in file /etc/cups/cups-files.conf `SystemGroup sys root wheel`
 - Associate a user to the "sys" group by replacing "username" below: `gpasswd -a username sys`
- Add A Printer Using CUPS Web Interface
 - Open "Manage Printing" or browse to `http://localhost:631/`
 - Click on "Administration" at the top of the web page.
 - Click on "Add Printers".
 - Select the desired printer under "Discovered Network Printers" and click the "Continue" button.
 - Set the "Name", "Description" and "Location" and then click on the "Continue" button.
 - Select the "Model" of printer and click the "Add Printer" button.
 - Select default options and click the "Set Default Options" button.
- Add A Printer Using Printer Settings This utilizes "Printer Settings" (system-config-printer package) a native GUI application.
 - Open "Printer Settings".
 - Click on the "Unlock" button.
 - Click on the "Add" button.
 - Select the desired printer and click the "Forward" button.
 - Set the desired "Printer Name", "Description" and "Location".
 - Click the "Apply" button.

After these steps, it should work. Do not need to go for avahi!!!!

34.2. AVAHI

- Packages to install:
 - avahi, nss-mdns
- `sudo systemctl enable avahi-daemon.service`
- edit the file `/etc/nsswitch.conf` and change the hosts line to include `mdns_minimal` `[NOTFOUND=return]` before the word `resolve`
- `avahi-browse --all --ignore-local --resolve --terminate` or
- `avahi-discover` (needs `gtk3`, `dbus-python` and `python-gobject`)

The question is not avahi or cups but : Do I need/want printer autodiscovery or not ? If answer is yes > enable avahi , if answer is no > disable avahi Either use cups or cups + avahi

34.3. HP SCANNER

- wiki page: SANE/Scanner-specific problems
- `pacman -S sane-airscan ipp-usb`
- `pacman -S hplip`
- Go to `system-config-printer` and now add printer (printing should work from now on). In order to scan:
 - `hp-makeuri <scanner_ip> / scanimage -L`
 - `scanimage --device "<hpaio:/net....>" --format=png --resolution 300 >scan.png`

35. Sway

35.1. Packages to check for base arch install

```
pacman -S grub efibootmgr networkmanager network-manager-applet dialog  
wpa_supplicant mtools dosfstools reflector base-devel linux-headers avahi  
xdg-user-dirs xdg-utils gvfs gvfs-smb nfs-utils inetutils dnsutils bluez  
bluez-utils cups hplip alsa-utils bash-completion openssh rsync reflector  
acpi acpi_call tlp virt-manager qemu qemu-arch-extra edk2-ovmf bridge-utils  
dnsmasq vde2 openbsd-netcat iptables-nft ipset firewalld flatpak sof-  
firmware nss-mdns acpid os-prober ntfs-3g terminus-font  
pacman -S xdg-desktop-portal-wlr
```

35.2. Services

```
systemctl enable NetworkManager  
systemctl enable bluetooth  
systemctl enable cups.service  
systemctl enable sshd  
systemctl enable avahi-daemon  
systemctl enable tlp # You can comment this command out if you didn't  
install tlp, see above  
systemctl enable reflector.timer  
systemctl enable fstrim.timer  
systemctl enable libvirtd  
systemctl enable firewalld  
systemctl enable acpid
```

35.3. Sway install from YT:

```
pacman -S sway swaylock swayidle xorg-xwayland ttf-font-awesome
```

35.4. Sway my experience

35.4.1. Packages

```
pacman -S sway swaylock  
pacman -S mako grim  
yay -S grimshot  
pacman -S wl-clipboard  
pacman -S light (manage brightness)  
pacman -S playerctl (waybar config)  
pacman -S waybar  
yay -S swaylock-effects-git  
pacman -S swayidle
```

```
pacman -S xdg-desktop-portal-wlr
pacman -S dex
yay -S rambox-bin
yay -S albert-minimal
pacman -S pamixer
pacman -S brightnessctl
yay -S nordic-theme
yay -S clipman
# installed i3-quickterm from github: https://github.com/lbonn/i3-quickterm.git
```

35.4.2. Configuration

- The first config lines are concerned with environment variables needed to make gtk applications launch faster:
 - `exec systemctl --user import-environment DISPLAY WAYLAND_DISPLAY SWAYSOCK`
 - `exec hash dbus-update-activation-environment 2>/dev/null &&`
`dbus-update-activation-environment --systemd DISPLAY WAYLAND_DISPLAY SWAYSOCK`
- The keyboard and touchpad are configured in sway config. To get the inputs run: `swaymsg -t get_inputs`
- using i3-quickterm to have a dropdown menu. Need to install rofi for it to work but I can also use i3-quickterm shell and then I do not need to install rofi.
- binding albert in config with `exec albert toggle`
- using swaylock-effects-git for sway lock
- Using "exec grimshot copy area" for screenshots (requires wl-clipboard)
- Bind media keys (brightness and volume) on config. Associated icons to notifications. The icons are from Arc-X-D package.
- If I want to use light, need to add the following line to sudoers: `%wheel ALL=(root) NOPASSWD: /usr/bin/light`
- Install playerctl for these controls and waybar.
- For the autostart applications, need to add the flag `--indicator` to nm-applet
- For the dual monitor, check the monitor with `swaymsg -t get_outputs`
- Sway doesn't work very well with lightdm -> use lydm -> `systemctl enable ly.service -f`
- Instead of using ly, simply use .zprofile to login. For it to work, need whiptail and Rebelo's package shiftstate (it is on lap_dotfiles). `Ctrl+Enter` after putting pw on tty takes me to a tui to choose the wm. `Shift+Enter` takes me to tty login
- The env variable `MOZ_ENABLE_WAYLAND=1` enables to run firefox on wayland mode. However, it doesn't load the gtk theme this way. Then, I added to .confi/sway/env the flag `GTK_THEME=Nordic`. Need to change this in accordance to the gtk theme I want

35.4.3. Fix cannot open display

```
pacman -S xorg-server-xwayland
```

35.4.4. Mathematica

- In order to run mathematica: `QT_QPA_PLATFORM="xcb" mathematica &`

- A better way is to add a folder: `$HOME/bin` and the following script name `mathematica` (same name as the original in `/usr/local/bin`):

```
#!/bin/sh
QT_QPA_PLATFORM="xcb" /usr/local/bin/mathematica "$@"
```

- Then, if in sway, add to the env script in `.config/sway` the following line:
`PATH="${HOME}/bin:${PATH}"` The fact that `$HOME/bin` comes before path overrides the original `mathematica` script! Now, I can launch `mathematica` from `dmenu`
- Although the above steps solve the problem when we call the binary `mathematica`, it doesn't solve the problem when we want to open a `mathematica` notebook through the file manager. To solve that problem I need to change the `wolfram-mathematica12.desktop` file in `/usr/share/applications/wolfram-mathematica12.desktop`. In the field `exec` I need to put the path to `$HOME/bin/mathematica` script. I saved the original desktop file in `/usr/share/applications/mathematica.desktop`.
- `mathematica` was crashing with 3D graphics. Solution: run `mathematica` with `mesa`: `mathematica -mesa notebook_name`.

35.4.5. Zoom

- Currently doesn't allow for screen sharing. Use zoom in firefox and it works fine!
- Eventually try `XGD_CURRENT_DESKTOP=gnome zoom`

35.4.6. Albert

- `albert` crashing after search or cancelling search: `rm .config/albert/core.db`

36. Rclone

36.1. Config

- rclone is best configured using ssh-agent:
 - rclone config
- new remote
- Storage > sftp
- host: 192.168.1.64 (e.g)
- user: goncalo (e.g)
- ssh port: blank
- To use ssh-agent, leave all the other options blank (and eventually refuse them)

36.2. Rclone union

```
[paulo_http_single]
type = http
url = https://joserebelo:PASSWORD@paulo

[paulo_http]
type = union
upstreams = paulo_http_single::ro /cache/union
```

- The first part on the union config is read-only but `/cache/union` is not, allowing to add our own stuff
- We need to mount (for the union to work) the `[paulo_http]` one.
- what we write in the mounted drive will go to `/cache/union` and reading merges both

36.3. Problem

- NewFs: couldn't connect SSH: ssh: handshake failed: ssh: unable to authenticate, attempted methods [none publickey], no supported methods remain
- This was happening because of the type of keys. I should generate: `ssh-keygen -t ed25519`
- Solution: add to `/etc/ssh/sshd_config`: `PubkeyAcceptedAlgorithms+=ssh-rsa`
- I should also add:

```
PermitRootLogin no
PasswordAuthentication no
```

36.4. Sync

- `rclone sync /home/goncalo/Documents pi:/home/goncalo/HDD/Documents/Backups/Laptop/Documents --log-file /home/goncalo/.local/my_logs/backup.log -v --exclude lap_dotfiles/ --transfers=8 --progress`
- `-i` flag asks question about copying

36.5. OneDrive

- `rclone copy UsefulScripts OneDrive:Documents/UsefulScripts` (copies the contents of UsefulScripts -> therefore I copy to Documents/UsefulScripts, otherwise would populate Documents with its contents)

37. Pipewire

- `pacman -S pipewire`
- `pacman -S pipewire-pulse`. Remove pulseaudio and pulseaudio-bluetooth
- It automatically creates symlink `/etc/systemd/user/sockets.target.wants/pipewire-pulse.socket` → `/usr/lib/systemd/user/pipewire-pulse.socket`
- Disable pulseaudio on sway config
- `pacman -S libpulse` (comes with pulseaudio)
- `pacman -Qo pactl`
- bluetooth should not be affected by this
- `pacmd` used by volume-script no longer works. Need to use `amixer` (which comes with `alsa-utils`) to check if muted or not.

38. Fail2Ban

- `pacman -S fail2ban`
- `enable/start fail2ban.service`

38.1. Configuration

Edit file `/etc/fail2ban/jail.local`:

```
[DEFAULT]
bantime = -1
findtime = 1d
maxretry = 5

[sshd]
enabled = true
```

39. Systemd-Resolved

`/etc/systemd/resolved.conf:`

```
[Resolve]
DNS=1.1.1.1#cloudflare-dns.com 9.9.9.9#dns.quad9.net
FallbackDNS=1.0.0.1#cloudflare-dns.com 9.9.9.10#dns.quad9.net
DNSSEC=yes
DNSOverTLS=yes
Cache=yes
CacheFromLocalhost=no
DNSStubListener=yes
ReadEtcHosts=yes
```

`/etc/resolv.conf:`

```
ln -rsf /run/systemd/resolve/stub-resolv.conf /etc/resolv.conf
```

`/etc/NetworkManager/NetworkManager.conf:`

```
[main]
# Ignore network-provided dns
dns = none
```

39.1. Activate Service:

```
systemctl enable systemd-resolved.service
```

40. Dual Boot

40.1. Windows After Linux

- Install windows;
- Boot live iso; mount disk with linux:
 - `mount /dev/sdX2 /mnt`
 - `mount /dev/sdX1 /mnt/boot/efi`
 - `manjaro-chroot /mnt`
 - `update-grub`
- If windows keeps changing boot entry order:
 - Install EasyUefi (easyuefi.com)
 - Go to Manage EFI boot option
 - Check the path to the manjaro boot option
 - `Bcdedit /set {bootmgr} path path\from\above\step` (e.g. \EFI\Manjaro\grubx64.efi)

40.2. Fix Windows bootloader Gone

- shift+f10
- diskpart
- list disk
- select disk X (Where windows was installed)
- list volume
- select volume Y
- assign letter=Z (where Z is the letter you want to "mount")
- do the same to efi partition:
 - list disk
 - select disk X (Where is the EFI partition)
 - list volume
 - select volume volume-number
 - assign letter=M
- exit diskpart (exit)
- run: `bcdboot <Letter-Assigned-To-Windows>:\Windows` eg: `bcdboot Z:\Windows`
 - optionally: `bcdboot Z:\Windows /s M:` (/s copies to drive M)
- Unmount devices:
 - diskpart
 - list volume
 - select volume VOLUME-NUMBER
 - remove letter DRIVE_LETTER

41. RP Monitor

- for the monitoring need 3 docker containers: grafana, influxdb (database), telegraf
 - the ports on docker-compose need to match the ones in telegraf.conf
 - In the telegraf conf:
 - urls: needs to be 127.0.0.1:(port of docker compose)
 - username and pw must match what I put in influxdb
 - hostname must be the one on of pi

41.1. Create db in influxdb

```
docker exec -it influxdb bash
influx
CREATE USER "grafana" WITH PASSWORD 'qwe' (pw configured in grafana)
CREATE USER "telegraf" WITH PASSWORD 'asd' (pw put on config)
CREATE DATABASE "pi"
GRANT ALL ON "pi" TO "grafana"
GRANT ALL ON "pi" TO "telegraf"
SHOW DATABASES
```

41.2. CONFIG GRAFANA

- add data source:
 - Configuration -> Data Sources:
 - url: http://influxdb:8086
 - database: pi
 - User: grafana (same as defined in influxdb)
 - Pw: same as defined in influxdb
- import dashboard:
 - ID: 10578
 - Select data source added above

41.3. Notes

- In order to restart a container do docker-compose up container_name (this reloads the yml if it changed); otherwise use docker-compose restart container_name
- `docker rm -f container_name` (deletes container)
- `docker inspect influxdb | jq ".[0].Config.Volumes"`
- In telegram.conf I need 127.0.0.1 : nas portas means "bind to all addresses" mas aqui quero mesmo aceder ao localhost

42. Docker

- `pacman -S docker docker-compose`
- `systemctl enable docker.service`
- `docker info`; `sudo chmod 666 /var/run/docker.sock`
- On folder, run: `docker-compose up -d`
- To access things on the web, check the port on .yml file and: `http://localhost:8080`
- To access using any device on the network, substitute 127.0.0.1 to 0.0.0.0 in all containers in the .yml file Then, only need to do `ip(192.168.1.64):port` on any device and it will work.
- Login on web: admin, pw: adminadmin
- On qbittorrent, tools->options->default save path: /downloads/

Notes on the downloads folder:

- It is important that this folder is mounted to some directory on my computer (check docker-compose) and that this mount point is the same in radarr/sonarr. Radarr/sonarr will check the download folder in the qbittorrent settings (which is /downloads) and will therefore look in the directory /downloads. Therefore, /downloads must be a volume in docker-compose and should point to the same folder as in qbittorrent.
- On qbittorrent, tools->options->(under automatically add torrents from) Monitored Folder -> /blackhole
- Get image: `https://hub.docker.com/r/linuxserver/radarr`
- `docker ps -a` -> check running containers
- To set pw and username on qbittorrent: Tools -> Options -> Connection -> Authentication
- Rebuild image: `docker-compose build rclone-extension --no-cache`

42.1. Jacket

- `http://localhost:9117`
- Add indexer -> RARBG and 1337x;

42.2. Sonarr

- Download clients -> Cliq + -> Select qbittorrent -> host é qbittorrent (you can access containers by name)
- Port: 8080
- Username and Pw : same as qbittorrent login (admin, adminadmin)

- We can access a container from the terminal: `docker exec -it qbittorrent bash`
- Go to Indexers -> Select Torznab -> In URL paste the Torznab feed from jackett (and change localhost to jockett in the URL)
- Add API key from jockett (on top of the page)
- If this doesn't work, change dns:
 - `vim /etc/resolv.conf`
 - `nameserver 1.1.1.2`
- `vim /etc/NetworkManager/NetworkManager.conf`

```
[main]
# Ignore network-provided dns
dns = none
```

- check if I can ping from jockett: `docker exec -it jockett bash; curl 1337x.to`
- `systemctl restart docker`
- `docker-compose up -d`
- When adding series, the root folder should be: /media -> this is mapped to a volume outside the container
- qbittorrent downloads to /downloads and sonarr moves it to /media
- old episodes on sonarr must be downloaded manually
- A lupa saca automatico e o boneco deixa escolher o torrent
- If I can't add indexer, I can add one that I know that works and then edit it and substitute the url for the one I want to add.
- Add series on read-only file system:
 - Mount read-only fs inside container
 - Add new series to default path where sonarr can write
 - Open sqlitebrowser -> Open Database -> sonarrdb (inside config folder in container) -> In table, select Series -> find series -> Select Path -> Change on the right

43. System service to run docker

```
/etc/systemd/system/docker-compose.service

[Unit]
Description=Docker Compose Service
```

```
Requires=docker.service
After=docker.service
After=network-online.target
Wants=network-online.target

[Service]
Type=oneshot
RemainAfterExit=yes
WorkingDirectory=/home/jose/dotfiles/pi
ExecStart=/usr/sbin/docker-compose up -d
ExecStop=/usr/sbin/docker-compose down
TimeoutStartSec=0

[Install]
WantedBy=multi-user.target
```

43.1. Rclone DLNA

- Settings -> Download clients -> Advanced options -> Enable remove imported downloads from download client history
- This is streaming the /media folder to my network
- In VLC go to view -> playlist -> local network -> universal plug and play

43.2. Transdrone

Description: App for android to manage torrents

43.3. JellyFin

- drive ntfs -> does not support inotify -> scan manually: Settings -> dashboard -> scan all libraries
- In order to change folder go to settings -> Dashboard -> Libraries
- If informations are not correct, select movie or series and click identify
- Do not watch jellyfin on browser. Instead, yay -S jellyfin-media-player
- DNLA
 - add to yml: "network_mode: host" on jellyfin container and remove ports section

43.4. QBitTorrent

- In order to stop seeding go to tools -> bittorrent -> seeding limits -> min ratio 0.01 -> max seed time 1 minute (Pause torrent, remove doesnt work)

43.5. Bazarr

- Go to settings -> Languages -> Add New Profile -> Add desired languages -> Below this option, check the boxes Series and Movies and choose the profile just created in the step before

43.6. Organizrr

- In order for qbittorrent to work: Tools -> WebUI -> Untick "Enable clickjacking protection" and "Enable Cross-Site Request Forgery protection"

43.7. NginX

- Need to get nginx.conf and proxy.conf from swag github;
- On the nginx.conf carefull with the following lines:
 - include /config/nginx/worker_processes.conf;
 - include /config/nginx/resolver.conf;
- /config/nginx/resolver.conf:
 - `resolver 127.0.0.11 valid=30s;` (note that the ";" is important in these files)
- The configs to reverse proxy can be found in github: linuxserver/reverse-proxy-confs (I want the subfolder ones)
- In order to setup the sonarr, jackett, etc reverse-proxy config, I need to read the config because it asks to change the Base URL, etc
- In order to setup grafana, needed to add to the docker-compose config:
 - environment:
 - "GF_SERVER_ROOT_URL=%(protocol)s://%(domain)s:%(http_port)s/grafana/"
- The above configs only have the "location" block which goes inside the server block. The default server config can be found in /config/nginx/site-confs/default. There, I should add "include /config/nginx/proxy-confs/*.subfolder.conf;" and comment both "location" blocks there.
- The organizr config has as upstream_port port 80. In docker-compose.yml, organizr has host port 9983 mapped to port 80 on the container. However, nginx bypasses that and goes straight to port 80 on the container -> that's why the reverse proxy config works.
- It happened that, when I connected to organizr behind the nginx server, I could not login. This happened because the browser was rejecting cookies. The problem was in proxy.conf file. It assumed it was in https. Only need to comment the lines:
 - `proxy_set_header X-Forwarded-Proto https;`
 - `proxy_set_header X-Forwarded-Ssl on;`
- Changed all port mapping in docker-compose.yml to 127.0.0.1:port so it can only be access from pi. Since everything is reverse proxied, it's fine
- The nginx docker-compose config has in port section:
 - 80:80 which defaults to 0.0.0.0:80:80 (that's why I can access nginx from the entire network)
- In order to reverse-proxy emby I commented out the line "network_mode: host" otherwise the reverse-proxy config does not work by default. If I want to use "network_mode: host" I need change

the reverse-proxy config: "set \$upstream_app emby" -> "set \$upstream_app 10.0.10.1". Inside emby, in Network, need to change "Secure connection mode" to "Handled by reverse proxy". One thing I noticed was that UPnP was not working. In order for it to work, in emby, I need to add, in Network -> Lan Networks: 192.168.0.0/24, 10.0.10.0/24

- Couldn't find rclone serve dlina in laptop with firewalld. Use firewall gui, go to options -> change zones of connections -> select my network and put it as home. Then, select my network in connections, in zones tab select home, then services, and tick upnp-client
- In the media reverse proxy config, the lines: "alias /media" and "fancyindex on" are the ones responsible to show the content of the folder /media of the container (folder where I wanna mount the stuff I wanna show). Note that I also need to "git clone <https://github.com/alehaa/nginx-fancyindex-flat-theme.git>" and

```
sed -i '/<small>/,/<\small>/d'
"$FANCYINDEX_THEME_PATH/layout/footer.html"
sed -i "s/File Browser/$(cat /etc/hostname) \ | media/g" -i
"$FANCYINDEX_THEME_PATH/layout/header.html"
sed -i "s/'Home'/' '/g" -i
"$FANCYINDEX_THEME_PATH/layout/js/breadcrumbs.js"
```

43.8. Some Important Concepts

- Docker bypasses iptables
- localhost de um container não é o mesmo que de outro (estao isolados)
- Can't specify ports with network_mode host
- In iptables.rules, the line: ":FORWARD DROP [0:0]"

blocks all forwarded packets

- If I want to find the docker ip of a container: `docker network inspect -f '{{range .IPAM.Config}}{{.Subnet}}{{end}}' <container_id>`
- The <container_id> can be found by running `docker ps -a`
- `docker inspect <container_name>`
- `docker stop/logs/(rm -f)/restart <container_name>`
- `docker inspect -f '{{range .NetworkSettings.Networks}}{{.IPAddress}}{{end}}' <container_id>`
- `docker images ->` prints images of containers
- `docker image inspect <image_id_from_above_step>`
- `docker manifest inspect --verbose <container_name>`

43.9. Update Containers

- `docker-compose pull`
- `docker-compose up`
- Container to update containers

```
watchtower:
  container_name: watchtower
  image: containrrr/watchtower:latest
  networks:
    - monitoring
  volumes:
    - /var/run/docker.sock:/var/run/docker.sock
  command: >-
    --cleanup --rolling-restart --schedule "0 0 4 * * *"
```

Info: `--cleanup` doesn't leave older version on the computer. `--rolling-restart` restarts the containers one by one (important to deal with dependencies) The container pulls automatically

- `docker system prune -a` (after doing `docker-compose up`, otherwise deletes images I just pulled)
- list images: `docker images -a`
- remove all images: `docker rmi $(docker images -a -q)`

43.10. Some notes based on experience

- `docker run -it image_name sh ->` runs an interactive shell container using the image "image_name" The above command can be necessary because if the container is a one-shot, it will simply die after running: `docker run <image_name>` However, I can also do `docker run -t -d <image_name> sh` and, even it's an one-shot, it will be kept alive. Then, I can always do a `docker exec -it <container_id> sh` to enter again inside the container
- Other ways of starting a container: `sudo docker create <image_name>; sudo docker start <container_id_from_previous_command>`
- `docker image history --no-trunc image_name > image_history ->` steps in the Dockerfile
- `docker ps -a ->` lists containers and the container id
- save the id in a variable: `container_id=$(docker create image_name)`
- Extracting a file from an image: `docker cp "$container_id:$source_path" "$destination_path"`
- Pushing a file to an image: `docker cp folder/. "<container_id>:/path/in/container" ->` this actually pushes all files inside folder
- `docker image inspect <image>`
- `docker container prune ->` removes all containers
- `git reset HEAD~1 ->` go back one commit before pushing
- jenkins scm
- <https://www.infoq.com/articles/build-a-container-golang/>

44. VPN

45. Misc

1. By disabling all F86 binds in config and installing xfce-power-management (which needs to be started in config and need to get config from Manjaro/Home/.config) and installed pa-applet-git, pavucontrol and pulseaudio (initiated in config) all the F86 binds work.

2. It is preferable to have xfce4-notify (initiated in config by running `/usr/lib/xfce4/notifyd/xfce4-notifyd`) than dunst... Better notifications. Check i3 config and uninstall dunst (in endeavour). In manjaro, do: `sudo mv /usr/share/dbus-1/services/org.knopwob.dunst.service{,.disabled}`

3. Bluetooth:

- `pacman -S pulseaudio-bluetooth`
- `pulseaudio -k`
- `yay -S bluez-hcidb`
- `hciconfig ->` lists bluetooth interfaces
- `sudo hciconfig hci1 down ->` turn off specific interface

4. Sticky xrandr:

- `xrandr --output eDP --primary`
- `pacman -S autorandr`
- `autorandr --save laptop`

5. FSTAB

```
sshfs : jose@pi:/mnt/rebelo-pi fuse.sshfs noauto,x-
systemd.automount,_netdev,user,idmap=user,follow_symlinks,identityfile
=/root/.ssh/id_rsa,allow_other,default_permissions,uid=1995,gid=1995,n
oatime,reconnect,ServerAliveInterval=45,ServerAliveCountMax=2 0 0
```

6. SYMBOLIC LINKS

- `ln -s /complete/path/to/original/file /complete/path/to/target/file` (the target file will be a "pointer" to the original file, but it's like the file is in the new target location)
- `ln -sr /relative/path/to/original/directory /complete/path/to/target/directory` (the target directory will be a link to the first; the -r flag means relative)
- The -f flag will force the link, meaning it deletes the target file/directory if it exists
- Remember to always use complete paths and not relative paths if the -r flag is not specified

7. SSH

- I can run commands over ssh like this: `ssh user@host 'command'`
 - Example: `liplisboacluster 'echo ${hostname}'` -> prints hostname
- Writing on a remote file:

```
echo 'Some Text' | ssh user@remotehost -T "cat > /remotefile.txt"
# (-T flag forwards stdin local through ssh)
cat ~/.ssh/id_rsa.pub | ssh user@remote.host 'dd
of=ssh/authorized_keys oflag=append conv=notrunc'
```

- In order to have several ssh keys, do:

```
ssh-keygen -t rsa -b 4096 -C "your_email@example.com"
eval $(ssh-agent)
ssh-add ~/.ssh/id_rsa2 (newly created key)
```

- In order to have ssh-agent always running, check `~/.config/systemd` and `.zshrc`
- `systemctl --user enable ssh-agent.service` (probably don't need to do this since I have a backup of `.config/systemd`)
- Check services: `systemctl --user list-unit-files | grep enabled`
- Check services (all): `systemctl list-unit-files | grep enabled`
- Also, need to add to `zshrc` a function to load keys, since `ssh-add` only works for the current session
- To have a proxy:

```
Host 10.0.10.3
User goncalo
ProxyCommand ssh goncalo@jgroboredo.ddns.net -W %h:%p
```

- If ssh service fails to start with error: Start request repeated too quickly, do the following:

```
sudo systemctl stop sshd.socket and sshd.service
sudo /usr/bin/sshd -d
#If message from above command states a permission issue:
sudo chmod 400 /etc/ssh/ssh*key
```

8. Firefox crash

- Seems like it was the gtk theme from popOS that made firefox to crash
- In sway, if font problems, export `GTK_USE_PORTAL=1`
- In what concerns crashes, picom with xrender crashes! Need to use glx

- Today, 10/08/2021, firefox started crashing. Disabled picom and it did not solve the problem. Updated picom config from arch linux wiki, did not help. Firefox->Settings->Performance did not change anything
- Starting firefox from terminal does not seem to solve the problem. Does not output any errors.
- Testing launching firefox and terminal from i3 bind with the flag --no-startup-id -> doesnt work
- Testing google-chrome-stable; disabled guake
- Google-chrome also crashed; However, it recovered after a few seconds, similar to what previously happened to vscode. It seems like a X11 problem. Moved to sway.
- Testing again firefox crashes on i3. For now, uninstalled xf86-video-intel. Since then, no crashes yet.
- FIREFOX SLOW START:
 - about:config
 - set 0 to all widget.use-xdg-desktop-portal

9. ARCH NOT BOOTING IN VM

- On a recent installation of arch on a VM, it did not boot after installing the custom grub-theme. In order to solve this, either chroot or open a terminal using ctrl+alt+F2. There, delete the grub theme in /usr/share/grub/themes and after that run grub-mkconfig -o /boot/grub/grub.cfg
- The above solution doesn't work. In fact I am very dumb. This was only related with the fact that I have a intel config file in /etc/X11/xorg.d.... DUMB BBBB

10. FIND UUID OF DISK

- `sudo blkid | grep UUID=`

11. FIX YAY

- Error: yay: error while loading shared libraries: libalpm.so.11: cannot open shared object file: No such file or directory
- Fix: rebuild yay:

```
cd /tmp && git clone 'https://aur.archlinux.org/yay.git'
&& cd /tmp/yay && makepkg -si && cd ~ && rm -rf /tmp/yay/
```

12. FIX PAMAC

- Error: libpamac-aur: /etc/pamac.conf exists in filesystem(owned by pamac-aur)
- Fix: `pacman -R pamac-aur && yay -S pamac-aur`

13. FIX TIME

- `sudo ntpd -qq`

- install ntp
- `sudo ntpdate pool.ntp.org`
- `timedatectl set-ntp true`

14. CHECK RAM `sudo dmidecode -t memory`

15. lxrandr to change monitors

16. CONFIG LINUX ACCOUNT

```
sudo useradd -m test
userdel <nome de utilizador do utilizador>
adduser username sudo
/etc/ssh/sshd_config # Allow pubkey and add authorized_keys file;
chsh -s $(which zsh)
sudo service ssh restart
# For redmine: couldn't add repos to redmine: change permissions:
chmod 775 /path/to/dir
```

17. Dmenu-extended

- For apps to open I need desktop files to associate a given mimetype to a binary
- After doing the above step, rebuild cache

18. NetworkManager/Network interface stopped working

- Solution: boot to a pen with manjaro and reboot
- See logs:

```
find /sys/class/net -follow -maxdepth 2 -name wireless
cat /proc/net/wireless
iw dev
sudo iw dev wlp0s20f3 connect "ROBOREDO"
sudo dmesg | grep firmware
sudo dmesg --level=emerg,alert,crit,err
lspci | grep net
lsmod
sudo ls /etc/netctl/interfaces
```

19. Rebuild all yay packages depending on python: `yay -S $(pacman -Qoq /usr/lib/python3.9) --answerclean All`

20. nc : install `pacman -S gnu-netcat`

21. Can add stuff to path in .xinitrc; a user systemd service needs to have WantedBy=default.target and not multi-user The rclone command will not work in a user service since systemd doesn't have access to env variables. For that, just add a env.conf file to .config/environment.d/ (check printenv)

22. Delay a systemd service:

```
[Service]
ExecStartPre=/bin/sleep 30
```

23. DMZ - portas abertas para toda a internet

24. `dhcpcd -T eth0` - check dns

25. PERMISSIONS

```
chown -R root:root /etc
find /etc -type f -exec chmod 644 {} +
find /etc -type d -exec chmod 755 {} +
chmod 755 /etc/init.d/* /etc/rc.local /etc/network/* /etc/cron.*/*
chmod 400 /etc/ssh/ssh*key
check desktop_dotfiles
```

26. Need imagemagick for blurlock

27. samba

```
smbclient '//print-server.critical.pt/Drivers/' -U critical/jgroboredo
(smbclient '//ip/Directory')
smbclient '\\files.critical.pt/Repository' -U critical/jgroboredo
get file
```

28. bluedevil; bluedevil-wizard; systemctl start bluetooth; pavucontrol: High Fidelity Playback (A2DP Sink, codec LDAC) blueberry-tray

29. `sudo lsof -i -P -n | grep LISTEN`

30. bash gum package

31. `gtk-update-icon-cache -f -t .icons` ou `(/usr/share/icons/)` Add icon field in desktop file - only the name.png