

In-Class Exercise/Demo



In-Class Demo

- Let's practice our [Redux](#) example with Vanilla CDN version of Redux
- First, create a new Github repository [m6-w2-d1-demo](#) and clone this in your WESTCLIFF folder.
- Next, head over to GAP and download [m3-week6-d1-demo.zip](#) folder, unzip and drop the content into the clone folder.
- We will create Vanilla JS code in this demo but let's first run [NPM install](#). Make sure you are in [counter-Vanilla](#) folder. This will install some basic dependencies.
- Next, open [index.html](#).
- We have basic codes that shows us [+ - increment if odd](#) and [increment async](#)
- Next let's preview [index.html](#). We will type [open index.html](#) or you can also use "Live server" to preview this page.



In-Class Demo

- You will see but the actions do not work.

Clicked: 0 times

+

-

Increment if odd

Increment async



In-Class Demo

- Let's write some code using redux state to make these actions work.
- First we will write our **function for counter** that will take **state** and **action**.
- Next, we will write an **if statement** and **switch** to setup case scenarios.

```
function counter(state, action) {  
  if (typeof state === 'undefined') {  
    return 0  
  }  
  switch (action.type) {  
    case 'INCREMENT':  
      return state + 1  
    case 'DECREMENT':  
      return state - 1  
    default:  
      return state  
  }  
}
```



In-Class Demo

- Next, we will set up some **variables** and a **function to render** our variables.
- Then we call the **render function**

```
var store = Redux.createStore(counter)
var valueEl = document.getElementById('value')

function render() {
  valueEl.innerHTML =
store.getState().toString()
}

render()
store.subscribe(render)
```



In-Class Demo

- Next, we will setup click actions for buttons that we are using in HTML

#1

```
document.getElementById('increment')
  .addEventListener('click', function () {
    store.dispatch({ type: 'INCREMENT' })
  })
```

#2

```
document.getElementById('decrement')
  .addEventListener('click', function () {
    store.dispatch({ type: 'DECREMENT' })
  })
```

#3

```
document.getElementById('incrementIfOdd')
  .addEventListener('click', function () {
    if (store.getState() % 2 !== 0) {
      store.dispatch({ type: 'INCREMENT' })
    }
  })
```



In-Class Demo

- Next, we will setup click actions for buttons that we are using in HTML

#4

```
document.getElementById('incrementAsync')  
  .addEventListener('click', function () {  
    setTimeout(function () {  
      store.dispatch({ type: 'INCREMENT' })  
    }, 1000)  
  })
```



In-Class Demo

- You should be able to increment by clicking + and decrement by clicking -
- You can also increment if the number is odd, it will not increment if the number is even. (**review code**)
- Increment async will increment every 1000ms

Clicked: 15 times

+

-

Increment if odd

Increment async



In-Class Exercise Demo

- **DUE:**
Today 10.30PM PT
- **Submission:**
Post Github link on GAP Week 6 Day 1 Exercise