



ELECTROLYTE ANALYZER

Na⁺, K⁺, Cl⁻
Ca²⁺, pH, Hct

25 s

Fastest System

20 µL

Lowest sample volume

oQC

Fully programmable
automated 3 level on-board QC
for max. 60 measurements per level

Levey - Jennings-Chart

QC-Trend visualization

Cont. Monitored Sensor Signals

Highest within-run precision
Self-detection and corrective actions

Maintenance free

The all-in-one cartridge includes

- Sensors, solutions, waste
- All wear & tear parts like tubings, sample input and valves etc.

Ease of use

Versatile sample input

Intuitive user interface

Full connectivity

Data exchange with LIS


Network connection via LAN (RJ45)

Data export via USB flash drive

Robust and clever design

Compact footprint

Dimensions 20 x 31 x 28 cm (W x H x D)



Sample tube mode



Capillary mode



TECHNICAL SPECIFICATIONS

OPERATIONAL CHARACTERISTICS

Parameters	Na ⁺ , K ⁺ , Cl ⁻ , Ca ²⁺ , pH, Hct
Calculated parameters	nCa ²⁺ , tHb(c)
Min. sample volume	20 µL
Sample type	whole blood, serum, plasma, urine (undiluted)
Sample container	sample tubes, syringes, capillaries (no adapter required)
Time to result	25 s
Throughput	TYP 104 samples/hour
Wet-up time	30 min (new cartridge installation)

ALL-IN-ONE CARTRIDGE

Number of samples	150, 300, 600
On-board stability	42 days / 28 days
Storage temperature	+2°C to +25°C
Shelf life	9 months

QUALITY CONTROL

Integrated on-board QC (oQC)	3 levels
oQC measurements / Level	30, 50, 60
Manual QC	3 levels
QC-Trend visualization	Levey-Jennings-Chart
Proficiency testing / External Quality Assurance	3 rd party external quality control measurements possible

CALIBRATION DATA

Calibration	Automatic 2-point cal
Duration	30 s
Interval	4, 8, 12 h (configurable)

STORAGE CAPACITY

Patient results	500.000
QC & Calibration data	min. 24 months
Operators	100

INTERFACE

Touch Display	7" TFT
Resolution	800 x 480 px
Ethernet	RJ45
USB flash drive	2 USB ports (2.0)
Barcode reader	optional
WiFi dongle	optional

COMMUNICATION

Data exchange	LIS
Protocol	LIS2-A2 protocol (ASTM)
Remote access	Screen sharing

ADDITIONAL INFORMATION

Printer	Built-in 2" thermal printer (easy load)
Dimensions (W x H x D)	20 x 31 x 28 cm
Instrument weight	4.0 kg
In-use weight	4.7 kg

POWER REQUIREMENTS

Voltage	100 – 240V
Power	mean 15 W; max. 60 W
Frequency	50 / 60 Hz

ENVIRONMENTAL REQUIREMENTS

Temperature	+15°C to +32°C
Humidity	15 % to 90 %
Barometric pressure	462 mmHg to 769 mmHg

IVD © 2021 EXIAS Medical GmbH
All rights reserved

CE Kratkysstraße 2
8020 Graz, Austria
info@exias-medical.com

"The e | 1 Analyzer uses an all-in-one cartridge that enables maintenance free operation."

